

#### FCC RF EXPOSURE REPORT

#### **CERTIFICATION TEST REPORT**

For

WIFI Module

**MODEL NUMBER: WC5FM2601F** 

FCC ID: 2AC23-WC5F

REPORT NUMBER: 4790487037-5

**ISSUE DATE: August 5, 2022** 

Prepared for

Hui Zhou Gaoshengda Technology Co.,LTD No.2,Jin-da Road,Huinan High-tech Industrial Park,Hui-ao Avenue,Huizhou City,Guangdong,China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China


> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4790487037-5 Page 2 of 7

# **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	08/05/2022	Initial Issue	





# **TABLE OF CONTENTS**

1.	ATTESTATION OF TEST RESULTS	4
2	TEST METHODOLOGY	5
	FACILITIES AND ACCREDITATION	
	REQUIREMENT	



REPORT NO.: 4790487037-5 Page 4 of 7

### 1. ATTESTATION OF TEST RESULTS

Applicant Informati	io	n
---------------------	----	---

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD

Address: No.2, Jin-da Road, Huinan High-tech Industrial Park, Hui-ao

Avenue, Huizhou City, Guangdong, China

**Manufacturer Information** 

Company Name: Hui Zhou Gaoshengda Technology Co.,LTD

Address: No.2, Jin-da Road, Huinan High-tech Industrial Park, Hui-ao

Avenue, Huizhou City, Guangdong, China

**EUT Information** 

EUT Name: WIFI Module Model: WC5FM2601F

Brand: GSD

Sample Received Date: July 12, 2022 Sample Status: Normal Sample ID: 5143871

Date of Tested: July 12, 2022 ~ August 2, 2022

APPLICABLE STANDARDS				
STANDARD TEST RESULTS				
FCC 47CFR§2.1091	PASS			

STANDA	אט	IESI KESULIS
FCC 47CFR§	2.1091	PASS
Prepared By:	Checked By	<i>r</i> :
kebo. rhang.	Shemm	lies
Kebo Zhang Project Engineer	Shawn Wen Laboratory L	_eader
Approved By:		
Lephenbus		
Stephen Guo		

Laboratory Manager



REPORT NO.: 4790487037-5 Page 5 of 7

### 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

### 3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA.
	FCC (FCC Designation No.: CN1187)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Has been recognized to perform compliance testing on equipment subject
	to the Commission's Delcaration of Conformity (DoC) and Certification rules
	ISED (Company No.: 21320)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Accreditation	has been registered and fully described in a report filed with ISED.
Certificate	The Company Number is 21320 and the test lab Conformity Assessment
	Body Identifier (CABID) is CN0046.
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	Facility Name:
	Chamber D, the VCCI registration No. is G-20019 and R-20004
	,
	Shielding Room B , the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.

REPORT NO.: 4790487037-5 Page 6 of 7

## 4. REQUIREMENT

#### **LIMIT AND CALCULATION METHOD**

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

#### **RF EXPOSURE LIMIT**

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E ²,  H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

## **CALCULATION METHOD**

S=PG/4πR<sup>2</sup>

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



REPORT NO.: 4790487037-5 Page 7 of 7

### **CALCULATED RESULTS**

Worst Case						
Mode	Output Power	Directional Gain	Power Density	Power Density Limit	Test Result	
	dBm	dBi	mW/cm2	mW/cm2	1	
WIFI 2.4G	20.0	5.17	0.0654	1.0	Complies	

Worst Case						
Mode	Output Power	Directional Gain	Power Density	Power Density Limit	Test Result	
	dBm	dBi	mW/cm2	mW/cm2		
WIFI 5G	20	6.59	0.0907	1.0	Complies	

#### Note:

- 1. The Power comes from report operation description.
- 2. The EUT cannot support simultaneous emission.
- 3. The minimum separation distance of the device is greater than 20 cm.
- 3. Calculate by WORST-CASE mode.

END OF REPORT