

HAC_E_Dipole_835**DUT: HAC-Dipole 835 MHz**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.5 °C

DASY5 Configuration:

- Probe: EF3DV3 - SN4047; ConvF(1, 1, 1) @ 835 MHz; Calibrated: 2019/1/30
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn914; Calibrated: 2019/6/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

E Scan - measurement distance from the probe sensor center to CD835 = 10mm & 15mm/Hearing Aid Compatibility Test at 15mm distance (41x361x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 130.1 V/m; Power Drift = 0.01 dB

PMR not calibrated. PMF = 1.000 is applied.

E-field emissions = 114.1 V/m

Average value of Total=(114.1+112.4) / 2 = 113.25 V/m

PMF scaled E-field



Grid 1 M4 114.1 V/m	Grid 2 M4 114.1 V/m	Grid 3 M4 109.0 V/m
Grid 4 M4 62.77 V/m	Grid 5 M4 63.04 V/m	Grid 6 M4 60.41 V/m
Grid 7 M4 112.3 V/m	Grid 8 M4 112.4 V/m	Grid 9 M4 107.3 V/m

Cursor:

Total = 114.1 V/m

E Category: M4

Location: 3, -72, 9.7 mm



0 dB = 114.1 V/m = 41.15 dBV/m

HAC_E_Dipole_1880**DUT: HAC Dipole 1880 MHz**

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.5 °C

DASY5 Configuration:

- Probe: EF3DV3 - SN4047; ConvF(1, 1, 1) @ 1880 MHz; Calibrated: 2019/1/30
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn914; Calibrated: 2019/6/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

E Scan - measurement distance from the probe sensor center to CD1880 = 10mm & 15mm/Hearing Aid Compatibility Test at 15mm distance (41x181x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 156.6 V/m; Power Drift = 0.01 dB

PMR not calibrated. PMF = 1.000 is applied.

E-field emissions = 88.21 V/m

Average value of Total=(88.21+87.01) / 2 = 87.61 V/m

PMF scaled E-field



Grid 1 M3 87.89 V/m	Grid 2 M3 88.21 V/m	Grid 3 M3 84.78 V/m
Grid 4 M3 65.54 V/m	Grid 5 M3 65.64 V/m	Grid 6 M3 64.19 V/m
Grid 7 M3 86.29 V/m	Grid 8 M3 87.01 V/m	Grid 9 M3 84.10 V/m

Cursor:

Total = 88.21 V/m

E Category: M3

Location: 1.5, -33, 9.7 mm



0 dB = 88.21 V/m = 38.91 dBV/m

HAC_E_Dipole_2600**DUT: HAC Dipole 2600 MHz**

Communication System: CW ; Frequency: 2600 MHz;Duty Cycle: 1:1

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Ambient Temperature : 23.5 °C

DASY5 Configuration:

- Probe: EF3DV3 - SN4047; ConvF(1, 1, 1) @ 2600 MHz; Calibrated: 2019/1/30
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn854; Calibrated: 2019/5/21
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

E Scan - measurement distance from the probe sensor center to CD2600 = 10mm & 15mm/Hearing Aid Compatibility Test at 15mm distance (41x181x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 74.00 V/m; Power Drift = 0.03 dB

PMR not calibrated. PMF = 1.000 is applied.

E-field emissions = 90.48 V/m

Average value of Total=(87.93+90.48) / 2 = 89.205 V/m

PMF scaled E-field



Grid 1 M3 86.87 V/m	Grid 2 M3 87.93 V/m	Grid 3 M3 85.45 V/m
Grid 4 M3 81.33 V/m	Grid 5 M3 82.07 V/m	Grid 6 M3 80.32 V/m
Grid 7 M3 89.47 V/m	Grid 8 M3 90.48 V/m	Grid 9 M3 87.91 V/m

Cursor:

Total = 90.48 V/m

E Category: M3

Location: 0.5, 23, 9.7 mm



0 dB = 90.48 V/m = 39.13 dBV/m