





# RF Exposure Evaluation Report

FCC ID 2AZT5-481100627

**Equipment** Semi Passive LED Tag

**Brand Name** SAG

**Model Name** 481100627

**Applicant Securitag Assembly Group** 

No.1, Gongye 9th Rd., Dali Industrial District

Taichung 412, Taiwan

Manufacturer **Securitag Assembly Group** 

No.1, Gongye 9th Rd., Dali Industrial District

Taichung 412, Taiwan

Standard 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Mar. 09, 2021, and testing was started from May 03, 2021 and completed on May 11, 2021. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Allen Lin

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)

TEL: 886-3-327-3456 : 1 of 5 Page Number

FAX: 886-3-327-0973 Issued Date : Jun. 10, 2021

Report Template No.: HE1-A3 Ver4.0 Report Version : 01



# RF Exposure Evaluation Report

## **Table of Contents**

1.	General Description					
		•				
		Information				
	1.1.1	EUT General Information	4			
	1.1.2	Antenna Information	4			
	1.2	Testing Location Information	4			
2 RF Exposure Evaluation						
		·				
	2.1	Applicable Standard	5			
	2.2	SAR evaluation	5			

Photographs of EUT V01

TEL: 886-3-327-3456 FAX: 886-3-327-0973

Report Template No.: HE1-A3 Ver4.0

FCC ID: 2AZT5-481100627

Page Number : 2 of 5

Issued Date : Jun. 10, 2021

Report No.: FA0N0601-02

Report Version : 01



## RF Exposure Evaluation Report

# **History of This Test Report**

Report No.: FA0N0601-02

Report No.	Version	Description	Issued Date
FA0N0601-02	01	Initial issue of report	Jun. 10, 2021

Reviewed by: Sam Tsai

Report Producer: Amber Chiu

TEL: 886-3-327-3456 Page Number : 3 of 5
FAX: 886-3-327-0973 Issued Date : Jun. 10, 2021

Report Template No.: HE1-A3 Ver4.0 Report Version : 01

# 1. General Description

#### 1.1 Information

#### 1.1.1 EUT General Information

RF General Information				
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type	
RFID	902 ~ 928	902.75-927.25	ASK	

**Report No. : FA0N0601-02** 

#### 1.1.2 Antenna Information

Ant.	Ant. Brand		Antenna Type	Connector	Gain (dBi)
1	SAG	340707195	PCB antenna	-	-10.55

## 1.2 Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory						
$\boxtimes$	Hsinhua	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)				
	(TAF: 3785)	TEL: 886-3-327-3456	<b>FAX:</b> 886-3-327-0973			
	Test site Designation No. TW3785 with FCC.					
	Wen 33rd.St.	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)				
	(TAF: 3785)	<b>TEL:</b> 886-3-318-0787	<b>FAX:</b> 886-3-318-0287			
	Test site Designation No. TW0008 with FCC.					

TEL: 886-3-327-3456 Page Number : 4 of 5
FAX: 886-3-327-0973 Issued Date : Jun. 10, 2021

Report Template No.: HE1-A3 Ver4.0 Report Version : 01



### 2. RF Exposure Evaluation

#### 2.1 Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Report No.: FA0N0601-02

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

#### 2.2 SAR evaluation

Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
 [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]•

 $[\sqrt{f}_{(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Max. Power	Tolerance	Tune-up Max. Power		<b>Test Distance</b>	Frequency	Exclusion
(dBm)	(dB)	(dBm)	(mW)	(mm)	(GHz)	Thresholds
-2.59	0.50	-2.09	0.62	5	0.90275	0.12

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is 0.12 < 3, RF exposure evaluation is not required.

——THE END——

TEL: 886-3-327-3456 Page Number : 5 of 5
FAX: 886-3-327-0973 Issued Date : Jun. 10, 2021

Report Template No.: HE1-A3 Ver4.0 Report Version : 01