



# RF MPE Report

**Applicant:** Assetflo Inc.  
**Address:** 9105 Derry Rd., unit 2 Milton, L9T7Y9 Canada  
**Product:** Assetflo 5G Tracker  
**Model No.:** MI-606-V07  
**Brand Name:** Assetflo  
**FCC ID:** 2BNZ6-5GTRACKERR2  
**Standards:** 47 CFR Part 2.1091  
FCC KDB 447498 D01 v06  
**Report No.:** PD20250020-R3B  
**Issue Date:** 2025/02/25  
**Test Result:** PASS \*

\* Testing performed at Hefei Panwin Technology Co., Ltd. on the above equipment indicates the product meets the requirements of the relevant standards.

**Reviewed By:** Charlie Wang

**Approved By:** Alec Yang

## Hefei Panwin Technology Co., Ltd.

Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin  
Avenue, High-tech Zone, Hefei City, Anhui Province, China  
TEL: +86-0551-63811775

## Revision History

Report No.	Version	Description	Issue Date	Note
PD20250020-R3B	01	Initial Report	2025/02/25	Valid

### Remark:

- The samples tested have been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and have been proven to meet the applicable limit requirements.

## CONTENTS

<b>1 General Information .....</b>	<b>4</b>
1.1 Notes of the Test Report .....	4
1.2 Testing Laboratory .....	4
<b>2 General Description of Equipment under Test .....</b>	<b>4</b>
2.1 Details of Application .....	4
2.2 Details of EUT .....	5
<b>3 Test Condition .....</b>	<b>6</b>
3.1 Laboratory Environment .....	6
<b>4 Maximum Permissible Exposure (MPE) .....</b>	<b>7</b>
<b>ANNEX A: RF Exposure Evaluation .....</b>	<b>8</b>
<b>ANNEX B: The EUT Appearance .....</b>	<b>10</b>

## 1 General Information

### 1.1 Notes of the Test Report

This report is invalid without signature of auditor and approver or with any alterations. The report shall not be partially reproduced without written approval of the testing company. Entrusted test results are only responsible for incoming samples. If there is any objection to the testing report, it shall be raised to the testing company within 15 days from the date of receiving the report. In the test results, "NA" means "not applicable", and the test items marked with "Δ" are subcontracted projects.

### 1.2 Testing Laboratory

Company Name	Hefei Panwin Technology Co., Ltd.
Address	Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province, China
Telephone	+86-0551-63811775
Post Code	230031

## 2 General Description of Equipment under Test

### 2.1 Details of Application

Applicant	Assetflo Inc.
Applicant Address	9105 Derry Rd., unit 2 Milton, L9T7Y9 Canada
Manufacturer	Assetflo Inc.
Manufacturer Address	9105 Derry Rd., unit 2 Milton, L9T7Y9 Canada

## 2.2 Details of EUT

Product	Assetflo 5G Tracker
Model	MI-606-V07
Hardware Version	MI-606-V07
Software Version	mfw_nrf9160_1.3.6
Category	LTE Cat-M1
Antenna Type	<input checked="" type="checkbox"/> Internal <input type="checkbox"/> External <input type="checkbox"/> Integrated
<b>Note:</b> The declared of product specification for EUT and/or Antenna presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.	

## 3 Test Condition

### 3.1 Laboratory Environment

Temperature	Min.= 20℃, Max.=30℃
Relative Humidity	Min.= 25%, Max.=75%
Ground System Resistance	< 1 Ω
<p>Ambient noise is checked and found very low and in compliance with requirement of standards.</p> <p>Reflection of surrounding objects is minimized and in compliance with requirement of standards.</p>	

## 4 Maximum Permissible Exposure (MPE)

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Table 1 to § 1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)				
Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30–300	61.4	0.163	1.0	<6
300–1,500	--	--	f/300	<6
1,500–100,000	--	--	5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30–300	27.5	0.073	0.2	<30
300–1,500	--	--	f/1500	<30
1,500–100,000	--	--	1.0	<30
f = frequency in MHz. * = Plane-wave equivalent power density.				

The transmitter is using external antennas that operate at 20 cm or more from nearby persons. The maximum permitted level is calculated using the general equation:

$$S = PG / 4\pi R^2$$

Where:

**S** = power density (in appropriate units, e.g. Wm<sup>2</sup>)

**P** = power input to the antenna (in appropriate units, e.g., W)

**G** = power gain of the antenna in the direction of interest relative to an isotropic radiator

**R** = distance to the center of radiation of the antenna (appropriate units, e.g., m)

Solve S, the power density at 20 cm is shown in Appendix A, so the limit is kept.

----- THE END -----

## ANNEX A: RF Exposure Evaluation

### Maximum Measured Conducted Output Power and Antenna Gain

Band	TX Freq. (MHz)	Maximum conducted output power(Incl. Tune-Up) (dBm)	Maximum Antenna Gain (dBi)
LTE Band 2	1850 to 1910	24.00	3.58
LTE Band 4	1710 to 1755	24.00	5.17
LTE Band 12	699 to 716	24.00	0.68
LTE Band 66	1710 to 1780	24.00	5.17



## Test Results of Maximum Permissible Exposure

Band	Frequency (MHz)	Maximum Power (dBm)	Antenna Gain (dBi)	FCC ERP/EIRP Limit(W)	FCC MPE Result (mW/cm^2)	MPE Limit (mW/cm^2)	Ant Gain to Meet FCC MPE limit (dBi)	Ant Gain to Meet FCC ERP/EIRP limit (dBi)	Max Gain Allowed (dBi)
LTE Band 2	1850.0	24.00	3.58	2.000	0.1140	1.0000	13.0	9.0	9.0
LTE Band 4	1710.0	24.00	5.17	1.000	0.1643	1.0000	13.0	6.0	6.0
LTE Band 12	699.0	24.00	0.68	3.000	0.0584	0.4660	9.7	10.8	9.7
LTE Band 66	1710.0	24.00	5.17	1.000	0.1643	1.0000	13.0	6.0	6.0

**Note 1:** For mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate EMF distance is less.

**Note 2:** For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band.

**Note 3:** Chose the maximum RF output tune up power of all antennas among same frequency WWAN bands and the maximum antenna gain to perform MPE calculation conservatively.

## ANNEX B: The EUT Appearance

The EUT Appearance (internal and external photographs) are submitted separately.