


|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                          |                                                                                    |                                          |                                                                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Prüfbericht-Nr.:</b><br>Test report no.:                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>CN22YF1T 001</b>                                                                                                                      | <b>Auftrags-Nr.:</b><br>Order no.:                                                 | <b>168345062</b>                         | <b>Seite 1 von 23</b><br>Page 1 of 23                                                 |
| <b>Kunden-Referenz-Nr.:</b><br>Client reference no.:                                                                                                                                                                                                                                                                                                                                                                                                        | <b>N/A</b>                                                                                                                               | <b>Auftragsdatum:</b><br>Order date:                                               | <b>2021-11-25</b>                        |                                                                                       |
| <b>Auftraggeber:</b><br>Client:                                                                                                                                                                                                                                                                                                                                                                                                                             | <b>Autel Intelligent Tech. Corp., Ltd.</b><br>7th-8th, 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd. Xili, Nanshan, Shenzhen, 518055, China |                                                                                    |                                          |                                                                                       |
| <b>Prüfgegenstand:</b><br>Test item:                                                                                                                                                                                                                                                                                                                                                                                                                        | <b>AUTOMOTIVE DIAGNOSTIS &amp; ANALYSIS SYSTEM</b>                                                                                       |                                                                                    |                                          |                                                                                       |
| <b>Bezeichnung / Typ-Nr.:</b><br>Identification / Type no.:                                                                                                                                                                                                                                                                                                                                                                                                 | <b>MaxiCOM MK808BT, MaxiDAS DS808BT, MaxiPRO MP808BT</b><br>(Trademark: AUTEL)                                                           |                                                                                    |                                          |                                                                                       |
| <b>Auftrags-Inhalt:</b><br>Order content:                                                                                                                                                                                                                                                                                                                                                                                                                   | <b>Test Report</b>                                                                                                                       |                                                                                    |                                          |                                                                                       |
| <b>Prüfgrundlage:</b><br>Test specification:                                                                                                                                                                                                                                                                                                                                                                                                                | <b>CFR47 FCC Part 15: Subpart C Section 15.247</b>                                                                                       |                                                                                    |                                          |                                                                                       |
| <b>Wareneingangsdatum:</b><br>Date of sample receipt:                                                                                                                                                                                                                                                                                                                                                                                                       | <b>2022-01-28</b>                                                                                                                        | <b>Please refer to Photo Document</b>                                              |                                          |                                                                                       |
| <b>Prüfmuster-Nr.:</b><br>Test sample no:                                                                                                                                                                                                                                                                                                                                                                                                                   | <b>A003191554-005~006</b><br><b>A003191554-017</b>                                                                                       |                                                                                    |                                          |                                                                                       |
| <b>Prüfzeitraum:</b><br>Testing period:                                                                                                                                                                                                                                                                                                                                                                                                                     | <b>2022-02-23 – 2022-03-08</b>                                                                                                           |                                                                                    |                                          |                                                                                       |
| <b>Ort der Prüfung:</b><br>Place of testing:                                                                                                                                                                                                                                                                                                                                                                                                                | <b>TÜV Rheinland (Shenzhen) Co., Ltd.</b>                                                                                                |                                                                                    |                                          |                                                                                       |
| <b>Prüflaboratorium:</b><br>Testing laboratory:                                                                                                                                                                                                                                                                                                                                                                                                             | <b>TÜV Rheinland (Shenzhen) Co., Ltd.</b>                                                                                                |                                                                                    |                                          |                                                                                       |
| <b>Prüfergebnis*:</b><br>Test result*:                                                                                                                                                                                                                                                                                                                                                                                                                      | <b>Pass</b>                                                                                                                              |                                                                                    |                                          |                                                                                       |
| <b>geprüft von:</b><br>tested by:                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                       |                                                                                    | <b>genehmigt von:</b><br>authorized by:  |  |
| <b>Datum:</b><br>Date:                                                                                                                                                                                                                                                                                                                                                                                                                                      | <b>2022-08-25</b>                                                                                                                        | <small>Signed by: Breeze Jiang</small>                                             | <b>Ausstellungsdatum:</b><br>Issue date: | <b>2022-08-25</b>                                                                     |
| <b>Stellung / Position:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>Assistant Project Manager</b>                                                                                                         |                                                                                    | <b>Stellung / Position:</b>              | <b>Reviewer</b>                                                                       |
| <b>Sonstiges / Other:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                   | <b>FCC ID: WQ8-MK808BT</b>                                                                                                               |                                                                                    |                                          |                                                                                       |
| <b>Zustand des Prüfgegenstandes bei Anlieferung:</b><br>Condition of the test item at delivery:                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                          | <b>Prüfmuster vollständig und unbeschädigt</b><br>Test item complete and undamaged |                                          |                                                                                       |
| <p>* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft<br/>P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet</p> <p>* Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor<br/>P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested</p>            |                                                                                                                                          |                                                                                    |                                          |                                                                                       |
| <p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b><br/>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</p> |                                                                                                                                          |                                                                                    |                                          |                                                                                       |

## ***Test Summary***

**5.1.1 ANTENNA REQUIREMENT**

*RESULT: Pass*

**5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER**

*RESULT: Pass*

**5.1.3 99% BANDWIDTH**

*RESULT: Pass*

**5.1.4 20dB BANDWIDTH**

*RESULT: Pass*

**5.1.5 CARRIER FREQUENCY SEPARATION**

*RESULT: Pass*

**5.1.6 NUMBER OF HOPPING FREQUENCY**

*RESULT: Pass*

**5.1.7 TIME OF OCCUPANCY**

*RESULT: Pass*

**5.1.8 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH**

*RESULT: Pass*

**5.1.9 RADIATED SPURIOUS EMISSION**

*RESULT: Pass*

**5.1.10 CONDUCTED EMISSION**

*RESULT: Pass*

## **Contents**

|               |                                                                         |           |
|---------------|-------------------------------------------------------------------------|-----------|
| <b>1</b>      | <b>GENERAL REMARKS .....</b>                                            | <b>4</b>  |
| <b>1.1</b>    | <b>COMPLEMENTARY MATERIALS .....</b>                                    | <b>4</b>  |
| <b>2</b>      | <b>TEST SITES .....</b>                                                 | <b>5</b>  |
| <b>2.1</b>    | <b>TEST FACILITIES .....</b>                                            | <b>5</b>  |
| <b>2.2</b>    | <b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>                    | <b>5</b>  |
| <b>2.3</b>    | <b>TRACEABILITY .....</b>                                               | <b>6</b>  |
| <b>2.4</b>    | <b>CALIBRATION .....</b>                                                | <b>6</b>  |
| <b>2.5</b>    | <b>MEASUREMENT UNCERTAINTY.....</b>                                     | <b>6</b>  |
| <b>2.6</b>    | <b>LOCATION OF ORIGINAL DATA.....</b>                                   | <b>6</b>  |
| <b>2.7</b>    | <b>STATUS OF FACILITY USED FOR TESTING.....</b>                         | <b>6</b>  |
| <b>3</b>      | <b>GENERAL PRODUCT INFORMATION .....</b>                                | <b>7</b>  |
| <b>3.1</b>    | <b>PRODUCT FUNCTION AND INTENDED USE.....</b>                           | <b>7</b>  |
| <b>3.2</b>    | <b>RATINGS AND SYSTEM DETAILS .....</b>                                 | <b>7</b>  |
| <b>3.3</b>    | <b>INDEPENDENT OPERATION MODES .....</b>                                | <b>8</b>  |
| <b>3.4</b>    | <b>NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>               | <b>9</b>  |
| <b>3.5</b>    | <b>SUBMITTED DOCUMENTS.....</b>                                         | <b>9</b>  |
| <b>4</b>      | <b>TEST SET-UP AND OPERATION MODES .....</b>                            | <b>10</b> |
| <b>4.1</b>    | <b>PRINCIPLE OF CONFIGURATION SELECTION .....</b>                       | <b>10</b> |
| <b>4.2</b>    | <b>TEST OPERATION AND TEST SOFTWARE .....</b>                           | <b>10</b> |
| <b>4.3</b>    | <b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>                | <b>10</b> |
| <b>4.4</b>    | <b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE .....</b>                  | <b>10</b> |
| <b>4.5</b>    | <b>TEST SETUP DIAGRAM .....</b>                                         | <b>11</b> |
| <b>5</b>      | <b>TEST RESULTS .....</b>                                               | <b>13</b> |
| <b>5.1</b>    | <b>TRANSMITTER REQUIREMENT &amp; TEST SUITES .....</b>                  | <b>13</b> |
| <b>5.1.1</b>  | <i>Antenna Requirement .....</i>                                        | <i>13</i> |
| <b>5.1.2</b>  | <i>Maximum Peak Conducted Output Power .....</i>                        | <i>14</i> |
| <b>5.1.3</b>  | <i>99% Bandwidth .....</i>                                              | <i>15</i> |
| <b>5.1.4</b>  | <i>20dB Bandwidth .....</i>                                             | <i>16</i> |
| <b>5.1.5</b>  | <i>Carrier Frequency Separation.....</i>                                | <i>17</i> |
| <b>5.1.6</b>  | <i>Number of Hopping Frequency .....</i>                                | <i>18</i> |
| <b>5.1.7</b>  | <i>Time of Occupancy .....</i>                                          | <i>19</i> |
| <b>5.1.8</b>  | <i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth .....</i> | <i>20</i> |
| <b>5.1.9</b>  | <i>Radiated Spurious Emission .....</i>                                 | <i>21</i> |
| <b>5.1.10</b> | <i>Conducted Emission .....</i>                                         | <i>22</i> |
| <b>6</b>      | <b>PHOTOGRAPHS OF THE TEST SET-UP .....</b>                             | <b>23</b> |
| <b>7</b>      | <b>LIST OF TABLES.....</b>                                              | <b>23</b> |

# 1 General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of FCC Part 15C

## 2 Test Sites

### 2.1 Test Facilities

**TÜV Rheinland (Shenzhen) Co., Ltd.**

362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China

FCC Registration No.: 694916

ISED wireless device testing laboratory: 25069

### 2.2 List of Test and Measurement Instruments

**Table 1: List of Test and Measurement Equipment**

| <b>Radio Spectrum Testing (SRD-Tonscend)</b>   |                     |                   |                   |                   |
|------------------------------------------------|---------------------|-------------------|-------------------|-------------------|
| <b>Equipment</b>                               | <b>Manufacturer</b> | <b>Model</b>      | <b>Serial No.</b> | <b>Cal. until</b> |
| EXA Signal Analyzer, Multi-touch               | Keysight            | N9010B            | MY60241175        | 2022-09-28        |
| MXG X-Series RF Vector Signal Generator        | Keysight            | N5182B            | MY61250137        | 2022-09-28        |
| EXG X-Series Microwave Analog Signal Generator | Keysight            | N5173B            | MY61250141        | 2022-09-28        |
| DC power supply                                | Keysight            | E3642A            | MY61276100        | 2022-09-28        |
| Power Control Unit                             | Tonscend            | JS0806-4ADC       | N/A               | 2022-09-28        |
| Automation Control Unit                        | Tonscend            | JS0806-2          | 21C8060396        | 2022-09-28        |
| Test Software                                  | Tonscend            | JS1120-3          | N/A               | N/A               |
| Control PC                                     | Lenovo              | TianYi510S-071MB  | Y LX23JMF         | N/A               |
| <b>Unwanted Emission Testing (TS9975)</b>      |                     |                   |                   |                   |
| <b>Equipment</b>                               | <b>Manufacturer</b> | <b>Model</b>      | <b>Serial No.</b> | <b>Cal. until</b> |
| EMI Test Receiver                              | R&S                 | ESR 7             | 102021            | 2022-08-10        |
| Signal Analyzer                                | R&S                 | FSV 40            | 101439            | 2022-08-09        |
| System Controller Interface                    | R&S                 | SCI-100           | S10010038         | N/A               |
| Filterbank                                     | R&S                 | Wlan              | 100759            | 2022-08-09        |
| OSP                                            | R&S                 | OSP 120           | 102040            | N/A               |
| Pre-amplifier                                  | R&S                 | SCU08F1           | 08320031          | 2022-08-09        |
| Amplifier                                      | R&S                 | SCU-18F           | 180070            | 2022-08-09        |
| Amplifier                                      | R&S                 | SCU40A            | 100475            | 2022-08-09        |
| Trilog Broadband Antenna (30 MHz - 7 GHz)      | Schwarzbeck         | VULB 9162         | 193               | 2022-08-08        |
| Double-Ridged Antenna (1 -18 GHz)              | ETS-LINDGREN        | 3117              | 00218717          | 2022-08-08        |
| Wideband Ridged Horn Antenna (18-40 GHz)       | Steatite            | QMS-00880         | 19067             | 2022-08-08        |
| Active Loop Antenna                            | Schwarzbeck         | FMZB 1513         | 302               | 2022-09-13        |
| Test software                                  | R&S                 | EMC32 (V10.60.10) | N/A               | N/A               |
| Control PC                                     | Dell                | OptiPlex 7050     | 36NV9P2           | N/A               |
| 3m Semi-Anechoic Chamber                       | Albatross           | SAC-3m            | APC17151-SAC      | 2024-06-22        |

**Prüfbericht - Nr.: CN22YF1T 001**  
*Test Report No.:*

Seite 6 von 23  
Page 6 of 23

| <b>Conducted Emission</b> |                     |                     |                   |                   |
|---------------------------|---------------------|---------------------|-------------------|-------------------|
| <b>Equipment</b>          | <b>Manufacturer</b> | <b>Model No.</b>    | <b>Serial No.</b> | <b>Cal. Until</b> |
| EMI Test Receiver         | R&S                 | ESR3                | 102680            | 2022-08-10        |
| Artificial Mains Network  | R&S                 | ENV216              | 101445            | 2022-08-10        |
| EMC32 test software       | R&S                 | EMC32(Ver.10.50.00) | N/A               | N/A               |

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

| <b>Parameter</b>                                       | <b>Uncertainty</b>            |
|--------------------------------------------------------|-------------------------------|
| Radio Frequency                                        | $\pm 1 \times 10^{-7}$        |
| RF Power (conducted)                                   | $\pm 2.5$ dB                  |
| Radiated Emission of Transmitter, valid up to 26.5 GHz | $\pm 6$ dB                    |
| Radiated Emission of Receiver, valid up to 26.5 GHz    | $\pm 6$ dB                    |
| Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz) | $\pm 3.70$ dB / $\pm 3.30$ dB |
| Temperature                                            | $\pm 1$ °C                    |
| Humidity                                               | $\pm 5$ %                     |
| Voltage (DC)                                           | $\pm 1$ %                     |
| Voltage (AC, <10kHz)                                   | $\pm 2$ %                     |

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

## 2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

## 3 General Product Information

### 3.1 Product Function and Intended Use

The EUT is AUTOMOTIVE DIAGNOSTIS & ANALYSIS SYSTEM which supports Bluetooth and 2.4GHz Wi-Fi wireless technology.

All models are identical except model no. difference for market strategy.

Note:1. 2.4G Bluetooth all test data in this report.  
2. 2.4G Bluetooth and 2.4GHz Wi-Fi to simultaneous transmitting test data with Radiated Spurious Emission and Peak Conducted Output Power

For details refer to the User Manual, Technical Description and Circuit Diagram.

### 3.2 Ratings and System Details

Table 2: Technical Specification of EUT

| General Information of EUT                    | Value                                                                                      |
|-----------------------------------------------|--------------------------------------------------------------------------------------------|
| Kind of Equipment:                            | AUTOMOTIVE DIAGNOSTIS & ANALYSIS SYSTEM                                                    |
| Type Designation:                             | MaxiCOM MK808BT, MaxiDAS DS808BT, MaxiPRO MP808BT                                          |
| Trademark:                                    | AUTEL                                                                                      |
| FCC ID:                                       | WQ8-MK808BT                                                                                |
| Operating Voltage:                            | AC 100~240V, 50/60Hz input via Power Adapter<br>DC 3.7V@5000mAh input via internal battery |
| Testing Voltage:                              | Fully charged battery                                                                      |
| Power Adapter:                                | Model: GME10C-050200FUu<br>Input: 100~240V, 50/60Hz, 0.28A<br>Output: DC 5V@2A             |
| Operating Temperature Range:                  | 0 °C ~ +55 °C                                                                              |
| Technical Specification of Bluetooth BDR/EDR  |                                                                                            |
| Operating Frequency:                          | 2402 MHz to 2480 MHz                                                                       |
| Type of Modulation:                           | GFSK(BDR), $\pi/4$ -DQPSK(EDR), 8DPSK(EDR)                                                 |
| Channel Number:                               | 79 channels                                                                                |
| Channel Separation:                           | 1MHz                                                                                       |
| Antenna Type:                                 | Ceramic Antenna                                                                            |
| Antenna Gain:                                 | 0.5 dBi                                                                                    |
| Technical Specification of Wi-Fi 802.11 b/g/n |                                                                                            |
| Operating Frequency:                          | 2412 - 2462 MHz for 802.11b/g/n(HT20)<br>2422 - 2452 MHz for 802.11n(HT40)                 |
| Type of Modulation:                           | DSSS(DBPSK/DQPSK/CCK)<br>OFDM(BPSK/QPSK/16QAM/64QAM)                                       |
| Channel Number:                               | 11 channels                                                                                |
| Channel Separation:                           | 5MHz                                                                                       |
| Antenna Type:                                 | Integral Antenna                                                                           |
| Antenna Gain:                                 | -0.9 dBi                                                                                   |

**Table 3: RF Channel and Frequency of Bluetooth BDR/EDR**

| RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) |
|------------|-----------------|------------|-----------------|------------|-----------------|------------|-----------------|
| <b>0</b>   | <b>2402.00</b>  | 20         | 2422.00         | 40         | 2442.00         | 60         | 2462.00         |
| 1          | 2403.00         | 21         | 2423.00         | 41         | 2443.00         | 61         | 2463.00         |
| 2          | 2404.00         | 22         | 2424.00         | 42         | 2444.00         | 62         | 2464.00         |
| 3          | 2405.00         | 23         | 2425.00         | 43         | 2445.00         | 63         | 2465.00         |
| 4          | 2406.00         | 24         | 2426.00         | 44         | 2446.00         | 64         | 2466.00         |
| 5          | 2407.00         | 25         | 2427.00         | 45         | 2447.00         | 65         | 2467.00         |
| 6          | 2408.00         | 26         | 2428.00         | 46         | 2448.00         | 66         | 2468.00         |
| 7          | 2409.00         | 27         | 2429.00         | 47         | 2449.00         | 67         | 2469.00         |
| 8          | 2410.00         | 28         | 2430.00         | 48         | 2450.00         | 68         | 2470.00         |
| 9          | 2411.00         | 29         | 2431.00         | 49         | 2451.00         | 69         | 2471.00         |
| 10         | 2412.00         | 30         | 2432.00         | 50         | 2452.00         | 70         | 2472.00         |
| 11         | 2413.00         | 31         | 2433.00         | 51         | 2453.00         | 71         | 2473.00         |
| 12         | 2414.00         | 32         | 2434.00         | 52         | 2454.00         | 72         | 2474.00         |
| 13         | 2415.00         | 33         | 2435.00         | 53         | 2455.00         | 73         | 2475.00         |
| 14         | 2416.00         | 34         | 2436.00         | 54         | 2456.00         | 74         | 2476.00         |
| 15         | 2417.00         | 35         | 2437.00         | 55         | 2457.00         | 75         | 2477.00         |
| 16         | 2418.00         | 36         | 2438.00         | 56         | 2458.00         | 76         | 2478.00         |
| 17         | 2419.00         | 37         | 2439.00         | 57         | 2459.00         | 77         | 2479.00         |
| 18         | 2420.00         | 38         | 2440.00         | 58         | 2460.00         | 78         | <b>2480.00</b>  |
| 19         | 2421.00         | 39         | <b>2441.00</b>  | 59         | 2461.00         |            |                 |

Test frequencies are lowest channel: 2402 MHz, middle channel: 2441 MHz and highest channel: 2480 MHz for Bluetooth.

### 3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth transmitting mode
  - 1) Low Channel
  - 2) Middle Channel
  - 3) High Channel
- B. On, Transmitting on Hopping channel
- C. On, Normal Operation(BT Link)
- D. Off



## 3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

## 3.5 Submitted Documents

- |                              |                         |
|------------------------------|-------------------------|
| - User Manual                | - Operation Description |
| - Block Diagram              | - Schematics            |
| - PCB Layout                 | - Parts List            |
| - ID Label and Location Info |                         |

## 4 Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

**Radio Spectrum:** The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013.

### 4.3 Special Accessories and Auxiliary Equipment

Table 4: Auxiliary Equipment Used during Test

| Description | Manufacturer | Model | S/N       |
|-------------|--------------|-------|-----------|
| Laptop      | Lenovo       | T480  | PF-16A6N8 |

### 4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

## 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)







Diagram of Measurement Configuration for Radiation Test (Above 1GHz)



### Diagram of Measurement Configuration for Conducted Transmitter Measurement



### Diagram of Measurement Configuration for Mains Conduction Measurement



## 5 Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

RESULT:

Pass

**Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has an ceramic antenna, the directional gain of antenna is 0.5 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

**Prüfbericht - Nr.: CN22YF1T 001**
*Test Report No.:*

Seite 14 von 23

Page 14 of 23

## 5.1.2 Maximum Peak Conducted Output Power

**RESULT:**
**Pass**
**Test Specification**

Test standard : FCC Part 15.247(b)(1)  
 Basic standard : ANSI C63.10: 2013  
 Limits : FHSS < 0.125 Watts  
 Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2022-02-23 to 2022-03-07  
 Input voltage : Fully charged battery  
 Operation mode : A  
 Test channel : Low / Middle / High  
 Ambient temperature : 24.8 °C  
 Relative humidity : 51 %  
 Atmospheric pressure : 101 kPa

**Table 5: Test Result of Maximum Peak Conducted Output Power**
**Bluetooth BDR/EDR**

| Test Mode              | Test Channel (MHz) | Measured Peak Power |        | Limit (W) |
|------------------------|--------------------|---------------------|--------|-----------|
|                        |                    | (dBm)               | (W)    |           |
| GFSK (BDR)             | 2402.0             | 1.84                | 0.0015 | < 0.125   |
|                        | 2441.0             | 4.09                | 0.0026 |           |
|                        | 2480.0             | 3.75                | 0.0024 |           |
| Maximum Measured Value |                    | 4.09                | 0.0026 |           |

| Test Mode              | Test Channel (MHz) | Measured Peak Power |        | Limit (W) |
|------------------------|--------------------|---------------------|--------|-----------|
|                        |                    | (dBm)               | (W)    |           |
| 8DPSK (EDR)            | 2402.0             | -2.10               | 0.0006 | < 0.125   |
|                        | 2441.0             | 0.17                | 0.0010 |           |
|                        | 2480.0             | -0.32               | 0.0009 |           |
| Maximum Measured Value |                    | 0.17                | 0.0010 |           |

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): 0.5 dBi

**2.4G Wi-Fi**

| Test Mode              | Test Channel (MHz) | Measured Peak Power |       | Limit (W) |
|------------------------|--------------------|---------------------|-------|-----------|
|                        |                    | (dBm)               | (W)   |           |
| TX 802.11b             | 2412.0             | 15.81               | 0.038 | < 1.0     |
|                        | 2437.0             | 15.86               | 0.039 |           |
|                        | 2462.0             | 15.43               | 0.035 |           |
| Maximum Measured Value |                    | 15.86               | 0.039 |           |

Antenna gain(G): -0.9 dBi

Remarks: This WiFi power (max. power) less than GTS original report No.: GTSL202101000019F03

**Prüfbericht - Nr.: CN22YF1T 001**

Test Report No.:

Seite 15 von 23

Page 15 of 23

### 5.1.3 99% Bandwidth

**RESULT:****Pass****Test Specification**

|                   |                      |
|-------------------|----------------------|
| Test standard     | : FCC Part 15.247(a) |
| Basic standard    | : ANSI C63.10: 2013  |
| Kind of test site | : Shielded Room      |

**Test Setup**

|                      |                         |
|----------------------|-------------------------|
| Date of testing      | : 2022-03-07            |
| Input voltage        | : Fully charged battery |
| Operation mode       | : A                     |
| Test channel         | : Low / Middle / High   |
| Ambient temperature  | : 24.8 °C               |
| Relative humidity    | : 51 %                  |
| Atmospheric pressure | : 101 kPa               |

For the measurement records, refer to the appendix B.

**Prüfbericht - Nr.: CN22YF1T 001**

Test Report No.:

Seite 16 von 23

Page 16 of 23

### 5.1.4 20dB Bandwidth

**RESULT:****Pass****Test Specification**

|                   |                         |
|-------------------|-------------------------|
| Test standard     | : FCC Part 15.247(a)(1) |
| Basic standard    | : ANSI C63.10: 2013     |
| Kind of test site | : Shielded Room         |

**Test Setup**

|                      |                         |
|----------------------|-------------------------|
| Date of testing      | : 2022-03-07            |
| Input voltage        | : Fully charged battery |
| Operation mode       | : A                     |
| Test channel         | : Low / Middle / High   |
| Ambient temperature  | : 24.8 °C               |
| Relative humidity    | : 51 %                  |
| Atmospheric pressure | : 101 kPa               |

For the measurement records, refer to the appendix B.



**Prüfbericht - Nr.: CN22YF1T 001**

Test Report No.:

Seite 17 von 23

Page 17 of 23

### 5.1.5 Carrier Frequency Separation

**RESULT:****Pass****Test Specification**

|                   |                                                                      |
|-------------------|----------------------------------------------------------------------|
| Test standard     | : FCC Part 15.247(a)(1)                                              |
| Basic standard    | : ANSI C63.10: 2013                                                  |
| Limits            | : $\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth, whichever is greater |
| Kind of test site | : Shielded Room                                                      |

**Test Setup**

|                      |                         |
|----------------------|-------------------------|
| Date of testing      | : 2022-03-07            |
| Input voltage        | : Fully charged battery |
| Operation mode       | : B                     |
| Test channel         | : Low / Middle / High   |
| Ambient temperature  | : 24.8 °C               |
| Relative humidity    | : 51 %                  |
| Atmospheric pressure | : 101 kPa               |

For the measurement records, refer to the appendix B.

**Prüfbericht - Nr.: CN22YF1T 001**

Test Report No.:

Seite 18 von 23

Page 18 of 23

### 5.1.6 Number of Hopping Frequency

**RESULT:****Pass****Test Specification**

|                   |                                      |
|-------------------|--------------------------------------|
| Test standard     | : FCC part 15.247(a)(1)(iii)         |
| Basic standard    | : ANSI C63.10: 2013                  |
| Limits            | : $\geq 15$ non-overlapping channels |
| Kind of test site | : Shielded Room                      |

**Test Setup**

|                      |                         |
|----------------------|-------------------------|
| Date of testing      | : 2022-03-07            |
| Input voltage        | : Fully charged battery |
| Operation mode       | : B                     |
| Ambient temperature  | : 24.8 °C               |
| Relative humidity    | : 51 %                  |
| Atmospheric pressure | : 101 kPa               |

For the measurement records, refer to the appendix B.

**Prüfbericht - Nr.: CN22YF1T 001**

Test Report No.:

Seite 19 von 23

Page 19 of 23

### 5.1.7 Time of Occupancy

**RESULT:****Pass****Test Specification**

|                   |                              |
|-------------------|------------------------------|
| Test standard     | : FCC part 15.247(a)(1)(iii) |
| Basic standard    | : ANSI C63.10: 2013          |
| Limits            | : < 0.4s                     |
| Kind of test site | : Shielded Room              |

**Test Setup**

|                      |                         |
|----------------------|-------------------------|
| Date of testing      | : 2022-03-07            |
| Input voltage        | : Fully charged battery |
| Operation mode       | : B                     |
| Test channel         | : Low / Middle / High   |
| Ambient temperature  | : 24.8 °C               |
| Relative humidity    | : 51 %                  |
| Atmospheric pressure | : 101 kPa               |

For the measurement records, refer to the appendix B.

**Prüfbericht - Nr.: CN22YF1T 001**

Test Report No.:

Seite 20 von 23

Page 20 of 23

**5.1.8 Conducted Spurious Emissions Measured in 100 kHz Bandwidth****RESULT:****Pass****Test Specification**

|                   |                                                                                                                                                                                                                                                                    |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test standard     | : FCC Part 15.247(d)                                                                                                                                                                                                                                               |
| Basic standard    | : ANSI C63.10: 2013                                                                                                                                                                                                                                                |
| Limits            | : 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power);<br>In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a) |
| Kind of test site | : Shielded Room                                                                                                                                                                                                                                                    |

**Test Setup**

|                      |                         |
|----------------------|-------------------------|
| Date of testing      | : 2022-03-07            |
| Input voltage        | : Fully charged battery |
| Operation mode       | : A                     |
| Test channel         | : Low / Middle / High   |
| Ambient temperature  | : 24.8 °C               |
| Relative humidity    | : 51 %                  |
| Atmospheric pressure | : 101 kPa               |

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

**Prüfbericht - Nr.: CN22YF1T 001**

Test Report No.:

Seite 21 von 23

Page 21 of 23

### 5.1.9 Radiated Spurious Emission

**RESULT:****Pass****Test Specification**

|                   |                                            |
|-------------------|--------------------------------------------|
| Test standard     | : FCC Part 15.247(d) & FCC Part 15.205     |
| Basic standard    | : ANSI C63.10: 2013                        |
| Limits            | : Refer to 15.209(a) of FCC part 15.247(d) |
| Kind of test site | : 3m Semi-anechoic Chamber                 |

**Test Setup**

|                      |                         |
|----------------------|-------------------------|
| Date of testing      | : 2022-03-08            |
| Input voltage        | : Fully charged battery |
| Operation mode       | : A                     |
| Test channel         | : Low / Middle / High   |
| Ambient temperature  | : Refer to test result  |
| Relative humidity    | : Refer to test result  |
| Atmospheric pressure | : 101 kPa               |

**Remark:**

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B.

**Prüfbericht - Nr.: CN22YF1T 001**

Test Report No.:

Seite 22 von 23

Page 22 of 23

**5.1.10 Conducted Emission****RESULT:****Pass****Test Specification**

|                   |                      |
|-------------------|----------------------|
| Test standard     | : FCC Part 15.207(a) |
| Basic standard    | : ANSI C63.10: 2013  |
| Frequency range   | : 0.15 – 30MHz       |
| Limits            | : FCC Part 15.207(a) |
| Kind of test site | : Shielded Room      |

**Test Setup**

|                      |                        |
|----------------------|------------------------|
| Date of testing      | : 2022-05-12           |
| Input voltage        | : AC 120V, 60Hz        |
| Operation mode       | : C                    |
| Earthing             | : Not connected        |
| Ambient temperature  | : Refer to test result |
| Relative humidity    | : Refer to test result |
| Atmospheric pressure | : 101 kPa              |

For the measurement records, refer to the appendix B.

## 6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

## 7 List of Tables

|                                                                   |    |
|-------------------------------------------------------------------|----|
| Table 1: List of Test and Measurement Equipment.....              | 5  |
| Table 2: Technical Specification of EUT.....                      | 7  |
| Table 3: RF Channel and Frequency of Bluetooth BDR/EDR.....       | 8  |
| Table 4: Auxiliary Equipment Used during Test .....               | 10 |
| Table 5: Test Result of Maximum Peak Conducted Output Power ..... | 14 |