RF Exposure Report				
	FCC ID: 2A2BY-SU9A			
Report No.	: SSP24120052-2E			
Applicant	: Dongguan Huien Electronic Technology Co., Ltd			
Product Name	: <u>TWS</u>			
Model Name	: <u>SU9A</u>			
Test Standard	: FCC CFR 47 PART 2.1093			
Date of Issue	: 2025-01-06			
	CCUT			
She	enzhen CCUT Quality Technology Co., Ltd.			
1F, Building 35, Changxing Teo Guangdong, China;	chnology Industrial Park, Yutang Street, Guangming District, Shenzhen, (Tel.:+86-755-23406590 website: www.ccuttest.com)			
This test report is limited to the a without prior p	bove client company and the product model only. It may not be duplicated ermitted by Shenzhen CCUT Quality Technology Co., Ltd.			

Test Report Basic Information

Applicant: Address of Applicant	Dongguan Huien Electronic Technology Co., Ltd Room 301, Building of 1, No. 429, Changdong Road, Changping Town, Dongguan city, Guangdong Province, China				
Manufacturer: Address of Manufacturer:	Dongguan Huien Electronic Technology Co., Ltd Room 301, Building of 1, No. 429, Changdong Road, Changping Town, Dongguan city, Guangdong Province, China				
Product Name	TWS				
Brand Name:	-				
Main Model	SU9A				
Series Models	L8 ProA				
Test Standard Date of Test Test Result	FCC CFR 47 PART 2.1093 KDB 447498 D01 v06 2024-12-06 to 2024-12-13 PASSED				
Tested By:	Walker Walker Wu) St Quality Technic				
Reviewed By	Lieber Ougang (Lieber Ouyang)				
Authorized Signatory	Lahm Peng (Lahm Peng)				
Note : This test report is limited duplicated without prior permit this test report is only applicabl	to the above client company and the product model only. It may not be ted by Shenzhen CCUT Quality Technology Co., Ltd All test data presented in e to presented test sample.				

CONTENTS

1. General Information	5
1.1 Product Information	5
1.2 Test Facilities	5
2. RF Exposure	6
2.1 Standard and Limit	6
2.2 Test Procedure	6
2.3 Test Data and Results	7

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2025-01-06	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	TWS		
Trade Name:	-		
Main Model:	SU9A		
Series Models:	L8 ProA		
Rated Voltage:	DC 3.7V by battery, USB 5V charging		
Battery:	DC 3.7V, 470mAh		
Test Sample No:	SSP24120052-1		
Hardware Version:	V1.2		
Software Version:	V241		
Note 1: The test data is gathered from a production sample, provided by the manufacturer.			

Note 2: The headphone case shape and model name of the listed models differ from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.

Wireless Specification				
Wireless Standard:	Bluetooth BLE			
Operating Frequency:	2402MHz ~2480MHz			
RF Output Power:	1.61dBm			
Antenna Gain:	2.78dBi			
Type of Antenna:	SMD Antenna			
Type of Device:	Portable Device Device Mobile Device			

1.2 Test Facilities

	Shenzhen CCUT Quality Technology Co., Ltd.				
Laboratory Name:	1F, Building 35, Changxing Technology Industrial Park, Yutang Street,				
	Guangming District, Shenzhen, Guangdong, China				
CNAS Laboratory No.:	L18863				
A2LA Certificate No.:	6893.01				
FCC Registration No:	583813				
ISED Registration No.:	CN0164				
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing					
Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.					

2. RF Exposure

2.1 Standard and Limit

3.0 for 1g SAR.

2.2 Test Procedure

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.

To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures.

When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion.

When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions.

a) For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] • [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

b) For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B):

1) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance - 50 mm)·(f(MHz)/150)]} mW, for 100 MHz to 1500 MHz

2) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance – 50 mm) \cdot 10]} mW, for > 1500 MHz and ≤ 6 GHz

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(MHz))]$

2) For test separation distances $\leqslant 50$ mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$

3) SAR measurement procedures are not established below 100 MHz.

When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any SAR test results below 100 MHz to be acceptable.

2.3 Test Data and Results

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

For BLE

Max	Tune-up	Max	Max		Min	Calc	
Conducted	Power(dBm)	Tune-up	Power(mW)	Frequency(MHz)	distance(mm)	thresholds	limit
Power(dBm)		Power(dBm)			usance(iiiii)	tillesiloids	
1.61	1(±1)	2	1.585	2402	5	0.4913	3.0

So a SAR test is not required