

TEST REPORT

Reference No...... : WTU24D09222550W002
FCC ID : 2AOTUKDH144
Applicant..... : Changzhou Kaidi Electrical Inc.
Address..... : Jiangcun, Henglin Town, 213101, Changzhou City , Jiangsu Province, China
Manufacturer : Changzhou Kaidi Electrical Inc.
Address..... : Jiangcun, Henglin Town, 213101, Changzhou City , Jiangsu Province, China
Product..... : Handset
Model(s) : KDH144
Standards..... : FCC 47CFR Part 2 Subpart J Section 2.1093
Date of Receipt sample : 2024-09-25
Date of Test : 2024-09-26 to 2024-10-10
Date of Issue..... : 2024-10-18
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

James Cheng

James Cheng / Project Engineer

Approved by:

Deval Qin
The stamp is a circular blue ink seal. The outer ring contains the text 'WALTEK TESTING GROUP CO., LTD.' at the top and 'TEST REPORT' at the bottom. In the center, there is a stylized 'W' logo with the word 'WALTEK' underneath it.

Deval Qin / Designated Reviewer

2. Contents

	Page
1 COVER PAGE.....	1
2. CONTENTS.....	2
3. REVISION HISTORY.....	3
4. GENERAL INFORMATION.....	4
4.1. GENERAL DESCRIPTION OF E.U.T.....	4
4.2. DETAILS OF E.U.T.	4
4.3. TEST FACILITY	5
4.4. SUBCONTRACTED	5
4.5. ABNORMALITIES FROM STANDARD CONDITIONS	5
5. TEST SUMMARY	6
6. RF EXPOSURE.....	7
6.1. PROCEDURES AND REQUIREMENTS	7
6.2. MPE CALCULATION METHOD.....	7
6.3. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION.....	7

3. Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTU24D09222550W002	2024-09-25	2024-09-26 to 2024-10-10	2024-10-18	Original	-	Valid

4. General Information

4.1. General Description of E.U.T.

Product:	Handset
Model(s):	KDH144
Model Description:	N/A
Test Sample No.:	1-1/1
Hardware Version:	V00
Software Version:	V00

4.2. Details of E.U.T.

Frequency Range:	2420MHz
Type of Modulation:	GFSK
Antenna installation:	PCB Antenna
Antenna Gain:	3.64dBi

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.

Ratings: Input: DC 4.5V by 1.5V*3 batteries

4.3. Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.4. Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.5. Abnormalities from Standard Conditions

None.

5. Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC Part 2.1093	PASS

6. RF Exposure

Test Requirement: FCC 47CFR Part 2 Subpart J Section 2.1093
 Evaluation Method: FCC 47CFR Part 1 Subpart I Section 1.1307,
 KDB 447498 D01 General RF Exposure Guidance v06

6.1. Procedures and Requirements

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

6.2. MPE Calculation Method

$$\text{Result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

6.3. Radio Frequency Radiation Exposure Evaluation

According to ANSI C63.10:2013 clause 9.5

Calculate the EIRP from the radiated field strength in the far field using Equation (22):

$$\text{EIRP} = E_{\text{Meas}} + 20 \log(d_{\text{Meas}}) - 104.7 \quad (22)$$

where

EIRP	is the equivalent isotropically radiated power, in dBm
E_{Meas}	is the field strength of the emission at the measurement distance, in dB μ V/m
d_{Meas}	is the measurement distance, in m

NOTE—Because this equation yields the identical result whether the field strength is extrapolated using the default 20 dB/decade of distance extrapolation factor, or the field strength is not extrapolated for distance, this equation can generally be applied directly (with no further correction) to determine EIRP. In some cases, a different distance correction factor may be required; see 9.1.

Frequency(MHz)	E-Field Strength (dBuV/m)	Measurement Distance (m)	EIRP (dBm)
2420	83.5	3	-11.66

A distance of 5mm normally can be maintained between the user and the device.

Frequency (GHz)	Antenna Gain (dBi)	Max Power (dBm)	Max Tune-up Power (dBm)	Max Tune-up Power (mW)	Distance (mm)	Result	Limit
2.42	3.64	-15.30	-14.30	0.04	5	0.0116	3

Note:

1. EIRP (dBm)= Max Power (dBm) +G(dBi).
2. Chose the maximum power to do MPE analysis.

Conclusion:

No SAR measurement is required.

=====End of Report=====