

# RF Exposure Evaluation Report

**Product** : Door sensor  
**Trade mark** :   
**Model/Type reference** : 77-S108  
**Serial Number** : N/A  
**Report Number** : EED32P81743002  
**FCC ID** : 2ASKH-BT02  
**Date of Issue** : Dec. 08, 2023  
**Test Standards** : 47 CFR Part 1.1307  
47 CFR Part 1.1310  
47 CFR Part 2.1091  
47 CFR Part 2.1093  
KDB 447498 D04 Interim General RF  
Exposure Guidance v01  
**Test result** : PASS

Prepared for:

**PHILLIPS CONNECT TECHNOLOGIES LLC**  
**5231 California Avenue, Suite 110 Irvine California 92617 United States**

Prepared by:

**Centre Testing International Group Co., Ltd.**  
**Hongwei Industrial Zone, Bao'an 70 District,**  
**Shenzhen, Guangdong, China**  
**TEL: +86-755-3368 3668**  
**FAX: +86-755-3368 3385**

Compiled by:

*Frazer Li*

Frazer Li

Reviewed by:

*Tom Chen*

Tom Chen

Approved by:

*Aaron Ma*

Aaron Ma

Date:

Dec. 08, 2023



Check No.: 9715131023

2 Version

| Version No. | Date          | Description |
|-------------|---------------|-------------|
| 00          | Dec. 08, 2023 | Original    |
|             |               |             |
|             |               |             |

3 Contents

|                                                             | Page |
|-------------------------------------------------------------|------|
| 1 COVER PAGE .....                                          | 1    |
| 2 VERSION .....                                             | 2    |
| 3 CONTENTS .....                                            | 3    |
| 4 GENERAL INFORMATION .....                                 | 4    |
| 4.1 CLIENT INFORMATION .....                                | 4    |
| 4.2 GENERAL DESCRIPTION OF EUT .....                        | 4    |
| 4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD ..... | 4    |
| 4.4 TEST LOCATION .....                                     | 5    |
| 4.5 DEVIATION FROM STANDARDS .....                          | 5    |
| 4.6 ABNORMALITIES FROM STANDARD CONDITIONS .....            | 5    |
| 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....       | 5    |
| 5 SAR EVALUATION .....                                      | 6    |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....                | 6    |
| 5.1.1 Limits .....                                          | 6    |
| 5.1.2 Test Procedure .....                                  | 6    |
| 5.1.3 EUT RF Exposure Evaluation .....                      | 7    |

## 4 General Information

### 4.1 Client Information

|                          |                                                                         |
|--------------------------|-------------------------------------------------------------------------|
| Applicant:               | PHILLIPS CONNECT TECHNOLOGIES LLC                                       |
| Address of Applicant:    | 5231 California Avenue, Suite 110 Irvine California 92617 United States |
| Manufacturer:            | PHILLIPS CONNECT TECHNOLOGIES LLC                                       |
| Address of Manufacturer: | 5231 California Avenue, Suite 110 Irvine California 92617 United States |
| Factory:                 | PHILLIPS CONNECT TECHNOLOGIES LLC                                       |
| Address of Factory:      | 5231 California Avenue, Suite 110 Irvine California 92617 United States |

### 4.2 General Description of EUT

|                 |                                                                                   |
|-----------------|-----------------------------------------------------------------------------------|
| Product Name:   | Door sensor                                                                       |
| Model No.(EUT): | 77-S108                                                                           |
| Trade Mark:     |  |

### 4.3 Product Specification subjective to this standard

|                       |                                                                                                                                                                                              |         |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| Frequency Range:      | 2402MHz~2480MHz                                                                                                                                                                              |         |
| Modulation Type:      | GFSK                                                                                                                                                                                         |         |
| Test Power Grade:     | Default                                                                                                                                                                                      |         |
| Test Software of EUT: | nRF Connect for Desktop.exe                                                                                                                                                                  |         |
| Antenna Type:         | Internal Antenna                                                                                                                                                                             |         |
| Antenna Gain:         | 2.37dBi                                                                                                                                                                                      |         |
| Power Supply:         | Battery:                                                                                                                                                                                     | DC 3.6V |
| Sample Received Date: | Nov. 07, 2023                                                                                                                                                                                |         |
| Sample tested Date:   | Nov. 07, 2023 to Nov. 10, 2023                                                                                                                                                               |         |
| Remark:               | Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified. |         |

## 4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

## 4.5 Deviation from Standards

None.

## 4.6 Abnormalities from Standard Conditions

None.

## 4.7 Other Information Requested by the Customer

None.

## 5 SAR Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

**5.1.3 EUT RF Exposure Evaluation****For Stand alone:****For BLE**

| Frequency<br>(MHz) | Max. Conducted Output power<br>(dBm) | Antenna Gain<br>(dBi) | EIRP<br>(dBm) | ERP<br>(dBm) | ERP<br>(mW) | Limit<br>(mW) | Result |
|--------------------|--------------------------------------|-----------------------|---------------|--------------|-------------|---------------|--------|
| 2402               | -0.67                                | 2.37                  | 1.70          | -0.45        | 0.902       | ≤2.788        | PASS   |

**Note:**

①EIRP=conducted power+antenna gain;

②ERP=EIRP-2.15

③The test data refer to the report of EED32P81743001, and only the worst case data was recorded in the report.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

**\*\*\* End of Report \*\*\***