

# **TEST REPORT**

Report No.: BCTC2304220658E

Applicant: Dongguan OSM Digital Co., Ltd

Product Name: Vlogging Tripod

Model/Type Ref.: Oth-AB216

Tested Date: 2023-04-06 to 2023-04-20

Issued Date: 2023-04-20

Shenzhen BCTC Testing Co., Ltd.



No.: BCTC/RF-EMC-005 Page: 1 of 43 / / / Édition: A.5



## **FCC ID: 2A6KA-AB216**

**Product Name:** Vlogging Tripod

**SEAJIC** Trademark:

Oth-AB216

Oth-AB216B, Oth-AB216Max, Oth-AB216Max+, Oth-AB403E, Oth-AB202, Model/Type Ref.:

Oth-AB202B, Oth-AB202C, AB202D, AB202E, AB202F, AB202G, Oth-AB202Max,

Oth-AB202PRO

Prepared For: Dongguan OSM Digital Co., Ltd

501, Building 2, No.6 Tiansha Road, Keyuan City, Tangxia Town, Dong guan City, Address:

China

Manufacturer: Dongguan OSM Digital Co., Ltd

501, Building 2, No.6 Tiansha Road, Keyuan City, Tangxia Town, Dong guan City, Address:

China

Prepared By: Shenzhen BCTC Testing Co., Ltd.

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Address:

Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2023-04-06

Sample tested Date: 2023-04-06 to 2023-04-20

Issue Date: 2023-04-20

Report No .: BCTC2304220658E

FCC Part15.247 Test Standards:

ANSI C63.10-2013

**PASS** Test Results:

Remark: This is Bluetooth BLE radio test report.

Tested by:

Lei Chen/Project Handler

Approved by:

Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Edition: A.5 No.: BCTC/RF-EMC-005 Page: 2 of 43



## **Table Of Content**

Test	Report Declaration	Page
1.	Version	5
2.	Test Summary	
3.	Measurement Uncertainty	
4.	Product Information And Test Setup	8
4.1	Product Information	
4.2	Test Setup Configuration	8
4.4	Channel List	
4.5	Test Mode	
4.6	Table Of Parameters Of Text Software Setting	10
5.	Test Facility And Test Instrument Used	
5.1	Test Facility	
5.2	Test Instrument Used	
6.	Conducted Emissions	13
6.1	Block Diagram Of Test Setup	13
6.2	Limit	
6.3	Test Procedure	13
6.4	EUT Operating Conditions	
6.5	Test Result	
7.	Radiated Emissions	16
7.1	Block Diagram Of Test Setup	
7.2	Limit	
7.3	Test Procedure	18
7.4	EUT Operating Conditions	
7.5	Test Result	
8.	Radiated Band Emission Measurement And Restricted Bands Of Oper	ation23
8.1	Block Diagram Of Test Setup	
8.2	Limit	
8.3	Test Procedure	24
8.4	EUT operating Conditions	24
8.5	Test Result	25
9.	Power Spectral Density Test	
9.1	Block Diagram Of Test Setup Limit Test Procedure EUT Operating Conditions	
9.2	Limit	26
9.3	Test Procedure	26
9.4	EUT Operating Conditions	26
u h	LAST RASHIT	• • • • • • • • • • • • • • • • • • • •
10.	Randwidth Lest	- 76
10.1	Block Diagram Of Test SetupLimit	29
10.2	Limit	29
10.3	Test Procedure EUT Operating Conditions Test Result	29
10.4	EUT Operating Conditions	29
10.5	Test Result	30
11.	Peak Output Power Test	32
11.1	Block Diagram Of Test Setup	32












11.2	Limit	32
11.3	Test Procedure	32
11.4	EUT Operating Conditions	32
11.5	Test Result	32
12.	100 KHz Bandwidth Of Frequency Band Edge	33
12.1	Block Diagram Of Test Setup	33
12.2	Limit	33
12.3	Test Procedure	33
12.4	EUT Operating Conditions	33
12.5	Test Result	34
13.	Antenna Requirement	39
13.1	Limit	39
13.2	Test Result	39
14.	EUT Photographs	40
15.	EUT Test Setup Photographs	41

(Note: N/A Means Not Applicable)



No.: BCTC/RF-EMC-005


Page: 4 of 43

Edition: A.5



## 1. Version

Report No.	Issue Date	Description	Approved
BCTC2304220658E	2023-04-20	Original	Valid




No.: BCTC/RF-EMC-005 Page: 5 of 43



## 2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No	Results
1	Conducted Emission	15.207	PASS
2	6dB Bandwidth	15.247 (a)(2)	PASS
3	Peak Output Power	15.247 (b)	PASS
4	Radiated Spurious Emission	15.247 (d), 15.205	PASS
5	Power Spectral Density	15.247 (e)	PASS
6	Restricted Band of Operation	15.205	PASS
7	Band Edge (Out of Band Emissions)	15.247(d)	PASS
8	Antenna Requirement	15.203	PASS



No.: BCTC/RF-EMC-005 Page: 6 of 43 // Edition



## 3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission(150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	Ü=0.59°C

No.: BCTC/RF-EMC-005 Page: 7 of 43 // Edition: A.5





### 4. Product Information And Test Setup

#### 4.1 Product Information

Oth-AB216

Model/Type Ref.: Oth-AB216B, Oth-AB216Max, Oth-AB216Max+, Oth-AB203E, Oth-AB202, Oth AB203E, AB202E, A

Oth-AB202B, Oth-AB202C, AB202D, AB202E, AB202F, AB202G, Oth-AB202Max,

Oth-AB202PRO

Model differences: All the model are the same circuit and RF module, except model names.

Bluetooth Version: 4.2 Hardware Version: V1 Software Version: V1

Operation Frequency: 2402-2480MHz

Type of Modulation: GFSK Number Of Channel 40CH

Antenna installation: PCB antenna


Antenna Gain: 0 dBi

Ratings: USB: DC5V, Battery: DC 3.7V


#### 4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

Conducted Emission:



Radiated Spurious Emission:



No.: BCTC/RF-EMC-005 Page: 8 of 43

Edition: A.5



## 4.3 Support Equipment

Report No.: BCTC	C2304220658E
------------------	--------------

No.	Device Type	Brand	Model	Series No.	Note
E-1	Vlogging Tripod	SEAJIC	Oth-AB216	N/A	EUT
E-2	Adapter	N/A	BCTC001	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.5M	DC cable unshielded

#### Notes:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

#### 4.4 Channel List

Channel List						
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
01	2402	11	2422	21	2442	
02	2404	12	2424	22	2444	
03	2406	13	2426	23	2446	
~	~	~	~	~	~	
09	2418	19	2438	39	2478	
10	2420	20	2440	40	2480	

#### 4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For All Mode	Description	Modulation Type		
Mode 1	CH01			
Mode 2	CH20	GFSK		
Mode 3	CH40			
Mode 4 Charging (Conducted emission)				
Mode 5	Link mode ( Radiated emission)			

#### Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Fully-charged battery is used during the test

No.: BCTC/RF-EMC-005 Page: 9 of 43 / / / Édition: A.5










## 4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Test software Version	MxdBleMPTool				
Frequency	2402 MHz	2440 MHz	2480 MHz		
Parameters	DEF	DEF	DEF		



No.: BCTC/RF-EMC-005 Page: 10 of 43



### 5. Test Facility And Test Instrument Used

## 5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850 A2LA certificate registration number is: CN1212

ISED Registered No.: 23583 ISED CAB identifier: CN0017

#### 5.2 Test Instrument Used

Conducted Emissions Test						
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.	
Receiver	R&S	ESR3	102075	May 24, 2022	May 23, 2023	
LISN	R&S	ENV216	101375	May 24, 2022	May 23, 2023	
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\	
Attenuator	\	10dB DC-6GHz	1650	May 24, 2022	May 23, 2023	

RF Conducted Test						
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.	
Power Metter	Keysight	E4419	\	May 24, 2022	May 23, 2023	
Power Sensor (AV)	Keysight	E9300A	1	May 24, 2022	May 23, 2023	
Signal Analyzer20kH z-26.5GHz	Keysight	N9020A	MY49100060	May 24, 2022	May 23, 2023	
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	100363	May 24, 2022	May 23, 2023	
Radio frequency control box	MAIWEI	MW100-RFC B	\		\	
Software	MAIWEI	MTS 8310	,,,,,,,,,,		\	

No.: BCTC/RF-EMC-005 Page: 11 of 43 / / / Edition: A.5






Radiated Emissions Test (966 Chamber01)						
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.	
966 chamber	ChengYu	966 Room	966	Jun. 06. 2020	Jun. 05, 2023	
Receiver	R&S	ESR3	102075	May 24, 2022	May 23, 2023	
Receiver	R&S	ESRP	101154	May 24, 2022	May 23, 2023	
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 24, 2022	May 23, 2023	
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 26, 2022	May 25, 2023	
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 26, 2022	May 25, 2023	
Amplifier	SKET	LAPA_01G18 G-45dB	\	May 24, 2022	May 23, 2023	
Horn Antenna	Schwarzbeck	BBHA9120D	1541	Jun. 06, 2022	Jun. 05, 2023	
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35- HG	2034381	May 26, 2022	May 25, 2023	
Horn Antenna(18G Hz-40GHz)	Schwarzbeck	BBHA9170	00822	Jun. 06, 2022	Jun. 05, 2023	
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	100363	May 24, 2022	May 23, 2023	
Software	Frad	EZ-EMC	FA-03A2 RE	\	. \	

No.: BCTC/RF-EMC-005 Page: 12 of 43 / Edition A.5



#### 6. Conducted Emissions

### 6.1 Block Diagram Of Test Setup



#### 6.2 Limit

EDEOLIENCY (MHz)	Limit (	dBuV)
FREQUENCY (MHz)	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

#### Notes

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The lower limit shall apply at the transition frequencies.

#### 6.3 Test Procedure

Setting
10 dB
0.15 MHz
30 MHz
9 kHz

- a. The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- b. The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- c. For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

#### 6.4 EUT Operating Conditions


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

No.: BCTC/RF-EMC-005 Page: 13 of 43 / / / / Edition: A.5



#### 6.5 Test Result

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4



#### Remark:


- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.
- 3. Measurement=Reading Level+ Correct Factor
- 4. Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.1500	11.01	19.67	30.68	66.00	-35.32	QP
2		0.1500	-8.23	19.67	11.44	56.00	-44.56	AVG
3	*	0.7273	13.22	19.74	32.96	56.00	-23.04	QP
4		0.7273	-0.16	19.74	19.58	46.00	-26.42	AVG
5		1.1844	1.20	19.78	20.98	56.00	-35.02	QP
6		1.1844	-12.53	19.78	7.25	46.00	-38.75	AVG
7		2.1783	-0.97	19.90	18.93	56.00	-37.07	QP
8		2.1783	-13.09	19.90	6.81	46.00	-39.19	AVG
9		6.3859	5.61	20.16	25.77	60.00	-34.23	QP
10		6.3859	-7.28	20.16	12.88	50.00	-37.12	AVG
11	1	3.6952	-1.62	20.28	18.66	60.00	-41.34	QP
12	1	3.6952	-13.61	20.28	6.67	50.00	-43.33	AVG

Page: 14 of 43 No.: BCTC/RF-EMC-005 Edition: A.5



Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4



#### Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Factor = Insertion Loss + Cable Loss.
- 3. Measurement=Reading Level+ Correct Factor
- 4. Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.3116	5.06	19.77	24.83	59.93	-35.10	QP
2		0.3116	-7.81	19.77	11.96	49.93	-37.97	AVG
3	*	0.7508	10.12	19.74	29.86	56.00	-26.14	QP
4		0.7508	-4.60	19.74	15.14	46.00	-30.86	AVG
5		1.2621	-1.07	19.79	18.72	56.00	-37.28	QP
6		1.2621	-12.69	19.79	7.10	46.00	-38.90	AVG
7		2.4218	-1.79	19.93	18.14	56.00	-37.86	QP
8		2.4218	-12.31	19.93	7.62	46.00	-38.38	AVG
9		6.2189	6.34	20.16	26.50	60.00	-33.50	QP
10		6.2189	-8.29	20.16	11.87	50.00	-38.13	AVG
11		13.6952	-2.53	20.28	17.75	60.00	-42.25	QP
12		13.6952	-14.35	20.28	5.93	50.00	-44.07	AVG

No.: BCTC/RF-EMC-005 Page: 15 of 43 // / Edition A.5

,TC

3C







#### 7. Radiated Emissions

## 7.1 Block Diagram Of Test Setup

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



No.: BCTC/RF-EMC-005 Page: 16 of 43 / / / Edition A.5



## (C) Radiated Emission Test-Up Frequency Above 1GHz



#### 7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency	Field Strength	Distance	Field Strength Lir	mit at 3m Distance
(MHz)	uV/m	(m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log <sup>(2400/F(kHz))</sup> + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log <sup>(24000/F(kHz))</sup> + 40
1.705 ~ 30	30	30	100 * 30	20log <sup>(30)</sup> + 40
30 ~ 88	100	3	100	20log <sup>(100)</sup>
88 ~ 216	150	3	150	20log <sup>(150)</sup>
216 ~ 960	200	3	200	20log <sup>(200)</sup>
Above 960	500	3	500	20log <sup>(500)</sup>

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY	Limit (dBuV/m) (at 3M)				
(MHz)	PEAK	AVERAGE			
Above 1000	74	54			

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

No.: BCTC/RF-EMC-005 Page: 17 of 43 / / / / Edition: A.5





#### FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

#### 7.3 Test Procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Spectrum Parameter	Setting		
1-25GHz	RBW 1 MHz /VBW 1 MHz for Peak, RBW 1 MHz / VBW 10Hz for Average		

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre( Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

No.: BCTC/RF-EMC-005 Page: 18 of 43 / / / / Edition: A.5



Above 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

### 7.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

#### 7.5 Test Result

#### Below 30MHz

Temperature:	<b>26</b> ℃	Relative Humidity:	24%
Pressure:	101 kPa	Test Voltage :	DC 3.7V
Test Mode:	Mode 5	Polarization :	

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

#### Note

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);


Limit line = specific limits(dBuv) + distance extrapolation factor.

No.: BCTC/RF-EMC-005 Page: 19 of 43 / / / Edition: A.5



#### Between 30MHz - 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Test Voltage :	AC 120V/60Hz
Test Mode:	Mode 5	Polarization :	Horizontal



#### Remark:


- 1. Factor = Antenna Factor + Cable Loss Pre-amplifier.
- 2. Measurement=Reading Level+ Correct Factor
- 3. Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		47.6586	25.32	-15.85	9.47	40.00	-30.53	QP
2		104.1701	27.30	-18.03	9.27	43.50	-34.23	QP
3		152.6641	34.85	-20.85	14.00	43.50	-29.50	QP
4		250.3012	31.65	-15.82	15.83	46.00	-30.17	QP
5		300.3672	29.63	-14.57	15.06	46.00	-30.94	QP
6	*	432.5457	40.13	-11.74	28.39	46.00	-17.61	QP

No.: BCTC/RF-EMC-005 Page: 20 of 43 / / /Edition A.5



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Test Voltage :	AC 120V/60Hz
Test Mode:	Mode 5	Polarization :	Vertical



#### Remark:

- Factor = Antenna Factor + Cable Loss Pre-amplifier.
   Measurement=Reading Level+ Correct Factor
   Over=Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		50.0566	32.51	-15.60	16.91	40.00	-23.09	QP
2		60.9176	34.29	-17.35	16.94	40.00	-23.06	QP
3		99.8777	35.45	-17.78	17.67	43.50	-25.83	QP
4		158.6677	38.37	-20.41	17.96	43.50	-25.54	QP
5	•	434.0651	38.05	-11.72	26.33	46.00	-19.67	QP
6	*	890.7278	34.32	-4.69	29.63	46.00	-16.37	QP

Page: 21 of 43 No.: BCTC/RF-EMC-005 Edition: A.5





#### Between 1GHz - 25GHz

			GFSK								
Polar	Frequency	Reading Level		Measure- ment	Limits	Over	Detector				
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	Туре				
Low channel											
V	4804.00	52.72	-0.43	52.29	74.00	-21.71	PK				
V	4804.00	42.29	-0.43	41.86	54.00	-12.14	AV				
V	7206.00	44.12	8.31	52.43	74.00	-21.57	PK				
V	7206.00	33.69	8.31	42.00	54.00	-12.00	AV				
Н	4804.00	48.91	-0.43	48.48	74.00	-25.52	PK				
Н	4804.00	39.56	-0.43	39.13	54.00	-14.87	AV				
Н	7206.00	43.01	8.31	51.32	74.00	-22.68	PK				
Н	7206.00	34.38	8.31	42.69	54.00	-11.31	AV				
			Middle char	nnel							
V	4880.00	50.16	-0.38	49.78	74.00	-24.22	PK				
V	4880.00	43.02	-0.38	42.64	54.00	-11.36	AV				
V	7320.00	39.99	8.83	48.82	74.00	-25.18	PK				
V	7320.00	30.01	8.83	38.84	54.00	-15.16	AV				
Н	4880.00	47.30	-0.38	46.92	74.00	-27.08	PK				
Н	4880.00	36.89	-0.38	36.51	54.00	-17.49	AV				
Н	7320.00	37.43	8.83	46.26	74.00	-27.74	PK				
Н	7320.00	30.13	8.83	38.96	54.00	-15.04	AV				
			High chan	nel							
V	4960.00	51.26	-0.32	50.94	74.00	-23.06	PK				
V	4960.00	42.92	-0.32	42.60	54.00	-11.40	AV				
V	7440.00	43.77	9.35	53.12	74.00	-20.88	PK				
V	7440.00	34.44	9.35	43.79	54.00	-10.21	AV				
Н	4960.00	48.42	-0.32	48.10	74.00	-25.90	PK				
Н	4960.00	39.42	-0.32	39.10	54.00	-14.90	AV				
Н	7440.00	42.19	9.35	51.54	74.00	-22.46	PK				
Н	7440.00	34.95	9.35	44.30	54.00	-9.70	AV				

#### Remark

1.Emission Level = Meter Reading + Factor,

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Over= Emission Level - Limit

2.If peak below the average limit, the average emission was no test.

3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB

No.: BCTC/RF-EMC-005 Page: 22 of 43 / / / Edition A.5








<sup>4.</sup> The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



## 8. Radiated Band Emission Measurement And Restricted Bands Of Operation

## 8.1 Block Diagram Of Test Setup

Radiated Emission Test-Up Frequency Above 1GHz



#### 8.2 Limit

#### FCC Part15 C Section 15.209 and 15.205

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

No.: BCTC/RF-EMC-005 Page: 23 of 43 / / / / Edition: A.5





#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY	Limit (dBuV/m) (at 3M)			
(MHz)	PEAK	AVERAGE		
Above 1000	74	54		

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3)Emission level (dBuV/m)=20log Emission level (uV/m).

#### 8.3 Test Procedure

Receiver Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Above 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

## 8.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

No.: BCTC/RF-EMC-005 Page: 24 of 43 / / / Edition A.5



#### 8.5 Test Result

	Polar (H/V)	Frequency Reading Level		Correct Factor	Measure- ment (dBuV/m)	Lim (dBu		Result
	(11/4)	(11112)	(dBuV/m)	(dB)	PK	PK	AV	
			Lov	v Channel 24	402MHz			
	Н	2390.00	53.04	-6.70	46.34	74.00	54.00	PASS
	Н	2400.00	56.97	-6.71	50.26	74.00	54.00	PASS
	V	2390.00	53.75	-6.70	47.05	74.00	54.00	PASS
GFSK	V	2400.00	57.00	-6.71	50.29	74.00	54.00	PASS
OI SIX	High Channel 2480MHz							
	Н	2483.50	56.50	-6.79	49.71	74.00	54.00	PASS
	Н	2500.00	51.49	-6.81	44.68	74.00	54.00	PASS
	V	2483.50	57.56	-6.79	50.77	74.00	54.00	PASS
	V	2500.00	52.98	-6.81	46.17	74.00	54.00	PASS

#### Remark:

1. Emission Level = Meter Reading + Factor, Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Over= Emission Level - Limit

- 2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.
- 3 In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
- 4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Page: 25 of 43 Edition: A.5 No.: BCTC/RF-EMC-005



## 9. Power Spectral Density Test

## 9.1 Block Diagram Of Test Setup

EUT	SPECTRUM
	ANALYZER

#### 9.2 Limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

#### 9.3 Test Procedure

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS bandwidth.
- 3. Set the RBW to: 3 kHz
- 4. Set the VBW  $\geq$  3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

## 9.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4	4.6 Unless otherwise a special operating
condition is specified in the follows during the testing.	
Note: Power Spectral Density(dBm)=Reading+Cable Loss	


No.: BCTC/RF-EMC-005 Page: 26 of 43 / / / Edition A.5



#### 9.5 Test Result

Temperature :	26℃	Relative Humidity:	54%
Test Mode :	GFSK	Test Voltage :	DC 3.7V

	Frequency	Power Spectral Density(dBm/3kHz)	Limit (dBm/3kHz)	Result
	2402 MHz	-15.2	8	PASS
GFSK	2440 MHz	-14.84	8	PASS
	2480 MHz	-14.18	8	PASS



No.: BCTC/RF-EMC-005 Page: 27 of 43 // Edition A.5

,TC

3C









No.: BCTC/RF-EMC-005 Page: 28 of 43 / / / /Edition: A.5



#### 10. Bandwidth Test

## 10.1 Block Diagram Of Test Setup



## 10.2 Limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

#### 10.3 Test Procedure

- 1. Set RBW = 100 kHz.
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 10.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Note: Power Spectral Density(dBm)=Reading+Cable Loss

No.: BCTC/RF-EMC-005 Page: 29 of 43 / / /Edition: A.5






#### 10.5 Test Result

Temperature :	26℃	Relative Humidity:	54%
Test Mode :	GFSK	Test Voltage :	DC 3.7V


	Frequency (MHz)	-6dB bandwidth (MHz)	Limit (kHz)	Result
	2402	0.652	500	Pass
GFSK	2440	0.649	500	Pass
	2480	0.689	500	Pass




No.: BCTC/RF-EMC-005 Page: 30 of 43 // Edition A.5









No.: BCTC/RF-EMC-005 Page: 31 of 43 / / / Edition A.5



### 11. Peak Output Power Test

## 11.1 Block Diagram Of Test Setup

POWER METER

#### 11.2 Limit

FCC Part15 (15.247), Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

#### 11.3 Test Procedure

a. The EUT was directly connected to the Power meter

## 11.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Note: Power Spectral Density(dBm)=Reading+Cable Loss

#### 11.5 Test Result

Temperature :	26℃	Relative Humidity:	54%
Test Mode :	GFSK	Test Voltage :	DC 3.7V

	Frequency	Maximum Conducted Output Power(PK)	Conducted Output Power Limit
	(MHz)	(dBm)	dBm
	2402	-2.27	30
GFSK	2440	-2.24	30
	2480	-2.22	30

No.: BCTC/RF-EMC-005 Page: 32 of 43 / / / Edition A.5



#### 12. 100 KHz Bandwidth Of Frequency Band Edge

## 12.1 Block Diagram Of Test Setup

EUT	SPECTRUM
	ANALYZER

#### 12.2 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### 12.3 Test Procedure

Using the following spectrum analyzer setting:

- a) Set the RBW = 100KHz.
- b) Set the VBW = 300KHz.
- c) Sweep time = auto couple.
- d) Detector function = peak.
- e) Trace mode = max hold.
- Allow trace to fully stabilize..

### 12.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Note: Power Spectral Density(dBm)=Reading+Cable Loss

,TC


3C

781

差测





#### 12.5 Test Result



No.: BCTC/RF-EMC-005 Page: 34 of 43 / / / /Edition: A.5









No.: BCTC/RF-EMC-005 Page: 35 of 43 / / / Edition: A.5




#### Tx. Spurious






No.: BCTC/RF-EMC-005 Page: 36 of 43 / / / / Edition: A.5









No.: BCTC/RF-EMC-005 Page: 37 of 43 / / / Edition: A.5







No.: BCTC/RF-EMC-005 Page: 38 of 43 / / / Edition: A.5




## 13. Antenna Requirement

#### 13.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 13.2 Test Result

The EUT antenna is PCB antenna, Antenna Gain is 0dBi, fulfill the requirement of this section.



No.: BCTC/RF-EMC-005 Page: 39 of 43




## 14. EUT Photographs

**EUT Photo** 



NOTE: Appendix-Photographs Of EUT Constructional Details





No.: BCTC/RF-EMC-005



## 15. EUT Test Setup Photographs

## **Conducted Emissions Photo**






No.: BCTC/RF-EMC-005 Page: 41 of 43 // / Edition A.5

ES FC



## **Radiated Measurement Photos**





No.: BCTC/RF-EMC-005 Page: 42 of 43 // Edition A.5



#### **STATEMENT**

- 1. The equipment lists are traceable to the national reference standards.
- 2. The test report can not be partially copied unless prior written approval is issued from our lab.
- 3. The test report is invalid without the "special seal for inspection and testing".
- 4. The test report is invalid without the signature of the approver.
- 5. The test process and test result is only related to the Unit Under Test.
- 6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
- 7. The test report without CMA mark is only used for scientific research, teaching, enterprise product development and internal quality control purposes.
- 8. The quality system of our laboratory is in accordance with ISO/IEC17025.
- 9. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

#### Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

**BCTC** 

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com

E-Mail: bctc@bctc-lab.com.cn

\*\*\*\* END \*\*\*\*

No.: BCTC/RF-EMC-005 Page: 43 of 43 / / Edition A.5