

## Setup photos for HAC RF Emissions and T-Coil Test Report

Test report no.:	HAC_Photo_RM-983_03	Date of report:	2014-07-25
Template version:	3.2	Number of pages:	3
Testing laboratory:	TCC Microsoft Salo Laboratory P.O.Box 86 Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220	Client:	Microsoft 16620 West Bernardo Drive SAN DIEGO CA. 92127 USA Tel. +1 858 831 5000 Fax. +1 858 831 6500
Responsible test engineer:	Janne Hirsimäki	Product contact person:	Victoria Abadilla
Measurements made by:	Janne Hirsimäki		
Tested devices:	RM-983 (Hearing aid mode active)		
FCC ID:	QMNRM-983	IC:	-
Supplement reports:	RF_RM-983_01, T-Coil_RM-983_02		
Testing has been carried out in accordance with:	<b>ANSI C63.19-2011</b> American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test results:	<b>The tested device complies with the requirements in respect of all parameters subject to the test.</b> The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		

### Date and signatures:

For the contents:

---

## CONTENTS

1.1	PICTURE OF DEVICE .....	3
1.2	TEST POSITIONS.....	3
1.2.1	<i>Scan area centered at the acoustic output.....</i>	<i>3</i>

---

## 1.1 Picture of Device



## 1.2 Test Positions

### 1.2.1 Scan area centered at the acoustic output

The device was positioned such that Device Reference plane was touching the bottom of the Test Arch. The scan is centered at the acoustic output by aligning the acoustic output with the intersection of the Test Arch's middle bar and dielectric wire.




Photo of the device positioned under Test Arch