



中国认可
国际互认
检测
TESTING
CNAS L0310



FCC SAR Exemption Evaluation Report

Product Name: Smart Watch

Model: FTN-B19

Report No.: SYBH(Z-SAR)20180808013001-2

FCC ID: QISFTN-B19

	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	<i>Wei Huanbin</i>	<i>ou jwong</i>
DATE	2018-08-28	2018-08-28

Reliability Laboratory of Huawei Technologies Co., Ltd.

(Global Compliance and Testing Center of Huawei Technologies Co., Ltd)

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang
District, Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518

※ ※ **Notice** ※ ※

1. The laboratory has passed the accreditation by China National Accreditation Service for Conformity Assessment (CNAS). The accreditation number is L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01 & 2174.02 & 2174.03
3. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named as “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.
4. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
5. The test report is invalid if there is any evidence of erasure and/or falsification.
6. The test report is only valid for the test samples.
7. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

※ ※ Modified History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
v1.0	Initial Test Report Release	2018-08-28	Ou Junsong

Table of Contents

1	EUT Description	5
1.1	General Description	5
2	Test specification(s).....	6
3	Testing laboratory	6
4	Applicant and Manufacturer	6
5	Application details.....	6
6	Ambient Condition	6
7	RF Exposure Limits	7
8	SAR Exemption Evaluation	8

1 EUT Description

Device Information:			
Product Name :	Smart Watch		
Model :	FTN-B19		
FCC ID:	QISFTN-B19		
Device Type :	Portable Device		
Device Phase:	Identical Prototype		
Exposure Category:	Uncontrolled environment/general population		
Hardware Version :	309000121206R2		
Software Version :	1.0.0.10		
Antenna Type :	Internal Antenna		
Device Operating Configurations:			
Supporting Mode(s)	BT		
Test Modulation	GFSK		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	BT	2400-2483.5	2400-2483.5
	NFC	NA	13.56

1.1 General Description

FTN-B19 is a Smart Watch, it can be communicated with mobile phone via Bluetooth. FTN-B19 also support alarm clock, intelligent user can judge the state of motion, scientific sleep monitoring, information assistance, heart rate monitoring, GPS functionalities and NFC pay function.

Battery information:

Name	Manufacture	Model name	Description
Lithium ion secondary rechargeable battery	LISHEN	HB512627ECW+	Li-ion Polymer Battery Capacity:410mA/h Rated Voltage:3.82V Cutoff Voltage:4.4V DischargeVoltage:3.0V Size:28.6mm*26.1mm*5.1mm
	ATL		

2 Test specification(s)

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991)
KDB 447498 D01	General RF Exposure Guidance v06

3 Testing laboratory

Test Site	The Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	NO.2 New City Avenue Songshan Lake Sci.&Tech.Industry Park, Dongguan ,Guangdong ,P.R.C
Telephone	+86 755 28780808
Fax	+86 755 89652518
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01& 2174.02 & 2174.03

4 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

5 Application details

Start Date of test	2018-08-28
End Date of test	2018-08-28

6 Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

7 RF Exposure Limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain/Body/Arms/Legs)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Table 1: RF exposure limits

The limit applied in this test report is shown in **bold** letters.

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.

8 SAR Exemption Evaluation

Per FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Exposure Condition	Band	P_{max} (dBm)*	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	Exclusion threshold	SAR evaluation
10-g Extremity	BT	5.00	3.16	<5	2.48	1.00	7.50	Not required

Table 2: Standalone SAR test exclusion for BT

Note:

- 1)*- Maximum possible output power (including tune-up tolerance) declared by manufacturer
- 2) The test separation distance for 10-g Extremity exposure is ≤ 5 mm, so a distance of 5 mm is applied to determine SAR test exclusion per FCC KDB 447498D01.
- 3) The device does not support voice speaker mode. So Next-to-Mouth Exposure SAR test for BT is not required.

According to the table above, the device can meet the SAR test exclusion thresholds requirement of FCC KDB 447498 D01 and SAR evaluation is not required.

End