

FCC Part 15C

Measurement and Test Report

For

Shenzhen Qianhai Patuoxun Network & Technology co., ltd

Wuhe RD 49#, Bantian District B-202, 6th Building Shenzhen Guandong CN

FCC ID: 2AOXY-PC230A-1

FCC Rule(s):	<u>FCC Part 15.249</u>
Product Description:	<u>Wireless mouse</u>
Tested Model:	<u>PC230A-1</u>
Report No.:	<u>WTE19X01002252W</u>
Sample Receipt Date:	<u>2019-01-10</u>
Tested Date:	<u>2019-01-10 to 2019-01-15</u>
Issued Date:	<u>2019-01-15</u>
Tested By:	<u>Mike Shi / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	

Mike Shi

Silin Chen

Jandy So

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 MEASUREMENT UNCERTAINTY.....	6
1.7 TEST EQUIPMENT LIST AND DETAILS.....	7
2. SUMMARY OF TEST RESULTS.....	8
3. ANTENNA REQUIREMENTS.....	9
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
4. RADIATED EMISSIONS.....	10
4.1 STANDARD APPLICABLE.....	10
4.2 TEST PROCEDURE.....	10
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	12
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	12
5. OUT OF BAND EMISSIONS.....	21
5.1 STANDARD APPLICABLE.....	21
5.2 TEST PROCEDURE.....	21
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	21
6. EMISSION BANDWIDTH.....	24
6.1 STANDARD APPLICABLE.....	24
6.2 TEST PROCEDURE.....	24
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	24

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Qianhai Patuoxun Network&Technology co., Ltd
Address of applicant: Wuhe RD 49#, Bantian District B-202, 6th Building Shenzhen Guangdong CN
Manufacturer: Dongguan Couso Technology Co., Ltd
Address of manufacturer: No. 26 Minye Road, TangXia Town, DongGuan City, GuangDong, China

General Description of EUT	
Product Name:	Wireless mouse
Trade Name:	/
Model No.:	PC230A-1
Adding Model(s):	CS1000G, CS2000G, CS3000G, CS4000G, CS4100G, CS4200G, CS4300G, CS4400G, CS4500G, CS4550G, CS4600G, CS4700G, CS4800G, CS4900G, CS5000G, CS5100G, CS5200G, CS5300G, CS5400G, CS5500G, CS5600G, CS5700G, CS5800G, CS5900G, CS6000G, CS6100G, CS6200G, CS6300G, CS6400G, CS6500G, CS6600G, CS6700G, CS6800G, CS6900G, CS7000G, CS7100G, CS7200G, CS7300G, CS7400G, CS7500G, CS7600G, CS7700G, CS7800G, CS7900G, CS8000G, CS8100G, CS8200G, CS8300G, CS8400G, CS8500G, CS8600G, CS8700G, CS8800G, CS8900G, CS9000G, CS9100G, CS9200G, CS9300G, CS9400G, CS9500G, CS9600G, CS9700G, CS9800G, CS9900G, CX100, CX120, CX130, CX140, CX150, CX160, CX170, CX180, CX190, CK410B, CK910B, CS9100L, CS9200L, CK470TL, CS4570G, CS4380G, CK400G, CK410G, CK420G, CK430G, CK440G, CK450G, CK455G, CK465G, CK460G, CK470T, CK480G, CK490G, CK500G, CK510G, CK520G, CK530G, CK540G, CK550G, CK560G, CK570G, CK580G, CK590G, CK600G, CK601G, CK700G, CK710G, CK720G, CK730G, CK740G, CK750G, CK760G, CK770G, CK780G, CK790G, CK900G, CK910G, CK920G, CK921G, CK923G, CK927G, CK930G, CK940G, CK950G, CK960G, CK970G, CK980G, CK990G, CG16G, CM610G, CM611G, CM612G, CM613G, CM614G, CM615G, CM616G, CM617G, CM618G, CM619G, CM620G, CM621G, CM622G, CM623G, CM624G, CM625G, CM626G, CM627G, CM628G, CM629G, CM630G, CM631G,

	CM632G, CM633G, CM634G, CM635G, CM636G, CM637G, CM638G, CM639G, CM640G, CM650G, CM660G, CM670G, CM680G, CM690G, CM610B, CM620B, CM630B, CM640B, CM650B, CM660B, CM670B, CM680B, CM690B, CM840B, CM850B, CM860B, CM870B, CM800G, CM810G, CM815G, CM820G, CM830G, CM840G, CM850G, CM860G, CM870G, CM880G, CM890G, CM891G, CM892G, CM893G, CM894G, CM895G, CM896G, CM897G, CM898G, CM899G, CM898GL, PC204A, PC204A-1, PC184AB, PC184BB, Wireless Receiver PC230A, PC230A-1, PC230A-2
Rated Voltage:	Battery:DC3V
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model PC230A-1, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	2408MHz-2474MHz
Max. Field Strength:	92.79dBuV/m
Modulation:	GFSK
Antenna Type:	PCB Antenna
Antenna Gain:	-0.61dBi
Lowest Internal Frequency of EUT:	12MHz

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.249: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2408MHz
TM2	Middle Channel	2440MHz
TM3	High Channel	2474MHz

Test Conditions	
Temperature:	22~25 °C
Relative humidity	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-03-19	2019-03-18
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-03-19	2019-03-18
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-03-19	2019-03-18
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-03-19	2019-03-18
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	N/A
§ 15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215 (c)	Emission Bandwidth	Compliant

N/A: not Compliant

*Remark: The AC Line Conducted Emissions testing is exempted because it is powered solely by batteries. Thus, the AC Line Conducted Emissions testing is not applicable.

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a PCB antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.9881	34.89	-8.28	26.61	40.00	-13.39	248	100	peak
2	48.5016	34.31	-8.26	26.05	40.00	-13.95	100	100	peak
3	99.5281	33.76	-14.94	18.82	43.50	-24.68	226	100	peak
4	271.3246	30.54	-10.40	20.14	46.00	-25.86	91	100	peak
5	638.3686	31.08	-3.55	27.53	46.00	-18.47	234	100	peak
6	1000.0000	29.79	4.04	33.83	54.00	-20.17	204	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.6719	35.08	-8.29	26.79	40.00	-13.21	266	100	peak
2	106.0126	33.69	-14.49	19.20	43.50	-24.30	99	100	peak
3	249.4250	31.99	-11.26	20.73	46.00	-25.27	217	100	peak
4	426.5210	31.16	-6.97	24.19	46.00	-21.81	114	100	peak
5	752.7432	30.16	-1.71	28.45	46.00	-17.55	353	100	peak
6	972.3374	29.86	3.38	33.24	54.00	-20.76	142	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	47.6586	35.91	-8.15	27.76	40.00	-12.24	274	100	peak
2	105.2718	33.14	-14.51	18.63	43.50	-24.87	132	100	peak
3	322.1886	31.53	-8.81	22.72	46.00	-23.28	87	100	peak
4	504.7062	31.08	-5.98	25.10	46.00	-20.90	108	100	peak
5	771.4486	30.75	-1.86	28.89	46.00	-17.11	219	100	peak
6	1000.0000	29.77	4.04	33.81	54.00	-20.19	229	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.5670	34.91	-8.14	26.77	40.00	-13.23	334	100	peak
2	98.1419	33.93	-14.99	18.94	43.50	-24.56	172	100	peak
3	278.0669	30.89	-10.13	20.76	46.00	-25.24	76	100	peak
4	447.9822	31.91	-6.97	24.94	46.00	-21.06	281	100	peak
5	651.9417	30.91	-3.40	27.51	46.00	-18.49	98	100	peak
6	979.1804	30.21	3.69	33.90	54.00	-20.10	260	100	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	49.1866	35.29	-8.38	26.91	40.00	-13.09	186	100	peak
2	103.4421	34.46	-14.64	19.82	43.50	-23.68	151	100	peak
3	324.4561	32.88	-8.70	24.18	46.00	-21.82	148	100	peak
4	414.7223	31.09	-7.04	24.05	46.00	-21.95	129	100	peak
5	675.2080	31.00	-3.03	27.97	46.00	-18.03	100	100	peak
6	986.0717	29.72	3.82	33.54	54.00	-20.46	311	100	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.3318	34.83	-8.22	26.61	40.00	-13.39	69	100	peak
2	98.8326	33.98	-14.96	19.02	43.50	-24.48	168	100	peak
3	239.1473	32.59	-11.47	21.12	46.00	-24.88	104	100	peak
4	419.1081	30.56	-6.92	23.64	46.00	-22.36	148	100	peak
5	612.0642	31.30	-3.88	27.42	46.00	-18.58	55	100	peak
6	866.0879	31.75	0.29	32.04	46.00	-13.96	337	100	peak

Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2408MHz							
2408	96.58	-7.38	89.20	114	-24.80	H	PK
2408	87.68	-7.38	80.30	94	-13.70	H	AV
4816	50.54	-6.42	44.12	74	-29.88	H	PK
4816	50.80	-6.42	44.38	54	-9.62	H	AV
7224	54.30	-8.64	45.66	74	-28.34	H	PK
7224	53.02	-8.64	44.38	54	-9.62	H	AV
2408	95.71	-7.38	88.33	114	-25.67	V	PK
2408	87.51	-7.38	80.13	94	-13.87	V	AV
4816	51.47	-6.42	45.05	74	-28.95	V	PK
4816	48.27	-6.42	41.85	54	-12.15	V	AV
7224	51.83	-8.64	43.19	74	-30.81	V	PK
7224	49.19	-8.64	40.55	54	-13.45	V	AV
Middle Channel-2440MHz							
2440	96.78	-7.30	89.48	114	-24.52	H	PK
2440	88.35	-7.30	81.05	94	-12.95	H	AV
4880	52.13	-6.12	46.01	74	-27.99	H	PK
4880	50.85	-6.12	44.73	54	-9.27	H	AV
7320	54.50	-6.81	47.69	74	-26.31	H	PK
7320	54.23	-6.81	47.42	54	-6.58	H	AV
2440	96.14	-7.30	88.84	114	-25.16	V	PK
2440	85.58	-7.30	78.28	94	-15.72	V	AV
4880	50.67	-6.12	44.55	74	-29.45	V	PK
4880	49.73	-6.12	43.61	54	-10.39	V	AV
7320	58.34	-6.81	51.53	74	-22.47	V	PK
7320	53.20	-6.81	46.39	54	-7.61	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2474MHz							
2474	99.6	-6.81	92.79	114	-21.21	H	PK
2474	91.15	-6.81	84.34	94	-9.66	H	AV
4948	51.81	-7.02	44.79	74	-29.21	H	PK
4948	49.23	-7.02	42.21	54	-11.79	H	AV
7422	55.18	-9.24	45.94	74	-28.06	H	PK
7422	52.58	-9.24	43.34	54	-10.66	H	AV
2474	93.59	-6.81	86.78	114	-27.22	V	PK
2474	83.96	-6.81	77.15	94	-16.85	V	AV
4948	48.08	-7.02	41.06	74	-32.94	V	PK
4948	50.50	-7.02	43.48	54	-10.52	V	AV
7422	54.23	-9.24	44.99	74	-29.01	V	PK
7422	51.17	-9.24	41.93	54	-12.07	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3^h Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz.

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.


5.3 Summary of Test Results/Plots

Test mode	Frequency	Limit	Result
	MHz	dBuV / dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.


Please refer to the test plots as below.

Test Channel	Low	Polarity:	Vertical(worst case)
--------------	-----	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.15	-7.78	33.37	54.00	-20.63	Ave Detector
	2310.000	54.20	-7.78	46.42	74.00	-27.58	Peak Detector
2	2390.000	44.48	-7.32	37.16	54.00	-16.84	Ave Detector
	2390.000	56.77	-7.32	49.45	74.00	-24.55	Peak Detector
3	2395.910	58.11	-7.28	50.83	54.00	-3.17	Ave Detector
	2400.000	76.36	-7.26	69.10	74.00	-4.90	Peak Detector
4	2400.000	58.85	-7.26	51.59	54.00	-2.41	Ave Detector
	2408.560	103.79	-7.21	96.58	/	/	Peak Detector
5	2408.230	94.89	-7.21	87.68	/	/	Ave Detector

Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2473.990	97.97	-6.82	91.15	/	/	Ave Detector
	2474.500	106.42	-6.82	99.60	/	/	Peak Detector
2	2483.500	58.58	-6.77	51.81	54.00	-2.19	Ave Detector
	2483.500	70.74	-6.77	63.97	74.00	-10.03	Peak Detector
3	2500.000	53.23	-6.67	46.56	54.00	-7.44	Ave Detector
	2484.790	74.59	-6.76	67.83	74.00	-6.17	Peak Detector
4	2500.000	62.04	-6.67	55.37	74.00	-18.63	Peak Detector

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW $\geq$ 1% 20dB Bandwidth, VBW $\geq$ RBW

Sweep = auto

Detector function = peak




Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.3 Summary of Test Results/Plots

Test Channel	20dB Bandwidth(kHz)
Low Channel	2759
Middle Channel	2628
High Channel	2870

Please refer to the following test plots

Low Channel	
Middle Channel	
High Channel	

***** END OF REPORT *****