



TEST REPORT

No. I18D00208-SAR01

For

Client : Shanghai SIMCom Wireless Solution Ltd.

Production : SIMCom 4G Smart module

Model Name : SIM8905A

FCC ID: 2AJYU-8PSA301

Hardware Version: V1.01

Software Version: B01

Issued date: 2018-11-8

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

Test Laboratory:

ECIT Shanghai, East China Institute of Telecommunications

Add: 7F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: welcome@ecit.org.cn

Revision Version

| Report Number | Revision | Date | Memo |
|-----------------|----------|-----------|---------------------------------|
| I18D00208-SAR01 | 00 | 2018-11-8 | Initial creation of test report |

CONTENTS

| | |
|---|----------|
| 1. TEST LABORATORY | 4 |
| 1.1. TESTING LOCATION | 4 |
| 1.2. PROJECT DATA | 4 |
| 1.3. SIGNATURE | 4 |
| 2. CLIENT INFORMATION..... | 5 |
| 2.1. APPLICANT INFORMATION..... | 5 |
| 2.2. MANUFACTURER INFORMATION..... | 5 |
| 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) | 6 |
| 3.1. ABOUT EUT | 6 |
| 3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST | 6 |
| 3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST | 6 |
| 4. TEST RESULTS | 7 |
| 4.1. RF POWER OUTPUT..... | 7 |
| 4.2. DUTY CYCLE | 7 |
| 5. REFERENCE DOCUMENTS FOR FCC | 8 |
| 5.1. APPLICABLE STANDARDS..... | 8 |
| 5.2. TEST LIMITS..... | 8 |
| 5.3. CALCULATION INFORMATION | 9 |
| 5.4. CALCULATIONS..... | 9 |

1. Test Laboratory

1.1. Testing Location

| | |
|---------------|---|
| Company Name: | ECIT Shanghai, East China Institute of Telecommunications |
| Address: | 7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China |
| Postal Code: | 200001 |
| Telephone: | (+86)-021-63843300 |
| Fax: | (+86)-021-63843301 |

1.2. Project Data

| | |
|-----------------|---------|
| Project Leader: | Yu Anlu |
|-----------------|---------|


1.3. Signature



Yan Hang
(Prepared this test report)



Fu Erliang
(Reviewed this test report)



Zheng Zhongbin
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: Shanghai SIMCom Wireless Solution Ltd.
Address Bldg. B, SIM Technology Bldg., No.633, Jinzhong Rd,
Changning Dist., Shanghai, P.R.China
Telephone: 021-31575186
Postcode: 200335

2.2. Manufacturer Information

Company Name: Shanghai SIMCom Wireless Solution Ltd.
Address /Post: Bldg. B, SIM Technology Bldg., No.633, Jinzhong Rd,
Changning Dist., Shanghai, P.R.China
Telephone: 021-31575186
Postcode: 200335

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

| | |
|--------------------|------------------------|
| EUT Description | SIMCom 4G Smart module |
| Model name | SIM8905A |
| LTE Frequency Band | 2/4/5/12 |
| Antenna Type | External Antenna |
| FCC ID: | 2AJYU-8PSA301 |

3.2. Internal Identification of EUT used during the test

| EUT ID* | SN or IMEI | HW Version | SW Version: |
|---------|------------|------------|-------------|
| N01 | N/A | V1.01 | B01 |

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

| AE ID* | Description | Model | SN | Manufacturer |
|--------|-------------|-------|-----|--------------|
| N/A | N/A | N/A | N/A | N/A |

*AE ID: is used to identify the test sample in the lab internally.

4. Test Results

4.1. RF Power Output

| Frequency Band | Max power(dBm) | Highest Frame-Averaged Output Power (dBm) | Antenna Gain(dBi) |
|----------------|----------------|---|-------------------|
| LTE Band 2 | 25.7 | 25.7 | 1.79 |
| LTE Band 4 | 25.7 | 25.7 | 2.96 |
| LTE Band 5 | 25.7 | 25.7 | 0.67 |
| LTE Band 12 | 25.7 | 25.7 | -1.5 |

4.2. Duty cycle

| Mode | Duty Cycle |
|------|------------|
| LTE | 1:1 |

5. Reference Documents for FCC

5.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

FCC CFR 47, Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

5.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

Limits for Occupational / Controlled Exposure

| Frequency Range [MHz] | Electric Field Strength [V/m] | Magnetic Field Strength [A/m] | Power Density (S) [mW/cm ²] | Averaging Times E ² , H ² or S [minutes] |
|-----------------------|-------------------------------|-------------------------------|---|--|
| 0.3 – 3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0 – 30 | 1824/f | 4.89/f | (900/f)* | 6 |
| 30 – 300 | 61.4 | 0.163 | 1.0 | 6 |
| 300 – 1500 | -- | -- | F/300 | 6 |
| 1500 - 100000 | -- | -- | 5 | 6 |

Limits for General Population / Uncontrolled Exposure

| Frequency Range [MHz] | Electric Field Strength [V/m] | Magnetic Field Strength [A/m] | Power Density (S) [mW/cm ²] | Averaging Times E ² , H ² or S [minutes] |
|-----------------------|-------------------------------|-------------------------------|---|--|
| 0.3 – 1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34 – 30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30 – 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300 – 1500 | -- | -- | F/1500 | 30 |
| 1500 - 100000 | -- | -- | 1.0 | 30 |

Note: f=frequency in MHz; *Plane-wave equivalent power density

For the DUT, the limits for General Population / Uncontrolled Exposure are applicable.

5.3. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

$$\text{Given } S = \frac{P \times G}{4\pi d^2} \quad \text{Equation 1}$$

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

| Band | Frequency (MHz) | Highest Frame-Averaged Output Power (dBm) | Antenna Gain (dBi) | Power density at 20cm | Limit mW/cm ² |
|-------------|-----------------|---|--------------------|-----------------------|--------------------------|
| LTE Band 2 | 1850 | 25.7 | 1.79 | 0.112 | 1 |
| LTE Band 4 | 1710 | 25.7 | 2.96 | 0.146 | 1 |
| LTE Band 5 | 824 | 25.7 | 0.67 | 0.086 | 0.549 |
| LTE Band 12 | 698 | 25.7 | -1.5 | 0.052 | 0.465 |

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band

5.4. Calculations

The product is under the MPE limits. All is pass.

*****END OF REPORT*****