CENTRO DE TECNOLOGÍA DE LAS COMUNICACIONES, S.A.

Parque Tecnológico de Andalucía, c/Severo Ochoa nº 2 29590 Campanillas/ Málaga/ España Tel. 952 61 91 00 - Fax 952 61 91 13 MÁLAGA, C.I.F. A29 507 456 Registro Mercantil Tomo 1169 Libro 82 Folio 133 Hoja MA3729

TEST REPORT

| 1 | Report No.: 21007REM.002 |
|-----------------------------------|--|
| TEST NAME: ELECTROMA | AGNETIC COMPATIBILITY TESTS |
| Product | : WIRELESS HEADSET |
| Trade Mark | : NOKIA |
| Model/ type Ref. | : HS-11W |
| Manufacturer | : NOKIA CORPORATION |
| Requested by | : NOKIA CORPORATION |
| Other identification of the prod | luct : The HS-11W, bluetooth headset will be used together with phones and other audio devices, which are supporting bluetooth audio features and handsfree/Headset profile. Following accessories were used: LCH-12, ACP-1E, ACP-12E |
| Standard(s) | : On the sample S/01: |
| | ELECTROMAGNETIC EMISSION. FCC Rules and Regulations 47 CFR Part 15, Subpart B (2003/07/22 Ed.); Continuos Conducted Emission (Class B). Radiated Emission (Class B). |
| | On the sample S/02: |
| | ELECTROMAGNETIC EMISSION. - FCC Rules and Regulations 47 CFR Part 15, Subpart B (2003/07/22 Ed.); - Continuos Conducted Emission (Class B). - Radiated Emission (Class B). |
| | On the sample S/03: |
| | ELECTROMAGNETIC EMISSION. - FCC Rules and Regulations 47 CFR Part 15, Subpart B (2003/07/22 Ed.); - Radiated Emission (Class B). |
| This test report includes 1 annex | and therefore, the total number of pages is 37. |

IMPORTANT: No part of this report must be quoted out of context, reproduced or transmitted partially, in any form or by any means, except in full, without the previous written permission of Centro de Tecnología de las Comunicaciones, S.A. (CETECOM).

| | Test operator: Rafael López | Revised by: Date: Juan Carlos soler EMC Consultant | Approved by: Date: Francisco Broissin Division Director | |
|------------------|--------------------------------|---|--|--------------|
| Date: 2004-10-14 | | | | Page: 1 of 7 |



INDEX

| 1. | COMPETENCE AND GUARANTEES |
|----|--|
| 2. | GENERAL CONDITIONS |
| 3. | CHARACTERISTICS OF THE TEST |
| | 3.1. SERVICES REQUESTED |
| | 3.2. REQUIREMENTS AND METHOD |
| 4. | IDENTIFICATION DATA SUPPLIED BY THE APPLICANT |
| | 4.1. APPLICANT |
| | 4.2. TEST SAMPLES SUPPLIER |
| | 4.3. IDENTIFICATION OF ITEM/ITEMS TESTED |
| 5. | USAGE OF SAMPLES, TESTING PERIOD AND ENVIRONMENTAL CONDITIONS5 |
| | 5.1. USAGE OF SAMPLES |
| | 5.2. TESTING PERIOD |
| | 5.3. ENVIROMENTAL CONDITIONS |
| 6. | TEST RESULTS |
| | 6.1. RESULTS FOR ELECTROMAGNETIC EMISSION |
| 7. | REMARKS AND COMMENTS7 |
| 8. | SUMMARY7 |
| | |

ANNEXES OF RESULTS

| A. MEASURING RESULTS FOR ELECTROMAGNETIC EMISSIONS |
|--|
|--|



1. COMPETENCE AND GUARANTEES

This certificate of conformity was issued in accordance with the decision N° 3/2000 of the Joint Committee established under the Agreement on Mutual Recognition between the European Community and the United States of America. By this decision, CETECOM can act as Conformity Assessment Body (CAB) on Electromagnetic Compatibility. This Certificate applies to the samples listed at technical reports.

CETECOM is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, CETECOM has a calibration and maintenance programme for its measurement equipment.

CETECOM guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at CETECOM at the time of performance of the test.

CETECOM is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

2. GENERAL CONDITIONS

- 1. This report is only referred to the item that has undergone the test.
- 2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
- 3. This document is only valid if complete; no partial reproduction can be made without previous written permission of CETECOM.
- 4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of CETECOM and the Accreditation Bodies.

3. CHARACTERISTICS OF THE TEST

3.1. SERVICES REQUESTED

The ordered services were to carry out the following tests:

1. Continuous conducted emission, power leads:

Standard: FCC Rules and Regulations 47 CFR Part 15

Limit: Class B

Method: FCC Rules and Regulations 47 CFR Part 15, Subpart B

2. Radiated emission, electromagnetic field:

Standard: FCC Rules and Regulations 47 CFR Part 15

Report No.: 21007REM.002

Date: 2004-06-08



Limit:Class BMethod:FCC Rules and Regulations 47 CFR Part 15, Subpart B

3.2. REQUIREMENTS AND METHOD

The test has been carried out according to the following documents and standards:

1. FCC Rules and Regulations 47 CFR Part 15, Subpart B: Limits and methods of measurements for radio frequency devices. Unintentional radiators.

The testing procedures used are:

- 1. PEEM001: Medida de la tensión perturbadora en bornes de alimentación según EN 55022.
- 2. PEEM002: Medida del campo perturbador radiado según EN 55022.

Uncertainty (factor k=2) was calculated according to the following CETECOM's internal documents:

- 1. PODT000: Procedimiento para el cálculo de incertidumbres de medida
- 2. FEM12_07: Formato de cálculo de incertidumbre a aplicar en la medida de la tensión perturbadora en bornes de alimentación según EN 55022.
- 3. FEM13_08: Formato de cálculo de incertidumbre a aplicar en la medida del campo perturbador radiado según EN 55022.
- 4. FET298_01: Formato de cálculo de incertidumbre a aplicar en la medida del campo perturbador radiado entre 1 y 25 GHz.

4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT

Identification data included in this section has been supplied by the client.

4.1. APPLICANT

Name / Company: NOKIA CORPORATION

V.A.T. Registration number / Passport number: FI01120389

Address: Joensuunkatu 7E. P.C.: 24100. City: SALO

Country: FINLAND

 Telephone: 943 71 94 99
 Fax: 943 79 23 49

Contact person: Olli Pekka Ahokas

4.2. TEST SAMPLES SUPPLIER

The same as the applicant.

Samples undergoing test have been selected by the applicant.

Report No.: 21007REM.002

Date: 2004-06-08



4.3. IDENTIFICATION OF ITEM/ITEMS TESTED

Product: WIRELESS HEADSET

Trade mark: NOKIA Model: HS-11W

Manufacturer: NOKIA CORPORATION

Country of manufacture: FINLAND

Manufacture site address: See applicant.

Other identification remarks : Prototype

Description: The HS-11W, bluetooth headset will be used together with phones and other audio devices, which are supporting bluetooth audio features and handsfree/Headset profile

5. USAGE OF SAMPLES, TESTING PERIOD AND ENVIRONMENTAL CONDITIONS

5.1. USAGE OF SAMPLES

Sample S/01 is composed of the following elements:

| <u>Control No.</u> | Description | Model | <u>Serial No.</u> | Date of reception | | | |
|--|---|---|-------------------|----------------------------|--|--|--|
| 03 | Headset | HS-11W | Prototype | 21/09/2004 | | | |
| 05 | Charger | HS-11W Prot ACP-12E 067 ng elements: <u>Model Seria</u> HS-11W Prot ACP-1E 067 ng elements: <u>Model Seria</u> | 0675294 | 21/09/2004 | | | |
| Sample S/02 is co | omposed of the follow | ing elements: | | | | | |
| <u>Control No.</u> | Headset HS Charger AC composed of the following element M Description M Headset HS Charger AC Charger AC Charger AC Charger AC Description M Description M Charger AC Charger AC Charger AC | Model | <u>Serial No.</u> | <u>.</u> Date of reception | | | |
| 03 | Headset | HS-11W | Prototype | 21/09/2004 | | | |
| 06 | Charger | ACP-1E | 0675349 | 21/09/2004 | | | |
| 06 Charger ACP-1E 0675349 21/09/2004 Sample S/03 s composed of the following elements: Composed of t | | | | | | | |
| | <u>Serial No.</u> | Date of reception | | | | | |
| 03 | Headset | HS-11W | Prototype | 21/09/2004 | | | |

LCH-12

0675349

Different samples were used in the following way:

1. Sample S/01 has undergone to the following test(s):

Charger

- 1. Continuous conducted emission, power leads.
- 2. Radiated emission, electromagnetic field.
- 2. Sample S/02 has undergone to the following test(s):
 - 1. Continuous conducted emission, power leads.
 - 2. Radiated emission, electromagnetic field.
- 3 Sample S/03 has undergone to the following test(s):
 - 1. Radiated emission, electromagnetic field.

07

21/09/2004



5.2. TESTING PERIOD

The performed test started on 21/09/2004 and finished on 24/09/2004.

The tests have been performed at CETECOM.

5.3. ENVIROMENTAL CONDITIONS

Environmental conditions:

In the control chamber, the following limits were not exceeded during the test:

| Temperature | $Min. = 15 ^{\circ}C$ |
|-------------------------------|------------------------|
| | Max. = 35 °C |
| Relative humidity | Min. = 20 % |
| | Max. = 80 % |
| Shielding effectiveness | > 100 dB |
| Electric insulation | $> 10 \text{ k}\Omega$ |
| Reference resistance to earth | $< 0.5 \Omega$ |

In the semianechoic chamber (21 meters x 11 meters x 8 meters), the following limits were not exceeded during the test.

| Temperature | Min. = 15 °C |
|-------------------------------|--|
| - | Max. $= 30 \ ^{\circ}\text{C}$ |
| Relative humidity | Min. = 45 % |
| | Max. = 60 % |
| Air pressure | Min. = 860 mbar |
| | Max. = 1060 mbar |
| Shielding effectiveness | > 100 dB |
| Electric insulation | $> 10 \text{ k}\Omega$ |
| Reference resistance to earth | $<$ 0,5 Ω |
| Normal site attenuation (NSA) | $< \pm 4$ dB at 10 m distance between item |
| | under test and receiver antenna, (30 |
| | MHz to 1000 MHz) |
| Field homogeneity | More than 75% of illuminated surface |
| | is between 0 and 6 dB (26 MHz to 1000 |
| | MHz). |

In the chamber for conducted measurements, the following limits were not exceeded during the test:

| Temperature | Min. = 15 °C |
|-------------------------------|------------------------|
| | Max. = 30 °C |
| Relative humidity | Min. = 45 % |
| | Max. = 60 % |
| Air pressure | Min. = 860 mbar |
| | Max. = 1060 mbar |
| Shielding effectiveness | > 100 dB |
| Electric insulation | $> 10 \text{ k}\Omega$ |
| Reference resistance to earth | $< 0,5 \Omega$ |

Report No.: 21007REM.002

Date: 2004-06-08



6. TEST RESULTS

Abbreviations used in the VERDICT column of the following tables are:

- P Pass
- F Fail
- NA not applicable
- NM not measured

6.1. RESULTS FOR ELECTROMAGNETIC EMISSION

See Annex: A

| MEASURING RESULTS FOR ELECTROMAGNETIC EMISSION | IC EMISSION VERDICT | | | |
|--|---------------------|---|---|----|
| | NA | Р | F | NM |
| Continuous conducted emission, power leads. Class B. | | Р | | |
| (On samples S/01, S/02) | | | | |
| Radiated emission, electromagnetic field . Class B. | | Р | | |
| (On samples S/01, S/02 and S/03) | | | | |

7. REMARKS AND COMMENTS

The total uncertainty of the measurement system for the measured radio disturbance characteristics of EUT from 150 kHz to 30 MHz is $I = \pm 3$ dB for quasi-peak measurements, $I = \pm 2,8$ dB for peak measurements (k = 2).

The total uncertainty of the measurement system for the measured radio disturbance characteristics of EUT from 30 MHz to 1 GHz is $I = \pm 3,1$ dB for quasi-peak measurements, $I = \pm 2,9$ dB for peak measurements (k = 2) and from 1 to 12,75 GHz is $I = \pm 4,04$ dB for average measurements. And for average measurements from 1 to 12,75 GHz the uncertainty $I = \pm 4,04$ dB and from 12,75 GHz to 25 GHz is 4,21 dB.

7.1. SUMMARY

Considering the results of the performed test, stated in annex A, the item under test is **IN COMPLIANCE** with the specifications listed in section 3.1 "TEST REQUESTED".

NOTE: The results presented in this Test Report apply only to the particular item under test established in section "4.3. IDENTIFICATION OF ITEM/ITEMS TESTED" of this document, as presented for test on the date(s) shown in section 5, "USAGE OF SAMPLES, TESTING PERIOD AND ENVIRONMENTAL CONDITIONS".

