

System / software:	SARA2 / 2.3 VPM	Input Power Drift:	
Date / Time:	8/18/2005 11:40:19 AM	DUT Battery Model/No:	
Filename:	tab_side_3d.txt	Probe Serial Number:	0123
Ambient Temperature:	22.0°C	Liquid Simulant:	2450
Device Under Test:	Broadcom	Relative Permittivity:	50.99
Relative Humidity:	50%	Conductivity:	1.909
Phantom S/No:	HeadBox_new_spout.c sv	Liquid Temperature:	22.0°C
Phantom Rotation:	0°	Max SAR Y-axis Location:	22.67 mm
DUT Position:	side	Max SAR Z-axis Location:	-196.40 mm
Antenna Configuration:	Auxillary	Max E Field:	2.62 V/m
Test Frequency:	2437MHz	SAR 1g:	0.009 W/kg
Air Factors:	346 / 318 / 386	SAR 10g:	0.004 W/kg
Conversion Factors:	0.705 / 0.705 / 0.705	SAR Start:	0.006 W/kg
Type of Modulation:		SAR End:	0.006 W/kg
Modn. Duty Cycle:		SAR Drift during Scan:	0.03 dB
Diode Compression Factors (V*200):	19 / 19 / 19	Probe battery last changed:	7/25/05
Input Power Level:	max	Extrapolation:	poly4

