

Test Laboratory: BTL Inc.

Date: 2024/5/22

W07_2.4G SRD_CH36_Horizontal Up_5mm**DUT: USB Dongle;**

Communication System: UID 0, BT (0);

Frequency: 2474 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2474$ MHz; $\sigma = 1.848$ S/m; $\epsilon_r = 39.553$; $\rho = 1000$ kg/m³

Ambient Temperature: 22.9 °C; Liquid Temperature: 22.2 °C

DASY Configuration:

- Probe: EX3DV4 - SN7693; ConvF(8.33, 8.33, 8.33) @ 2474 MHz; Calibrated: 2023/10/31
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1390; Calibrated: 2023/11/20
- Phantom: ELI v5.0_Left; Type: QDOVA002AA; Serial: TP:1222
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Area Scan (5x9x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.147 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.918 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.254 W/kg

SAR(1 g) = 0.112 W/kg; SAR(10 g) = 0.052 W/kg

Maximum value of SAR (measured) = 0.192 W/kg

