



## **FCC 47 CFR PART 15 SUBPART C**

### **TEST REPORT**

**For**

**Wireless Keyboard**

**Model: G247**

**Trade Name: Cherry**

*Issued to*

**Cherry Mikroschalter Gmbh  
Cherrystrabe Industriest 19 PO Box 1220 D-91275  
Auerbach/Opf GERMANY**

*Issued by*

**Compliance Certification Services Inc.  
No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang,  
Taoyuan Hsien, (338) Taiwan, R.O.C.  
<http://www.ccsemc.com.tw>  
[service@tw.ccsemc.com](mailto:service@tw.ccsemc.com)**



---

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



## **TABLE OF CONTENTS**

|                                                          |           |
|----------------------------------------------------------|-----------|
| <b>1. TEST RESULT CERTIFICATION.....</b>                 | <b>3</b>  |
| <b>2. EUT DESCRIPTION .....</b>                          | <b>4</b>  |
| <b>3. TEST METHODOLOGY .....</b>                         | <b>5</b>  |
| 3.1 EUT CONFIGURATION .....                              | 5         |
| 3.2 EUT EXERCISE .....                                   | 5         |
| 3.3 GENERAL TEST PROCEDURES .....                        | 5         |
| 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS ..... | 6         |
| 3.5 DESCRIPTION OF TEST MODES .....                      | 6         |
| <b>4. INSTRUMENT CALIBRATION.....</b>                    | <b>7</b>  |
| 4.1 MEASURING INSTRUMENT CALIBRATION .....               | 7         |
| 4.2 MEASUREMENT EQUIPMENT USED .....                     | 7         |
| <b>5. FACILITIES AND ACCREDITATIONS .....</b>            | <b>8</b>  |
| 5.1 FACILITIES .....                                     | 8         |
| 5.2 EQUIPMENT .....                                      | 8         |
| 5.3 TABLE OF ACCREDITATIONS AND LISTINGS .....           | 9         |
| <b>6. SETUP OF EQUIPMENT UNDER TEST .....</b>            | <b>10</b> |
| 6.1 SETUP CONFIGURATION OF EUT .....                     | 10        |
| 6.2 SUPPORT EQUIPMENT .....                              | 10        |
| <b>7. FCC PART 15.227 REQUIREMENTS.....</b>              | <b>11</b> |
| 7.1 20 DB BANDWIDTH .....                                | 11        |
| 7.2 RADIATED EMISSIONS .....                             | 13        |
| 7.3 POWERLINE CONDUCTED EMISSIONS .....                  | 17        |
| <b>APPENDIX I PHOTOGRAPHS OF TEST SETUP .....</b>        | <b>18</b> |



## 1. TEST RESULT CERTIFICATION

**Applicant:** Cherry Mikroschalter Gmbh  
Cherrystrabe Industriest 19 PO Box 1220 D-91275  
Auerbach/Opf GERMANY

**Equipment Under Test:** Wireless Keyboard

**Trade Name:** Cherry

**Model:** G247

**Date of Test:** August 9 ~ 18, 2006

| APPLICABLE STANDARDS         |                         |
|------------------------------|-------------------------|
| STANDARD                     | TEST RESULT             |
| FCC 47 CFR Part 15 Subpart C | No non-compliance noted |

### We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.227.

The test results of this report relate only to the tested sample identified in this report.

*Approved by:*

Gavin Lim  
Section Manager  
Compliance Certification Services Inc.

*Reviewed by:*

Amanda Wu  
Section Manager  
Compliance Certification Services Inc.



## 2. EUT DESCRIPTION

|                             |                                                                         |
|-----------------------------|-------------------------------------------------------------------------|
| <b>Product</b>              | Wireless Keyboard                                                       |
| <b>Trade Name</b>           | Cherry                                                                  |
| <b>Model Number</b>         | G247                                                                    |
| <b>Model Difference</b>     | N/A                                                                     |
| <b>Power Supply</b>         | Powered by AAA batteries $\times 2$ (Rating: $2 \times 1.5\text{Vdc}$ ) |
| <b>Frequency Range</b>      | 26.995 MHz, 27.045 MHz, 27.095 MHz, 27.145 MHz, 27.195 MHz              |
| <b>Modulation Technique</b> | FSK                                                                     |

**Remark:**

1. The sample selected for test was production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **GDDG247** filing to comply with Section 15.227 of the FCC Part 15, Subpart C Rules.



### **3. TEST METHODOLOGY**

The tests documented in this report were performed in accordance with ANSI C63.4, FCC 47 CFR 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, and 15.227.

#### **3.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### **3.2 EUT EXERCISE**

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

#### **3.3 GENERAL TEST PROCEDURES**

##### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane according to the requirements in Section 13.1.4.1 of ANSI C63.4. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



### 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                        | MHz                 | MHz             | GHz              |
|----------------------------|---------------------|-----------------|------------------|
| 0.090 - 0.110              | 16.42 - 16.423      | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614       | 5.35 - 5.46      |
| 2.1735 - 2.1905            | 16.80425 - 16.80475 | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128              | 25.5 - 25.67        | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775          | 37.5 - 38.25        | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775          | 73 - 74.6           | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218              | 74.8 - 75.2         | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825          | 108 - 121.94        | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225          | 123 - 138           | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294              | 149.9 - 150.05      | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 - 8.366              | 156.52475 -         | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675          | 156.52525           | 2655 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475          | 156.7 - 156.9       | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293             | 162.0125 - 167.17   | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025        | 167.72 - 173.2      | 3345.8 - 3358   | 36.43 - 36.5     |
| 12.57675 - 12.57725        | 240 - 285           | 3600 - 4400     | ( <sup>2</sup> ) |
| 13.36 - 13.41              | 322 - 335.4         |                 |                  |

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

### 3.5 DESCRIPTION OF TEST MODES

The EUT (model: G247) had been tested under engineering test mode condition and the EUT staying in continuous transmitting mode.

Channel Mid (27.095 MHz) was chosen for full testing.



## 4. INSTRUMENT CALIBRATION

### 4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### 4.2 MEASUREMENT EQUIPMENT USED

#### Equipment Used for Emissions Measurement

*Remark: Each piece of equipment is scheduled for calibration once a year.*

| 3M Semi Anechoic Chamber |                 |                   |                            |                 |
|--------------------------|-----------------|-------------------|----------------------------|-----------------|
| Name of Equipment        | Manufacturer    | Model             | Serial Number              | Calibration Due |
| Spectrum Analyzer        | Agilent         | E4446A            | US42510252                 | 07/25/2007      |
| Spectrum Analyzer        | Rohde&Schwarz   | FSEK30            | 100264                     | 03/22/2007      |
| Test Receiver            | Rohde&Schwarz   | ESCI              | 100064                     | 11/05/2006      |
| Switch Controller        | TRC             | Switch Controller | SC94050010                 | 05/05/2007      |
| 4 Port Switch            | TRC             | 4 Port Switch     | SC94050020                 | 05/05/2007      |
| Horn-Antenna             | TRC             | HA-0502           | 06                         | 07/09/2007      |
| Horn-Antenna             | TRC             | HA-0801           | 04                         | 05/05/2007      |
| Horn-Antenna             | TRC             | HA-1201A          | 01                         | 07/04/2007      |
| Horn-Antenna             | TRC             | HA-1301A          | 01                         | 07/04/2007      |
| Loop Antenna             | EMCO            | 6502              | 8905/2356                  | 06/03/2007      |
| Bilog- Antenna           | Sunol Sciences  | JB3               | A030205                    | 03/09/2007      |
| Turn Table               | Max-Full        | MFT-120S          | T120S940302                | N.C.R.          |
| Antenna Tower            | Max-Full        | MFA-430           | A440940302                 | N.C.R.          |
| Controller               | Max-Full        | MF-CM886          | CC-C-1F-13                 | N.C.R.          |
| Site NSA                 | CCS             | N/A               | FCC: 965860<br>IC: IC 6106 | 09/26/2008      |
| Test S/W                 | LABVIEW (V 6.1) |                   |                            |                 |

*Remark: The measurement uncertainty is less than  $\pm 2.0065\text{dB}$  (30MHz ~ 1GHz),  $\pm 3.0958\text{dB}$  (Above 1GHz) which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.*



## **5. FACILITIES AND ACCREDITATIONS**

### **5.1 FACILITIES**

All measurement facilities used to collect the measurement data are located at

☐ No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

☒ No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

☒ No.81-1, Lane 210, Bade 2nd Rd., Luchu Hsiang, Taoyuan Hsien 338, Taiwan

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### **5.2 EQUIPMENT**

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5.3 TABLE OF ACCREDITATIONS AND LISTINGS

| Country | Agency          | Scope of Accreditation                                                                                                                                                                                                                                                                                                                                                                               | Logo                                                                                                                                                                                        |
|---------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USA     | A2LA            | EN 55011, EN 55014-1/2, CISPR 11, CISPR 14-1/2, EN 55022, EN 55015, CISPR 22, CISPR 15, AS/NZS 3548, VCCI V3 (2001), CFR 47, FCC Part 15/18, CNS 13783-1, CNS 13439, CNS 13438, CNS 13803, CNS 14115, EN 55024, IEC 801-2, IEC 801-3, IEC 801-4, IEC/EN 61000-3-2, EIC/EN 61000-3-3, IEC/EN 61000-4-2/3/4/5/6/8/11, EN 50081-1/ EN 61000-6-3, EN 50081-2/EN 61000-6-4, EN 50081-2/EN 61000-6-1: 2001 | <br>0824-01                                                                                              |
| USA     | FCC             | 3/10 meter Open Area Test Sites (93105, 90471) / 3M Semi Anechoic Chamber (965860) to perform FCC Part 15/18 measurements                                                                                                                                                                                                                                                                            | <br>93105, 90471<br>965860                                                                               |
| Japan   | VCCI            | 3/10 meter Open Area Test Sites to perform conducted/radiated measurements                                                                                                                                                                                                                                                                                                                           | <br>R-393/1066/725/879<br>C-402/747/912                                                                  |
| Norway  | NEMKO           | EN 50081-1/2, EN 50082-1/2, IEC 61000-6-1/2, EN 50091-2, EN 50130-4, EN 55011, EN 55013, EN 55014-1/2, EN 55015, EN 55022, EN 55024, EN 61000-3-2/3, EN 61326-1, IEC 61000-4-2/3/4/5/6/8/11, EN 60601-1-2, EN 300 328, EN 300 422-2, EN 301 419-1, EN 301 489-01/03/07/08/09/17, EN 301 419-2/3, EN 300 454-2, EN 301 357-2                                                                          | <br>ELA 124a<br>ELA 124b<br>ELA 124c                                                                     |
| Taiwan  | TAF             | EN 300 328, EN 300 220-1, EN 300 220-2, EN 300 220-3, 47 CFR FCC Part 15 Subpart C, EN 61000-3-2, EN 61000-3-3, CNS 13439, CNS 13783-1, CNS 14115, CNS 13438, AS/NZS CISPR 22, CNS 13022-1, IEC 61000-4-2/3/4/5/6/8/11, CNS 13022-2/3                                                                                                                                                                |                                                                                                        |
| Taiwan  | BSMI            | CNS 13438, CNS 13783-1, CNS 13439, CNS 14115                                                                                                                                                                                                                                                                                                                                                         | <br>SL2-IS-E-0014<br>SL2-IN-E-0014<br>SL2-A1-E-0014<br>SL2-R1-E-0014<br>SL2-R2-E-0014<br>SL2-L1-E-0014 |
| Canada  | Industry Canada | 3/10 meter Open Area Test Sites (IC 3991-3, IC 3991-4) / 3M Semi Anechoic Chamber (IC 6106) to perform RSS 212 Issue 1                                                                                                                                                                                                                                                                               | <br>IC 3991-3<br>IC 3991-4<br>IC 6106                                                                  |

\* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



## 6. SETUP OF EQUIPMENT UNDER TEST

### 6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

### 6.2 SUPPORT EQUIPMENT

| No. | Device Type | Brand | Model | Series No. | FCC ID | Data Cable | Power Cord |
|-----|-------------|-------|-------|------------|--------|------------|------------|
|     | N/A         | N/A   | N/A   | N/A        | N/A    | N/A        | N/A        |

**Remark:**

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*




## 7. FCC PART 15.227 REQUIREMENTS

### 7.1 20 DB BANDWIDTH

#### LIMIT

None; for reporting purposes only.

#### Test Configuration



#### TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=1kHz, VBW = RBW, Span = 200kHz, Sweep = auto.
4. Mark the peak frequency and 20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

#### TEST RESULTS

*No non-compliance noted*




## CH / Mid

### Test Plot

Agilent 15:16:02 Aug 18, 2006

T



Transmit Freq Error 814.700 Hz  
x dB Bandwidth 25.361 kHz



## 7.2 RADIATED EMISSIONS

### LIMIT

The field strength of any emission within this band shall not exceed 10,000 microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in Section 15.35 for limiting peak emissions apply.

The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (mV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 30-88           | 100*                  | 3                        |
| 88-216          | 150*                  | 3                        |
| 216-960         | 200*                  | 3                        |
| Above 960       | 500                   | 3                        |

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

| Frequency (MHz) | Field Strength ( $\mu$ V/m at 3-meter) | Field Strength (dB $\mu$ V/m at 3-meter) |
|-----------------|----------------------------------------|------------------------------------------|
| 30-88           | 100                                    | 40                                       |
| 88-216          | 150                                    | 43.5                                     |
| 216-960         | 200                                    | 46                                       |
| Above 960       | 500                                    | 54                                       |


3. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength ( $\mu$ V/m at meter) | Measurement Distance (meter) |
|-----------------|--------------------------------------|------------------------------|
| 0.009 – 0.490   | 2400 / F (kHz)                       | 300                          |
| 0.490 – 1.705   | 24000 / F (kHz)                      | 30                           |
| 1.705 – 30.0    | 30                                   | 30                           |
| 30 - 88         | 100**                                | 3                            |
| 88-216          | 150**                                | 3                            |
| 216-960         | 200**                                | 3                            |
| Above 960       | 500                                  | 3                            |


\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

## Test Configuration

### **9kHz ~ 30MHz**



### **30MHz ~ 1 GHz**





## **TEST PROCEDURE**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:  
RBW=100kHz / VBW=300kHz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

**TEST RESULTS**

**Operation Mode:** TX mode / CH Mid      **Test Date:** August 9, 2006  
**Temperature:** 24°C      **Tested by:** James Yu  
**Humidity:** 52 % RH      **Polarity:** Ver. / Hor.

| Frequency (MHz) | Ant.Pol. (H/V) | Detector Mode (PK/QP/AVG) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit 3m (dBuV/m) | Margin (dB) |
|-----------------|----------------|---------------------------|----------------|--------------------------|-----------------|-------------------|-------------|
| 27.10           | V              | Peak                      | 52.55          | 5.92                     | 46.63           | 80.00             | -33.37      |
| 132.30          | V              | Peak                      | 42.25          | -13.53                   | 28.72           | 43.50             | -14.78      |
| 215.35          | V              | Peak                      | 43.18          | -15.22                   | 27.96           | 46.00             | -18.04      |
| 470.15          | V              | Peak                      | 40.50          | -7.70                    | 32.80           | 46.00             | -13.20      |
| 480.20          | V              | Peak                      | 42.57          | -7.83                    | 34.74           | 46.00             | -11.26      |
| 555.42          | V              | Peak                      | 37.95          | -6.47                    | 31.48           | 46.00             | -14.52      |
| 800.50          | V              | Peak                      | 31.42          | -2.78                    | 28.64           | 46.00             | -17.36      |
| 27.10           | H              | Peak                      | 50.75          | 5.92                     | 44.83           | 80.00             | -35.17      |
| 132.70          | H              | Peak                      | 50.60          | -13.53                   | 37.07           | 43.50             | -6.43       |
| 208.53          | H              | QP                        | 55.25          | -15.22                   | 40.03           | 46.00             | -5.97       |
| 262.50          | H              | QP                        | 52.58          | -12.77                   | 39.81           | 46.00             | -6.19       |
| 366.97          | H              | Peak                      | 47.45          | -10.18                   | 37.27           | 46.00             | -8.73       |
| 771.22          | H              | Peak                      | 43.65          | -3.22                    | 40.43           | 46.00             | -5.57       |
| 805.70          | H              | Peak                      | 41.25          | -2.78                    | 38.47           | 46.00             | -7.53       |

**Remark:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).



### 7.3 POWERLINE CONDUCTED EMISSIONS

#### **LIMIT**

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency Range<br>(MHz) | Limits<br>(dB $\mu$ V) |           |
|--------------------------|------------------------|-----------|
|                          | Quasi-peak             | Average   |
| 0.15 to 0.50             | 66 to 56*              | 56 to 46* |
| 0.50 to 5                | 56                     | 46        |
| 5 to 30                  | 60                     | 50        |

\* Decreases with the logarithm of the frequency.

#### **Test Procedure**

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

#### **TEST RESULTS**

*Since this EUT is battery powered, this test item is not applicable.*