

## RF Exposure Evaluation declaration

Product Name : 802.11g Wireless ADSL2+ 4-port Gateway  
Model No. : P-660HW-D1 v2, P-660HW-D1 v2, P-660HW-D1 v2, 401619  
FCC ID. : I88P660HWD1V2

Applicant : ZyXEL Communications Corporation

Address : No. 6, Innovation Rd II, Science-Based Industrial Park, Hsin-Chu,  
Taiwan, R.O.C.

Date of Receipt : 2006/09/15  
Date of Declaration : 2006/10/05  
Report No. : 069H035-RF-US-Exp

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range<br>(MHz)                                  | Electric Field<br>Strength (V/m) | Magnetic Field<br>Strength (A/m) | Power Density<br>(mW/cm <sup>2</sup> ) | Average Time<br>(Minutes) |
|---|----------------------------------|----------------------------------|--|---------------------------|
| (A) Limits for Occupational/ Control Exposures            |                                  |                                  |  |                           |
| 300-1500  | --                               | --                               | F/300                                  | 6                         |
| 1500-100,000  | --                               | --                               | 5                                      | 6                         |
| (B) Limits for General Population/ Uncontrolled Exposures |                                  |                                  |  |                           |
| 300-1500  | --                               | --                               | F/1500                                 | 6                         |
| 1500-100,000  | --                               | --                               | 1                                      | 30                        |

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

|                |  |
|----------------|--|
| Product        | 802.11g Wireless ADSL2+ 4-port Gateway |
| Test Mode      | Mode 1: Transmit                       |
| Test Condition | RF Exposure Evaluation                 |

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3 dBi or 2 in linear scale.

#### Output Power Into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11b |                         |                              |  |
|--------------|-------------------------|------------------------------|--|
| Channel      | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm <sup>2</sup> ) |
| 1            | 2412.00                 | 88.1049                      | 0.0350   |
| 6            | 2437.00                 | 362.243                      | 0.0553   |
| 11           | 2462.00                 | 83.9460                      | 0.0333   |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

|                |  |
|----------------|--|
| Product        | 802.11g Wireless ADSL2+ 4-port Gateway |
| Test Mode      | Mode 1: Transmit                       |
| Test Condition | RF Exposure Evaluation                 |

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3 dBi or 2 in linear scale.

### Output Power Into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11g |                         |                              |  |
|--------------|-------------------------|------------------------------|--|
| Channel      | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm <sup>2</sup> ) |
| 1            | 2412.00                 | 90.1571                      | 0.0358   |
| 6            | 2437.00                 | 797.9946                     | 0.1625   |
| 11           | 2462.00                 | 87.4984                      | 0.0347   |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.