

**RF Exposure / SAR Statement**  
**No. : 10399701S-H-R1**

<b>Applicant</b>	:	<b>Clarion Co., Ltd.</b>
<b>Type of Equipment</b>	:	<b>Navigation Unit</b>
<b>Model No.</b>	:	<b>QY-5092</b>
<b>Similar Model</b>	:	<b>PH-3709, QY-5099, QY-5089</b>
<b>FCC ID</b>	:	<b>AX2QY5099</b>

---

Clarion Co., Ltd. declares that Model : QY-5092  
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.

**RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the “QY-5092” as calculated  
from FCC Part 1, §1.1310, TABLE 1 (B) Limits for General Population / Uncontrolled Exposure.  
This calculation is based on the highest EIRP possible from the system,  
considering maximum power and antenna gain, and considering a 1.0mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

**Where**

<b>P =</b>	<b>22.08 mW (Maximum average output power)</b>
<b>G =</b>	<b>0.77 Numerical Antenna gain; equal to -1.11 dBi</b>
<b>r =</b>	<b>20.0 cm</b>

**For: QY-5092**

$$S = 0.00340 \text{ mW/cm}^2$$

Even taking into account the tolerance, this device can be satisfied with the limits.

---

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401