

SPECIFICATION

Shenzhen Feixin Wireless Communication Co., Ltd.

2.4G/5.8 FPC antenna

Product specification

Customer		Frequency	2400MHz——2500MHz
R F design	XIAO BIN	Version	A1
Technical director	ANDY	date	2023-12-14

Customer confirmation:

Whether the assembly meets your company's requirements: ☐OK ☐NG

Confidentiality requirements

Our company already possesses the proprietary technology provided, and these proprietary information should be strictly kept confidential. Without the prior written consent of Shenzhen Feixin Wireless Communication Co., Ltd., it is not allowed to be disclosed to anyone or the company.


Directory

Cover	1
1、 Directory.....	2
2、 Product pictures	3
3、 S11 data	4
4、 Antenna test data (gain, efficiency, apple chart).....	4
5、 Product structure drawing.....	7

Confidentiality requirements

Our company already possesses the proprietary technology provided, and these proprietary information should be strictly kept confidential. Without the prior written consent of Shenzhen Feixin Wireless Communication Co., Ltd., it is not allowed to be disclosed to anyone or the company.

1、Product pictures



2、Product parameters


Product testing parameters			
产品名称(Name)	2.4G WIFI	产品型号(Model Type)	FX-2.4/5.8-QYCX-F PC-V1.2
电 性 能 指 标 (Electrical Specifications)			
频率范围 (Frequency Range)	2400-2500MHz 5200-5800MHz	极化方式 (Polarization)	vertical
输入阻抗(Impedance)	50 Ω	辐射方向	Omnidirectional
驻波比 (VSWR)	≤ 3.0	功率容量(Power)	50W
增益(Gain)	2.74dBi	带宽 (Bandwidth)	100/600MHz
机 械 指 标 (Mechanical Specifications)			
尺寸 (Dimensions)	29.6*10.4 $\pm$ 0.15 mm	外壳颜色(ANT Color)	black
连接器型号 (Connector)	IPEX 4	引线长度(Cable Length)	110 $\pm$ 3 mm
外壳材料 Radome Material	FPC		
工作温度 (Working Temperature)	-40 $^{\circ}$ C--+85 $^{\circ}$ C	存放温度 (Limit Temperature)	-40 $^{\circ}$ C--+85 $^{\circ}$ C

<http://www.flxant.com> <http://www.fly-core.com>

Confidentiality requirements

Our company already possesses the proprietary technology provided, and these proprietary information should be strictly kept confidential. Without the prior written consent of Shenzhen Feixin Wireless Communication Co., Ltd., it is not allowed to be disclosed to anyone or the company.

3. VSWR, Return loss and Smith data



Confidentiality requirements

Our company already possesses the proprietary technology provided, and these proprietary information should be strictly kept confidential. Without the prior written consent of Shenzhen Feixin Wireless Communication Co., Ltd., it is not allowed to be disclosed to anyone or the company.



4、Antenna test data (gain, efficiency, apple chart)

Test Point ID	Freq. (MHz)	TRP (dBm)	Gain (dBi)	Directivity (dBi)	Efficiency (%)
1	2400.0	2400.00	-2.59	4.90	24.8%
2	2410.0	2410.00	-2.11	5.22	25.5%
3	2420.0	2420.00	-2.00	4.98	26.1%
4	2430.0	2430.00	-1.96	5.12	27.6%
5	2440.0	2440.00	-1.72	5.09	28.8%
6	2450.0	2450.00	-1.72	5.05	30.0%
7	2460.0	2460.00	-1.52	5.33	31.6%
8	2470.0	2470.00	-1.84	5.45	28.7%
9	2480.0	2480.00	-1.43	5.94	27.3%
10	2490.0	2490.00	-1.33	6.06	26.2%
11	2500.0	2500.00	-0.69	6.60	26.7%

Test Point ID	Freq. (MHz)	TRP (dBm)	Gain (dBi)	Directivity (dBi)	Efficiency (%)
1	5200.0	5200.00	0.75	8.23	25.9%
2	5225.0	5225.00	0.52	7.91	26.3%
3	5250.0	5250.00	0.79	8.11	28.5%
4	5275.0	5275.00	0.53	7.70	29.2%
5	5300.0	5300.00	0.05	7.08	29.8%
6	5325.0	5325.00	0.31	6.63	30.3%
7	5350.0	5350.00	-0.26	6.06	25.3%
8	5375.0	5375.00	-0.59	5.06	26.2%
9	5400.0	5400.00	-0.39	5.16	25.8%
10	5425.0	5425.00	0.05	5.10	31.2%
11	5450.0	5450.00	0.51	5.27	33.4%
12	5475.0	5475.00	0.76	5.47	33.8%
13	5500.0	5500.00	1.13	5.76	34.5%
14	5525.0	5525.00	1.04	6.01	31.8%
15	5550.0	5550.00	0.96	5.99	31.4%
16	5575.0	5575.00	0.79	6.28	28.3%
17	5600.0	5600.00	0.61	6.24	27.4%
18	5625.0	5625.00	1.36	6.52	30.5%
19	5650.0	5650.00	1.65	6.59	32.1%
20	5675.0	5675.00	1.77	6.19	36.1%
21	5700.0	5700.00	1.69	6.06	36.6%
22	5725.0	5725.00	1.84	5.92	39.1%
23	5750.0	5750.00	1.73	6.28	35.1%
24	5775.0	5775.00	1.90	6.51	34.6%
25	5800.0	5800.00	2.74	7.08	36.8%

Confidentiality requirements

Our company already possesses the proprietary technology provided, and these proprietary information should be strictly kept confidential. Without the prior written consent of Shenzhen Feixin Wireless Communication Co., Ltd., it is not allowed to be disclosed to anyone or the company.



<http://www.flxant.com> <http://www.fly-core.com>

Our company already possesses the proprietary technology provided, and these proprietary information should be strictly kept confidential. Without the prior written consent of Shenzhen Feixin Wireless Communication Co., Ltd., it is not allowed to be disclosed to anyone or the company.

Figure 2: Cross-section of the fitting (Figure 2) showing dimensions: 110±3MM, 29.60±0.15, and *10.40±0.15.

Figure 1: Side view of the fitting (Figure 1) showing dimensions: 110±3MM, 29.60±0.15, and *10.40±0.15.

Technical drawing of a 4代PEX pipe fitting. The drawing shows a cross-section of the fitting (Figure 2) and a side view (Figure 1). The side view shows a pipe with a diameter of 110±3MM and a length of 29.60±0.15. The fitting is labeled '4代PEX'. The drawing includes dimensions for the fitting and the pipe, as well as a table of material properties.

Confidentiality requirements

Our company already possesses the proprietary technology provided, and these proprietary information should be strictly kept confidential. Without the prior written consent of Shenzhen Feixin Wireless Communication Co., Ltd., it is not allowed to be disclosed to anyone or the company.
