

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Mobile Phone

Trademark : Bmobile

Model Name : AX1080

Family Model : N/A

Report No. : S19012403602001

FCC ID : ZSW-30-085

Prepared for

b mobile HK Limited

Flat 18; 14/F Block 1; Golden Industrial Building; 16-26 KwaiTak Street; Kwai Chung;
New Territories; Hong Kong, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District,
Shenzhen, Guangdong, China

Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599

Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name**..... : b mobile HK LimitedAddress..... : Flat 18; 14/F Block 1; Golden Industrial Building;16-26 KwaiTak
Street; Kwai Chung;New Territories; Hong Kong, China**Manufacturer's Name**..... : b mobile HK LimitedAddress..... : Flat 18; 14/F Block 1; Golden Industrial Building;16-26 KwaiTak
Street; Kwai Chung;New Territories; Hong Kong, China**Product description**

Product name..... : Mobile Phone

Trademark : Bmobile

Model Name : AX1080

Family Model..... : N/A

FCC 47 CFR Part 2(2.1093)

ANSI/IEEE C95.1-1992

Standards..... : IEEE Std 1528-2013

Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests..... : Jan. 26, 2019 ~ Feb. 21, 2019

Date of Issue : May 10, 2019

Test Result : **Pass**

Prepared By : Cheng Jiawen
(Test Engineer) (Cheng Jiawen)

Approved By : Sam. Chen
(Lab Manager) (Sam Chen)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	May 10, 2019	Cheng Jiawen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	8
1.4. Test specification(s)	10
1.5. Ambient Condition.....	10
2. SAR Measurement System	11
2.1. SATIMO SAR Measurement Set-up Diagram	11
2.2. Robot	12
2.3. E-Field Probe.....	13
2.3.1. E-Field Probe Calibration	13
2.4. SAM phantoms	14
2.4.1. Technical Data	15
2.5. Device Holder	16
2.6. Test Equipment List	17
3. SAR Measurement Procedures	19
3.1. Power Reference	19
3.2. Area scan & Zoom scan.....	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure	22
4.1. Tissue Verification	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results	25
5. SAR Measurement variability and uncertainty	26
5.1. SAR measurement variability.....	26
5.2. SAR measurement uncertainty	26
6. RF Exposure Positions	27
6.1. Ear and handset reference point	27
6.2. Definition of the cheek position	27
6.3. Definition of the tilt position	29
6.4. Body Worn Accessory	29
6.5. Wireless Router Devices	30
7. RF Output Power	31
7.1. Maximum Tune-up Limit.....	31
7.2. GSM Conducted Power	32
7.3. WCDMA Conducted Power	32

7.4. LTE Conducted Power	34
7.5. WLAN & Bluetooth Output Power	43
7.5.1. Output Power Results Of WLAN	43
7.5.2. Output Power Results Of Bluetooth.....	43
8. Antenna Location.....	44
9. Stand-alone SAR test exclusion.....	45
10. SAR Results	46
10.1. SAR measurement results.....	46
10.1.1. SAR measurement Result of GSM850.....	46
10.1.2. SAR measurement Result of GSM1900.....	46
10.1.3. SAR measurement Result of WCDMA Band V.....	47
10.1.4. SAR measurement Result of WCDMA Band IV.....	48
10.1.5. SAR measurement Result of WCDMA Band II.....	49
10.1.6. SAR measurement Result of LTE Band V.....	49
10.1.7. SAR measurement Result of LTE Band IV.....	51
10.1.8. SAR measurement Result of LTE Band II.....	53
10.1.9. SAR measurement Result of LTE Band VII.....	54
10.1.10. SAR measurement Result of WLAN 2.4G.....	56
10.2. SAR Summation Scenario.....	57
11. Appendix A. Photo documentation	64
12. Appendix B. System Check Plots.....	65
13. Appendix C. Plots of High SAR Measurement.....	86
14. Appendix D. Calibration Certificate	127

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
HEAD AND TRUNK LIMIT
1.6 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for AX1080 are as follows.

Band	Max Reported SAR Value(W/kg)			
	1-g Head	1-g Body-Worn (Separation distance of 10mm)	1-g Hotspot (Separation distance of 10mm)	Max Simultaneous Tx
GSM 850	0.660	0.653	0.653	1.101
GSM 1900	0.305	0.638	0.638	
WCDMA Band V	0.400	0.394	0.394	
WCDMA Band IV	0.340	0.466	0.466	
WCDMA Band II	0.371	0.512	0.531	
LTE Band V	0.348	0.321	0.321	
LTE Band IV	0.398	0.567	0.567	
LTE Band II	0.360	0.624	0.624	
LTE Band VII	0.120	0.552	0.671	
WLAN 2.4G	0.441	0.421	0.421	

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information			
Product Name		Mobile Phone	
Trade Name		Bmobile	
Model Name		AX1080	
Family Model		N/A	
FCC ID		ZSW-30-085	
Device Phase		Identical Prototype	
Exposure Category		General population / Uncontrolled environment	
Antenna		PIFA Antenna	
Battery Information		DC 3.8V/2000mAh	
Device Operating Configurations			
Supporting Mode(s)		GSM 850/1900, WCDMA Band V/IV/II, LTE Band V/IV/III/VII, WLAN 2.4G, Bluetooth	
Test Modulation		GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK)	
Device Class		B	
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band V	824-849	869-894
	WCDMA Band IV	1710-1755	2110-2155
	WCDMA Band II	1850-1910	1930-1990
	LTE Band V	824-849	869-894
	LTE Band IV	1710-1755	2110-2155
	LTE Band II	1850-1910	1930-1990
	LTE Band VII	2500-2570	2620-2690
	WLAN 2.4G	2412-2462	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EDGE Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control “all 1”(WCDMA Band V)		
	3, tested with power control “all 1”(WCDMA Band IV)		

	3, tested with power control "all 1"(WCDMA Band II)
	3, tested with power control all Max.(LTE Band V)
	3, tested with power control all Max.(LTE Band IV)
	3, tested with power control all Max.(LTE Band II)
	3, tested with power control all Max.(LTE Band VII)
Test Channels (low-mid-high)	128-189-251(GSM 850)
	512-661-810(GSM 1900)
	4132-4182-4233(WCDMA Band V)
	1313-1413-1512 (WCDMA Band IV)
	9262-9400-9538(WCDMA Band II)
	20407-20525-20643(LTE Band V BW=1.4MHz)
	20415-20525-20635(LTE Band V BW=3MHz)
	20425-20525-20625(LTE Band V BW=5MHz)
	20450-20525-20600(LTE Band V BW=10MHz)
	19957-20175-20393(LTE Band IV BW=1.4MHz)
	19965-20175-20385(LTE Band IV BW=3MHz)
	19975-20175-20375(LTE Band IV BW=5MHz)
	20000-20175-20350(LTE Band IV BW=10MHz)
	20025-20175-20325(LTE Band IV BW=15MHz)
	20050-20175-20300(LTE Band IV BW=20MHz)
	18607-18900-19193(LTE Band II BW=1.4MHz)
	18615-18900-19185(LTE Band II BW=3MHz)
	18625-18900-19175(LTE Band II BW=5MHz)
	18650-18900-19150(LTE Band II BW=10MHz)
	18675-18900-19125(LTE Band II BW=15MHz)
	18700-18900-19100(LTE Band II BW=20MHz)
	20775-21100-21425(LTE Band VII BW=5MHz)
	20800-21100-21400(LTE Band VII BW=10MHz)
	20825-21100-21375(LTE Band VII BW=15MHz)
	20850-21100-21350(LTE Band VII BW=20MHz)
	1-6-11(WLAN 2.4G)

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 08/16 EPGO287 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter: 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.08 dB
 - Axial isotropy: 0.06 dB
 - Hemispherical Isotropy: 0.08 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 7mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm $\pm$ 0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μ m.

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 08/16 EPGO287	Sep. 17, 2018	Sep. 16, 2019
☐	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Aug. 05, 2018	Aug. 04, 2019
☒	R&S	Wideband radio communication tester	CMW500	103917	Oct. 08, 2018	Oct. 07, 2019
☒	HP	Network Analyzer	8753D	3410J01136	Aug. 05, 2018	Aug. 04, 2019
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Aug. 05, 2018	Aug. 04, 2019

☒	Agilent	Power meter	E4419B	MY45102538	Aug. 05, 2018	Aug. 04, 2019
☒	Agilent	Power sensor	E9301A	MY41495644	Aug. 05, 2018	Aug. 04, 2019
☒	Agilent	Power sensor	E9301A	US39212148	Aug. 05, 2018	Aug. 04, 2019
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Aug. 05, 2018	Aug. 04, 2019

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23
Ingredients (% of weight)	Body Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88	79.54	79.54
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97	11.24	11.24
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99	9.22	9.22

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 850	835	41.50 (39.43~43.57)	0.90 (0.86~0.94)	41.60	0.90	21.6 °C	Feb. 19, 2018
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.01)	54.88	1.00	21.4 °C	Feb. 20, 2018
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.63	1.40	21.6 °C	Feb. 13, 2018
Body 1800	1800	53.30 (50.64~55.96)	1.52 (1.44~1.59)	53.75	1.53	21.6 °C	Feb. 16, 2018
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.97	1.41	21.5 °C	Feb. 15, 2018
Body 1900	1900	53.30 (50.64~55.96)	1.52 (1.44~1.59)	53.14	1.55	21.3 °C	Feb. 15, 2018
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	39.96	1.79	21.4 °C	Jan. 26, 2019
Body 2450	2450	52.70 (50.07~55.33)	1.95 (1.85~2.04)	52.64	1.98	21.4 °C	Feb. 16, 2018
Head 2600	2600	39.00 (37.05~40.95)	1.96 (1.86~2.05)	39.00	1.96	21.5 °C	Jan. 26, 2019
Body 2600	2600	52.50 (49.88~55.13)	2.16 (2.05~2.27)	53.01	2.17	21.7 °C	Feb. 21, 2018

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
835MHz Head	9.56 (8.60~10.51)	6.22 (5.60~6.84)	9.48	6.20	21.6 °C	Feb. 19, 2018
835MHz Body	9.48 (8.53~10.42)	6.29 (5.66~6.91)	9.52	6.39	21.4 °C	Feb. 20, 2018
1800MHz Head	38.40 (34.56~42.24)	20.10 (18.09~22.11)	41.39	20.73	21.6 °C	Feb. 13, 2018
1800MHz Body	37.04 (33.34~40.74)	20.26 (18.23~22.29)	36.29	20.68	21.6 °C	Feb. 16, 2018
1900MHz Head	39.70 (35.73~43.67)	20.50 (18.45~22.55)	37.46	19.42	21.5 °C	Feb. 15, 2018
1900MHz Body	38.43 (34.59~42.27)	20.34 (18.31~22.37)	37.53	19.88	21.3 °C	Feb. 15, 2018
2450MHz Head	52.40 (47.16~57.64)	24.00 (21.60~26.40)	54.19	22.14	21.4 °C	Jan. 26, 2019
2450MHz Body	49.32 (44.39~54.25)	22.89 (20.60~25.17)	47.52	22.78	21.4 °C	Feb. 16, 2018
2600MHz Head	55.30 (49.77~60.83)	24.60 (22.14~27.06)	52.31	24.14	21.5 °C	Jan. 26, 2019
2600MHz Body	52.95 (47.66~58.25)	23.64 (21.28~26.00)	50.81	23.88	21.7 °C	Feb. 21, 2018

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. Maximum Tune-up Limit

Band	Mode	The Tune-up Maximum Power (Customer Declared)(dBm)	Range	Measured Maximum Output Power(dBm)
GSM 850	GSM Voice	31.5±1	30.5~32.5	32.50
	GPRS	31.5±1	30.5~32.5	32.48
	EDGE	25.5±1	24.5~26.5	26.49
GSM 1900	GSM Voice	30±1	29~31	30.80
	GPRS	30±1	29~31	30.92
	EDGE	24±1	23~25	25.00
WCDMA Band V	RMC 12.2Kbps	22.5±1	21.5~23.5	23.27
	HSDPA	21.5±1	20.5~22.5	22.24
	HSUPA	21.5±1	20.5~22.5	22.23
WCDMA Band IV	RMC 12.2Kbps	22.5±1	21.5~23.5	23.50
	HSDPA	22.5±1	21.5~23.5	23.05
	HSUPA	22.5±1	21.5~23.5	23.01
WCDMA Band II	RMC 12.2Kbps	22.5±1	21.5~23.5	23.49
	HSDPA	22.5±1	21.5~23.5	23.09
	HSUPA	22.5±1	21.5~23.5	22.96
LTE Band V	QPSK	20±1	19~21	21.00
	16QAM	20±1	19~21	20.73
LTE Band IV	QPSK	21±1	20~22	21.82
	16QAM	20±1	19~21	21.00
LTE Band II	QPSK	22±1	21~23	22.58
	16QAM	21±1	20~22	21.75
LTE Band VII	QPSK	21±1	20~22	22.00
	16QAM	20±1	19~21	20.99
WLAN 2.4G	802.11b	14±1	13~15	14.6
	802.11g	13±1	12~14	13.8
	802.11n HT20	13±1	12~14	13.7
	802.11n HT40	13±1	12~14	13.2
Bluetooth	BR+EDR	3±1	2~4	3.89
	BLE	3±1	2~4	3.67

7.2. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	32.50	32.36	32.44	32.50	23.47	23.33	23.41	23.47
GPRS(GMSK, 1 TS)	32.50	32.37	32.45	32.48	23.47	23.34	23.42	23.45
GPRS(GMSK, 2 TS)	31.50	31.49	31.49	31.47	25.48	25.47	25.47	25.45
GPRS(GMSK, 3 TS)	29.50	29.46	29.48	29.47	25.24	25.20	25.22	25.21
GPRS(GMSK, 4 TS)	28.50	28.50	28.45	28.49	25.49	25.49	25.44	25.48
EDGE(GMSK, 1 TS)	26.50	26.49	26.47	26.45	17.47	17.46	17.44	17.42
EDGE(GMSK, 2 TS)	25.50	25.32	25.27	25.22	19.48	19.30	19.25	19.20
EDGE(GMSK, 3 TS)	22.50	22.49	22.41	22.48	18.24	18.23	18.15	18.22
EDGE(GMSK, 4 TS)	21.50	21.39	21.43	21.35	18.49	18.38	18.42	18.34
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	31.00	30.80	30.78	30.69	21.97	21.77	21.75	21.66
GPRS(GMSK, 1 TS)	31.00	30.92	30.88	30.82	21.97	21.89	21.85	21.79
GPRS(GMSK, 2 TS)	30.00	29.60	29.64	29.58	23.98	23.58	23.62	23.56
GPRS(GMSK, 3 TS)	28.00	27.90	27.85	27.93	23.74	23.64	23.59	23.67
GPRS(GMSK, 4 TS)	27.00	26.72	26.69	26.78	23.99	23.71	23.68	23.77
EDGE(GMSK, 1 TS)	25.00	24.62	24.97	25.00	15.97	15.59	15.94	15.97
EDGE(GMSK, 2 TS)	23.00	22.98	22.92	22.85	16.98	16.96	16.90	16.83
EDGE(GMSK, 3 TS)	21.00	20.47	20.49	20.51	16.74	16.21	16.23	16.25
EDGE(GMSK, 4 TS)	19.00	18.59	18.55	18.62	15.99	15.58	15.54	15.61

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) - 3.01 dB

7.3. WCDMA Conducted Power

Band	WCDMA Band V			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	23.50	23.27	23.16	23.04
HSDPA Subtest-1	22.50	22.24	22.15	22.04

HSDPA Subtest-2	21.50	21.47	21.49	21.47
HSDPA Subtest-3	21.50	21.45	21.48	21.49
HSDPA Subtest-4	21.50	21.46	21.46	21.50
HSUPA Subtest-1	21.50	21.48	21.45	21.50
HSUPA Subtest-2	21.50	21.49	21.49	21.49
HSUPA Subtest-3	21.50	21.44	21.41	21.48
HSUPA Subtest-4	21.50	21.43	21.48	21.47
HSUPA Subtest-5	22.50	22.23	22.14	22.06
Band	WCDMA Band IV			
Tx Channel	Tune-up	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC 12.2Kbps	23.50	23.50	23.48	23.47
HSDPA Subtest-1	23.50	23.05	22.78	22.85
HSDPA Subtest-2	22.50	22.24	22.18	22.25
HSDPA Subtest-3	22.50	22.25	22.20	22.26
HSDPA Subtest-4	22.50	22.22	22.19	22.23
HSUPA Subtest-1	22.50	22.25	22.18	22.27
HSUPA Subtest-2	22.50	22.27	22.21	22.29
HSUPA Subtest-3	22.50	22.29	22.16	22.28
HSUPA Subtest-4	22.50	22.31	22.20	22.30
HSUPA Subtest-5	23.50	23.01	22.98	22.91
Band	WCDMA Band II			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC 12.2Kbps	23.50	23.10	23.49	23.20
HSDPA Subtest-1	23.50	22.95	23.09	23.07
HSDPA Subtest-2	22.50	22.02	22.48	22.46
HSDPA Subtest-3	22.50	22.03	22.48	22.48
HSDPA Subtest-4	22.50	22.05	22.50	22.45
HSUPA Subtest-1	22.50	22.06	22.49	22.47
HSUPA Subtest-2	22.50	22.08	22.46	22.45
HSUPA Subtest-3	22.50	22.08	22.45	22.46
HSUPA Subtest-4	22.50	22.04	22.48	22.43
HSUPA Subtest-5	23.50	22.89	22.95	22.96

7.4. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band V	1.4MHz	QPSK	1	0	21.00	20.87	20.89	20.62
			1	2	21.00	20.96	20.97	20.80
			1	5	21.00	20.92	20.51	20.56
			3	0	21.00	20.93	20.78	20.68
			3	1	21.00	20.92	20.74	20.65
			3	2	21.00	20.91	20.68	20.68
		16QAM	6	0	20.00	19.98	19.99	19.70
			1	0	21.00	20.00	20.15	19.65
			1	2	21.00	20.21	20.36	19.87
			1	5	21.00	20.01	20.14	19.67
			3	0	21.00	19.98	20.42	19.85
			3	1	21.00	19.97	20.40	19.84
			3	2	21.00	19.96	20.38	19.83
			6	0	20.00	19.00	19.22	18.64
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band V	3MHz	QPSK	1	0	21.00	20.90	20.98	20.75
			1	7	21.00	20.86	20.99	20.65
			1	14	21.00	20.88	20.34	20.60
			8	0	20.00	19.96	19.98	19.73
			8	4	20.00	19.96	19.97	19.69
			8	7	20.00	19.95	19.93	19.70
			15	0	20.00	19.95	19.99	19.71
		16QAM	1	0	21.00	20.54	20.23	19.95
			1	7	21.00	20.53	20.18	19.83
			1	14	21.00	20.57	20.12	19.83
			8	0	19.00	18.97	19.00	18.71
			8	4	19.00	18.99	18.96	18.64
			8	7	19.00	18.93	18.97	18.61
			15	0	19.00	18.98	18.95	18.64
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band V	5MHz	QPSK	1	0	21.00	20.85	20.99	20.80
			1	12	21.00	21.00	20.68	20.78
			1	24	21.00	20.94	20.49	20.58
			12	0	20.00	19.95	19.98	19.86
			12	6	20.00	19.97	19.97	19.75
			12	11	20.00	19.98	19.96	19.70
			25	0	20.00	19.99	19.97	19.80
		16QAM	1	0	20.00	19.79	19.97	19.99
			1	12	20.00	19.94	19.86	19.97
			1	24	20.00	19.90	19.95	19.93
			12	0	19.00	18.96	18.85	18.89
			12	6	19.00	18.95	18.93	18.82
			12	11	19.00	18.96	18.97	18.75
			25	0	19.00	19.00	18.99	18.76
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band V	10MHz	QPSK	1	0	21.00	20.91	21.00	20.73
			1	24	21.00	20.98	20.62	20.96
			1	49	21.00	20.96	20.75	20.63
			25	0	21.00	20.17	20.20	19.99
			25	12	21.00	20.15	20.21	19.87
			25	24	21.00	20.14	20.22	19.80
			50	0	21.00	20.15	20.23	19.92
		16QAM	1	0	21.00	20.53	20.19	20.12
			1	24	21.00	20.73	20.29	20.16
			1	49	21.00	20.72	19.99	19.82
			25	0	20.00	19.23	19.35	19.02
			25	12	20.00	19.21	19.31	18.92
			25	24	20.00	19.19	19.26	18.80
			50	0	20.00	19.20	19.27	18.91

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3

LTE Band IV	1.4MHz	QPSK	1	0	22.00	21.15	21.36	21.54
			1	2	22.00	21.45	21.60	21.82
			1	5	22.00	21.14	21.38	21.47
			3	0	22.00	21.26	21.45	21.67
			3	1	22.00	21.25	21.48	21.52
			3	2	22.00	21.26	21.51	21.49
			6	0	21.00	20.27	20.57	20.74
		16QAM	1	0	21.00	20.21	20.43	20.74
			1	2	21.00	20.48	20.60	21.00
			1	5	21.00	20.24	20.41	20.82
			3	0	21.00	20.53	20.59	20.79
			3	1	21.00	20.55	20.58	20.81
			3	2	21.00	20.57	20.58	20.86
			6	0	20.00	19.28	19.39	19.76
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band IV	3MHz	QPSK	1	0	22.00	21.19	21.43	21.64
			1	7	22.00	21.26	21.43	21.66
			1	14	22.00	21.30	21.45	21.37
			8	0	21.00	20.28	20.47	20.72
			8	4	21.00	20.29	20.45	20.73
			8	7	21.00	20.31	20.44	20.75
			15	0	21.00	20.32	20.48	20.74
		16QAM	1	0	21.00	20.89	20.51	20.85
			1	7	21.00	20.86	20.52	20.88
			1	14	21.00	20.95	20.47	20.85
			8	0	20.00	19.45	19.47	19.73
			8	4	20.00	19.46	19.49	19.72
			8	7	20.00	19.48	19.50	19.72
			15	0	20.00	19.37	19.50	19.72
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band IV	5MHz	QPSK	1	0	22.00	21.15	21.37	21.60
			1	12	22.00	21.32	21.48	21.71
			1	24	22.00	21.24	21.38	21.57
			12	0	21.00	20.29	20.42	20.71

			12	6	21.00	20.31	20.45	20.70
			12	11	21.00	20.35	20.48	20.69
			25	0	21.00	20.34	20.47	20.73
		16QAM	1	0	21.00	20.09	20.47	20.93
			1	12	21.00	20.27	20.60	21.00
			1	24	21.00	20.14	20.49	20.98
			12	0	20.00	19.27	19.48	19.79
			12	6	20.00	19.31	19.48	19.76
			12	11	20.00	19.36	19.48	19.75
			25	0	20.00	19.39	19.52	19.73
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band IV	10MHz	QPSK	1	0	22.00	21.19	21.41	21.50
			1	24	22.00	21.44	21.60	21.74
			1	49	22.00	21.31	21.44	21.62
			25	0	21.00	20.38	20.56	20.71
			25	12	21.00	20.41	20.55	20.69
			25	24	21.00	20.46	20.54	20.70
			50	0	21.00	20.45	20.54	20.74
		16QAM	1	0	21.00	20.83	20.43	20.69
			1	24	21.00	20.98	20.61	20.92
			1	49	21.00	20.94	20.48	20.87
			25	0	20.00	19.45	19.64	19.75
			25	12	20.00	19.49	19.63	19.74
			25	24	20.00	19.51	19.61	19.75
			50	0	20.00	19.47	19.56	19.73
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band IV	15MHz	QPSK	1	0	22.00	21.16	21.30	21.40
			1	37	22.00	21.30	21.49	21.62
			1	74	22.00	21.29	21.40	21.60
			36	0	21.00	20.39	20.51	20.68
			36	18	21.00	20.42	20.52	20.65
			36	37	21.00	20.50	20.54	20.62
			75	0	21.00	20.44	20.57	20.70
		16QAM	1	0	21.00	20.81	20.75	20.58

			1	37	21.00	20.98	20.93	20.83
			1	74	21.00	20.88	20.84	20.81
			36	0	20.00	19.41	19.47	19.70
			36	18	20.00	19.46	19.49	19.68
			36	37	20.00	19.51	19.51	19.67
			75	0	20.00	19.44	19.49	19.66
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band IV	20MHz	QPSK	1	0	22.00	21.02	21.10	21.21
			1	49	22.00	21.51	21.56	21.80
			1	99	22.00	21.19	21.24	21.50
			50	0	21.00	20.37	20.49	20.64
			50	24	21.00	20.43	20.47	20.58
			50	49	21.00	20.47	20.45	20.55
			100	0	21.00	20.43	20.43	20.62
		16QAM	1	0	21.00	20.41	20.71	20.50
			1	49	21.00	20.85	20.92	20.99
			1	99	21.00	20.53	20.90	20.75
			50	0	20.00	19.36	19.49	19.63
			50	24	20.00	19.40	19.47	19.55
			50	49	20.00	19.48	19.46	19.53
			100	0	20.00	19.44	19.46	19.60

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band II	1.4MHz	QPSK	1	0	23.00	22.26	22.41	22.21
			1	2	23.00	22.45	22.40	22.23
			1	5	23.00	22.22	22.42	22.26
			3	0	23.00	22.34	22.58	22.23
			3	1	23.00	22.32	22.45	22.25
			3	2	23.00	22.33	22.46	22.21
			6	0	22.00	21.67	20.89	20.85
		16QAM	1	0	22.00	21.64	20.87	20.84
			1	2	22.00	21.71	20.85	20.87
			1	5	22.00	21.70	20.81	20.89
			3	0	22.00	21.69	20.82	20.83

			3	1	22.00	21.71	20.80	20.80
			3	2	22.00	21.75	20.71	20.84
			6	0	21.00	20.33	20.01	20.09
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band II	3MHz	QPSK	1	0	22.00	21.96	21.43	20.96
			1	7	22.00	21.93	21.37	21.24
			1	14	22.00	21.98	21.32	20.78
			8	0	21.00	20.98	20.44	20.27
			8	4	21.00	20.95	20.39	20.25
			8	7	21.00	20.97	20.35	20.24
			15	0	21.00	20.96	20.41	20.28
		16QAM	1	0	22.00	21.75	20.52	20.39
			1	7	22.00	21.58	20.39	20.36
			1	14	22.00	21.54	20.36	20.36
			8	0	21.00	20.38	19.50	19.23
			8	4	21.00	20.35	19.48	19.22
			8	7	21.00	20.32	19.41	19.21
			15	0	21.00	20.27	19.47	19.22
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band II	5MHz	QPSK	1	0	22.00	21.98	21.34	20.82
			1	12	22.00	21.96	21.41	20.84
			1	24	22.00	21.87	21.17	20.84
			12	0	21.00	20.98	20.46	20.28
			12	6	21.00	20.96	20.44	20.27
			12	11	21.00	20.94	20.42	20.26
			25	0	21.00	21.00	20.43	20.31
		16QAM	1	0	21.00	20.98	20.48	20.49
			1	12	21.00	20.96	20.50	20.60
			1	24	21.00	20.79	20.34	20.44
			12	0	20.00	19.98	19.45	19.36
			12	6	20.00	19.96	19.42	19.35
			12	11	20.00	19.93	19.39	19.35
			25	0	20.00	19.96	19.51	19.29
Band	Band	Modulation	RB		Tune-up	Channel/Frequency(MHz)		

	Width		Configuration					
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band II	10MHz	QPSK	1	0	22.00	21.96	21.44	20.80
			1	24	22.00	21.95	21.28	20.80
			1	49	22.00	21.65	21.17	20.82
			25	0	21.00	20.92	20.55	20.43
			25	12	21.00	20.99	20.49	20.39
			25	24	21.00	20.96	20.45	20.34
			50	0	21.00	20.97	20.51	20.42
		16QAM	1	0	22.00	21.71	20.53	20.43
			1	24	22.00	21.67	20.58	20.58
			1	49	22.00	21.34	20.23	20.39
			25	0	21.00	20.23	19.67	19.48
			25	12	21.00	20.18	19.65	19.45
			25	24	21.00	20.11	19.60	19.41
			50	0	21.00	20.14	19.57	19.44
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band II	15MHz	QPSK	1	0	22.00	22.00	21.49	21.08
			1	37	22.00	21.90	21.42	21.02
			1	74	22.00	21.60	21.03	21.12
			36	0	21.00	20.99	20.57	20.35
			36	18	21.00	20.96	20.40	20.31
			36	37	21.00	20.85	20.35	20.28
			75	0	21.00	21.00	20.51	20.36
		16QAM	1	0	21.00	20.98	21.00	20.26
			1	37	21.00	20.99	20.85	20.47
			1	74	21.00	20.96	20.50	20.29
			36	0	20.00	19.94	19.56	19.37
			36	18	20.00	19.93	19.45	19.36
			36	37	20.00	19.90	19.37	19.35
			75	0	20.00	19.95	19.45	19.35
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE	20MHz	QPSK	1	0	22.00	22.00	21.18	20.90

Band II			1	49	22.00	21.66	21.23	20.39
			1	99	22.00	20.97	20.78	20.72
			50	0	21.00	20.98	20.65	20.30
			50	24	21.00	20.89	20.42	20.29
			50	49	21.00	20.72	20.37	20.28
			100	0	21.00	20.85	20.45	20.29
		16QAM	1	0	21.00	20.95	20.93	20.19
			1	49	21.00	20.99	20.95	20.56
			1	99	21.00	20.84	20.46	20.24
			50	0	20.00	20.00	19.67	19.36
			50	24	20.00	19.97	19.41	19.35
			50	49	20.00	19.76	19.35	19.31
			100	0	20.00	19.97	19.50	19.34

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band VII	5MHz	QPSK	1	0	22.00	21.76	21.44	21.88
			1	12	22.00	21.82	21.49	22.00
			1	24	22.00	21.70	21.42	21.96
			12	0	21.00	20.78	20.45	20.80
			12	6	21.00	20.77	20.45	20.94
			12	11	21.00	20.78	20.46	20.98
			25	0	21.00	20.80	20.46	20.93
		16QAM	1	0	21.00	20.97	20.28	20.94
			1	12	21.00	20.96	20.41	20.89
			1	24	21.00	20.93	20.30	20.87
			12	0	20.00	19.78	19.47	19.98
			12	6	20.00	19.80	19.50	19.96
			12	11	20.00	19.81	19.53	19.93
			25	0	20.00	19.73	19.54	20.00
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band VII	10MHz	QPSK	1	0	22.00	21.85	21.52	21.85
			1	24	22.00	21.94	21.71	21.82
			1	49	22.00	21.58	21.49	21.84
			25	0	21.00	20.78	20.49	20.96

			25	12	21.00	20.77	20.52	20.97
			25	24	21.00	20.78	20.59	20.98
			50	0	21.00	20.82	20.57	21.00
		16QAM	1	0	21.00	20.97	20.49	20.94
			1	24	21.00	20.98	20.64	20.95
			1	49	21.00	20.95	20.50	20.93
			25	0	20.00	19.79	19.60	19.96
			25	12	20.00	19.81	19.65	19.00
			25	24	20.00	19.84	19.69	19.97
			50	0	20.00	19.75	19.62	19.85
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band VII	15MHz	QPSK	1	0	22.00	21.77	21.52	21.65
			1	37	22.00	21.65	21.50	21.93
			1	74	22.00	21.39	21.43	21.97
			36	0	21.00	20.77	20.54	20.94
			36	18	21.00	20.68	20.58	20.95
			36	37	21.00	20.62	20.61	20.96
			75	0	21.00	20.70	20.62	20.95
		16QAM	1	0	21.00	20.96	20.86	20.94
			1	37	21.00	20.93	20.89	20.99
			1	74	21.00	20.94	20.90	20.94
			36	0	20.00	19.78	19.54	19.96
			36	18	20.00	19.69	19.55	20.00
			36	37	20.00	19.66	19.56	19.87
			75	0	20.00	19.67	19.56	19.95
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band VII	20MHz	QPSK	1	0	22.00	21.64	21.38	21.46
			1	49	22.00	21.73	21.56	21.89
			1	99	22.00	21.22	21.27	21.80
			50	0	21.00	20.64	20.54	20.88
			50	24	21.00	20.60	20.58	20.90
			50	49	21.00	20.58	20.62	20.92
			100	0	21.00	20.61	20.57	20.94
		16QAM	1	0	21.00	20.88	20.93	20.66

			1	49	21.00	20.91	20.94	20.95
			1	99	21.00	20.53	20.83	20.98
			50	0	20.00	19.63	19.52	19.89
			50	24	20.00	19.58	19.57	19.92
			50	49	20.00	19.53	19.60	19.96
			100	0	20.00	19.65	19.62	19.98

7.5. WLAN & Bluetooth Output Power

7.5.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	15.0	14.1
	6	2437	15.0	14.5
	11	2462	15.0	14.6
802.11g	1	2412	14.0	13.1
	6	2437	14.0	13.6
	11	2462	14.0	13.8
802.11n HT20	1	2412	14.0	12.8
	6	2437	14.0	13.3
	11	2462	14.0	13.7
802.11n HT40	3	2422	14.0	12.3
	6	2437	14.0	12.7
	9	2452	14.0	13.2

7.5.2. Output Power Results Of Bluetooth


BR+EDR	Output Power (dBm)				
	Channel	Tune-up	Data Rates		
			0CH	39CH	78CH
	1M	4.00	3.65	3.68	3.89
	2M	4.00	2.47	2.73	2.91
	3M	4.00	2.78	2.99	3.15

BLE	Channel	Tune-up	Output Power (dBm)
	0CH	4.00	3.67
	19CH	4.00	3.22
	39CH	4.00	3.31

8. Antenna Location

Left Side

142mm



Right Side

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	Yes	Yes	NO	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	Yes	NO	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	4.00	2.51	5	2.480	0.79	3.0	Yes

NOTE: Standalone SAR test exclusion for Bluetooth

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}/x] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	4.00	2.51	5	2.480	7.5	0.105
Bluetooth	Body	4.00	2.51	10	2.480	7.5	0.053
Bluetooth	Hotspot	4.00	2.51	10	2.480	7.5	0.053

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	189/836.4	GPRS(GMSK 4TS)	0.652	0.481	0.80	28.45	28.50	0.660
Left Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.335	0.230	1.52	28.45	28.50	0.339
Right Cheek	189/836.4	GPRS(GMSK 4TS)	0.565	0.430	0.02	28.45	28.50	0.572
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.287	0.197	-2.14	28.45	28.50	0.290

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 4TS)	0.646	0.468	-1.66	28.45	28.50	0.653
Back Side	189/836.4	GPRS(GMSK 4TS)	0.580	0.435	1.48	28.45	28.50	0.587

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 4TS)	0.646	0.468	-1.66	28.45	28.50	0.653
Back Side	189/836.4	GPRS(GMSK 4TS)	0.580	0.435	1.48	28.45	28.50	0.587
Right Side	189/836.4	GPRS(GMSK 4TS)	0.317	0.221	0.42	28.45	28.50	0.321
Bottom Side	189/836.4	GPRS(GMSK 4TS)	0.200	0.130	0.70	28.45	28.50	0.202

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	661/1880	GPRS(GMSK 4TS)	0.284	0.171	1.93	26.69	27.00	0.305
Left Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.116	0.072	0.12	26.69	27.00	0.125

Right Cheek	661/1880	GPRS(GMSK 4TS)	0.271	0.167	0.51	26.69	27.00	0.291
Right Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.109	0.065	-0.34	26.69	27.00	0.117

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 4TS)	0.506	0.309	1.11	26.69	27.00	0.543
Back Side	661/1880	GPRS(GMSK 4TS)	0.594	0.335	-2.76	26.69	27.00	0.638

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 4TS)	0.506	0.309	1.11	26.69	27.00	0.543
Back Side	661/1880	GPRS(GMSK 4TS)	0.594	0.335	-2.76	26.69	27.00	0.638
Right Side	661/1880	GPRS(GMSK 4TS)	0.246	0.143	1.96	26.69	27.00	0.264
Bottom Side	661/1880	GPRS(GMSK 4TS)	0.514	0.268	-0.68	26.69	27.00	0.552

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band V

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	4182/836.4	RMC12.2K	0.370	0.281	2.05	23.16	23.50	0.400
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.196	0.115	3.15	23.16	23.50	0.212
Right Cheek	4182/836.4	RMC12.2K	0.328	0.251	-3.13	23.16	23.50	0.355
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.191	0.112	-0.42	23.16	23.50	0.207

NOTE: Head SAR test results of WCDMA Band V

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.364	0.275	-2.52	23.16	23.50	0.394
Back Side	4182/836.4	RMC12.2K	0.342	0.259	-2.11	23.16	23.50	0.370

NOTE: Body-Worn SAR test results of WCDMA Band V

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.364	0.275	-2.52	23.16	23.50	0.394
Back Side	4182/836.4	RMC12.2K	0.342	0.259	-2.11	23.16	23.50	0.370
Right Side	4182/836.4	RMC12.2K	0.218	0.141	1.06	23.16	23.50	0.236
Bottom Side	4182/836.4	RMC12.2K	0.239	0.152	-0.31	23.16	23.50	0.258

NOTE: Hotspot SAR test results of WCDMA Band V

10.1.4. SAR measurement Result of WCDMA Band IV

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	1413/1732.6	RMC12.2K	0.338	0.213	1.40	23.48	23.50	0.340
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.123	0.078	0.36	23.48	23.50	0.124
Right Cheek	1413/1732.6	RMC12.2K	0.332	0.208	2.58	23.48	23.50	0.334
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.117	0.072	1.62	23.48	23.50	0.118

NOTE: Head SAR test results of WCDMA Band IV

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.437	0.275	-3.21	23.48	23.50	0.439
Back Side	1413/1732.6	RMC12.2K	0.464	0.290	-1.09	23.48	23.50	0.466

NOTE: Body-Worn SAR test results of WCDMA Band IV

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.437	0.275	-3.21	23.48	23.50	0.439
Back Side	1413/1732.6	RMC12.2K	0.464	0.290	-1.09	23.48	23.50	0.466
Right Side	1413/1732.6	RMC12.2K	0.356	0.201	0.57	23.48	23.50	0.358
Bottom Side	1413/1732.6	RMC12.2K	0.405	0.226	0.80	23.48	23.50	0.407

NOTE: Hotspot SAR test results of WCDMA Band IV

10.1.5. SAR measurement Result of WCDMA Band II

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	9400/1880	RMC12.2K	0.370	0.221	-4.43	23.49	23.50	0.371
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.145	0.081	0.31	23.49	23.50	0.145
Right Cheek	9400/1880	RMC12.2K	0.362	0.217	1.58	23.49	23.50	0.363
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.136	0.072	-0.47	23.49	23.50	0.136

NOTE: Head SAR test results of WCDMA Band II

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.420	0.231	0.35	23.49	23.50	0.420
Back Side	9400/1880	RMC12.2K	0.511	0.289	-3.84	23.49	23.50	0.511

NOTE: Body-Worn SAR test results of WCDMA Band II

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.420	0.231	0.35	23.49	23.50	0.421
Back Side	9400/1880	RMC12.2K	0.511	0.289	-3.84	23.49	23.50	0.512
Right Side	9400/1880	RMC12.2K	0.405	0.210	4.02	23.49	23.50	0.406
Bottom Side	9400/1880	RMC12.2K	0.530	0.278	-1.25	23.49	23.50	0.531

NOTE: Hotspot SAR test results of WCDMA Band II

10.1.6. SAR measurement Result of LTE Band V

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	20525/836.5	10M QPSK(1,0)	0.310	0.233	-1.69	21.00	21.00	0.310
Left Tilt 15 Degree	20525/836.5	10M QPSK(1,0)	0.220	0.175	0.34	21.00	21.00	0.220

Right Cheek	20525/836.5	10M QPSK(1,0)	0.272	0.194	-1.47	21.00	21.00	0.272
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,0)	0.212	0.168	1.08	21.00	21.00	0.212
50%RB								
Left Cheek	20525/836.5	10M QPSK(25,24)	0.291	0.226	0.14	20.22	21.00	0.348
Left Tilt 15 Degree	20525/836.5	10M QPSK(25,24)	0.207	0.171	0.36	20.22	21.00	0.248
Right Cheek	20525/836.5	10M QPSK(25,24)	0.257	0.183	1.50	20.22	21.00	0.308
Right Tilt 15 Degree	20525/836.5	10M QPSK(25,24)	0.200	0.160	-0.51	20.22	21.00	0.239

NOTE: Head SAR test results of LTE Band V

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	10M QPSK(1,0)	0.286	0.215	-2.34	21.00	21.00	0.286
Back Side	20525/836.5	10M QPSK(1,0)	0.263	0.200	-2.13	21.00	21.00	0.263
50%RB								
Front Side	20525/836.5	10M QPSK(25,24)	0.268	0.212	1.47	20.22	21.00	0.321
Back Side	20525/836.5	10M QPSK(25,24)	0.235	0.195	-0.82	20.22	21.00	0.281

NOTE: Body-Worn SAR test results of LTE Band V

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	10M QPSK(1,0)	0.286	0.215	-2.34	21.00	21.00	0.286

Back Side	20525/836.5	10M QPSK(1,0)	0.263	0.200	-2.13	21.00	21.00	0.263
Right Side	20525/836.5	10M QPSK(1,0)	0.216	0.176	0.31	21.00	21.00	0.216
Bottom Side	20525/836.5	10M QPSK(1,0)	0.220	0.181	1.85	21.00	21.00	0.220
50%RB								
Front Side	20525/836.5	10M QPSK(25,24)	0.268	0.212	1.47	20.22	21.00	0.321
Back Side	20525/836.5	10M QPSK(25,24)	0.235	0.195	-0.82	20.22	21.00	0.281
Right Side	20525/836.5	10M QPSK(25,24)	0.203	0.172	1.06	20.22	21.00	0.243
Bottom Side	20525/836.5	10M QPSK(25,24)	0.207	0.176	-0.51	20.22	21.00	0.248

NOTE: Hotspot SAR test results of LTE Band V

10.1.7. SAR measurement Result of LTE Band IV

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	20175/1732.5	20M QPSK(1,49)	0.360	0.231	-4.03	21.56	22.00	0.398
Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.179	0.120	0.31	21.56	22.00	0.198
Right Cheek	20175/1732.5	20M QPSK(1,49)	0.352	0.227	1.28	21.56	22.00	0.390
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.168	0.110	-0.36	21.56	22.00	0.186
50%RB								
Left Cheek	20175/1732.5	1.4M QPSK(3,2)	0.342	0.227	1.25	21.51	22.00	0.383
Left Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,2)	0.162	0.116	0.37	21.51	22.00	0.181
Right	20175/1732.5	1.4M QPSK(3,2)	0.335	0.222	-1.28	21.51	22.00	0.375

Cheek								
Right Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,2)	0.152	0.104	2.37	21.51	22.00	0.170

NOTE: Head SAR test results of LTE Band IV

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732.5	20M QPSK(1,49)	0.247	0.169	0.36	21.56	22.00	0.273
Back Side	20175/1732.5	20M QPSK(1,49)	0.512	0.329	-0.38	21.56	22.00	0.567
50%RB								
Front Side	20175/1732.5	1.4M QPSK(3,2)	0.227	0.162	0.21	21.51	22.00	0.254
Back Side	20175/1732.5	1.4M QPSK(3,2)	0.492	0.315	-3.06	21.51	22.00	0.551

NOTE: Body-Worn SAR test results of LTE Band IV

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732. 5	20M QPSK(1,49)	0.247	0.169	0.36	21.56	22.00	0.273
Back Side	20175/1732. 5	20M QPSK(1,49)	0.512	0.329	-0.38	21.56	22.00	0.567
Right Side	20175/1732. 5	20M QPSK(1,49)	0.268	0.179	1.47	21.56	22.00	0.297
Bottom Side	20175/1732. 5	20M QPSK(1,49)	0.497	0.270	-1.09	21.56	22.00	0.550
50%RB								
Front Side	20175/1732. 5	1.4M QPSK(3,2)	0.227	0.162	0.21	21.51	22.00	0.254
Back Side	20175/1732. 5	1.4M QPSK(3,2)	0.492	0.315	-3.06	21.51	22.00	0.551
Right Side	20175/1732.	1.4M QPSK(3,2)	0.257	0.175	1.54	21.51	22.00	0.288

	5							
Bottom Side	20175/1732.5	1.4M QPSK(3,2)	0.482	0.263	2.34	21.51	22.00	0.540

NOTE: Hotspot SAR test results of LTE Band IV

10.1.8. SAR measurement Result of LTE Band II

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	18900/1880	1.4M QPSK(1,5)	0.315	0.192	-1.56	22.42	23.00	0.360
Left Tilt 15 Degree	18900/1880	1.4M QPSK(1,5)	0.205	0.126	0.36	22.42	23.00	0.234
Right Cheek	18900/1880	1.4M QPSK(1,5)	0.310	0.187	1.28	22.42	23.00	0.354
Right Tilt 15 Degree	18900/1880	1.4M QPSK(1,5)	0.196	0.118	1.47	22.42	23.00	0.224
50%RB								
Left Cheek	18900/1880	1.4M QPSK(3,0)	0.312	0.186	0.18	22.58	23.00	0.344
Left Tilt 15 Degree	18900/1880	1.4M QPSK(3,0)	0.201	0.123	1.34	22.58	23.00	0.221
Right Cheek	18900/1880	1.4M QPSK(3,0)	0.305	0.182	2.39	22.58	23.00	0.336
Right Tilt 15 Degree	18900/1880	1.4M QPSK(3,0)	0.193	0.115	2.07	22.58	23.00	0.213

NOTE: Head SAR test results of LTE Band II

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	1.4M QPSK(1,5)	0.236	0.136	0.32	22.42	23.00	0.270

Back Side	18900/1880	1.4M QPSK(1,5)	0.546	0.308	-4.37	22.42	23.00	0.624
50%RB								
Front Side	18900/1880	1.4M QPSK(3,0)	0.228	0.121	1.42	22.58	23.00	0.251
Back Side	18900/1880	1.4M QPSK(3,0)	0.536	0.287	-0.31	22.58	23.00	0.590

NOTE: Body-Worn SAR test results of LTE Band II

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	1.4M QPSK(1,5)	0.236	0.136	0.32	22.42	23.00	0.270
Back Side	18900/1880	1.4M QPSK(1,5)	0.546	0.308	-4.37	22.42	23.00	0.624
Right Side	18900/1880	1.4M QPSK(1,5)	0.263	0.165	0.14	22.42	23.00	0.301
Bottom Side	18900/1880	1.4M QPSK(1,5)	0.492	0.258	-0.97	22.42	23.00	0.562
50%RB								
Front Side	18900/1880	1.4M QPSK(3,0)	0.228	0.121	1.42	22.58	23.00	0.251
Back Side	18900/1880	1.4M QPSK(3,0)	0.536	0.287	-0.31	22.58	23.00	0.590
Right Side	18900/1880	1.4M QPSK(3,0)	0.261	0.157	0.47	22.58	23.00	0.288
Bottom Side	18900/1880	1.4M QPSK(3,0)	0.486	0.239	1.62	22.58	23.00	0.535

NOTE: Hotspot SAR test results of LTE Band II

10.1.9. SAR measurement Result of LTE Band VII

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	21100/2535	20M QPSK(1,49)	0.108	0.073	-2.39	21.56	22.00	0.120
Left Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.051	0.038	1.20	21.56	22.00	0.056
Right Cheek	21100/2535	20M QPSK(1,49)	0.102	0.065	0.36	21.56	22.00	0.113
Right Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.042	0.032	-0.27	21.56	22.00	0.046

NOTE: Head SAR test results of LTE Band VII

NOTE: Body-Worn SAR test results of LTE Band VII

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	20M QPSK(1,49)	0.264	0.174	1.24	21.56	22.00	0.292
Back Side	21100/2535	20M QPSK(1,49)	0.499	0.256	0.92	21.56	22.00	0.552
Right Side	21100/2535	20M QPSK(1,49)	0.226	0.157	0.27	21.56	22.00	0.250
Bottom Side	21100/2535	20M QPSK(1,49)	0.606	0.312	2.16	21.56	22.00	0.671
50%RB								

Front Side	21100/2535	20M QPSK(50,49)	0.251	0.165	0.14	20.62	21.00	0.274
Back Side	21100/2535	20M QPSK(50,49)	0.472	0.238	0.71	20.62	21.00	0.515
Right Side	21100/2535	20M QPSK(50,49)	0.206	0.132	2.51	20.62	21.00	0.225
Bottom Side	21100/2535	20M QPSK(50,49)	0.587	0.301	3.18	20.62	21.00	0.641

NOTE: Hotspot SAR test results of LTE Band VII

10.1.10. SAR measurement Result of WLAN 2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	6/2437	802.11 b	0.393	0.217	0.41	14.50	15.00	0.441
Left Tilt 15 Degree	6/2437	802.11 b	0.229	0.175	0.36	14.50	15.00	0.257
Right Cheek	6/2437	802.11 b	0.382	0.211	1.28	14.50	15.00	0.429
Right Tilt 15 Degree	6/2437	802.11 b	0.221	0.168	2.61	14.50	15.00	0.248

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.126	0.078	1.02	14.50	15.00	0.141
Back Side	6/2437	802.11 b	0.375	0.183	-2.44	14.50	15.00	0.421

NOTE: Body-Worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11 b	0.126	0.078	1.02	14.50	15.00	0.141
Back Side	6/2437	802.11 b	0.375	0.183	-2.44	14.50	15.00	0.421
Left Side	6/2437	802.11 b	0.137	0.080	0.25	14.50	15.00	0.154
Top Side	6/2437	802.11 b	0.110	0.070	-2.82	14.50	15.00	0.123

NOTE: Hotspot SAR test results of WLAN 2.4G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 2.4G			
Head	Left Cheek	0.660	0.441	1.101	N/A	N/A
	Left Tilt 15 Degree	0.339	0.257	0.596	N/A	N/A
	Right Cheek	0.572	0.429	1.000	N/A	N/A
	Right Tilt 15 Degree	0.290	0.248	0.538	N/A	N/A
Body-Worn	Front Side	0.653	0.141	0.795	N/A	N/A
	Back Side	0.587	0.421	1.007	N/A	N/A
Hotspot	Front Side	0.653	0.141	0.795	N/A	N/A
	Back Side	0.587	0.421	1.007	N/A	N/A
	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.321	N/A	0.321	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.202	N/A	0.202	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 2.4G			
Head	Left Cheek	0.305	0.441	0.746	N/A	N/A
	Left Tilt 15 Degree	0.125	0.257	0.382	N/A	N/A
	Right Cheek	0.291	0.429	0.720	N/A	N/A
	Right Tilt 15 Degree	0.117	0.248	0.365	N/A	N/A
Body-Worn	Front Side	0.543	0.141	0.685	N/A	N/A
	Back Side	0.638	0.421	1.059	N/A	N/A
Hotspot	Front Side	0.543	0.141	0.685	N/A	N/A
	Back Side	0.638	0.421	1.059	N/A	N/A
	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.264	N/A	0.264	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.552	N/A	0.552	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band V	WLAN 2.4G			
Head	Left Cheek	0.400	0.441	0.841	N/A	N/A
	Left Tilt 15 Degree	0.212	0.257	0.469	N/A	N/A
	Right Cheek	0.355	0.429	0.783	N/A	N/A
	Right Tilt 15 Degree	0.207	0.248	0.455	N/A	N/A
Body-Worn	Front Side	0.394	0.141	0.535	N/A	N/A
	Back Side	0.370	0.421	0.791	N/A	N/A
Hotspot	Front Side	0.394	0.141	0.535	N/A	N/A
	Back Side	0.370	0.421	0.791	N/A	N/A
	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.236	N/A	0.236	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.258	N/A	0.258	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band V and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band IV	WLAN 2.4G			
Head	Left Cheek	0.340	0.441	0.781	N/A	N/A
	Left Tilt 15 Degree	0.124	0.257	0.381	N/A	N/A
	Right Cheek	0.334	0.429	0.762	N/A	N/A
	Right Tilt 15 Degree	0.118	0.248	0.366	N/A	N/A
Body-Worn	Front Side	0.439	0.141	0.580	N/A	N/A
	Back Side	0.466	0.421	0.887	N/A	N/A
Hotspot	Front Side	0.439	0.141	0.580	N/A	N/A
	Back Side	0.466	0.421	0.887	N/A	N/A
	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.358	N/A	0.358	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.407	N/A	0.407	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band IV and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band II	WLAN 2.4G			
Head	Left Cheek	0.371	0.441	0.812	N/A	N/A
	Left Tilt 15	0.145	0.257	0.402	N/A	N/A

	Degree					
	Right Cheek	0.363	0.429	0.791	N/A	N/A
	Right Tilt 15 Degree	0.136	0.248	0.384	N/A	N/A
Body-Worn	Front Side	0.421	0.141	0.562	N/A	N/A
	Back Side	0.512	0.421	0.933	N/A	N/A
Hotspot	Front Side	0.421	0.141	0.562	N/A	N/A
	Back Side	0.512	0.421	0.933	N/A	N/A
	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.406	N/A	0.406	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.531	N/A	0.531	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band II and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band V	WLAN 2.4G			
Head	Left Cheek	0.348	0.441	0.789	N/A	N/A
	Left Tilt 15 Degree	0.248	0.257	0.505	N/A	N/A
	Right Cheek	0.308	0.429	0.736	N/A	N/A
	Right Tilt 15 Degree	0.239	0.248	0.487	N/A	N/A
Body-Worn	Front Side	0.321	0.141	0.462	N/A	N/A
	Back Side	0.281	0.421	0.702	N/A	N/A
Hotspot	Front Side	0.321	0.141	0.462	N/A	N/A
	Back Side	0.281	0.421	0.702	N/A	N/A
	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.243	N/A	0.243	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.248	N/A	0.248	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band V and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band IV	WLAN 2.4G			
Head	Left Cheek	0.398	0.441	0.839	N/A	N/A
	Left Tilt 15 Degree	0.198	0.257	0.455	N/A	N/A
	Right Cheek	0.390	0.429	0.818	N/A	N/A
	Right Tilt 15 Degree	0.186	0.248	0.434	N/A	N/A
Body-Worn	Front Side	0.273	0.141	0.415	N/A	N/A
	Back Side	0.567	0.421	0.987	N/A	N/A
Hotspot	Front Side	0.273	0.141	0.415	N/A	N/A
	Back Side	0.567	0.421	0.987	N/A	N/A

	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.297	N/A	0.297	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.550	N/A	0.550	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band IV and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band II	WLAN 2.4G			
Head	Left Cheek	0.360	0.441	0.801	N/A	N/A
	Left Tilt 15 Degree	0.234	0.257	0.491	N/A	N/A
	Right Cheek	0.354	0.429	0.783	N/A	N/A
	Right Tilt 15 Degree	0.224	0.248	0.472	N/A	N/A
Body-Worn	Front Side	0.270	0.141	0.411	N/A	N/A
	Back Side	0.624	0.421	1.045	N/A	N/A
Hotspot	Front Side	0.270	0.141	0.411	N/A	N/A
	Back Side	0.624	0.421	1.045	N/A	N/A
	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.301	N/A	0.301	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.562	N/A	0.562	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band II and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band VII	WLAN 2.4G			
Head	Left Cheek	0.120	0.441	0.560	N/A	N/A
	Left Tilt 15 Degree	0.056	0.257	0.313	N/A	N/A
	Right Cheek	0.113	0.429	0.541	N/A	N/A
	Right Tilt 15 Degree	0.046	0.248	0.294	N/A	N/A
Body-Worn	Front Side	0.292	0.141	0.434	N/A	N/A
	Back Side	0.552	0.421	0.973	N/A	N/A
Hotspot	Front Side	0.292	0.141	0.434	N/A	N/A
	Back Side	0.552	0.421	0.973	N/A	N/A
	Left Side	N/A	0.154	0.154	N/A	N/A
	Right Side	0.250	N/A	0.250	N/A	N/A
	Top Side	N/A	0.123	0.123	N/A	N/A
	Bottom Side	0.671	N/A	0.671	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band VII and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	Bluetooth			
Head	Left Cheek	0.660	0.105	0.765	N/A	N/A
	Left Tilt 15 Degree	0.339	0.105	0.444	N/A	N/A
	Right Cheek	0.572	0.105	0.677	N/A	N/A
	Right Tilt 15 Degree	0.290	0.105	0.396	N/A	N/A
Body-Worn	Front Side	0.653	0.053	0.706	N/A	N/A
	Back Side	0.587	0.053	0.639	N/A	N/A
Hotspot	Front Side	0.653	0.053	0.706	N/A	N/A
	Back Side	0.587	0.053	0.639	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.321	N/A	0.321	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.202	N/A	0.202	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	Bluetooth			
Head	Left Cheek	0.305	0.105	0.410	N/A	N/A
	Left Tilt 15 Degree	0.125	0.105	0.230	N/A	N/A
	Right Cheek	0.291	0.105	0.397	N/A	N/A
	Right Tilt 15 Degree	0.117	0.105	0.223	N/A	N/A
Body-Worn	Front Side	0.543	0.053	0.596	N/A	N/A
	Back Side	0.638	0.053	0.691	N/A	N/A
Hotspot	Front Side	0.543	0.053	0.596	N/A	N/A
	Back Side	0.638	0.053	0.691	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.264	N/A	0.264	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.552	N/A	0.552	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band V	Bluetooth			
Head	Left Cheek	0.400	0.105	0.506	N/A	N/A
	Left Tilt 15 Degree	0.212	0.105	0.317	N/A	N/A
	Right Cheek	0.355	0.105	0.460	N/A	N/A
	Right Tilt 15 Degree	0.207	0.105	0.312	N/A	N/A

Body-Worn	Front Side	0.394	0.053	0.446	N/A	N/A
	Back Side	0.370	0.053	0.423	N/A	N/A
Hotspot	Front Side	0.394	0.053	0.446	N/A	N/A
	Back Side	0.370	0.053	0.423	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.236	N/A	0.236	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.258	N/A	0.258	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band V and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band IV	Bluetooth			
Head	Left Cheek	0.340	0.105	0.445	N/A	N/A
	Left Tilt 15 Degree	0.124	0.105	0.229	N/A	N/A
	Right Cheek	0.334	0.105	0.439	N/A	N/A
	Right Tilt 15 Degree	0.118	0.105	0.223	N/A	N/A
Body-Worn	Front Side	0.439	0.053	0.492	N/A	N/A
	Back Side	0.466	0.053	0.519	N/A	N/A
Hotspot	Front Side	0.439	0.053	0.492	N/A	N/A
	Back Side	0.466	0.053	0.519	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.358	N/A	0.358	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.407	N/A	0.407	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band IV and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band II	Bluetooth			
Head	Left Cheek	0.371	0.105	0.476	N/A	N/A
	Left Tilt 15 Degree	0.145	0.105	0.251	N/A	N/A
	Right Cheek	0.363	0.105	0.468	N/A	N/A
	Right Tilt 15 Degree	0.136	0.105	0.242	N/A	N/A
Body-Worn	Front Side	0.421	0.053	0.474	N/A	N/A
	Back Side	0.512	0.053	0.565	N/A	N/A
Hotspot	Front Side	0.421	0.053	0.474	N/A	N/A
	Back Side	0.512	0.053	0.565	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.406	N/A	0.406	N/A	N/A

	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.531	N/A	0.531	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band II and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band V	Bluetooth			
Head	Left Cheek	0.348	0.105	0.454	N/A	N/A
	Left Tilt 15 Degree	0.248	0.105	0.353	N/A	N/A
	Right Cheek	0.308	0.105	0.413	N/A	N/A
	Right Tilt 15 Degree	0.239	0.105	0.345	N/A	N/A
Body-Worn	Front Side	0.321	0.053	0.373	N/A	N/A
	Back Side	0.281	0.053	0.334	N/A	N/A
Hotspot	Front Side	0.321	0.053	0.373	N/A	N/A
	Back Side	0.281	0.053	0.334	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.243	N/A	0.243	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.248	N/A	0.248	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band V and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band IV	Bluetooth			
Head	Left Cheek	0.398	0.105	0.504	N/A	N/A
	Left Tilt 15 Degree	0.198	0.105	0.304	N/A	N/A
	Right Cheek	0.390	0.105	0.495	N/A	N/A
	Right Tilt 15 Degree	0.186	0.105	0.291	N/A	N/A
Body-Worn	Front Side	0.273	0.053	0.326	N/A	N/A
	Back Side	0.567	0.053	0.619	N/A	N/A
Hotspot	Front Side	0.273	0.053	0.326	N/A	N/A
	Back Side	0.567	0.053	0.619	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.297	N/A	0.297	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.550	N/A	0.550	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band IV and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band II	Bluetooth			
Head	Left Cheek	0.360	0.105	0.465	N/A	N/A

	Left Tilt 15 Degree	0.234	0.105	0.340	N/A	N/A
	Right Cheek	0.354	0.105	0.460	N/A	N/A
	Right Tilt 15 Degree	0.224	0.105	0.329	N/A	N/A
Body-Worn	Front Side	0.270	0.053	0.322	N/A	N/A
	Back Side	0.624	0.053	0.677	N/A	N/A
Hotspot	Front Side	0.270	0.053	0.322	N/A	N/A
	Back Side	0.624	0.053	0.677	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.301	N/A	0.301	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.562	N/A	0.562	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band II and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band VII	Bluetooth			
Head	Left Cheek	0.120	0.105	0.225	N/A	N/A
	Left Tilt 15 Degree	0.056	0.105	0.162	N/A	N/A
	Right Cheek	0.113	0.105	0.218	N/A	N/A
	Right Tilt 15 Degree	0.046	0.105	0.152	N/A	N/A
Body-Worn	Front Side	0.292	0.053	0.345	N/A	N/A
	Back Side	0.552	0.053	0.605	N/A	N/A
Hotspot	Front Side	0.292	0.053	0.345	N/A	N/A
	Back Side	0.552	0.053	0.605	N/A	N/A
	Left Side	N/A	0.053	0.053	N/A	N/A
	Right Side	0.250	N/A	0.250	N/A	N/A
	Top Side	N/A	0.053	0.053	N/A	N/A
	Bottom Side	0.671	N/A	0.671	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band VII and Bluetooth.

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - SID835 - Head
MEASUREMENT 2 System Performance Check - SID835 - Body
MEASUREMENT 3 System Performance Check - SID1800 - Head
MEASUREMENT 4 System Performance Check - SID1800 - Body
MEASUREMENT 5 System Performance Check - SID1900 - Head
MEASUREMENT 6 System Performance Check - SID1900 - Body
MEASUREMENT 7 System Performance Check - SID2450 - Head
MEASUREMENT 8 System Performance Check - SID2450 - Body
MEASUREMENT 9 System Performance Check - SID2600 - Head
MEASUREMENT 10 System Performance Check - SID2600 - Body

MEASUREMENT 1


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	41.600000
Relative permittivity (imaginary part)	19.490000
Conductivity (S/m)	0.902944
Variation (%)	1.680000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=3.00

SAR Peak: 1.40 W/kg

SAR 10g (W/Kg)	0.620169
SAR 1g (W/Kg)	0.948026



MEASUREMENT 2


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	54.880000
Relative permittivity (imaginary part)	21.520000
Conductivity (S/m)	1.000944
Variation (%)	1.670000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=3.00

SAR Peak: 1.47 W/kg

SAR 10g (W/Kg)	0.638611
SAR 1g (W/Kg)	0.952095



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.631691
Relative permittivity (imaginary part)	13.993442
Conductivity (S/m)	1.401344
Variation (%)	-0.040000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.85 W/kg

SAR 10g (W/Kg)	2.073074
SAR 1g (W/Kg)	4.138838



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.752691
Relative permittivity (imaginary part)	15.303442
Conductivity (S/m)	1.531344
Variation (%)	-0.080000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.84 W/kg

SAR 10g (W/Kg)	2.068176
SAR 1g (W/Kg)	3.628803



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	39.971098
Relative permittivity (imaginary part)	13.392900
Conductivity (S/m)	1.410656
Variation (%)	-0.400000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=3.00

SAR Peak: 6.13 W/kg

SAR 10g (W/Kg)	1.941975
SAR 1g (W/Kg)	3.745533



MEASUREMENT 6


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1900</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	53.143098
Relative permittivity (imaginary part)	14.642900
Conductivity (S/m)	1.552656
Variation (%)	-0.660000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=3.00

SAR Peak: 6.13 W/kg

SAR 10g (W/Kg)	1.988026
SAR 1g (W/Kg)	3.753470



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	39.961099
Relative permittivity (imaginary part)	13.180900
Conductivity (S/m)	1.792598
Variation (%)	-0.100000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=1.00

SAR Peak: 12.07 W/kg

SAR 10g (W/Kg)	2.214004
SAR 1g (W/Kg)	5.419445



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	52.642801
Relative permittivity (imaginary part)	14.563800
Conductivity (S/m)	1.983834
Variation (%)	-0.190000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.01 W/kg

SAR 10g (W/Kg)	2.278012
SAR 1g (W/Kg)	4.751633



MEASUREMENT 9


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2600</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	39.001646
Relative permittivity (imaginary part)	13.572936
Conductivity (S/m)	1.962317
Variation (%)	-0.300000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=2.00

SAR Peak: 9.12 W/kg

SAR 10g (W/Kg)	2.414475
SAR 1g (W/Kg)	5.230801



MEASUREMENT 10


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	53.011646
Relative permittivity (imaginary part)	15.052940
Conductivity (S/m)	2.172325
Variation (%)	-0.330000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=2.00

SAR Peak: 9.06 W/kg

SAR 10g (W/Kg)	2.387681
SAR 1g (W/Kg)	5.080973



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band II Head
MEASUREMENT 6 WCDMA Band II Body
MEASUREMENT 7 WCDMA Band IV Head
MEASUREMENT 8 WCDMA Band IV Body
MEASUREMENT 9 WCDMA Band V Head
MEASUREMENT 10 WCDMA Band V Body
MEASUREMENT 11 WLAN 2.4G Head
MEASUREMENT 12 WLAN 2.4G Body
MEASUREMENT 13 LTE Band II Head
MEASUREMENT 14 LTE Band II Body
MEASUREMENT 15 LTE Band IV Head
MEASUREMENT 16 LTE Band IV Body
MEASUREMENT 17 LTE Band V Head
MEASUREMENT 18 LTE Band V Body
MEASUREMENT 19 LTE Band VII Head
MEASUREMENT 20 LTE Band VII Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.510960
Relative permittivity (imaginary part)	19.511539
Conductivity (S/m)	0.906636
Variation (%)	0.800000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-36.00

SAR Peak: 0.84 W/kg

SAR 10g (W/Kg)	0.480844
SAR 1g (W/Kg)	0.652232



MEASUREMENT 2


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>GSM850</u>
Channels	<u>Middle</u>
Signal	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.889580
Relative permittivity (imaginary part)	21.502741
Conductivity (S/m)	0.999161
Variation (%)	-1.660000

SURFACE SAR





VOLUME SAR



Maximum location: X=6.00, Y=2.00

SAR Peak: 0.87 W/kg

SAR 10g (W/Kg)	0.467846
SAR 1g (W/Kg)	0.645634



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.040401
Relative permittivity (imaginary part)	13.437800
Conductivity (S/m)	1.403504
Variation (%)	1.930000

SURFACE SAR





VOLUME SAR



Maximum location: X=-54.00, Y=-51.00

SAR Peak: 0.43 W/kg

SAR 10g (W/Kg)	0.171074
SAR 1g (W/Kg)	0.283645



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	53.218899
Relative permittivity (imaginary part)	14.727700
Conductivity (S/m)	1.538226
Variation (%)	-2.760000

SURFACE SAR





VOLUME SAR



Maximum location: X=-20.00, Y=-44.00

SAR Peak: 0.99 W/kg

SAR 10g (W/Kg)	0.334946
SAR 1g (W/Kg)	0.594088



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.040401
Relative permittivity (imaginary part)	13.437800
Conductivity (S/m)	1.403504
Variation (%)	-4.430000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-52.00

SAR Peak: 0.56 W/kg

SAR 10g (W/Kg)	0.220717
SAR 1g (W/Kg)	0.369605




MEASUREMENT 6

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	WCDMA (Crest factor: 1.0)

B. SAR Measurement Results



Frequency (MHz)	1880.000000
Relative permittivity (real part)	53.218899
Relative permittivity (imaginary part)	14.727700
Conductivity (S/m)	1.538226
Variation (%)	-1.250000



Maximum location: X=2.00, Y=5.00

SAR Peak: 0.88 W/kg

SAR 10g (W/Kg)	0.278079
SAR 1g (W/Kg)	0.530385



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	WCDMA (Crest factor: 1.0)


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	40.087391
Relative permittivity (imaginary part)	13.945742
Conductivity (S/m)	1.341890
Variation (%)	1.400000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-51.00

SAR Peak: 0.48 W/kg

SAR 10g (W/Kg)	0.212856
SAR 1g (W/Kg)	0.337941



MEASUREMENT 8


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>Band4 WCDMA1700</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	54.146168
Relative permittivity (imaginary part)	15.341370
Conductivity (S/m)	1.476181
Variation (%)	-1.090000

SURFACE SAR




VOLUME SAR




Maximum location: X=-9.00, Y=-36.00

SAR Peak: 0.71 W/kg


SAR 10g (W/Kg)	0.290015
SAR 1g (W/Kg)	0.463699



3D screen shot



Hot spot position



MEASUREMENT 9


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>Band5 WCDMA850</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.510960
Relative permittivity (imaginary part)	19.511539
Conductivity (S/m)	0.906636
Variation (%)	2.050000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-36.00

SAR Peak: 0.45 W/kg

SAR 10g (W/Kg)	0.280700
SAR 1g (W/Kg)	0.370355



MEASUREMENT 10


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>Band5 WCDMA850</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.889580
Relative permittivity (imaginary part)	21.502741
Conductivity (S/m)	0.999161
Variation (%)	-2.520000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=3.00

SAR Peak: 0.45 W/kg

SAR 10g (W/Kg)	0.274544
SAR 1g (W/Kg)	0.364357



MEASUREMENT 11


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11b ISM</u>
Channels	<u>Middle</u>
Signal	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	40.011002
Relative permittivity (imaginary part)	13.100300
Conductivity (S/m)	1.773635
Variation (%)	0.410000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=-15.00

SAR Peak: 0.69 W/kg

SAR 10g (W/Kg)	0.216948
SAR 1g (W/Kg)	0.392755



MEASUREMENT 12


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	52.701599
Relative permittivity (imaginary part)	14.515620
Conductivity (S/m)	1.965254
Variation (%)	-2.440000

SURFACE SAR





VOLUME SAR



Maximum location: X=8.00, Y=37.00

SAR Peak: 0.67 W/kg

SAR 10g (W/Kg)	0.182963
SAR 1g (W/Kg)	0.374593



MEASUREMENT 13


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>LTE band 2</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.046951
Relative permittivity (imaginary part)	13.422750
Conductivity (S/m)	1.401559
Variation (%)	-1.560000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-52.00

SAR Peak: 0.47 W/kg

SAR 10g (W/Kg)	0.192205
SAR 1g (W/Kg)	0.315032



MEASUREMENT 14


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	53.225948
Relative permittivity (imaginary part)	14.736150
Conductivity (S/m)	1.538700
Variation (%)	-4.370000

SURFACE SAR





VOLUME SAR



Maximum location: X=-15.00, Y=-45.00

SAR Peak: 0.89 W/kg

SAR 10g (W/Kg)	0.307540
SAR 1g (W/Kg)	0.546131



MEASUREMENT 15


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	40.095291
Relative permittivity (imaginary part)	13.930592
Conductivity (S/m)	1.340819
Variation (%)	-4.030000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-52.00

SAR Peak: 0.51 W/kg

SAR 10g (W/Kg)	0.231375
SAR 1g (W/Kg)	0.359952



MEASUREMENT 16


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>LTE band 4</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	54.133366
Relative permittivity (imaginary part)	15.323220
Conductivity (S/m)	1.474860
Variation (%)	-0.380000

SURFACE SAR





VOLUME SAR



Maximum location: X=-9.00, Y=-31.00

SAR Peak: 0.78 W/kg

SAR 10g (W/Kg)	0.328618
SAR 1g (W/Kg)	0.512459



MEASUREMENT 17


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>LTE band 5</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	41.513550
Relative permittivity (imaginary part)	19.510201
Conductivity (S/m)	0.906682
Variation (%)	-1.690000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-38.00

SAR Peak: 0.38 W/kg

SAR 10g (W/Kg)	0.233281
SAR 1g (W/Kg)	0.310211



MEASUREMENT 18


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	54.893501
Relative permittivity (imaginary part)	21.497000
Conductivity (S/m)	0.999013
Variation (%)	-2.340000

SURFACE SAR






VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.215106
SAR 1g (W/Kg)	0.286076



MEASUREMENT 19


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>LTE band 7</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.335487
Relative permittivity (imaginary part)	13.441160
Conductivity (S/m)	1.892963
Variation (%)	-2.390000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-10.00

SAR Peak: 0.16 W/kg

SAR 10g (W/Kg)	0.072697
SAR 1g (W/Kg)	0.107870



MEASUREMENT 20


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	53.346947
Relative permittivity (imaginary part)	14.917840
Conductivity (S/m)	2.100929
Variation (%)	2.160000

SURFACE SAR





VOLUME SAR



Maximum location: X=6.00, Y=21.00

SAR Peak: 1.01 W/kg

SAR 10g (W/Kg)	0.312471
SAR 1g (W/Kg)	0.606322



14. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 08/16 EPGO287
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356



COMOSAR E-Field Probe Calibration Report

Ref : ACR.260.1.18.SATU.A

**SHENZHEN NTEK TESTING TECHNOLOGY
CO., LTD.**

**BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 08/16 EPG0287**

**Calibrated at MVG US
2105 Barrett Park Dr. - Kennesaw, GA 30144**



Calibration Date: 09/17/2018

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in MVG USA using the CALISAR / CALIBAIR test bench, for use with a COMOSAR system only. All calibration results are traceable to national metrology institutions.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme LUC	Product Manager	9/17/2018	
<i>Checked by :</i>	Jérôme LUC	Product Manager	9/17/2018	
<i>Approved by :</i>	Kim RUTKOWSKI	Quality Manager	9/17/2018	

	<i>Customer Name</i>
<i>Distribution :</i>	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

<i>Issue</i>	<i>Date</i>	<i>Modifications</i>
A	9/17/2018	Initial release



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.5	Boundary Effect	5
4	Measurement Uncertainty	5
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	7
5.4	Isotropy	8
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 08/16 EPGO287
Product Condition (new / used)	Used
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.209 MΩ Dipole 2: R2=0.196 MΩ Dipole 3: R3=0.197 MΩ

A yearly calibration interval is recommended.

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 - 360 degrees in 15 degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.5 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Incident or forward power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Reflected power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Liquid conductivity	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Liquid permittivity	4.00%	Rectangular	$\sqrt{3}$	1	2.309%
Field homogeneity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Field probe positioning	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Field probe linearity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Combined standard uncertainty					5.831%
Expanded uncertainty 95 % confidence level k = 2					12.0%

Page: 5/10

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %


5.1 SENSITIVITY IN AIR

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
0.66	0.75	0.58

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
93	93	98

Calibration curves $e_i=f(V)$ ($i=1,2,3$) allow to obtain H-field value using the formula:


$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$





COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

5.2 LINEARITYLinearity: $\pm 1.89\%$ ($\pm 0.08\text{dB}$)5.3 SENSITIVITY IN LIQUID

Liquid	Frequency (MHz $\pm$ 100MHz)	Permittivity	Epsilon (S/m)	ConvF
HL750	750	40.03	0.93	1.45
BL750	750	56.83	1.00	1.49
HL850	835	42.19	0.90	1.50
BL850	835	54.67	1.01	1.56
HL900	900	42.08	1.01	1.51
HL1800	1800	41.68	1.46	1.71
BL1800	1800	53.86	1.46	1.77
HL1900	1900	38.45	1.45	2.03
BL1900	1900	53.32	1.56	2.07
HL2000	2000	38.26	1.38	1.76
HL2450	2450	37.50	1.80	2.00
BL2450	2450	53.22	1.89	2.08
HL2600	2600	39.80	1.99	2.12
BL2600	2600	52.52	2.23	2.19
HL5200	5200	35.64	4.67	2.55
BL5200	5200	48.64	5.51	2.62
HL5400	5400	36.44	4.87	2.53
BL5400	5400	46.52	5.77	2.59
HL5600	5600	36.66	5.17	2.64
BL5600	5600	46.79	5.77	2.73
HL5800	5800	35.31	5.31	2.72
BL5800	5800	47.04	6.10	2.81

LOWER DETECTION LIMIT: 7mW/kg

Page: 7/10

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to
be released in whole or part without written approval of MVG.*




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

5.4 ISOTROPY


HL900 MHz

- Axial isotropy: 0.04 dB
- Hemispherical isotropy: 0.07 dB



HL1800 MHz

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.08 dB






COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

HL5600 MHz

- Axial isotropy: 0.06 dB
- Hemispherical isotropy: 0.08 dB





COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.260.1.18.SATU.A

6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2016	02/2019
Reference Probe	MVG	EP 94 SN 37/08	10/2017	10/2018
Multimeter	Keithley 2000	1188656	01/2017	01/2020
Signal Generator	Agilent E4438C	MY49070581	01/2017	01/2020
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	01/2017	01/2020
Power Sensor	HP ECP-E26A	US37181460	01/2017	01/2020
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Control Company	150798832	11/2017	11/2020