

Specification for Approval

Customer:	Xiamen Lujiang Technology Co., Ltd
Part name:	S1 PCB ANT
Part No. :	
Customer Part No. :	
Manufacturer:	Xiamen Jihe Communication Co., Ltd
Address:	Unit 301-1, No. 55 Chengyi North Street, Phase III of Xiamen Software Park

Customer Approved By		
APPROVAL	CHIEF	DESIGN

Supplier Confirmed		
	CHIEF	DESIGN
	Jack	Lee
	2024. 5. 21	2024. 5. 21


List

NO	Content	Page
1	Cover	1
2	Catalog	2
3	Product chart/Antenna	3
4	Characteristics	4
5	OTA darkroom	5
6	efficiency and gain report	6
7	Directional and 3D diagram	7


Update of the Records

Rev	Formulate	Date	Content
01	Lee	2024. 5. 21	New Confirmation Letter

Product diagram




Antenna form



Antenna characteristics

product type	antenna
DESCRIPTION	VALUE
Frequency Range	2300~2540 MHz
V.S.W.R	Comparison of sample waveform (aerial measurement)
Impedance	50 Ω
Gain	-6~-1 dBi
Radiation	Omni-directional
Radiating element	1/4 Wave Helical
Polarization	Linear Vertical
Admitted power	2W
Connector	conduction
Operating temp	-40℃~+85℃




OTA darkroom diagram




Efficiency and gain report)

FREQUENCY (MHZ)	EFFICIENCY (%)	GAIN (dBi)
2300	22.8%	-1.4
2310	20.6%	-1.6
2320	20.3%	-1.8
2330	22.1%	-1.3
2340	23.9%	-1.3
2350	24.5%	-1.1
2360	20.4%	-2.3
2370	17.3%	-2.9
2380	18.5%	-3.1
2390	17.7%	-3.3
2400	17.1%	-3.5
2410	20.7%	-2.6
2420	17.8%	-3.4
2430	16.0%	-3.8
2440	15.2%	-3.8
2450	12.8%	-4.5
2460	13.5%	-4.4
2470	13.9%	-4.2
2480	13.2%	-4.3
2490	12.2%	-4.7
2500	10.9%	-5.2
2510	10.2%	-5.5
2520	10.0%	-5.7
2530	9.3%	-5.9
2540	9.7%	-5.9


Directional and 3D diagram




2300P0 Total




2300P90 Total




2300T90 Total




2450P0 Total




2450P90 Total




2450T90 Total



2500P0 Total



2500P90 Total



2500T90 Total

