



# TEST REPORT

No. I19Z70333-EMC02

for

**Samsung Electronics. Co., Ltd.**

**Mobile phone**

**Model Name: SM-A015A, SM-A015AZ**

**FCC ID: ZCASMA015A**

with

**Hardware Version: REV3.0**

**Software Version: A015A.001(A015AUCU0ATAC),**

**A015AZ.001(A015AZUCE0ATA1)**

**Issued Date: 2020-02-11**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: [cttl\\_terminals@caict.ac.cn](mailto:cttl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)

## **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I19Z70333-EMC02	Rev.0	1 <sup>st</sup> edition	2020-02-11

Note: the latest revision of the test report supersedes all previous version.

## **CONTENTS**

1. TEST LABORATORY.....	4
1.1. INTRODUCTION & ACCREDITATION .....	4
2. TEST LABORATORY.....	4
2.1. TESTING LOCATION .....	4
2.2. TESTING ENVIRONMENT .....	4
2.3. PROJECT DATA.....	4
2.4. SIGNATURE .....	4
3. CLIENT INFORMATION.....	5
3.1. APPLICANT INFORMATION.....	5
3.2. MANUFACTURER INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....	6
4.1. ABOUT EUT .....	6
4.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	6
4.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	6
4.4. EUT SET-UPS .....	7
5. REFERENCE DOCUMENTS .....	8
5.1. REFERENCE DOCUMENTS FOR TESTING.....	8
6. LABORATORY ENVIRONMENT .....	9
7. SUMMARY OF TEST RESULTS.....	10
8. TEST EQUIPMENTS UTILIZED.....	11
ANNEX A: MEASUREMENT RESULTS .....	12
ANNEX B: PERSONS INVOLVED IN THIS TESTING.....	25

## **1. Test Laboratory**

### **1.1. Introduction & Accreditation**

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

## **2. Test Laboratory**

### **2.1. Testing Location**

CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China 100191


### **2.2. Testing Environment**

Normal Temperature: 15-35° C  
Relative Humidity: 20-75%

### **2.3. Project data**

Testing Start Date: 2019-11-11  
Testing End Date: 2019-12-16

### **2.4. Signature**




---

Wang Junqing  
(Prepared this test report)



---

Zhang Ying  
(Reviewed this test report)



---

Liu Baodian  
Deputy Director of the laboratory  
(Approved this test report)

### **3. Client Information**

#### **3.1. Applicant Information**

Company Name: Samsung Electronics. Co., Ltd.  
R5, A Tower 22 Floor A-1,(Maetan dong)  
Address: 129,Samsung-ro,Yeongtong-gu, Suwon-Si, Gyeonggi-do 16677,  
Korea  
City: /  
Postal Code: /  
Country: Korea  
Telephone: +82-10-4376-0326  
Fax: /

#### **3.2. Manufacturer Information**

Company Name: Samsung Electronics. Co., Ltd.  
R5, A Tower 22 Floor A-1,(Maetan dong)  
Address: 129,Samsung-ro,Yeongtong-gu, Suwon-Si, Gyeonggi-do 16677,  
Korea  
City: /  
Postal Code: /  
Country: Korea  
Telephone: +82-10-4376-0326  
Fax: /

## 4. Equipment Under Test (EUT) and Ancillary Equipment (AE)

### 4.1. About EUT

Description	Mobile phone
Model Name	SM-A015A,SM-A015AZ
FCC ID	ZCASMA015A
Power Supply	3.85V

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

### 4.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	/	/	/
EUT3	351766110007292	REV3.0	A015A.001(A015AUCU0ATAC), A015AZ.001(A015AZUCE0ATA1)

\*EUT ID: is used to identify the test sample in the lab internally.

### 4.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	/
AE2	Battery	/	/
AE3	Charger	/	/
AE4	Charger	/	/
AE5	Charger	/	/
AE6	USB Cable	/	/
AE7	Headset	/	/
AE10	OTG Cable	/	/

#### AE1

Model	QL1695
Manufacturer	Ningde Amperex Technology Limited
Capacitance	/
Nominal voltage	3.85 V

#### AE2

Model	QL1695
Manufacturer	SCUD(Fujian) Electronics Co., Ltd.
Capacitance	/
Nominal voltage	3.85 V

#### AE3

Model	EP-TA50JWE
Manufacturer	DongYang E&P Inc.
Length of cable	/

#### AE4

Model	EP-TA50JWE
-------	------------

Manufacturer	HAEM Co.,Ltd
Length of cable	/
AE5	
Model	EP-TA50JWE
Manufacturer	RF Tech
Length of cable	/
AE6	
Model	EP-DR140AWE
Manufacturer	LUXSHARE-ICT (VIETNAM) LIMITED
Length of cable	/
AE7	
Model	EHS61ASFWE
Manufacturer	DONGGUAN YOUNGBO ELECTRONICS CO.,LTD
Length of cable	/
AE10	
Model	/
Manufacturer	/
Length of cable	/

\*AE ID: is used to identify the test sample in the lab internally.

Note: The USB cables are shielded.

#### 4.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.8	EUT1+ AE1/AE2+ AE4+ AE6	Charger
Set.9	EUT3+ AE1/AE2+ AE4+ AE6	Charger

Note: Mobile phone SM-A015A, SM-A015AZ manufactured by Samsung Electronics. Co., Ltd. is a variant model based on SM-A015T1 for conformance test. According to the declaration of changes, adding the tests as follow:

Test Item	Mode
Radiated Emission	Set.9 LTE band 14

The other results are cited from the initial model. The report number for initial model is I19Z70327-EMC02.

## **5. Reference Documents**

### **5.1. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2016
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.



## 6. LABORATORY ENVIRONMENT

**Semi-anechoic chamber SAC-1** (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 10 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 6GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

**Shielded room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz—1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

## 7. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	B.1	P	CTTL(huayuan North Road)

## 8. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATI ON INTERVAL
1	Test Receiver	ESU26	100235	R&S	2020-03-01	1 Year
2	Universal Radio Communication Tester	CMW500	150344	R&S	2020-11-17	1 year
3	Universal Radio Communication Tester	CMW500	116588	R&S	2020-12-26	1 year
4	EMI Antenna	VULB 9163	9163-1222	Schwarzbeck	2020-03-14	1 year

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 Radiated Emission**

#### **Reference**

FCC: CFR Part 15.109(a).

#### **A.1.1 Method of measurement**

The field strength of radiated emissions from the unintentional radiator at distances of 10 meters(for 30MHz-1GHz). Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

#### **A.1.2 EUT Operating Mode**

The MS is operating in the charging mode and transmitter receiver mode.

#### **A.1.3 Measurement Limit**

Frequency range (MHz)	Field strength limit ( $\mu\text{V/m}$ )		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

#### **A.1.4 Test Condition**

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak

### A.1.5 Measurement Results

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

$G_A$ : Antenna factor of receive antenna


$G_{\text{PL}}$ : Path Loss

$P_{\text{Mea}}$ : Measurement result on receiver.

Measurement uncertainty (worst case):  $U = 5.44 \text{ dB}$ ,  $k=2$ .

### Charging Mode, GSM850MHz, idle, channel 128

Full Spectrum



**Fig A.1 Radiated Emission from 30MHz to 1GHz, GSM850MHz, idle, channel 128**

## Charging Mode, GSM850MHz, idle, channel 190

Full Spectrum





Fig A.2 Radiated Emission from 30MHz to 1GHz, GSM850MHz, idle, channel 190

## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
46.846000	16.37	30.00	13.63	1000.0	120.000	125.0	V	263.0
65.077000	17.71	30.00	12.29	1000.0	120.000	104.0	V	183.0
95.905000	12.80	33.50	20.72	1000.0	120.000	179.0	V	261.0
112.662000	12.62	33.50	20.90	1000.0	120.000	125.0	V	255.0
263.271000	10.28	36.00	25.74	1000.0	120.000	125.0	V	90.0
824.675000	20.69	36.00	15.33	1000.0	120.000	125.0	V	-30.0

**Charging Mode, GSM850MHz, idle, channel 251**


Full Spectrum



**Fig A.3 Radiated Emission from 30MHz to 1GHz, GSM850MHz, idle, channel 251**

**Charging Mode, WCDMA850MHz, idle, channel 4132**

Full Spectrum



**Fig A.4 Radiated Emission from 30MHz to 1GHz, WCDMA850MHz, idle, channel 4132**



## Charging Mode, WCDMA850MHz, idle, channel 4183

Full Spectrum





Fig A.5 Radiated Emission from 30MHz to 1GHz, WCDMA850MHz, idle, channel 4183

## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
47.261000	17.47	30.00	12.53	1000.0	120.000	111.0	V	-5.0
64.333000	18.04	30.00	11.96	1000.0	120.000	225.0	V	-12.0
95.152000	12.68	33.50	20.84	1000.0	120.000	102.0	V	287.0
112.893000	12.38	33.50	21.14	1000.0	120.000	125.0	V	265.0
178.267000	8.87	33.50	24.65	1000.0	120.000	119.0	V	8.0
962.794000	22.43	44.00	21.55	1000.0	120.000	325.0	V	168.0

**Charging Mode, WCDMA850MHz, idle, channel 4233**


Full Spectrum



**Fig A.6 Radiated Emission from 30MHz to 1GHz, WCDMA850MHz, idle, channel 4233**

**Charging Mode, LTE band 5, idle, channel 20407**

Full Spectrum



**Fig A.7 Radiated Emission from 30MHz to 1GHz, LTE band 5, idle, channel 20407**

## Charging Mode, LTE band 5, idle, channel 20525

Full Spectrum





Fig A.8 Radiated Emission from 30MHz to 1GHz, LTE band 5, idle, channel 20525

## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
47.428000	18.13	30.00	11.87	1000.0	120.000	102.0	V	151.0
62.814000	18.72	30.00	11.28	1000.0	120.000	102.0	V	151.0
95.734000	12.35	33.50	21.17	1000.0	120.000	125.0	V	-30.0
255.534000	9.81	36.00	26.21	1000.0	120.000	288.0	V	30.0
390.240000	13.35	36.00	22.67	1000.0	120.000	282.0	V	107.0
745.029000	19.44	36.00	16.58	1000.0	120.000	125.0	V	30.0

**Charging Mode, LTE band 5, idle, channel 20643**


Full Spectrum



**Fig A.9 Radiated Emission from 30MHz to 1GHz, LTE band 5, idle, channel 20643**

**Charging Mode, LTE band 14, idle, channel 23305**


Full Spectrum



**Fig A.10 Radiated Emission from 30MHz to 1GHz, LTE band 14, idle, channel 23305**

**Charging Mode, LTE band 14, idle, channel 23330**

Full Spectrum




**Fig A.11 Radiated Emission from 30MHz to 1GHz, LTE band 14, idle, channel 23330**

**Final\_Result**

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
46.989000	12.22	30.00	17.78	1000.0	120.000	201.0	V	90.0
63.059000	15.31	30.00	14.69	1000.0	120.000	225.0	V	72.0
91.637000	7.20	33.50	26.32	1000.0	120.000	201.0	V	61.0
111.365000	9.01	33.50	24.51	1000.0	120.000	303.0	V	273.0
206.443000	8.68	33.50	24.84	1000.0	120.000	189.0	V	30.0
660.089000	18.39	36.00	17.63	1000.0	120.000	125.0	V	-30.0

**Charging Mode, LTE band 14, idle, channel 23355**

Full Spectrum



**Fig A.12 Radiated Emission from 30MHz to 1GHz, LTE band 14, idle, channel 23355**





## **ANNEX B: PERSONS INVOLVED IN THIS TESTING**

Test Item	Test Software and Version	Software Vendor	Test operator
Radiated Emission	EMC32 V9.01.00	R&S	Yan Hanchen

**\*\*\*END OF REPORT\*\*\***