



CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

Savage AWD OFFROAD RACER, Savage 1/10 Scale Buggy 4x4 Crawler

MODEL NUMBER: SC-2065,SC-2066,SC-2067,GV-4345

FCC ID: 2ASK3SC-2065T

REPORT NUMBER: 4788934645.1-1

ISSUE DATE: April 03, 2019

Prepared for

**AMAX INDUSTRIAL GROUP CHINA CO.,LTD
OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L TUNG CHOI STREET
MONGKOK KOWLOON HONG KONG.**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake
Hi-Tech Development Zone Dongguan, People's Republic of China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	04/03/2019	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	20dB Bandwidth and 99% Occupied Bandwidth	CFR 47 FCC 15.249(d)	Pass
2	Radiated emission	CFR 47 FCC §15.249 (a)(d)(e) CFR 47 FCC §15.205 and §15.209	Pass
3	Antenna Requirement	FCC Part 15.203	Pass



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. CHANNEL LIST	8
5.4. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.5. TEST CHANNEL CONFIGURATION.....	9
5.6. THE WORSE CASE POWER SETTING PARAMETER.....	9
5.7. TEST ENVIRONMENT	9
5.8. DESCRIPTION OF TEST SETUP.....	10
5.9. MEASURING INSTRUMENT AND SOFTWARE USED.....	11
6. ANTENNA PORT TEST RESULTS	12
6.1. ON TIME AND DUTY CYCLE.....	12
6.2. 20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH	14
7. RADIATED TEST RESULTS.....	18
7.1. LIMITS AND PROCEDURE	18
7.2. RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS 24	
7.3. SPURIOUS EMISSIONS (1~3GHz)	30
7.4. SPURIOUS EMISSIONS (3~18GHz)	36
7.5. SPURIOUS EMISSIONS (18~26GHz)	42
7.6. SPURIOUS EMISSIONS BELOW 30M.....	44
7.7. SPURIOUS EMISSIONS BELOW 1 GHz.....	50
8. ANTENNA REQUIREMENTS.....	52



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG

Manufacturer Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG

EUT Description

EUT Name: Savage AWD OFFROAD RACER, Savage 1/10 Scale Buggy
4x4 Crawler
Model: SC-2065,SC-2066,SC-2067,GV-4345
Brand Name: /
Sample Status: Normal
Sample Received Date: March 25, 2019
Date of Tested: March 25, 2019 ~ April 03, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Denny Huang
Engineer Project Associate
Approved By:

Stephen Guo
Laboratory Manager

Checked By:

Shawn Wen
Laboratory Leader



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2014.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>IC(Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test(include Fundamental emission) (9KHz-30MHz)	2.2dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz)(include Fundamental emission)	5.78dB (1GHz-18Gz)
	5.23dB (18GHz-26Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Savage AWD OFFROAD RACER, Savage 1/10 Scale Buggy 4x4 Crawler	
EUT Description	The EUT is a wireless remote controller .	
Model	SC-2065	
Series Model	SC-2066,SC-2067,GV-4345	
Model Difference	All the same except for the model name, product name and color.	
Product Description	Operation Frequency	2410 MHz ~ 2470 MHz
	Modulation Type	GFSK
Battery	DC 6V	

5.2. MAXIMUM OUTPUT POWER

Frequency Range (MHz)	Number of Transmit Chains (NTX)	Frequency (MHz)	Channel Number	Max Power (dBμV/m)
2410 ~ 2470	1	2440	31[61]	87.06

5.3. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2410	19	2428	37	2446	55	2464
2	2411	20	2429	38	2447	56	2465
3	2412	21	2430	39	2448	57	2466
4	2413	22	2431	40	2449	58	2467
5	2414	23	2432	41	2450	59	2468
6	2415	24	2433	42	2451	60	2469
7	2416	25	2434	43	2452	61	2470
8	2417	26	2435	44	2453		
9	2418	27	2436	45	2454		
10	2419	28	2437	46	2455		
11	2420	29	2438	47	2456		
12	2421	30	2439	48	2457		
13	2422	31	2440	49	2458		
14	2423	32	2441	50	2459		
15	2424	33	2442	51	2460		
16	2425	34	2443	52	2461		
17	2426	35	2444	53	2462		
18	2427	36	2445	54	2463		



5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2410 ~ 2470	Wire Antenna	1.1

Test Mode	Transmit and Receive Mode	Description
GFSK	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

5.5. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 1, CH 31, CH 61	2410MHz, 2440MHz, 2470MHz

5.6. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2402 ~ 2483.5MHz Band				
Test Software		/		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH 1	CH 31	CH 61
GFSK	1	Default	Default	Default

5.7. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	22 ~ 28°C
Voltage :	VL	N/A
	VN	DC 6V
	VH	N/A

Note: VL= Lower Extreme Test Voltage
VN= Nominal Voltage
VH= Upper Extreme Test Voltage
TN= Normal Temperature



5.8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	/	/	/	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	/	/	/	/	/


ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

TEST SETUP

The EUT have the engineering mode inside.

SETUP DIAGRAM FOR TEST



Note: New battery was used during all tests.

**5.9. MEASURING INSTRUMENT AND SOFTWARE USED**

Conducted Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	101961	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Two-Line V- Network	R&S	ENV216	101983	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Dec.10,2018	Dec.10,2019
Software						
Used	Description		Manufacturer	Name	Version	
<input checked="" type="checkbox"/>	Test Software for Conducted disturbance		Farad	EZ-EMC	Ver. UL-3A1	
Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17,2018	Sep.17,2021
<input checked="" type="checkbox"/>	Preamplifier	HP	8447D	2944A09099	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	EMI Measurement Receiver	R&S	ESR26	101377	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Horn Antenna	TDK	HRN-0118	130939	Sep.17,2018	Sep.17,2021
<input checked="" type="checkbox"/>	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.18,2018	Aug.18,2021
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-0118	TRS-305- 00066	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-2	TRS-307- 00003	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Software						
Used	Description		Manufacturer	Name	Version	
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance		Farad	EZ-EMC	Ver. UL-3A1	
Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8- 2350-2400- 2483.5- 2533.5-40SS	4	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	High Pass Filter	Wi	WHKX10- 2700-3000- 18000-40SS	23	Dec.10,2018	Dec.10,2019



6. ANTENNA PORT TEST RESULTS

6.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)
GFSK	0.190	39.45	0.005	0.48	23.0

Note:

Duty Cycle Correction Factor= $10\log(1/x)$.



Where: x is Duty Cycle(Linear)

Where: T is On Time (transmit duration)

If that calculated VBW is not available on the analyzer then the next higher value should be used.



ON TIME AND DUTY CYCLE PLOT





6.2. 20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.249) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.249(d)	20dB Bandwidth	for reporting purposes only	2400-2483.5


TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	1% to 5% of the occupied bandwidth
VBW	approximately 3×RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.


TEST SETUP






RESULTS

Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2410	1.163	1.1693	PASS






Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2440	1.126	1.1237	PASS





Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2470	1.168	1.1971	PASS





7. RADIATED TEST RESULTS

7.1. LIMITS AND PROCEDURE

LIMITS

CFR 47 FCC §15.205 and §15.209

CFR 47 FCC §15.249 (a)(d)(e)

The field strength of emissions from intentional radiators operated within these frequency bands			
Frequency (MHz)	Field strength of Fundamental	Field strength of Harmonics	Distance (m)
902 - 928	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
2400 – 2483.5	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
5725 – 5875	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3

Emissions radiated outside of the specified frequency bands above 30MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

Emissions radiated outside of the specified frequency bands below 30MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30



FCC Restricted bands of operation:


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK: 3M AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For average power measurement, set the detector to AVG, while maintaining all of the other instrument settings, if the duty cycle of the EUT is less than 98%, the Duty Cycle Correction Factor shall be added to the measured emission levels. For the Duty Cycle and Correction Factor please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:




Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.




7.2. RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS

RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2400.000	20.40	32.98	53.38	74.00	-20.62	peak
2	2409.935	53.26	33.05	86.31	114.00	-27.69	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2400.000	17.58	32.98	50.56	74.00	-23.44	peak
2	2409.935	46.90	33.05	79.95	114.00	-34.05	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2439.920	53.79	33.27	87.06	114.00	-26.94	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2440.400	46.79	33.27	80.06	114.00	-33.94	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2469.900	53.12	33.49	86.61	114.00	-27.39	peak
2	2483.500	18.73	33.58	52.31	74.00	-21.69	peak
3	2485.650	19.58	33.59	53.17	74.00	-20.83	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2470.460	46.85	33.49	80.34	114.00	-33.66	peak
2	2483.500	15.15	33.58	48.73	74.00	-25.27	peak
3	2488.100	16.73	33.62	50.35	74.00	-23.65	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




7.3. SPURIOUS EMISSIONS (1~3GHz)

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1205.343	45.56	-12.37	33.19	74.00	-40.81	peak
2	1364.663	45.05	-11.67	33.38	74.00	-40.62	peak
3	1600.324	44.01	-10.61	33.40	74.00	-40.60	peak
4	1882.877	43.75	-9.33	34.42	74.00	-39.58	peak
5	2547.007	44.20	-6.55	37.65	74.00	-36.35	peak
6	2886.835	44.28	-5.15	39.13	74.00	-34.87	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1346.790	44.09	-11.54	32.55	74.00	-41.45	peak
2	1548.440	44.79	-11.12	33.67	74.00	-40.33	peak
3	1870.506	44.44	-9.34	35.10	74.00	-38.90	peak
4	2174.326	44.06	-8.41	35.65	74.00	-38.35	peak
5	2314.838	43.57	-7.43	36.14	74.00	-37.86	peak
6	2626.574	44.84	-6.96	37.88	74.00	-36.12	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1219.998	45.14	-12.19	32.95	74.00	-41.05	peak
2	1574.168	44.63	-10.87	33.76	74.00	-40.24	peak
3	1716.895	45.49	-10.49	35.00	74.00	-39.00	peak
4	2062.637	44.47	-8.86	35.61	74.00	-38.39	peak
5	2472.566	44.14	-6.54	37.60	74.00	-36.40	peak
6	2765.759	44.72	-5.95	38.77	74.00	-35.23	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1225.371	44.84	-12.12	32.72	74.00	-41.28	peak
2	1452.852	44.86	-11.75	33.11	74.00	-40.89	peak
3	1924.705	43.34	-9.42	33.92	74.00	-40.08	peak
4	2103.832	43.23	-8.31	34.92	74.00	-39.08	peak
5	2589.328	45.39	-6.75	38.64	74.00	-35.36	peak
6	2938.028	43.33	-4.93	38.40	74.00	-35.60	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1137.164	45.83	-12.53	33.30	74.00	-40.70	peak
2	1433.824	45.37	-11.81	33.56	74.00	-40.44	peak
3	1772.475	44.23	-9.77	34.46	74.00	-39.54	peak
4	2067.175	44.80	-8.80	36.00	74.00	-38.00	peak
5	2368.864	44.44	-7.23	37.21	74.00	-36.79	peak
6	2744.571	45.45	-6.43	39.02	74.00	-34.98	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1407.294	45.57	-11.90	33.67	74.00	-40.33	peak
2	1666.715	43.94	-10.68	33.26	74.00	-40.74	peak
3	1807.875	44.00	-9.41	34.59	74.00	-39.41	peak
4	2186.303	44.66	-8.42	36.24	74.00	-37.76	peak
5	2467.139	44.41	-6.59	37.82	74.00	-36.18	peak
6	2690.830	45.66	-7.36	38.30	74.00	-35.70	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




7.4. SPURIOUS EMISSIONS (3~18GHz)

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4814.522	46.81	-0.23	46.58	74.00	-27.42	peak
2	6540.592	38.90	6.15	45.05	74.00	-28.95	peak
3	8450.700	38.87	8.64	47.51	74.00	-26.49	peak
4	11562.963	35.78	14.14	49.92	74.00	-24.08	peak
5	14413.908	35.30	16.41	51.71	74.00	-22.29	peak
6	17712.063	30.15	22.36	52.51	74.00	-21.49	peak

- Note:
1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. The high pass filter loss factor already add into the correct factor.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4820.000	55.39	-0.21	55.18	74.00	-18.82	peak
2	4820.000	48.70	-0.21	48.49	54.00	-5.51	AVG
3	7001.431	38.54	6.73	45.27	74.00	-28.73	peak
4	10163.476	37.09	10.85	47.94	74.00	-26.06	peak
5	13537.749	35.47	15.82	51.29	74.00	-22.71	peak
6	14439.758	35.28	16.39	51.67	74.00	-22.33	peak
7	17935.612	29.38	23.19	52.57	74.00	-21.43	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: Average value = AVG (Detector) Reading + Correct (included DCCF).
5. For transmit duration, please refer to clause 6.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.288	43.96	-0.12	43.84	74.00	-30.16	peak
2	7051.790	39.53	6.81	46.34	74.00	-27.66	peak
3	9359.385	38.04	10.04	48.08	74.00	-25.92	peak
4	13131.607	35.42	14.99	50.41	74.00	-23.59	peak
5	14439.758	35.17	16.39	51.56	74.00	-22.44	peak
6	17839.462	29.38	23.21	52.59	74.00	-21.41	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The high pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4880.288	55.17	-0.12	55.05	74.00	-18.95	peak
2	4880.288	47.47	-0.12	47.35	54.00	-6.65	AVG
3	7414.599	39.39	7.46	46.85	74.00	-27.15	peak
4	8270.940	39.61	8.84	48.45	74.00	-25.55	peak
5	12289.276	35.60	14.38	49.98	74.00	-24.02	peak
6	14439.758	35.23	16.39	51.62	74.00	-22.38	peak
7	18000.000	29.32	23.27	52.59	74.00	-21.41	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: Average value = AVG (Detector) Reading + Correct (included DCCF).
5. For transmit duration, please refer to clause 6.1.
6. The High Pass filter loss factor already add into the correct factor.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4990.180	47.23	0.42	47.65	74.00	-26.35	peak
2	8226.601	38.60	9.33	47.93	74.00	-26.07	peak
3	11377.996	36.60	13.25	49.85	74.00	-24.15	peak
4	13061.211	35.25	14.88	50.13	74.00	-23.87	peak
5	14388.105	34.98	16.42	51.40	74.00	-22.60	peak
6	17335.299	30.11	21.75	51.86	74.00	-22.14	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The high pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4771.582	52.85	-0.37	52.48	74.00	-21.52	peak
2	4919.161	53.57	0.02	53.59	74.00	-20.41	peak
3	7414.599	41.64	7.46	49.10	74.00	-24.90	peak
4	11562.963	35.88	14.14	50.02	74.00	-23.98	peak
5	14413.908	35.89	16.41	52.30	74.00	-21.70	peak
6	17680.356	29.96	22.07	52.03	74.00	-21.97	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The high pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




7.5. SPURIOUS EMISSIONS (18~26GHz)

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18544.000	51.26	-4.46	46.80	74.00	-27.20	peak
2	19912.000	49.91	-4.36	45.55	74.00	-28.45	peak
3	21024.000	50.62	-5.30	45.32	74.00	-28.68	peak
4	22744.000	52.18	-5.74	46.44	74.00	-27.56	peak
5	23536.000	50.96	-4.74	46.22	74.00	-27.78	peak
6	25784.000	48.73	-1.49	47.24	74.00	-26.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18784.000	51.05	-4.84	46.21	74.00	-27.79	peak
2	21248.000	51.98	-5.51	46.47	74.00	-27.53	peak
3	21848.000	52.26	-5.95	46.31	74.00	-27.69	peak
4	23512.000	51.01	-4.76	46.25	74.00	-27.75	peak
5	24664.000	48.89	-2.18	46.71	74.00	-27.29	peak
6	25936.000	49.79	-2.17	47.62	74.00	-26.38	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


Note: All test mode has been tested, only the worst data record in the report.



7.6. SPURIOUS EMISSIONS BELOW 30M


SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)

9kHz~ 150kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0091	71.79	-101.33	-29.54	48.29	-77.83	peak
2	0.0165	67.84	-101.37	-33.53	43.69	-77.22	peak
3	0.0193	67.65	-101.35	-33.70	42.00	-75.70	peak
4	0.0318	63.87	-101.40	-37.53	37.61	-75.14	peak
5	0.0492	59.05	-101.47	-42.42	33.78	-76.20	peak
6	0.0700	57.41	-101.57	-44.16	30.70	-74.86	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. All the modes had been tested, but only the worst data were recorded in the report.
3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

**150kHz ~ 490kHz**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1645	69.25	-101.66	-32.41	23.29	-55.70	peak
2	0.1895	65.65	-101.70	-36.05	22.05	-58.10	peak
3	0.2316	63.02	-101.77	-38.75	20.47	-59.22	peak
4	0.3019	61.93	-101.85	-39.92	18.01	-57.93	peak
5	0.3528	59.00	-101.91	-42.91	16.74	-59.65	peak
6	0.4097	56.02	-101.97	-45.95	15.37	-61.32	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. All the modes had been tested, but only the worst data were recorded in the report.

3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



490kHz ~ 30MHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.9121	66.44	-62.21	4.23	28.41	-24.18	peak
2	1.9128	56.23	-61.87	-5.64	29.54	-35.18	peak
3	2.3785	54.78	-61.72	-6.94	29.54	-36.48	peak
4	6.4508	51.86	-61.29	-9.43	29.54	-38.97	peak
5	12.8544	51.19	-60.92	-9.73	29.54	-39.27	peak
6	21.3826	51.69	-60.73	-9.04	29.54	-38.58	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. All the modes had been tested, but only the worst data were recorded in the report.
3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.




SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)

9kHz~ 150kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0097	74.79	-101.38	-26.59	47.83	-74.42	peak
2	0.0137	69.76	-101.38	-31.62	45.37	-76.99	peak
3	0.0235	65.52	-101.36	-35.84	40.35	-76.19	peak
4	0.0408	61.96	-101.44	-39.48	35.40	-74.88	peak
5	0.0636	58.04	-101.54	-43.50	31.56	-75.06	peak
6	0.0777	57.15	-101.61	-44.46	29.81	-74.27	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. All the modes had been tested, but only the worst data were recorded in the report.
3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.


150kHz ~ 490kHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1604	68.64	-101.65	-33.01	23.50	-56.51	peak
2	0.1768	67.55	-101.68	-34.13	22.66	-56.79	peak
3	0.2088	64.28	-101.73	-37.45	21.27	-58.72	peak
4	0.2358	62.91	-101.78	-38.87	20.32	-59.19	peak
5	0.2816	61.17	-101.83	-40.66	18.71	-59.37	peak
6	0.3496	60.52	-101.91	-41.39	16.82	-58.21	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. All the modes had been tested, but only the worst data were recorded in the report.

3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

490kHz ~ 30MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6864	67.42	-62.11	5.31	30.88	-25.57	peak
2	1.2059	63.84	-62.17	1.67	25.98	-24.31	peak
3	1.6563	57.62	-61.97	-4.35	23.22	-27.57	peak
4	3.9786	52.22	-61.34	-9.12	29.54	-38.66	peak
5	8.1920	51.85	-61.05	-9.20	29.54	-38.74	peak
6	23.2713	49.25	-60.58	-11.33	29.54	-40.87	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. All the modes had been tested, but only the worst data were recorded in the report.


3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

Note: All test mode has been tested, only the worst data record in the report.




7.7. SPURIOUS EMISSIONS BELOW 1 GHz

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	101.7800	27.55	-21.75	5.80	43.50	-37.70	peak
2	250.1900	28.54	-16.12	12.42	46.00	-33.58	peak
3	486.8700	25.73	-10.70	15.03	46.00	-30.97	peak
4	689.6000	25.42	-6.88	18.54	46.00	-27.46	peak
5	741.9800	26.59	-6.07	20.52	46.00	-25.48	peak
6	833.1599	27.97	-4.80	23.17	46.00	-22.83	peak

Note: 1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	82.3800	27.51	-20.70	6.81	40.00	-33.19	peak
2	204.6000	24.52	-15.92	8.60	43.50	-34.90	peak
3	288.0200	24.92	-14.50	10.42	46.00	-35.58	peak
4	466.5000	25.16	-11.15	14.01	46.00	-31.99	peak
5	717.7300	25.74	-6.16	19.58	46.00	-26.42	peak
6	838.0100	27.77	-4.68	23.09	46.00	-22.91	peak

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All test mode has been tested, only the worst data record in the report.



8. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies

END OF REPORT