




FCC SAR TEST REPORT

FCC ID : PY7-54264H
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa,
Shinagawa-ku, Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa,
Shinagawa-ku, Tokyo, 140-0002, Japan
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was received on Nov. 21, 2018 and testing was started from Nov. 26, 2018 and completed on Nov. 30, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 Device Serial Number	5
3.3 General LTE SAR Test and Reporting Considerations	6
4. RF Exposure Limits.....	7
4.1 Uncontrolled Environment.....	7
4.2 Controlled Environment.....	7
5. Specific Absorption Rate (SAR).....	8
5.1 Introduction	8
5.2 SAR Definition.....	8
6. System Description and Setup	9
6.1 E-Field Probe	10
6.2 Data Acquisition Electronics (DAE)	10
6.3 Phantom.....	11
6.4 Device Holder.....	12
7. Measurement Procedures	13
7.1 Spatial Peak SAR Evaluation.....	13
7.2 Power Reference Measurement.....	14
7.3 Area Scan	14
7.4 Zoom Scan.....	15
7.5 Volume Scan Procedures.....	15
7.6 Power Drift Monitoring.....	15
8. Test Equipment List.....	16
9. System Verification	17
9.1 Tissue Simulating Liquids.....	17
9.2 Tissue Verification	18
9.3 System Performance Check Results.....	19
10. RF Exposure Positions	20
10.1 Ear and handset reference point	20
10.2 Definition of the cheek position	21
10.3 Definition of the tilt position	22
10.4 Body Worn Accessory	22
10.5 Wireless Router.....	23
11. Conducted RF Output Power (Unit: dBm).....	24
12. RF Exposure Conditions	38
13. SAR Test Results	39
13.1 Head SAR	41
13.2 Hotspot SAR	43
13.3 Body Worn Accessory SAR.....	44
14. Simultaneous Transmission Analysis	46
14.1 Head Exposure Conditions	47
14.2 Hotspot Exposure Conditions.....	48
14.3 Body-Worn Accessory Exposure Conditions	49
15. Uncertainty Assessment	50
16. References.....	50
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Antenna Location & Test Setup Photos	

[illegible]

1. Statement of Compliance

Applicant Name	Sony Mobile Communications Inc.			
EUT Description	GSM/WCDMA/LTE Phone+Bluetooth, DTS/UNII a/b/g/n/ac and NFC			
Brand Name	Sony			
FCC ID	PY7-54264H			
HW Version	A			
SW Version	0.160			
RF Exposure Conditions	Equipment Class			
	Licensed	DTS	NII	DSS
Head (1g SAR W/kg)	0.51	0.52	0.71	0.21
Body-Worn (1g SAR W/kg)	0.61	0.08	0.43	0.02
Wireless Router (1g SAR W/kg)	0.70	0.18		0.05
Highest Simultaneous Transmission (1g SAR W/kg)	Head: 1.38 Body-worn: 1.05 Hotspot: 0.87	Head: 0.99 Body-worn: 0.68 Hotspot: 0.87	Head: 1.38 Body-worn: 1.05 Hotspot: NA	Head: 1.38 Body-worn: 1.05 Hotspot: 0.74
Date Tested	2018/11/26 ~ 2018/11/30			
Test Result	Pass			
Remark:				
1. This device 2.4GHz WLAN support Hotspot operation and Bluetooth support tethering applications.				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang

Report Producer: Wan Liu

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01



3. Equipment Under Test (EUT) Information

3.1 General Information

Wireless Technologies	Frequency	Operating Mode	
GSM	850 1900	<ul style="list-style-type: none">· GSM Voice· GPRS (GMSK)· EDGE (8PSK)	Multi-Slot Class: Class 33
	Does device support dual transfer mode? (Yes)		
W-CDMA (UMTS)	Band 5	<ul style="list-style-type: none">· AMR / RMC 12.2Kbps· HSDPA (Rel. 5)· HSUPA (Rel. 6)	
LTE (FDD)	Band 5 Band 12 Band 17	<ul style="list-style-type: none">· QPSK· 16QAM· 64QAM· Rel 12 Does not support Carrier Aggregation (CA)	
WiFi	2.4GHz: 2412 MHz ~ 2472 MHz	<ul style="list-style-type: none">· 11b· 11g· 11n (HT20)	
	5GHz: 5.2GHz: 5180 MHz ~ 5240 MHz 5.3GHz: 5260 MHz ~ 5320 MHz 5.5GHz: 5500 MHz ~ 5720 MHz 5.8GHz: 5745 MHz ~ 5825 MHz	<ul style="list-style-type: none">· 11a· 11n (HT20)· 11n (HT40)· 11ac (VHT20)· 11ac (VHT40)· 11ac (VHT80)	
Bluetooth	2.4GHz	<ul style="list-style-type: none">· BR / EDR / LE	
NFC	13.56MHz	<ul style="list-style-type: none">· ASK	

3.2 Device Serial Number

Band	SN
WWAN	BH9400FEE8
WLAN	BH9400RWE8

Note: Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device tested gave the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

3.3 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05								
FCC ID	PY7-54264H							
Operating Frequency Range of each LTE transmission band	LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz							
Channel Bandwidth	LTE Band 05:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz							
uplink modulations used	QPSK / 16QAM / 64QAM							
LTE Voice / Data requirements	Voice only.							
LTE MPR permanently built-in by design	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
		1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
256 QAM	≥ 1						≤ 5	
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)							
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							
Transmission (H, M, L) channel numbers and frequencies in each LTE band								
LTE Band 5								
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844
LTE Band 12								
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23060	704
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5
H	23173	715.3	23165	714.5	23155	713.5	23130	711
LTE Band 17								
	Bandwidth 5 MHz				Bandwidth 10 MHz			
	Channel #		Freq.(MHz)		Channel #		Freq. (MHz)	
L	23755		706.5		23780		709	
M	23790		710		23790		710	
H	23825		713.5		23800		711	

4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.


6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE


6.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1107	Feb. 27, 2018	Feb. 26, 2019
SPEAG	835MHz System Validation Kit	D835V2	499	Sep. 06, 2018	Sep. 05, 2019
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Sep. 11, 2018	Sep. 10, 2019
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 31, 2018	Aug. 30, 2019
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Sep. 27, 2018	Sep. 26, 2019
SPEAG	Data Acquisition Electronics	DAE4	853	Jul. 24, 2018	Jul. 23, 2019
SPEAG	Data Acquisition Electronics	DAE4	1424	Jan. 18, 2018	Jan. 17, 2019
SPEAG	Dosimetric E-Field Probe	ES3DV3	3169	May. 28, 2018	May. 27, 2019
SPEAG	Dosimetric E-Field Probe	EX3DV4	3976	Jan. 23, 2018	Jan. 22, 2019
RCPTWN	Thermometer	HTC-1	TM685-1	Nov. 12, 2018	Nov. 11, 2019
RCPTWN	Thermometer	HTC-1	TM281-1	Mar. 16, 2018	Mar. 15, 2019
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Apr. 17, 2018	Apr. 16, 2019
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 21, 2018	May. 20, 2019
R&S	BT Base Station	CBT	100815	Feb. 05, 2018	Feb. 04, 2019
SPEAG	Device Holder	N/A	N/A	N/A	N/A
R&S	Signal Generator	SMA100A	101091	Jul. 09, 2018	Jul. 08, 2019
Agilent	ENA Network Analyzer	E5071C	MY46316648	Jan. 17, 2018	Jan. 16, 2019
SPEAG	Dielectric Probe Kit	DAK-3.5	1146	Jul. 24, 2018	Jul. 23, 2019
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3169	Sep. 11, 2018	Sep. 10, 2019
Anritsu	Power Meter	ML2495A	1419002	May. 18, 2018	May. 17, 2019
Anritsu	Power Sensor	MA2411B	1339124	May. 18, 2018	May. 17, 2019
Anritsu	Power Meter	ML2495A	1240001	Sep. 13, 2018	Sep. 12, 2019
Anritsu	Power Sensor	MA2411B	1207349	Sep. 13, 2018	Sep. 12, 2019
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 28, 2018	Aug. 27, 2019
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 23, 2018	Jun. 22, 2019
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 09, 2018	Aug. 08, 2019
Mini-Circuits	Power Amplifier	ZHL-42W+	15542	Aug. 09, 2018	Aug. 08, 2019
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

9. System Verification

9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR

9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	HSL	22.7	0.890	43.047	0.89	41.90	0.00	2.74	±5	2018/11/28
750	MSL	22.6	0.974	54.234	0.96	55.50	1.46	-2.28	±5	2018/11/28
835	HSL	22.7	0.924	43.014	0.90	41.50	2.67	3.65	±5	2018/11/28
835	MSL	22.2	0.986	57.685	0.97	55.20	1.65	4.50	±5	2018/11/29
1900	HSL	22.1	1.436	38.651	1.40	40.00	2.57	-3.37	±5	2018/11/27
1900	MSL	22.5	1.553	52.961	1.52	53.30	2.17	-0.64	±5	2018/11/26
2450	HSL	22.2	1.771	38.909	1.80	39.20	-1.61	-0.74	±5	2018/11/29
2450	MSL	22.8	2.010	51.560	1.95	52.70	3.08	-2.16	±5	2018/11/29
5250	HSL	22.3	4.578	36.955	4.71	35.95	-2.80	2.80	±5	2018/11/30
5250	MSL	22.3	5.394	47.549	5.36	48.95	0.63	-2.86	±5	2018/11/30
5600	HSL	22.3	4.922	36.602	5.07	35.50	-2.92	3.10	±5	2018/11/30
5600	MSL	22.3	5.849	46.996	5.77	48.50	1.37	-3.10	±5	2018/11/30
5750	HSL	22.3	5.092	36.282	5.22	35.35	-2.45	2.64	±5	2018/11/30
5750	MSL	22.3	6.045	46.722	5.94	48.28	1.77	-3.23	±5	2018/11/30

9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2018/11/28	750	HSL	250	D750V3-1107	ES3DV3 - SN3169	DAE4 Sn853	1.90	8.18	7.6	-7.09
2018/11/28	750	MSL	250	D750V3-1107	ES3DV3 - SN3169	DAE4 Sn853	2.22	8.52	8.88	4.23
2018/11/28	835	HSL	250	D835V2-499	ES3DV3 - SN3169	DAE4 Sn853	2.42	9.59	9.68	0.94
2018/11/29	835	MSL	250	D835V2-499	ES3DV3 - SN3169	DAE4 Sn853	2.46	9.82	9.84	0.20
2018/11/27	1900	HSL	250	D1900V2-5d041	ES3DV3 - SN3169	DAE4 Sn853	9.93	40.20	39.72	-1.19
2018/11/26	1900	MSL	250	D1900V2-5d041	ES3DV3 - SN3169	DAE4 Sn853	9.75	40.20	39	-2.99
2018/11/29	2450	HSL	250	D2450V2-736	ES3DV3 - SN3169	DAE4 Sn853	13.00	52.70	52	-1.33
2018/11/29	2450	MSL	250	D2450V2-736	ES3DV3 - SN3169	DAE4 Sn853	13.00	51.50	52	0.97
2018/11/30	5250	HSL	100	D5GHzV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	8.23	80.70	82.3	1.98
2018/11/30	5250	MSL	100	D5GHzV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	7.85	78.30	78.5	0.26
2018/11/30	5600	HSL	100	D5GHzV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	8.72	83.30	87.2	4.68
2018/11/30	5600	MSL	100	D5GHzV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	8.21	81.00	82.1	1.36
2018/11/30	5750	HSL	100	D5GHzV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	7.58	80.40	75.8	-5.72
2018/11/30	5750	MSL	100	D5GHzV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	7.59	77.40	75.9	-1.94




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

10.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 9.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

10.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15° .
3. Rotate the handset around the horizontal line by 15° .
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

10.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position



10.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

11. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

- For DTM multi-slot class mode, the device was linked with base station simulator (Agilent E5515C) and transmit maximum power on maximum number of TX slots, i.e. one CS timeslot, and additional PS timeslots (1 for DTM class 5 and 9, 2 for DTM class 11) in one TDMA frame.
- Agilent E5515C was used to setup the device operated under DTM mode for power measurement and SAR testing. For conducted power, the power of the burst for voice and the power of the bursts for data was reported separately in the table above, and the frame-average power is derived below to determine SAR testing.

$$DTM \text{ frame average power (dBm)} = 10 * \log [\sum (\text{power of each slot, in mW}) / 8]$$

- Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
- Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode

GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot		32.88	32.93	33.16	33.70	23.88	23.93	24.16	24.70
GPRS 1 Tx slot		32.89	32.95	33.14	33.70	23.89	23.95	24.14	24.70
GPRS 2 Tx slots		30.97	31.01	31.22	31.70	24.97	25.01	25.22	25.70
GPRS 3 Tx slots		28.90	28.97	29.14	29.70	24.64	24.71	24.88	25.44
GPRS 4 Tx slots		28.11	28.28	28.37	28.70	25.11	25.28	25.37	25.70
EDGE 1 Tx slot		27.01	27.08	27.32	28.00	18.01	18.08	18.32	19.00
EDGE 2 Tx slots		25.59	25.68	25.83	26.50	19.59	19.68	19.83	20.50
EDGE 3 Tx slots		23.61	23.64	23.87	24.50	19.35	19.38	19.61	20.24
EDGE 4 Tx slots		22.81	22.75	23.09	23.50	19.81	19.75	20.09	20.50
DTM Multi-slot class 5	GSM 1 Tx slot	30.93	30.98	31.21	31.70	24.85	24.89	25.12	25.68
	GPRS 1 Tx slot	30.81	30.85	31.07	31.70				
DTM Multi-slot class 9	GSM 1 Tx slot	30.96	30.95	31.20	31.70	24.87	24.86	25.11	25.68
	GPRS 1 Tx slot	30.83	30.82	31.06	31.70				
DTM Multi-slot class 11	GSM 1 Tx slot	28.86	28.78	29.04	29.70	24.64	24.60	24.86	25.44
	GPRS 2 Tx slots	28.92	28.90	29.16	29.70				
DTM Multi-slot class 5	GSM 1 Tx slot	30.84	30.90	31.13	31.70	22.94	22.99	23.22	23.82
	EDGE 1 Tx slot	25.58	25.61	25.84	26.50				
DTM Multi-slot class 9	GSM 1 Tx slot	30.98	30.98	31.21	31.70	23.04	23.04	23.27	23.82
	EDGE 1 Tx slot	25.52	25.54	25.76	26.50				
DTM Multi-slot class 11	GSM 1 Tx slot	28.94	28.91	29.19	29.70	21.87	21.86	22.12	22.72
	EDGE 2 Tx slots	23.50	23.52	23.74	24.50				

GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot		28.72	28.94	28.86	29.20	19.72	19.94	19.86	20.20
GPRS 1 Tx slot		28.73	28.96	28.88	29.20	19.73	19.96	19.88	20.20
GPRS 2 Tx slots		27.10	27.17	27.20	27.20	21.10	21.17	21.20	21.20
GPRS 3 Tx slots		25.03	25.02	25.20	25.20	20.77	20.76	20.94	20.94
GPRS 4 Tx slots		24.02	24.03	24.15	24.20	21.02	21.03	21.15	21.20
EDGE 1 Tx slot		26.17	26.32	26.41	27.00	17.17	17.32	17.41	18.00
EDGE 2 Tx slots		24.64	24.77	24.80	25.50	18.64	18.77	18.80	19.50
EDGE 3 Tx slots		22.79	23.00	23.08	23.50	18.53	18.74	18.82	19.24
EDGE 4 Tx slots		21.77	21.88	21.95	22.50	18.77	18.88	18.95	19.50
DTM Multi-slot class 5	GSM 1 Tx slot	27.06	27.15	27.19	27.20	20.98	21.07	21.10	21.18
	GPRS 1 Tx slot	26.94	27.04	27.04	27.20				
DTM Multi-slot class 9	GSM 1 Tx slot	27.05	27.17	27.19	27.20	20.97	21.08	21.10	21.18
	GPRS 1 Tx slot	26.93	27.04	27.04	27.20				
DTM Multi-slot class 11	GSM 1 Tx slot	24.99	25.09	25.18	25.20	20.67	20.76	20.85	20.94
	GPRS 2 Tx slots	24.90	24.98	25.08	25.20				
DTM Multi-slot class 5	GSM 1 Tx slot	26.96	27.08	27.18	27.20	19.90	20.02	20.12	20.41
	EDGE 1 Tx slot	24.54	24.68	24.77	25.50				
DTM Multi-slot class 9	GSM 1 Tx slot	26.96	27.19	27.20	27.20	19.86	20.05	20.08	20.41
	EDGE 1 Tx slot	24.44	24.56	24.63	25.50				
DTM Multi-slot class 11	GSM 1 Tx slot	24.90	24.92	25.09	25.20	19.33	19.40	19.52	19.88
	EDGE 2 Tx slots	22.75	22.86	22.94	23.50				

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
<p>Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.</p> <p>Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.</p> <p>Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPCCH, DPCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.</p> <p>Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.</p>							

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

<WCDMA Conducted Power>
General Note:


1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA.

Band		WCDMA V			Tune-up Limit (dBm)
TX Channel		4132	4182	4233	
Rx Channel		4357	4407	4458	
Frequency (MHz)		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	23.09	23.11	23.19	23.20
3GPP Rel 99	RMC 12.2Kbps	23.10	23.09	23.20	23.20
3GPP Rel 6	HSDPA Subtest-1	22.09	22.11	22.23	22.50
3GPP Rel 6	HSDPA Subtest-2	22.13	22.17	22.27	22.50
3GPP Rel 6	HSDPA Subtest-3	21.64	21.65	21.65	22.00
3GPP Rel 6	HSDPA Subtest-4	21.65	21.65	21.74	22.00
3GPP Rel 6	HSUPA Subtest-1	22.10	22.11	22.22	22.50
3GPP Rel 6	HSUPA Subtest-2	20.10	20.12	20.21	20.50
3GPP Rel 6	HSUPA Subtest-3	21.10	21.12	21.23	21.50
3GPP Rel 6	HSUPA Subtest-4	20.10	20.13	20.23	20.50
3GPP Rel 6	HSUPA Subtest-5	22.09	22.12	22.22	22.50

<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B5 / B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 17 SAR test was covered by Band 12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM



<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	23.10	23.03	23.19	23.5	0
10	QPSK	1	25	23.05	22.95	23.09		
10	QPSK	1	49	22.95	22.96	23.11		
10	QPSK	25	0	22.63	22.55	22.54	23	0.5
10	QPSK	25	12	22.56	22.54	22.64		
10	QPSK	25	25	22.52	22.43	22.60		
10	QPSK	50	0	22.58	22.51	22.62	23	0.5
10	16QAM	1	0	22.29	22.26	22.42		
10	16QAM	1	25	22.39	22.32	22.46		
10	16QAM	1	49	22.32	22.27	22.45	22	1.5
10	16QAM	25	0	21.17	21.12	21.12		
10	16QAM	25	12	21.16	21.11	21.23		
10	16QAM	25	25	21.09	21.02	21.19	22	1.5
10	16QAM	50	0	21.15	21.07	21.21		
10	64QAM	1	0	21.17	21.17	21.31		
10	64QAM	1	25	21.31	21.18	21.38	22	1.5
10	64QAM	1	49	21.19	21.20	21.31		
10	64QAM	25	0	20.19	20.11	20.14		
10	64QAM	25	12	20.20	20.11	20.27	21	2.5
10	64QAM	25	25	20.08	20.01	20.22		
10	64QAM	50	0	20.14	20.06	20.22		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	22.99	23.00	23.05	23.5	0
5	QPSK	1	12	23.04	23.00	23.18		
5	QPSK	1	24	23.03	23.00	23.13		
5	QPSK	12	0	22.51	22.51	22.59	23	0.5
5	QPSK	12	7	22.63	22.55	22.76		
5	QPSK	12	13	22.58	22.51	22.70		
5	QPSK	25	0	22.58	22.48	22.61	23	0.5
5	16QAM	1	0	22.28	22.29	22.33		
5	16QAM	1	12	22.36	22.30	22.48		
5	16QAM	1	24	22.31	22.36	22.38	22	1.5
5	16QAM	12	0	21.13	21.10	21.16		
5	16QAM	12	7	21.22	21.08	21.28		
5	16QAM	12	13	21.13	21.04	21.23	22	1.5
5	16QAM	25	0	21.16	21.09	21.19		
5	64QAM	1	0	21.20	21.19	21.31		
5	64QAM	1	12	21.37	21.15	21.33	22	1.5
5	64QAM	1	24	21.29	21.25	21.40		
5	64QAM	12	0	20.23	20.13	20.21		
5	64QAM	12	7	20.27	20.14	20.31	21	2.5
5	64QAM	12	13	20.22	20.10	20.28		
5	64QAM	25	0	20.16	20.07	20.20		



FCC SAR TEST REPORT

Report No. : FA8O2416-02

Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	22.98	22.96	23.18	23.5	0
3	QPSK	1	8	22.94	22.94	23.02		
3	QPSK	1	14	23.01	22.96	23.14		
3	QPSK	8	0	22.31	22.50	22.71	23	0.5
3	QPSK	8	4	22.49	22.49	22.74		
3	QPSK	8	7	22.57	22.48	22.70		
3	QPSK	15	0	22.45	22.49	22.72		
3	16QAM	1	0	22.21	22.28	22.40	23	0.5
3	16QAM	1	8	22.21	22.24	22.51		
3	16QAM	1	14	22.28	22.20	22.43		
3	16QAM	8	0	21.10	21.13	21.33	22	1.5
3	16QAM	8	4	21.12	21.10	21.34		
3	16QAM	8	7	21.23	21.10	21.28		
3	16QAM	15	0	21.18	21.07	21.28		
3	64QAM	1	0	21.12	21.22	21.37	22	1.5
3	64QAM	1	8	21.16	21.24	21.38		
3	64QAM	1	14	21.33	21.11	21.33		
3	64QAM	8	0	20.12	20.10	20.29	21	2.5
3	64QAM	8	4	20.15	20.10	20.27		
3	64QAM	8	7	20.19	20.06	20.24		
3	64QAM	15	0	20.18	20.07	20.26		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	22.84	22.89	23.07	23.5	0
1.4	QPSK	1	3	22.96	22.97	23.15		
1.4	QPSK	1	5	22.88	22.88	23.07		
1.4	QPSK	3	0	22.95	22.93	23.12		
1.4	QPSK	3	1	23.00	22.95	23.13		
1.4	QPSK	3	3	22.95	22.96	23.10		
1.4	QPSK	6	0	22.07	22.38	22.60	23	0.5
1.4	16QAM	1	0	22.16	22.23	22.39	23	0.5
1.4	16QAM	1	3	22.16	22.27	22.44		
1.4	16QAM	1	5	22.21	22.22	22.36		
1.4	16QAM	3	0	21.98	22.00	22.18		
1.4	16QAM	3	1	21.97	22.00	22.22		
1.4	16QAM	3	3	21.93	21.96	22.16		
1.4	16QAM	6	0	21.05	21.05	21.26	22	1.5
1.4	64QAM	1	0	21.16	21.10	21.22	22	1.5
1.4	64QAM	1	3	21.13	21.17	21.32		
1.4	64QAM	1	5	21.07	21.12	21.31		
1.4	64QAM	3	0	21.13	21.09	21.28		
1.4	64QAM	3	1	21.15	21.15	21.32		
1.4	64QAM	3	3	21.17	21.09	21.28		
1.4	64QAM	6	0	20.20	20.11	20.16	21	2.5

<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130		
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	23.25	23.07	23.32	24	0
10	QPSK	1	25	22.93	22.79	22.93		
10	QPSK	1	49	22.95	22.68	22.82		
10	QPSK	25	0	22.07	21.90	21.97	23	1
10	QPSK	25	12	22.05	21.89	21.95		
10	QPSK	25	25	22.05	21.77	21.84		
10	QPSK	50	0	22.12	21.85	21.89	23	1
10	16QAM	1	0	22.39	22.15	22.26		
10	16QAM	1	25	22.24	22.16	22.17		
10	16QAM	1	49	22.31	21.93	22.04	22	2
10	16QAM	25	0	21.06	20.99	21.05		
10	16QAM	25	12	21.10	20.96	20.99		
10	16QAM	25	25	21.13	20.85	20.95	22	2
10	16QAM	50	0	21.17	20.92	21.02		
10	64QAM	1	0	21.28	21.05	21.26		
10	64QAM	1	25	21.15	21.11	21.11	22	2
10	64QAM	1	49	21.25	20.82	21.03		
10	64QAM	25	0	20.08	19.97	20.05		
10	64QAM	25	12	20.15	19.97	19.99	21	3
10	64QAM	25	25	20.15	19.88	19.94		
10	64QAM	50	0	20.21	19.97	19.98		
Channel				23035	23095	23155	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	22.92	22.73	23.27	24	0
5	QPSK	1	12	22.92	22.76	23.20		
5	QPSK	1	24	22.85	22.81	23.26		
5	QPSK	12	0	21.95	21.86	22.26	23	1
5	QPSK	12	7	21.94	21.85	22.25		
5	QPSK	12	13	21.88	21.83	22.06		
5	QPSK	25	0	21.93	21.86	22.25	23	1
5	16QAM	1	0	22.25	21.98	22.56		
5	16QAM	1	12	22.20	22.09	22.47		
5	16QAM	1	24	22.14	22.17	22.47	22	2
5	16QAM	12	0	21.02	20.94	21.38		
5	16QAM	12	7	21.08	20.99	21.39		
5	16QAM	12	13	20.98	20.92	21.11	22	2
5	16QAM	25	0	20.99	20.91	21.35		
5	64QAM	1	0	21.17	20.88	21.48		
5	64QAM	1	12	21.09	21.07	21.39	22	2
5	64QAM	1	24	20.98	21.03	21.52		
5	64QAM	12	0	20.08	19.95	20.43		
5	64QAM	12	7	20.06	20.02	20.41	21	3
5	64QAM	12	13	20.00	19.96	20.31		
5	64QAM	25	0	20.02	19.90	20.32		



FCC SAR TEST REPORT

Report No. : FA802416-02

Channel				23025	23095	23165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	22.93	22.68	23.27	24	0
3	QPSK	1	8	22.89	22.76	22.99		
3	QPSK	1	14	22.84	22.89	23.27		
3	QPSK	8	0	21.96	21.82	22.05	23	1
3	QPSK	8	4	21.96	21.88	21.92		
3	QPSK	8	7	21.89	21.81	21.97		
3	QPSK	15	0	21.93	21.84	22.00		
3	16QAM	1	0	22.23	21.92	22.50	23	1
3	16QAM	1	8	22.11	22.05	22.44		
3	16QAM	1	14	22.12	22.14	22.55		
3	16QAM	8	0	21.05	20.96	21.36	22	2
3	16QAM	8	4	21.07	21.02	21.17		
3	16QAM	8	7	21.05	20.97	21.21		
3	16QAM	15	0	21.02	20.92	21.22		
3	64QAM	1	0	21.15	20.86	21.45	22	2
3	64QAM	1	8	21.18	21.12	21.32		
3	64QAM	1	14	21.04	21.06	21.54		
3	64QAM	8	0	20.10	19.90	20.34	21	3
3	64QAM	8	4	20.08	19.95	20.25		
3	64QAM	8	7	20.02	19.92	20.22		
3	64QAM	15	0	20.05	19.94	20.30		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	22.73	22.67	22.98	24	0
1.4	QPSK	1	3	22.80	22.79	23.31		
1.4	QPSK	1	5	22.73	22.66	23.24		
1.4	QPSK	3	0	22.77	22.78	22.92		
1.4	QPSK	3	1	22.83	22.83	23.04		
1.4	QPSK	3	3	22.80	22.76	23.16		
1.4	QPSK	6	0	21.81	21.78	22.07	23	1
1.4	16QAM	1	0	22.00	22.02	22.33	23	1
1.4	16QAM	1	3	22.17	22.14	22.55		
1.4	16QAM	1	5	22.03	22.01	22.48		
1.4	16QAM	3	0	21.87	21.83	22.02		
1.4	16QAM	3	1	21.87	21.91	22.14		
1.4	16QAM	3	3	21.81	21.75	22.21		
1.4	16QAM	6	0	20.88	20.97	21.20	22	2
1.4	64QAM	1	0	21.02	21.00	21.45	22	2
1.4	64QAM	1	3	21.07	21.00	21.51		
1.4	64QAM	1	5	21.02	21.01	21.48		
1.4	64QAM	3	0	21.06	21.06	21.10		
1.4	64QAM	3	1	21.02	21.02	21.28		
1.4	64QAM	3	3	21.04	21.01	21.37		
1.4	64QAM	6	0	20.08	20.05	20.14	21	3

<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23780	23790	23800	24	0
Frequency (MHz)				709	710	711		
10	QPSK	1	0	22.93	22.91	22.89		
10	QPSK	1	25	22.92	22.88	22.79	23	1
10	QPSK	1	49	22.80	22.80	22.72		
10	QPSK	25	0	21.90	21.98	21.97		
10	QPSK	25	12	21.97	21.97	21.96	23	1
10	QPSK	25	25	21.90	21.90	21.89		
10	QPSK	50	0	21.96	21.96	21.95		
10	16QAM	1	0	22.11	22.28	22.21	23	1
10	16QAM	1	25	22.22	22.26	22.11		
10	16QAM	1	49	22.04	22.02	21.95		
10	16QAM	25	0	21.02	21.11	21.09	22	2
10	16QAM	25	12	21.09	21.07	21.03		
10	16QAM	25	25	20.97	20.93	20.93		
10	16QAM	50	0	21.02	21.04	21.02	22	2
10	64QAM	1	0	21.01	21.12	21.10		
10	64QAM	1	25	21.18	21.15	20.97		
10	64QAM	1	49	20.98	21.01	20.85	21	3
10	64QAM	25	0	20.00	20.12	20.10		
10	64QAM	25	12	20.10	20.09	20.06		
10	64QAM	25	25	19.97	19.96	19.93	21	3
10	64QAM	50	0	20.06	20.07	20.00		
Channel				23755	23790	23825	24	0
Frequency (MHz)				706.5	710	713.5		
5	QPSK	1	0	22.81	22.82	22.78		
5	QPSK	1	12	22.85	22.91	22.84	23	1
5	QPSK	1	24	22.78	22.74	22.71		
5	QPSK	12	0	21.92	21.96	21.90		
5	QPSK	12	7	21.94	21.97	21.91	23	1
5	QPSK	12	13	21.89	21.90	21.85		
5	QPSK	25	0	21.89	21.96	21.91		
5	16QAM	1	0	22.10	22.14	22.10	23	1
5	16QAM	1	12	22.23	22.23	22.20		
5	16QAM	1	24	22.07	22.00	22.03		
5	16QAM	12	0	20.95	21.04	20.95	22	2
5	16QAM	12	7	21.02	21.04	20.98		
5	16QAM	12	13	20.96	21.01	20.97		
5	16QAM	25	0	21.00	21.08	20.99	22	2
5	64QAM	1	0	20.96	21.12	21.10		
5	64QAM	1	12	21.10	21.02	21.07		
5	64QAM	1	24	21.00	20.94	20.88	21	3
5	64QAM	12	0	20.04	20.14	20.06		
5	64QAM	12	7	20.08	20.12	20.03		
5	64QAM	12	13	20.03	20.01	20.01	21	3
5	64QAM	25	0	19.98	20.00	19.96		

<WLAN Conducted Power>
General Note:

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	15.20	15.30	100.00
		6	2437	15.00	15.30	
		11	2462	15.08	15.30	
		12	2467	15.19	15.30	
		13	2472	9.54	10.00	
	802.11g 6Mbps	1	2412	15.08	15.10	95.28
		6	2437	14.98	15.10	
		11	2462	15.02	15.10	
		12	2467	9.40	9.40	
		13	2472	-4.47	-4.47	
	802.11n-HT20 MCS0	1	2412	15.01	15.10	98.13
		6	2437	14.96	15.10	
		11	2462	13.94	14.17	
		12	2467	8.88	8.88	
		13	2472	-4.57	-4.57	

<5GHz WLAN>

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	36	5180	16.28	16.28	95.31
		40	5200	16.58	16.80	
		44	5220	16.65	16.80	
		48	5240	16.49	16.80	
	802.11n-HT20 MCS0	36	5180	15.72	15.72	98.03
		40	5200	16.69	16.80	
		44	5220	16.72	16.80	
		48	5240	16.68	16.80	
	802.11n-HT40 MCS0	38	5190	13.10	13.10	95.63
		46	5230	16.77	16.80	
	802.11ac-VHT20 MCS0	36	5180	15.64	15.72	98.03
		40	5200	16.56	16.80	
		44	5220	16.72	16.80	
		48	5240	16.61	16.80	
	802.11ac-VHT40 MCS0	38	5190	13.02	13.10	96.03
		46	5230	16.67	16.80	
	802.11ac-VHT80 MCS0	42	5210	11.53	11.77	91.94

5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	52	5260	16.09	16.20	95.31
		56	5280	16.02	16.20	
		60	5300	16.01	16.20	
		64	5320	16.04	16.20	
	802.11n-HT20 MCS0	52	5260	16.18	16.20	98.03
		56	5280	16.16	16.20	
		60	5300	16.17	16.20	
		64	5320	16.18	16.20	
	802.11n-HT40 MCS0	54	5270	15.82	16.20	95.63
		62	5310	10.65	10.65	
	802.11ac-VHT20 MCS0	52	5260	16.16	16.20	98.03
		56	5280	16.15	16.20	
		60	5300	16.16	16.20	
		64	5320	16.15	16.20	
	802.11ac-VHT40 MCS0	54	5270	15.80	16.20	96.03
		62	5310	10.57	10.65	
	802.11ac-VHT80 MCS0	58	5290	11.12	11.12	91.94

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.5GHz WLAN	802.11a 6Mbps	100	5500	16.78	17.10	95.31
		116	5580	16.77	17.10	
		124	5620	16.82	17.10	
		132	5660	17.00	17.10	
		144	5720	17.01	17.10	
	802.11n-HT20 MCS0	100	5500	17.05	17.10	98.03
		116	5580	16.99	17.10	
		124	5620	16.66	17.10	
		132	5660	16.77	17.10	
		144	5720	16.74	17.10	
	802.11n-HT40 MCS0	102	5510	13.54	13.54	95.63
		110	5550	17.09	17.10	
		126	5630	16.66	17.10	
		134	5670	16.77	17.10	
		142	5710	16.72	17.10	
	802.11ac-VHT20 MCS0	100	5500	17.00	17.10	98.03
		116	5580	16.97	17.10	
		124	5620	16.59	17.10	
		132	5660	16.74	17.10	
		144	5720	16.73	17.10	
	802.11ac-VHT40 MCS0	102	5510	13.50	13.54	96.03
		110	5550	17.05	17.10	
		126	5630	16.64	17.10	
		134	5670	16.68	17.10	
		142	5710	16.70	17.10	
	802.11ac-VHT80 MCS0	106	5530	11.52	11.52	91.94
		122	5610	15.96	16.02	
		138	5690	15.60	16.02	

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN	802.11a MCS0	149	5745	15.48	15.79	95.31
		157	5785	16.67	16.80	
		165	5825	16.50	16.80	
	802.11n-HT20 MCS0	149	5745	15.30	15.59	98.03
		157	5785	16.55	16.80	
		165	5825	16.79	16.80	
	802.11n-HT40 MCS0	151	5755	14.13	14.17	95.63
		159	5795	16.54	16.80	
	802.11ac-VHT20 MCS0	149	5745	15.22	15.59	98.03
		157	5785	16.40	16.80	
		165	5825	16.77	16.80	
	802.11ac-VHT40 MCS0	151	5755	14.11	14.17	96.03
		159	5795	16.48	16.80	
	802.11ac-VHT80 MCS0	155	5775	13.15	13.17	91.94

<2.4GHz Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)			Tune-up Limit		
			1Mbps	2Mbps	3Mbps	1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	11.33	9.07	9.14	12.21	9.49	9.49
	CH 39	2441	10.36	8.58	8.50	11.06	9.11	9.11
	CH 78	2480	10.62	8.49	8.53	11.50	9.18	9.18

Mode	Channel	Frequency (MHz)	Average power (dBm)		Tune-up Limit	
			1Mbps	2Mbps	1Mbps	2Mbps
LE	CH 00	2402	6.15	6.12	7.56	7.56
	CH 19	2440	7.14	7.15	8.85	8.85
	CH 39	2480	7.07	7.04	8.86	8.86

General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 77.22% refer to part15C Bluetooth test report also considered in SAR testing.

12. RF Exposure Conditions

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	Yes	No

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge, The detail antenna location please refers to Appendix D.

13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.

GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.
3. Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 4Tx slot due to its highest frame-average power.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B5/B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 17 SAR test was covered by Band 12; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

13.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Right Cheek	0mm	251	848.8	28.37	28.70	1.079	0.03	0.351	0.379
	GSM850	GPRS (4 Tx slots)	Right Tilted	0mm	251	848.8	28.37	28.70	1.079	-0.03	0.168	0.181
01	GSM850	GPRS (4 Tx slots)	Left Cheek	0mm	251	848.8	28.37	28.70	1.079	-0.02	0.427	0.461
	GSM850	GPRS (4 Tx slots)	Left Tilted	0mm	251	848.8	28.37	28.70	1.079	0.04	0.162	0.175
02	GSM1900	GPRS (4 Tx slots)	Right Cheek	0mm	810	1909.8	24.15	24.20	1.012	0.13	0.508	0.514
	GSM1900	GPRS (4 Tx slots)	Right Tilted	0mm	810	1909.8	24.15	24.20	1.012	0.13	0.157	0.159
	GSM1900	GPRS (4 Tx slots)	Left Cheek	0mm	810	1909.8	24.15	24.20	1.012	0.03	0.306	0.310
	GSM1900	GPRS (4 Tx slots)	Left Tilted	0mm	810	1909.8	24.15	24.20	1.012	0.07	0.211	0.213

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4233	846.6	23.20	23.20	1.000	0.07	0.363	0.363
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	4233	846.6	23.20	23.20	1.000	0.05	0.212	0.212
03	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4233	846.6	23.20	23.20	1.000	-0.02	0.444	0.444
	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	4233	846.6	23.20	23.20	1.000	-0.03	0.207	0.207

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 5	10M	QPSK	1	0	Right Cheek	0mm	20525	836.5	23.03	23.50	1.114	0.07	0.344	0.383
	LTE Band 5	10M	QPSK	25	0	Right Cheek	0mm	20525	836.5	22.55	23.00	1.109	0.11	0.323	0.358
	LTE Band 5	10M	QPSK	1	0	Right Tilted	0mm	20525	836.5	23.03	23.50	1.114	-0.03	0.217	0.242
	LTE Band 5	10M	QPSK	25	0	Right Tilted	0mm	20525	836.5	22.55	23.00	1.109	0.01	0.195	0.216
04	LTE Band 5	10M	QPSK	1	0	Left Cheek	0mm	20525	836.5	23.03	23.50	1.114	0.01	0.420	0.468
	LTE Band 5	10M	QPSK	25	0	Left Cheek	0mm	20525	836.5	22.55	23.00	1.109	0.02	0.407	0.451
	LTE Band 5	10M	QPSK	1	0	Left Tilted	0mm	20525	836.5	23.03	23.50	1.114	0	0.238	0.265
	LTE Band 5	10M	QPSK	25	0	Left Tilted	0mm	20525	836.5	22.55	23.00	1.109	-0.02	0.214	0.237
	LTE Band 12	10M	QPSK	1	0	Right Cheek	0mm	23095	707.5	23.07	24.00	1.239	0.06	0.172	0.213
	LTE Band 12	10M	QPSK	25	0	Right Cheek	0mm	23095	707.5	21.90	23.00	1.288	0.09	0.145	0.187
	LTE Band 12	10M	QPSK	1	0	Right Tilted	0mm	23095	707.5	23.07	24.00	1.239	-0.17	0.108	0.134
	LTE Band 12	10M	QPSK	25	0	Right Tilted	0mm	23095	707.5	21.90	23.00	1.288	0.03	0.083	0.107
05	LTE Band 12	10M	QPSK	1	0	Left Cheek	0mm	23095	707.5	23.07	24.00	1.239	-0.01	0.216	0.268
	LTE Band 12	10M	QPSK	25	0	Left Cheek	0mm	23095	707.5	21.90	23.00	1.288	0.08	0.182	0.234
	LTE Band 12	10M	QPSK	1	0	Left Tilted	0mm	23095	707.5	23.07	24.00	1.239	0.15	0.068	0.084
	LTE Band 12	10M	QPSK	25	0	Left Tilted	0mm	23095	707.5	21.90	23.00	1.288	0	0.052	0.067

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	1	2412	15.20	15.30	1.023	100	1.000	0.11	0.187	0.191
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	1	2412	15.20	15.30	1.023	100	1.000	-0.14	0.127	0.130
06	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	1	2412	15.20	15.30	1.023	100	1.000	0.11	0.505	0.517
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	1	2412	15.20	15.30	1.023	100	1.000	0.15	0.218	0.223
	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	46	5230	16.77	16.80	1.006	95.63	1.046	-0.19	0.097	0.102
	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	46	5230	16.77	16.80	1.006	95.63	1.046	-0.09	0.045	0.047
07	WLAN5GHz	802.11n-HT40 MCS0	Left Cheek	0mm	46	5230	16.77	16.80	1.006	95.63	1.046	-0.1	0.591	0.622
	WLAN5GHz	802.11n-HT40 MCS0	Left Tilted	0mm	46	5230	16.77	16.80	1.006	95.63	1.046	0.02	0.166	0.175
	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	110	5550	17.09	17.10	1.001	95.63	1.046	0.14	0.067	0.070
	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	110	5550	17.09	17.10	1.001	95.63	1.046	0.19	0.047	0.049
08	WLAN5GHz	802.11n-HT40 MCS0	Left Cheek	0mm	110	5550	17.09	17.10	1.001	95.63	1.046	0.09	0.413	0.433
	WLAN5GHz	802.11n-HT40 MCS0	Left Tilted	0mm	110	5550	17.09	17.10	1.001	95.63	1.046	-0.16	0.143	0.150
	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	159	5795	16.54	16.80	1.061	95.63	1.046	-0.01	0.182	0.202
	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	159	5795	16.54	16.80	1.061	95.63	1.046	0	0.198	0.220
09	WLAN5GHz	802.11n-HT40 MCS0	Left Cheek	0mm	159	5795	16.54	16.80	1.061	95.63	1.046	0.12	0.639	0.709
	WLAN5GHz	802.11n-HT40 MCS0	Left Tilted	0mm	159	5795	16.54	16.80	1.061	95.63	1.046	-0.06	0.149	0.165

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	0mm	0	2402	11.33	12.21	1.225	0.03	0.056	0.069
	Bluetooth	1Mbps	Right Tilted	0mm	0	2402	11.33	12.21	1.225	-0.18	0.042	0.051
10	Bluetooth	1Mbps	Left Cheek	0mm	0	2402	11.33	12.21	1.225	0.07	0.168	0.206
	Bluetooth	1Mbps	Left Tilted	0mm	0	2402	11.33	12.21	1.225	0.03	0.072	0.088

13.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	10mm	251	848.8	28.37	28.70	1.079	0.03	0.346	0.373
11	GSM850	GPRS (4 Tx slots)	Back	10mm	251	848.8	28.37	28.70	1.079	-0.02	0.448	0.483
	GSM850	GPRS (4 Tx slots)	Left Side	10mm	251	848.8	28.37	28.70	1.079	-0.04	0.306	0.330
	GSM850	GPRS (4 Tx slots)	Right Side	10mm	251	848.8	28.37	28.70	1.079	-0.08	0.122	0.132
	GSM850	GPRS (4 Tx slots)	Bottom Side	10mm	251	848.8	28.37	28.70	1.079	0.05	0.071	0.077
	GSM1900	GPRS (4 Tx slots)	Front	10mm	810	1909.8	24.15	24.20	1.012	-0.04	0.352	0.356
	GSM1900	GPRS (4 Tx slots)	Back	10mm	810	1909.8	24.15	24.20	1.012	0.07	0.362	0.366
	GSM1900	GPRS (4 Tx slots)	Left Side	10mm	810	1909.8	24.15	24.20	1.012	-0.03	0.152	0.154
	GSM1900	GPRS (4 Tx slots)	Right Side	10mm	810	1909.8	24.15	24.20	1.012	-0.1	0.242	0.245
12	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	810	1909.8	24.15	24.20	1.012	-0.15	0.547	0.553

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	10mm	4233	846.6	23.20	23.20	1.000	-0.01	0.417	0.417
13	WCDMA V	RMC 12.2Kbps	Back	10mm	4233	846.6	23.20	23.20	1.000	-0.03	0.517	0.517
	WCDMA V	RMC 12.2Kbps	Left Side	10mm	4233	846.6	23.20	23.20	1.000	0	0.374	0.374
	WCDMA V	RMC 12.2Kbps	Right Side	10mm	4233	846.6	23.20	23.20	1.000	0.01	0.177	0.177
	WCDMA V	RMC 12.2Kbps	Bottom Side	10mm	4233	846.6	23.20	23.20	1.000	0.05	0.071	0.071

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 5	10M	QPSK	1	0	Front	10mm	20525	836.5	23.03	23.50	1.114	0.02	0.505	0.563
	LTE Band 5	10M	QPSK	25	0	Front	10mm	20525	836.5	22.55	23.00	1.109	-0.02	0.457	0.507
14	LTE Band 5	10M	QPSK	1	0	Back	10mm	20525	836.5	23.03	23.50	1.114	0.01	0.625	0.696
	LTE Band 5	10M	QPSK	25	0	Back	10mm	20525	836.5	22.55	23.00	1.109	-0.02	0.567	0.629
	LTE Band 5	10M	QPSK	1	0	Left Side	10mm	20525	836.5	23.03	23.50	1.114	-0.04	0.454	0.506
	LTE Band 5	10M	QPSK	25	0	Left Side	10mm	20525	836.5	22.55	23.00	1.109	-0.01	0.410	0.455
	LTE Band 5	10M	QPSK	1	0	Right Side	10mm	20525	836.5	23.03	23.50	1.114	-0.06	0.251	0.280
	LTE Band 5	10M	QPSK	25	0	Right Side	10mm	20525	836.5	22.55	23.00	1.109	-0.04	0.222	0.246
	LTE Band 5	10M	QPSK	1	0	Bottom Side	10mm	20525	836.5	23.03	23.50	1.114	0.07	0.061	0.068
	LTE Band 5	10M	QPSK	25	0	Bottom Side	10mm	20525	836.5	22.55	23.00	1.109	0.06	0.056	0.062
	LTE Band 12	10M	QPSK	1	0	Front	10mm	23095	707.5	23.07	24.00	1.239	0.01	0.201	0.249
	LTE Band 12	10M	QPSK	25	0	Front	10mm	23095	707.5	21.90	23.00	1.288	-0.01	0.171	0.220
15	LTE Band 12	10M	QPSK	1	0	Back	10mm	23095	707.5	23.07	24.00	1.239	0.02	0.290	0.359
	LTE Band 12	10M	QPSK	25	0	Back	10mm	23095	707.5	21.90	23.00	1.288	0.01	0.242	0.312
	LTE Band 12	10M	QPSK	1	0	Left Side	10mm	23095	707.5	23.07	24.00	1.239	-0.01	0.229	0.284
	LTE Band 12	10M	QPSK	25	0	Left Side	10mm	23095	707.5	21.90	23.00	1.288	-0.03	0.182	0.234
	LTE Band 12	10M	QPSK	1	0	Right Side	10mm	23095	707.5	23.07	24.00	1.239	-0.02	0.082	0.102
	LTE Band 12	10M	QPSK	25	0	Right Side	10mm	23095	707.5	21.90	23.00	1.288	0.01	0.075	0.097
	LTE Band 12	10M	QPSK	1	0	Bottom Side	10mm	23095	707.5	23.07	24.00	1.239	0.12	0.067	0.083
	LTE Band 12	10M	QPSK	25	0	Bottom Side	10mm	23095	707.5	21.90	23.00	1.288	0.13	0.054	0.070

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	1	2412	15.20	15.30	1.023	100	1.000	-0.13	0.092	0.094
16	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	1	2412	15.20	15.30	1.023	100	1.000	0.07	0.174	0.178
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	1	2412	15.20	15.30	1.023	100	1.000	0.09	0.166	0.170
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	1	2412	15.20	15.30	1.023	100	1.000	0.04	0.061	0.062

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	0	2402	11.33	12.21	1.225	0.01	0.020	0.024
17	Bluetooth	1Mbps	Back	10mm	0	2402	11.33	12.21	1.225	0.12	0.038	0.047
	Bluetooth	1Mbps	Right Side	10mm	0	2402	11.33	12.21	1.225	-0.03	0.035	0.043
	Bluetooth	1Mbps	Top Side	10mm	0	2402	11.33	12.21	1.225	-0.14	0.013	0.016

13.3 Body Worn Accessory SAR
<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	15mm	251	848.8	28.37	28.70	1.079	-0.03	0.286	0.309
18	GSM850	GPRS (4 Tx slots)	Back	15mm	251	848.8	28.37	28.70	1.079	0.17	0.374	0.404
19	GSM1900	GPRS (4 Tx slots)	Front	15mm	810	1909.8	24.15	24.20	1.012	-0.04	0.237	0.240
	GSM1900	GPRS (4 Tx slots)	Back	15mm	810	1909.8	24.15	24.20	1.012	0.01	0.217	0.220

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	15mm	4233	846.6	23.20	23.20	1.000	0.01	0.373	0.373
20	WCDMA V	RMC 12.2Kbps	Back	15mm	4233	846.6	23.20	23.20	1.000	0.02	0.429	0.429

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 5	10M	QPSK	1	0	Front	15mm	20525	836.5	23.03	23.50	1.114	0	0.483	0.538
	LTE Band 5	10M	QPSK	25	0	Front	15mm	20525	836.5	22.55	23.00	1.109	0	0.435	0.482
21	LTE Band 5	10M	QPSK	1	0	Back	15mm	20525	836.5	23.03	23.50	1.114	0	0.543	0.605
	LTE Band 5	10M	QPSK	25	0	Back	15mm	20525	836.5	22.55	23.00	1.109	-0.01	0.489	0.542
	LTE Band 12	10M	QPSK	1	0	Front	15mm	23095	707.5	23.07	24.00	1.239	-0.01	0.143	0.177
	LTE Band 12	10M	QPSK	25	0	Front	15mm	23095	707.5	21.90	23.00	1.288	-0.03	0.121	0.156
22	LTE Band 12	10M	QPSK	1	0	Back	15mm	23095	707.5	23.07	24.00	1.239	0	0.199	0.247
	LTE Band 12	10M	QPSK	25	0	Back	15mm	23095	707.5	21.90	23.00	1.288	0.01	0.165	0.213

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	1	2412	15.20	15.30	1.023	100	1.000	0.04	0.042	0.043
23	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	1	2412	15.20	15.30	1.023	100	1.000	-0.01	0.073	0.075
	WLAN5GHz	802.11n-HT40 MCS0	Front	15mm	46	5230	16.77	16.80	1.006	95.63	1.046	-0.1	0.065	0.068
24	WLAN5GHz	802.11n-HT40 MCS0	Back	15mm	46	5230	16.77	16.80	1.006	95.63	1.046	-0.09	0.368	0.387
	WLAN5GHz	802.11n-HT40 MCS0	Front	15mm	110	5550	17.09	17.10	1.001	95.63	1.046	-0.16	0.037	0.039
25	WLAN5GHz	802.11n-HT40 MCS0	Back	15mm	110	5550	17.09	17.10	1.001	95.63	1.046	0.02	0.235	0.246
	WLAN5GHz	802.11n-HT40 MCS0	Front	15mm	159	5795	16.54	16.80	1.061	95.63	1.046	0.11	0.058	0.064
26	WLAN5GHz	802.11n-HT40 MCS0	Back	15mm	159	5795	16.54	16.80	1.061	95.63	1.046	-0.11	0.385	0.427

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	15mm	0	2402	11.33	12.21	1.225	-0.18	0.008	0.010
27	Bluetooth	1Mbps	Back	15mm	0	2402	11.33	12.21	1.225	0.15	0.014	0.017

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset		
		Head	Body-worn	Hotspot
1.	GSM Voice + 2.4GHz WLAN	Yes	Yes	
2.	GPRS/EDGE + 2.4GHz WLAN	Yes	Yes	Yes
3.	WCDMA + 2.4GHz WLAN	Yes	Yes	Yes
4.	LTE + 2.4GHz WLAN	Yes	Yes	Yes
5.	GSM Voice + Bluetooth	Yes	Yes	
6.	GPRS/EDGE + Bluetooth	Yes	Yes	Yes
7.	WCDMA + Bluetooth	Yes	Yes	Yes
8.	LTE + Bluetooth	Yes	Yes	Yes
9.	GSM Voice + 5GHz WLAN	Yes	Yes	
10.	GPRS/EDGE + 5GHz WLAN	Yes	Yes	
11.	WCDMA + 5GHz WLAN	Yes	Yes	
12.	LTE + 5GHz WLAN	Yes	Yes	
13.	GSM Voice + 5GHz WLAN + Bluetooth	Yes	Yes	
14.	GPRS/EDGE + 5GHz WLAN + Bluetooth	Yes	Yes	
15.	WCDMA + 5GHz WLAN + Bluetooth	Yes	Yes	
16.	LTE + 5GHz WLAN + Bluetooth	Yes	Yes	
17.	5GHz WLAN + Bluetooth	Yes	Yes	

General Note:

1. This device WLAN 2.4GHz supports Hotspot operation and Bluetooth support tethering applications.
2. 2.4GHz WLAN and Bluetooth cannot transmit simultaneously.
3. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
4. The Scaled SAR summation is calculated based on the same configuration and test position.
5. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.



14.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)	3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth					
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)					
GSM	GSM850	Right Cheek	0.379	0.191	0.202	0.069	0.570	0.581	0.448	0.650	0.271
		Right Tilted	0.181	0.130	0.220	0.051	0.311	0.401	0.232	0.452	0.271
		Left Cheek	0.461	0.517	0.709	0.206	0.978	1.170	0.667	1.376	0.915
		Left Tilted	0.175	0.223	0.175	0.088	0.398	0.350	0.263	0.438	0.263
	GSM1900	Right Cheek	0.514	0.191	0.202	0.069	0.705	0.716	0.583	0.785	0.271
		Right Tilted	0.159	0.130	0.220	0.051	0.289	0.379	0.210	0.430	0.271
		Left Cheek	0.310	0.517	0.709	0.206	0.827	1.019	0.516	1.225	0.915
		Left Tilted	0.213	0.223	0.175	0.088	0.436	0.388	0.301	0.476	0.263
WCDMA	WCDMA V	Right Cheek	0.363	0.191	0.202	0.069	0.554	0.565	0.432	0.634	0.271
		Right Tilted	0.212	0.130	0.220	0.051	0.342	0.432	0.263	0.483	0.271
		Left Cheek	0.444	0.517	0.709	0.206	0.961	1.153	0.650	1.359	0.915
		Left Tilted	0.207	0.223	0.175	0.088	0.430	0.382	0.295	0.470	0.263
LTE	LTE Band 5	Right Cheek	0.383	0.191	0.202	0.069	0.574	0.585	0.452	0.654	0.271
		Right Tilted	0.242	0.130	0.220	0.051	0.372	0.462	0.293	0.513	0.271
		Left Cheek	0.468	0.517	0.709	0.206	0.985	1.177	0.674	1.383	0.915
		Left Tilted	0.265	0.223	0.175	0.088	0.488	0.440	0.353	0.528	0.263
	LTE Band 12	Right Cheek	0.213	0.191	0.202	0.069	0.404	0.415	0.282	0.484	0.271
		Right Tilted	0.134	0.130	0.220	0.051	0.264	0.354	0.185	0.405	0.271
		Left Cheek	0.268	0.517	0.709	0.206	0.785	0.977	0.474	1.183	0.915
		Left Tilted	0.084	0.223	0.175	0.088	0.307	0.259	0.172	0.347	0.263

14.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	4	1+2 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)		
GSM	GSM850	Front	0.373	0.094	0.024	0.467	0.397
		Back	0.483	0.178	0.047	0.661	0.530
		Left side	0.330			0.330	0.330
		Right side	0.132	0.170	0.043	0.302	0.175
		Top side		0.062	0.016	0.062	0.016
		Bottom side	0.077			0.077	0.077
	GSM1900	Front	0.356	0.094	0.024	0.450	0.380
		Back	0.366	0.178	0.047	0.544	0.413
		Left side	0.154			0.154	0.154
		Right side	0.245	0.170	0.043	0.415	0.288
		Top side		0.062	0.016	0.062	0.016
		Bottom side	0.553			0.553	0.553
WCDMA	WCDMA V	Front	0.417	0.094	0.024	0.511	0.441
		Back	0.517	0.178	0.047	0.695	0.564
		Left side	0.374			0.374	0.374
		Right side	0.177	0.170	0.043	0.347	0.220
		Top side		0.062	0.016	0.062	0.016
		Bottom side	0.071			0.071	0.071
LTE	LTE Band 5	Front	0.563	0.094	0.024	0.657	0.587
		Back	0.696	0.178	0.047	0.874	0.743
		Left side	0.506			0.506	0.506
		Right side	0.280	0.170	0.043	0.450	0.323
		Top side		0.062	0.016	0.062	0.016
		Bottom side	0.068			0.068	0.068
	LTE Band 12	Front	0.249	0.094	0.024	0.343	0.273
		Back	0.359	0.178	0.047	0.537	0.406
		Left side	0.284			0.284	0.284
		Right side	0.102	0.170	0.043	0.272	0.145
		Top side		0.062	0.016	0.062	0.016
		Bottom side	0.083			0.083	0.083

14.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)	3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth					
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)					
GSM	GSM850	Front	0.309	0.043	0.068	0.010	0.352	0.377	0.319	0.387	0.078
		Back	0.404	0.075	0.427	0.017	0.479	0.831	0.421	0.848	0.444
	GSM1900	Front	0.240	0.043	0.068	0.010	0.283	0.308	0.250	0.318	0.078
		Back	0.220	0.075	0.427	0.017	0.295	0.647	0.237	0.664	0.444
WCDMA	WCDMA V	Front	0.373	0.043	0.068	0.010	0.416	0.441	0.383	0.451	0.078
		Back	0.429	0.075	0.427	0.017	0.504	0.856	0.446	0.873	0.444
LTE	LTE Band 5	Front	0.538	0.043	0.068	0.010	0.581	0.606	0.548	0.616	0.078
		Back	0.605	0.075	0.427	0.017	0.680	1.032	0.622	1.049	0.444
	LTE Band 12	Front	0.177	0.043	0.068	0.010	0.220	0.245	0.187	0.255	0.078
		Back	0.247	0.075	0.427	0.017	0.322	0.674	0.264	0.691	0.444

Test Engineer : Neil Hsiang Randy Lin Andy Jiang Willy Yu Ted Hsieh Jay Jian Thomas Wang White
Huang Wilson Lin and Carter Chuang

15. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [11] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [12] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [13] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.