APPENDIX REPORT

Project No.	SHT2012093801EW	Radio Specification	Bluetooth EDR
Test sample No.	b mobile	Model No.	BS30
Start test date	2020-12-31	Finish date	2020-12-31
Temperature	23.4°C	Humidity	34.6%
Test Engineer	Qizhi Zhang	Auditor	Xiaodong Zhao

Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	20 dB Bandwidth	PASS
C	99% Occupied Bandwidth	PASS
D	Carrier Frequencies Separation	PASS
E	Hopping Channel Number	PASS
F	Dwell Time	PASS
G	Duty Cycle Correction Factor (DCCF)	PASS
H	Band edge and Spurious Emissions(coducted)	PASS

Appendix A：Peak Output Power

Modulation type	Channel	Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
GFSK	00	1.40	1.36	≤ 30.00	Pass
	39	2.43	2.41		
	78	3.45	3.42		
π/4DQPSK	00	1.36	1.33	≤ 21.00	Pass
	39	2.41	2.39		
	78	3.44	3.41		
8DPSK	00	1.38	1.34	≤ 21.00	Pass
	39	2.42	2.39		
	78	3.48	3.45		

Modulation Type:	GFSK
CH00	
CH39	
CH78	

Modulation Type:	π/4DQPSK
CH00	
CH39	
CH78	

Modulation Type:	8DPSK
CH00	
CH39	
CH78	

Appendix B : 20 dB Bandwidth

Modulation type	Channel	20 dB Bandwidth (kHz)	Limit (kHz)	Result
GFSK	00	927.50	-	Pass
	39	925.00		
	78	925.00		
π/4DQPSK	00	1235.00	-	Pass
	39	1227.50		
	78	1207.50		
8DPSK	00	1242.50	-	Pass
	39	1200.00		
	78	1198.50		

Modulation Type:	GFSK
CH00	
CH39	
CH78	

Modulation Type:	π/4DQPSK
CH00	
CH39	
CH78	

Modulation Type:	8DPSK
CH00	
CH39	
CH78	

Appendix C：99% Occupied Bandwidth

Modulation type	Channel	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.88	-	Pass
	39	0.87		
	78	0.87		
π/4DQPSK	00	1.14	-	Pass
	39	1.13		
	78	1.12		
8DPSK	00	1.15	-	Pass
	39	1.13		
	78	1.13		

Modulation Type:	GFSK
CH00	
CH39	
CH78	

Modulation Type:	π/4DQPSK
CH00	
CH39	
CH78	

Modulation Type:	8DPSK
CH00	
CH39	
CH78	

Appendix D：Carrier Frequencies Separation

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (kHz) *	Result
GFSK	39	1.00	≥927.50	Pass
π/4DQPSK	39	1.00	≥823.33	Pass
8DPSK	39	1.00	≥828.33	Pass

Note:

*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the appendix B.
π/4DQPSK limit = 2/3 * The maximum 20 dB Bandwidth for π/4DQPSK modulation on the appendix B.
8DPSK limit = 2/3 * The maximum 20 dB Bandwidth for 8DPSK modulation on the appendix B

GFSK	
π/4DQPSK	
8DPSK	

Appendix E：Hopping Channel Number

Modulation type	Channel number	Limit	Result
GFSK	79	≥15.00	Pass
π/4DQPSK	79		
8DPSK	79		

GFSK	
π/4DQPSK	
8DPSK	

Appendix F：Dwell Time

Modulation type	Packet	Burst Width [ms]	Total Hops[hop*ch]	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.41	319	0.13	≤ 0.40	Pass
	DH3	1.66	109	0.18		
	DH5	2.91	72	0.21		
π/4DQPSK	2DH1	0.41	320	0.13	≤ 0.40	Pass
	2DH3	1.66	110	0.18		
	2DH5	2.91	42	0.12		
8DPSK	3DH1	0.41	317	0.13	≤ 0.40	Pass
	3DH3	1.66	102	0.17		
	3DH5	2.91	74	0.22		

Modulation Type:	GFSK
DH1 Burst width	
DH1 Burst number	
DH3 Burst width	

DH3 Burst number	
DH5 Burst width	
DH5 Burst number	

Modulation Type:	π/4DQPSK
2DH1 Burst width	
2DH1 Burst number	
2DH3 Burst width	

2DH3 Burst number	
2DH5 Burst width	
2DH5 Burst number	

Modulation Type:	8DPSK
3DH1 Burst width	
3DH1 Burst number	
3DH3 Burst width	

3DH3 Burst number	
3DH5 Burst width	
3DH5 Burst number	

Appendix G：Duty Cycle Correction Factor (DCCF)

DCCF Calculate Formula					
DCCF=20 * Log(duty cycle) = 20 * Log($T_{on\ time}$ / T_{period})					
Modulation type	Test Frequency（MHz）	$T_{on\ time}$ for single burst [ms]	T_{period} [ms]	Burst Quantity	DCCF [dB]
GFSK	2441	2.89	100	1	-30.78
π/4 DQPSK	2441	2.89	100	2	-24.76
8DPSK	2441	2.89	100	1	-30.78

GFSK



$T_{on\ time}$ for single burst



Burst Quantity

π /4 DQPSK



$T_{on\ time}$ for single burst



Burst Quantity

8DPSK



$T_{on\ time}$ for single burst



Burst Quantity

Appendix H：Band edge and Spurious Emissions (conducted)

Test Item:	Band edge	Modulation type:	GFSK
CH00 No hopping mode	
CH00 Hopping mode	
CH78 No hopping mode	

CH78 Hopping mode	

Test Item:	Band edge	Modulation type:	π/4DQPSK
CH00 No hopping mode			
CH00 Hopping mode			
CH78 No hopping mode			

CH78 Hopping mode	

Test Item:	Band edge	Modulation type:	8DPSK
CH00 No hopping mode			
CH00 Hopping mode			
CH78 No hopping mode			

CH78 Hoppig mode	

Test Item:	Spurious Emission	Modulation type:	GFSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			

CH39 Reference level	
CH39 30MHz~1000MHz	
CH39 1GHz~26GHz	

CH78 Reference level	
CH78 30MHz~1000MHz	
CH78 1GHz~26GHz	

Test Item:	Spurious Emission	Modulation type:	π/4DQPSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			

CH39 Reference level	
CH39 30MHz~1000MHz	
CH39 1GHz~26GHz	

CH78 Reference level	
CH78 30MHz~1000MHz	
CH78 1GHz~26GHz	

Test Item:	Spurious Emission	Modulation type:	8DPSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			

CH39 Reference level	
CH39 30MHz~1000MHz	
CH39 1GHz~26GHz	

CH78 Reference level	
CH78 30MHz~1000MHz	
CH78 1GHz~26GHz	

--------End of Report--------