

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Hong Kong Etech Groups Ltd.

smart pulg

Model Number: ETS-C-006

Additional Model: EIX3-1003-PP2, EIX3-1003, EIX3-1003-ME2,

EIX3-1003-WHT, XWS7-2001-WHT, XWS7-2001

FCC ID: 2A3ZO-ETS-C-006

Applicant :	Hong Kong Etech Groups Ltd.
Address:	16/F, Block C, 2nd Phase of Central Avenue, Haihong Industrial
	Area, Xixiang, Baoan, Shenzhen, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808



Report Number:	ESTE-R2206049
Date of Test:	Jun. 25~Jul. 08, 2022
Date of Report:	Jul. 08, 2022

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT)	5
1.2. Antenna Information	5
1.3. Information of RF Cable	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities	7
2.3. Measurement uncertainty	8
2.4. Assistant equipment used for test.....	8
2.5. Block Diagram	8
2.6. Test Mode.....	9
2.7. Power Setting of Test Software.....	10
2.8. Duty Cycle.....	10
2.9. Test Result.....	10
2.10. Channel List	11
2.11. Test Equipment List	12
3. 6DB BANDWIDTH.....	14
3.1. Limit	14
3.2. Test Setup	14
3.3. Spectrum Analyzer Setting.....	14
3.4. Test Procedure	14
3.5. Test Result.....	14
4. MAXIMUM PEAK OUTPUT POWER.....	15
4.1. Limit	15
4.2. Test Setup	15
4.3. Spectrum Analyzer Setting.....	15
4.4. Test Procedure	15
4.5. Test Result.....	15
5. POWER SPECTRAL DENSITY	16
5.1. Limit	16
5.2. Test Setup	16
5.3. Spectrum Analyzer Setting.....	16
5.4. Test Procedure	16
5.5. Test Result.....	16
6. CONDUCTED BAND EDGE	17
6.1. Limit	17
6.2. Test Setup	17
6.3. Spectrum Analyzer Setting.....	17
6.4. Test Procedure	17
6.5. Test Result.....	17
7. CONDUCTED SPURIOUS EMISSIONS.....	18
7.1. Limit	18
7.2. Test Setup.....	18

7.3.	Spectrum Analyzer Setting.....	18
7.4.	Test Procedure.....	18
7.5.	Test Result.....	18
8.	RADIATED SPURIOUS EMISSIONS AND BAND EDGE	19
8.1.	Limit.....	19
8.2.	Test setup.....	20
8.3.	Spectrum Analyzer Setting.....	21
8.4.	Test Procedure.....	22
8.5.	Test Result.....	23
9.	AC POWER LINE CONDUCTED EMISSIONS	35
9.1.	Limit.....	35
9.2.	Test Setup.....	35
9.3.	Spectrum Analyzer Setting.....	35
9.4.	Test Procedure.....	35
9.5.	Test Result.....	36
10.	APPENDIX	40
11.	ANTENNA REQUIREMENTS.....	72
11.1.	Limit.....	72
11.2.	Test Result.....	72
12.	TEST SETUP PHOTO	73
13.	EUT PHOTO.....	75

EST Technology Co., Ltd.

Applicant:	Hong Kong Etech Groups Ltd.		
Address:	16/F, Block C, 2nd Phase of Central Avenue, Haihong Industrial Area, Xixiang, Baoan, Shenzhen, China		
Manufacturer:	China Etech Groups Ltd		
Address:	16/F, Block C, 2nd Phase of Central Avenue, Haihong Industrial Area, Xixiang Road, Baoan District, Shenzhen, 518102 China		
Factory 1:	DONGGUAN QIAOSIKE DIGITAL TECHNOLOGY CO., LTD		
Address:	Building 6, Room 501, Hong Jin Road, No. 2, Li Zhou Cun, Hongmei Town, DONGGUAN Guangdong Province 523160		
Factory 2:	PHUC MINH HUY MANUFACTURING AND TRADING LIMITED COMPANY.		
Address:	An Long Hamlet, Yen My Village, Lang Giang District, Bac Giang Province 234000 Viet Nam.		
Factory 3:	SI YUAN TECH COMPANY LIMITED		
Address:	Lot G3, N5 street, Chau Son Industrial Park, Chau Son Ward, Phu Ly city, Ha Nam Province		
E.U.T:	smart pulg		
Model Number:	ETS-C-006		
Additional Model:	EIX3-1003-PP2, EIX3-1003, EIX3-1003-ME2, EIX3-1003-WHT, XWS7-2001-WHT, XWS7-2001 Note: They are identical except model name.		
Power Supply:	AC 100-240V, 50-60Hz		
Trade Name:	ETECH	Serial No.:	-----
Date of Receipt:	May. 13, 2022	Date of Test:	Jun. 25~Jul. 08, 2022
Test Specification:	FCC Part 15 Subpart C (15.247) ANSI C63.10:2013 FCC KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
Prepared by:	Reviewed by:	Date: Jul. 08, 2022  Approved by:	
 Ring Yang / Assistant	 Seven Wang / Engineer	 Iceman Hu / Manager	
Other Aspects: None.			
<i>Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested</i>			
<i>This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.</i>			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	smart pulg
Model Number	:	EST-C-06
Software Version	:	N/A
Hardware Version	:	P-WS-VER03-1
Operation frequency	:	2412MHz~2462MHz 2422MHz~2452MHz
Number of channel	:	IEEE 802.11b: 11 Channels IEEE 802.11g: 11 Channels IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Max Output Power (PEAK)	:	IEEE 802.11b: 14.58dBm IEEE 802.11g: 16.91dBm IEEE 802.11n HT20:16.82dBm IEEE 802.11n HT40:16.04dBm
Modulation Type	:	DSSS(CCK,QPSK, BPSK) OFDM (BPSK/QPSK/16QAM/64QAM)
Sample Type	:	Prototype production

Note:For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

1.2. Antenna Information

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Internal	-	-0.68

Note: This information is provided by the applicant

1.3. Information of RF Cable

Cable Loss(dB)	Provided by
1.0	Hong Kong Etech Groups Ltd.
Note: 1.The customer declared the loss value of the RF Cable, and the test results of this report only apply to the sample as received. 2. This information is provided by the applicant.	

2. SUMMARY OF TEST

2.1. Summary of test result

Report Section	Description of Test Item	FCC Standard Section	Results
3	6dB Bandwidth	15.247(a)(2)	PASS
4	Maximum Peak Output Power	15.247(b)(3)	PASS
5	Power Spectral Density	15.247(e)	PASS
6	Conducted Band Edge	15.247(d)	PASS
7	Conducted Spurious Emissions	15.247(d)	PASS
8	Radiated Spurious Emissions and Band Edge	15.205 15.209 15.247(d)	PASS
9	AC Power Line Conducted Emissions	15.207	PASS
10	Antenna Requirement	15.203	PASS

Note: "N/A" denotes test is not applicable in this test report

2.2. Test Facilities

EMC Lab : Certificated by CNAS, CHINA
Registration No.: L5288
This Certificate is valid until: November 12, 2023

Certificated by FCC, USA
Designation Number: CN1215
This Certificate is valid until: January 31, 2024

Certificated by A2LA, USA
Registration No.: 4366.01
This Certificate is valid until: January 31, 2024

Certificated by Industry Canada
CAB identifier No.: CN0035
This Certificate is valid until: January 31, 2024

Certificated by VCCI, Japan
Registration No.: C-14103; T-20073; R-13663;
R-20103; G-20097
Date of registration: Apr. 20, 2020
This Certificate is valid until: Apr. 19, 2023

Certificated by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Certificated by Intertek
Registration No.: 2011-RTL-L2-64
Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	$\pm 3.48\text{dB}$
Uncertainty for spurious emissions test (Below 30MHz)	$\pm 1.62\text{ dB}$
Uncertainty for spurious emissions test (30MHz-1GHz)	$\pm 4.60\text{ dB(Polarize: H)}$
	$\pm 4.68\text{ dB(Polarize: V)}$
Uncertainty for spurious emissions test (1GHz to 25GHz)	$\pm 4.96\text{dB}$
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	1.08dB
Uncertainty for Power density test	0.26dB


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2.4. Assistant equipment used for test

Code	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
A	Laptop computer	DELL	Inspiron 5493	EST-E316	5376699759
1	cable	/	/	EST-E308	/

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into 2.4G WIFI test mode by software before test.



(EUT: smart pulg)

2.6. Test Mode

The test mode was selected for the final test as listed below.

Test Item	Mode	Data Rate	Test Channel
6dB Bandwidth	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High
Maximum Peak Output Power	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High
Power Spectral Density	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High
Conducted Band Edge	IEEE 802.11b	1Mbps	Low/ High
	IEEE 802.11g	6Mbps	Low/ High
	IEEE 802.11n HT20	MCS0	Low/ High
	IEEE 802.11n HT40	MCS0	Low/ High
Conducted Spurious Emissions	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High
Radiated Spurious Emissions(Below 1GHz)	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High
Radiated Spurious Emissions(Above 1GHz)	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High
Radiated Band Edge	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High
AC Power Line Conducted Emissions	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High

Note: In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7. Power Setting of Test Software

Software Name	Beken Wi-Fi Test Tool V1.6.0		
Frequency(MHz)	2412	2437	2462
IEEE 802.11b Setting	Auto	Auto	Auto
IEEE 802.11g Setting	Auto	Auto	Auto
IEEE 802.11n HT20 Setting	Auto	Auto	Auto
Frequency(MHz)	2422	2437	2452
IEEE 802.11n HT40 Setting	Auto	Auto	Auto

Note: This information is provided by the applicant

2.8. Duty Cycle

Note:

1. If duty cycle $< 98\%$, the conducted average output power and average power spectral density should be add duty factor.
2. If duty cycle $\geq 98\%$, the EUT is consider to be transmitting continuously, the conducted average output power and average power spectral density no need to add duty factor (consider to be zero).
3. The conducted peak output power and peak power spectral density no need to consider duty factor.
4. The on-time time is transmission duration(T).

2.9. Test Result

Refer to section 10: Appendix A

2.10.Channel List

IEEE 802.11b/802.11g/802.11n HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
2	2417	7	2442		
3	2422	8	2447		
4	2427	9	2452		
5	2432	10	2457		
IEEE 802.11n HT40					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452
4	2427	7	2442		
5	2432	8	2447		

2.11. Test Equipment List

For conducted emission test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	EST-E001	LISAI	June 13,22	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E002	LISAI	June 13,22	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	LISAI	June 13,22	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

For radiated emission test(9kHz-30MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 13,22	1 Year
Active Loop Antenna	SCHWARZB ECK	FMZB 1519B	EST-E054	LISAI	June 13,22	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
9kHz-30MHz Cable	N/A	EST-001	N/A	N/A	N/A	N/A

For radiated emissions test (30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 13,22	1 Year
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 13,22	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emission test(Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA9120D	EST-E031	LISAI	June 13,22	1 Year
Horn Antenna	Com-Power	AHA-840	EST-E133	LISAI	June 13,22	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	EST-E032	LISAI	June 13,22	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	EST-E069	LISAI	June 13,22	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A

For connect EUT antenna terminal test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
TS 1120	Tonscend	/	/	/	/	/
Test Software	Tonscend	TS1120-3	3.2.11	/	/	/
RF Control Unit	Tonscend	JS0806-2	EST-E134	LISAI	June 13,22	1 Year
Signal and Spectrum Analyzer	Rohde &Schwarz	FSV 40	EST-E136	LISAI	June 13,22	1 Year

3. 6dB BANDWIDTH

3.1. Limit

Systems using digital modulation techniques operate in the 2400-2483.5 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2. Test Setup



3.3. Spectrum Analyzer Setting

6dB Bandwidth

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth

Spectrum Parameters	Setting
RBW	300KHz(20MHz Bandwidth mode)/1MHz(40MHz Bandwidth mode)
VBW	1MHz(20MHz Bandwidth mode)/3MHz(40MHz Bandwidth mode)
Span	40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

3.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

3.5. Test Result


Refer to section 10: Appendix B

4. MAXIMUM PEAK OUTPUT POWER

4.1. Limit

For systems using digital modulation in 2400-2483.5MHz, the maximum peak output power is 1 Watt(30dBm).

4.2. Test Setup



4.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz
VBW	3MHz
Span	40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

4.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 4.3.
- Set the EUT transmit continuously with maximum output power.
- Use the channel power function to measure maximum peak output power, allow trace to stabilize, save test pictures.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

4.5. Test Result


Refer to section 10: Appendix C

5. POWER SPECTRAL DENSITY

5.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2. Test Setup



5.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	3KHz
VBW	10KHz
Span	30MHz(20MHz Bandwidth mode)/60MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

5.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 5.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

5.5. Test Result


Refer to section 10: Appendix D

6. CONDUCTED BAND EDGE

6.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2. Test Setup



6.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	100MHz(20MHz Bandwidth mode)/200MHz(40MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

6.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 6.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

6.5. Test Result


Refer to section 10: Appendix E & F

7. CONDUCTED SPURIOUS EMISSIONS

7.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.2. Test Setup



7.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	26.5GHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

7.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 7.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

7.5. Test Result

Refer to section 10: Appendix E & G

8. RADIATED SPURIOUS EMISSIONS AND BAND EDGE

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


15.209 Limit

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:

- (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$.
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. Test setup



8.3. Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting
RBW	1MHz
VBW	PEAK Measurement
	3MHz
	AVG Measurement
	Duty cycle $\geq 98\%$, VBW=10Hz
	Duty cycle $< 98\%$, VBW $\geq 1/T$
Start frequency	1GHz
Stop frequency	25GHz
Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

Note :T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.8 for the on-time time.

8.4. Test Procedure

- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 8.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.

Note:


1. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
2. The frequency 2412MHz/2422MHz/2437MHz/2452MHz/2462MHz are fundamental frequency, which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.
3. IEEE 802.11b, IEEE 802.11g, IEEE 802.11nHT20, IEEE 802.11nHT40 all have been tested, only worst case 802.11n HT20 is recorded.

8.5. Test Result

Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 1
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:22.1°C;Humi:51%;Press:101.52kPa
 Engineer : MRS
 EUT : smart plug
 Power : AC 120V/60Hz
 M/N : ETS-C-006
 Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.91	16.50	0.60	12.04	29.14	40.00	10.86	QP
2	45.52	10.60	0.63	18.92	30.15	40.00	9.85	QP
3	55.22	6.50	0.69	23.39	30.58	40.00	9.42	QP
4	74.62	6.90	0.91	18.22	26.03	40.00	13.97	QP
5	153.19	11.68	1.18	9.39	22.25	43.50	21.25	QP
6	257.95	13.82	1.56	8.37	23.75	46.00	22.25	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 2

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qi Ao\\QI AO.EM6 (4)

Date: 2022-06-25



Site no. : 1# 966 Chamber Data no. : 2
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 B(3M)
Env. / Ins. : Temp:22.1°C;Humi:51%;Press:101.52kPa
Engineer : MRS
EUT : smart plug
Power : AC 120V/60Hz
M/N : ETS-C-006
Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	158.04	11.54	1.19	2.24	14.97	43.50	28.53	QP
2	232.73	10.92	1.44	9.06	21.42	46.00	24.58	QP
3	275.41	12.60	1.62	8.87	23.09	46.00	22.91	QP
4	341.37	14.97	1.74	2.90	19.61	46.00	26.39	QP
5	384.05	16.14	1.87	3.16	21.17	46.00	24.83	QP
6	640.13	21.50	2.44	0.48	24.42	46.00	21.58	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test, only the worst case was reported.

Radiated Emissions Above 1G


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 1

File: \\EMC-966-1\test data\2022\RF\Q\Qi Ao\EST-C-006.EM6 (20)

Date: 2022-06-25




Site no. : 1# 966 Chamber Data no. : 1
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.8'; Humi:51%; Press:101.52kPa
 Engineer : JBR
 EUT : smart plug
 Power : AC 120V/60Hz
 M/N : EST-C-006
 Test Mode : IEEE 802.11n HT20 TX 2412MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2412.00	27.28	1.46	89.34	83.44	74.00	-9.44	Peak
2	4824.00	31.18	3.26	44.34	44.11	74.00	29.89	Peak
3	7236.00	36.28	5.20	38.60	45.26	74.00	28.74	Peak
4	9670.00	38.24	5.63	35.71	45.31	74.00	28.69	Peak
5	14566.00	40.99	6.89	33.36	46.77	74.00	27.23	Peak
6	17456.00	44.56	7.87	29.89	47.97	74.00	26.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 2
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
Engineer : JBR
EUT : smart plug
Power : AC 120V/60Hz
M/N : EST-C-006
Test Mode : IEEE 802.11n HT20 TX 2412MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2412.00	27.28	1.46	87.50	81.60	74.00	-7.60	Peak
2	4824.00	31.18	3.26	39.01	38.78	74.00	35.22	Peak
3	7236.00	36.28	5.20	37.39	44.05	74.00	29.95	Peak
4	13580.00	40.38	6.36	34.14	46.54	74.00	27.46	Peak
5	15484.00	40.37	6.44	34.58	46.98	74.00	27.02	Peak
6	17575.00	45.51	7.96	29.13	48.26	74.00	25.74	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 3

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qi Ao\\EST-C-006.EM6 (20)

Date: 2022-06-25




Site no. : 1# 966 Chamber Data no. : 3
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
 Engineer : JBR
 EUT : smart plug
 Power : AC 120V/60Hz
 M/N : EST-C-006
 Test Mode : IEEE 802.11n HT20 TX 2437MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2437.00	27.33	1.47	87.91	82.09	74.00	-8.09	Peak
2	4874.00	31.37	3.31	35.29	35.29	74.00	38.71	Peak
3	7311.00	36.42	5.22	32.67	39.48	74.00	34.52	Peak
4	10826.00	39.73	6.08	34.23	45.59	74.00	28.41	Peak
5	13920.00	40.96	6.50	33.50	46.65	74.00	27.35	Peak
6	17235.00	42.80	7.65	30.44	46.51	74.00	27.49	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 4
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
Engineer : JBR
EUT : smart plug
Power : AC 120V/60Hz
M/N : EST-C-006
Test Mode : IEEE 802.11n HT20 TX 2437MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2437.00	27.33	1.47	91.33	85.51	74.00	-11.51	Peak
2	4874.00	31.37	3.31	42.27	42.27	74.00	31.73	Peak
3	7311.00	36.42	5.22	36.22	43.03	74.00	30.97	Peak
4	14175.00	41.07	6.66	33.74	47.12	74.00	26.88	Peak
5	16266.00	40.10	7.02	34.96	47.83	74.00	26.17	Peak
6	17915.00	48.22	8.18	27.28	49.37	74.00	24.63	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 5

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qi Ao\\EST-C-006.EM6 (20)

Date: 2022-06-25



Site no. : 1# 966 Chamber Data no. : 5
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
 Engineer : JBR
 EUT : smart plug
 Power : AC 120V/60Hz
 M/N : EST-C-006
 Test Mode : IEEE 802.11n HT20 TX 2462MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.00	27.35	1.48	93.66	87.87	74.00	-13.87	Peak
2	4924.00	31.55	3.35	45.45	45.66	74.00	28.34	Peak
3	7386.00	36.59	5.24	38.83	45.82	74.00	28.18	Peak
4	12934.00	39.43	6.26	35.85	47.11	74.00	26.89	Peak
5	14600.00	40.98	6.88	34.53	47.91	74.00	26.09	Peak
6	17337.00	43.61	7.75	31.32	48.31	74.00	25.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 6

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qi Ao\\EST-C-006.EM6 (20)

Date: 2022-06-25



Site no. : 1# 966 Chamber Data no. : 6
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
 Engineer : JBR
 EUT : smart plug
 Power : AC 120V/60Hz
 M/N : EST-C-006
 Test Mode : IEEE 802.11n HT20 TX 2462MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2462.00	27.35	1.48	90.46	84.67	74.00	-10.67	Peak
2	4924.00	31.55	3.35	35.89	36.10	74.00	37.90	Peak
3	7386.00	36.59	5.24	34.69	41.68	74.00	32.32	Peak
4	14906.00	40.92	6.83	33.05	46.23	74.00	27.77	Peak
5	17286.00	43.21	7.70	31.22	47.76	74.00	26.24	Peak
6	17575.00	45.51	7.96	28.94	48.07	74.00	25.93	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note: The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Radiated Band Edge

EST Technology


Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878



Site no. : 1# 966 Chamber Data no. : 7
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
Engineer : JBR
EUT : smart plug
Power : AC 120V/60Hz
M/N : EST-C-006
Test Mode : IEEE 802.11n HT20 TX 2412MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.26	1.45	51.60	45.67	74.00	28.33	Peak
2	2407.90	27.28	1.46	86.21	80.31	74.00	-6.31	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.




Site no. : 1# 966 Chamber Data no. : 8
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
Engineer : JBR
EUT : smart plug
Power : AC 120V/60Hz
M/N : EST-C-006
Test Mode : IEEE 802.11n HT20 TX 2412MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.26	1.45	56.40	50.47	74.00	23.53	Peak
2	2407.64	27.28	1.46	89.28	83.38	74.00	-9.38	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 9
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
Engineer : JBR
EUT : smart plug
Power : AC 120V/60Hz
M/N : EST-C-006
Test Mode : IEEE 802.11n HT20 TX 2462MHz

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2457.80	27.35	1.48	90.03	84.24	74.00	-10.24	Peak
2	2483.50	27.38	1.48	47.35	41.60	54.00	12.40	Average
3	2483.50	27.38	1.48	58.05	52.30	74.00	21.70	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 10

File: \\EMC-966-1\\test data\\2022\\RF\\Q\\Qi Ao\\EST-C-006.EM6 (20)

Date: 2022-06-25



Site no. : 1# 966 Chamber Data no. : 10
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:20.8';Humi:51%;Press:101.52kPa
 Engineer : JBR
 EUT : smart plug
 Power : AC 120V/60Hz
 M/N : EST-C-006
 Test Mode : IEEE 802.11n HT20 TX 2462MHz

Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1 2457.50	27.35	1.48	89.93	84.14	74.00	-10.14	Peak
2 2483.50	27.38	1.48	56.33	50.58	74.00	23.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note: All channels had been pre-test, only of the worst case channels were reported.

9. AC POWER LINE CONDUCTED EMISSIONS


9.1. Limit

Frequency			Maximum RF Line Voltage	
			Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz	~	500kHz	66 ~ 56*	56 ~ 46*
500kHz	~	5MHz	56	46
5MHz	~	30MHz	60	50

Note:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

9.2. Test Setup



9.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold


9.4. Test Procedure

- a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
- b. The EUT Power connected to the power mains through a line impedance stabilization network.
- c. Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- d. Set the EUT transmit continuously with maximum output power.
- e. Spectrum analyzer setting parameters in accordance with section 9.3.
- f. The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.
- g. Record the results in the test report.

9.5. Test Result


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878




	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1703	9.78	9.69	23.00	42.47	54.94	12.47	Average
2	0.1703	9.78	9.69	41.50	60.97	64.94	3.97	QP
3	0.1997	9.72	9.77	19.14	38.63	53.62	14.99	Average
4	0.1997	9.72	9.77	40.20	59.69	63.62	3.93	QP
5	0.2353	9.84	9.92	18.81	38.57	52.26	13.69	Average
6	0.2353	9.84	9.92	40.66	60.42	62.26	1.84	QP
7	0.3303	9.76	9.92	19.05	38.73	49.44	10.71	Average
8	0.3303	9.76	9.92	37.50	57.18	59.44	2.26	QP
9	0.4444	9.75	9.92	16.92	36.59	46.98	10.39	Average
10	0.4444	9.75	9.92	36.49	56.16	56.98	0.82	QP
11	0.5210	9.76	9.92	18.53	38.21	46.00	7.79	Average
12	0.5210	9.76	9.92	33.53	53.21	56.00	2.79	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.



	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1650	9.82	9.69	19.59	39.10	55.21	16.11	Average
2	0.1650	9.82	9.69	42.11	61.62	65.21	3.59	QP
3	0.1997	9.84	9.77	20.08	39.69	53.62	13.93	Average
4	0.1997	9.84	9.77	40.01	59.62	63.62	4.00	QP
5	0.2404	9.73	9.92	18.84	38.49	52.08	13.59	Average
6	0.2404	9.73	9.92	38.22	57.87	62.08	4.21	QP
7	0.2803	9.77	9.92	18.34	38.03	50.81	12.78	Average
8	0.2803	9.77	9.92	38.21	57.90	60.81	2.91	QP
9	0.3149	9.81	9.92	18.70	38.43	49.84	11.41	Average
10	0.3149	9.81	9.92	37.21	56.94	59.84	2.90	QP
11	0.3791	9.81	9.92	16.54	36.27	48.30	12.03	Average
12	0.3791	9.81	9.92	36.21	55.94	58.30	2.36	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.



Trace: 5

Site no. : 2#CE Shield Room Data no. : 6

Env. / Ins. : Temp:24.1°C Humi:57% Press:101.70kPa. : LINE

Limit : FCC PART 15B QP

Engineer : XJF

EUT : smart plug

Power : AC 120V/60Hz

M/N : ETS-C-006

Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1703	9.82	9.69	22.01	41.52	54.94	13.42	Average
2	0.1703	9.82	9.69	40.12	59.63	64.94	5.31	QP
3	0.1796	9.84	9.77	19.12	38.73	54.50	15.77	Average
4	0.1796	9.84	9.77	33.25	52.86	64.50	11.64	QP
5	0.2404	9.73	9.92	17.60	37.25	52.08	14.83	Average
6	0.2404	9.73	9.92	35.15	54.80	62.08	7.28	QP
7	0.2744	9.77	9.92	22.73	42.42	50.98	8.56	Average
8	0.2744	9.77	9.92	36.55	56.24	60.98	4.74	QP
9	0.3751	9.81	9.92	12.55	32.28	48.39	16.11	Average
10	0.3751	9.81	9.92	36.48	56.21	58.39	2.18	QP
11	0.5611	9.84	9.92	16.42	36.18	46.00	9.82	Average
12	0.5611	9.84	9.92	33.55	53.31	56.00	2.69	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.

2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 8

File: \\EMC-CE-2\Test Data\2022\RF\Q\QI Ao\QI Ao.EM6 (8)

Date: 2022-06-25



Trace: 7

Site no. : 2#CE Shield Room Data no. : 8
Env. / Ins. : Temp:24.1°C Humi:57% Press:101.70kPa. : NEUTRAL
Limit : FCC PART 15B QP
Engineer : XJF
EUT : smart plug
Power : AC 120V/60Hz
M/N : ETS-C-006
Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1598	9.78	9.69	24.28	43.75	55.47	11.72	Average
2	0.1598	9.78	9.69	41.16	60.63	65.47	4.84	QP
3	0.2050	9.78	9.84	24.95	44.57	53.40	8.83	Average
4	0.2050	9.78	9.84	39.88	59.50	63.40	3.90	QP
5	0.2353	9.84	9.92	25.07	44.83	52.26	7.43	Average
6	0.2353	9.84	9.92	40.12	59.88	62.26	2.38	QP
7	0.2803	9.84	9.92	21.81	41.57	50.81	9.24	Average
8	0.2803	9.84	9.92	38.25	58.01	60.81	2.80	QP
9	0.3303	9.76	9.92	24.03	43.71	49.44	5.73	Average
10	0.3303	9.76	9.92	37.11	56.79	59.44	2.65	QP
11	0.4889	9.76	9.92	19.81	39.49	46.19	6.70	Average
12	0.4889	9.76	9.92	33.65	53.33	56.19	2.86	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

10. APPENDIX


Appendix A: Duty Cycle

Test Result

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2437	1.70	16.84	10.10
11G	Ant1	2437	1.40	14.00	10.00
11N20SISO	Ant1	2437	1.29	13.06	9.88
11N40SISO	Ant1	2437	0.64	6.54	9.79

Test Graphs






Appendix B: DTS Bandwidth


Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	11.96	2406.04	2418.00	0.5	PASS
		2437	12.24	2430.96	2443.20	0.5	PASS
		2462	11.72	2456.52	2468.24	0.5	PASS
11G	Ant1	2412	16.72	2403.88	2420.60	0.5	PASS
		2437	16.84	2428.36	2445.20	0.5	PASS
		2462	16.84	2453.36	2470.20	0.5	PASS
11N20SISO	Ant1	2412	18.24	2402.88	2421.12	0.5	PASS
		2437	18.28	2427.92	2446.20	0.5	PASS
		2462	17.56	2453.56	2471.12	0.5	PASS
11N40SISO	Ant1	2422	35.04	2404.48	2439.52	0.5	PASS
		2437	35.12	2419.48	2454.60	0.5	PASS
		2452	35.12	2434.48	2469.60	0.5	PASS


Test Graphs




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452




Appendix C: Maximum conducted output power


Test Result Peak

Test Mode	Antenna	Frequency [MHz]	Peak Power[dBm]	Conducted Limit[dBm]	Verdict
11B	Ant1	2412	14.58	≤30.00	PASS
		2437	13.98	≤30.00	PASS
		2462	12.85	≤30.00	PASS
11G	Ant1	2412	16.91	≤30.00	PASS
		2437	16.45	≤30.00	PASS
		2462	15.34	≤30.00	PASS
11N20SISO	Ant1	2412	16.82	≤30.00	PASS
		2437	16.06	≤30.00	PASS
		2462	14.91	≤30.00	PASS
11N40SISO	Ant1	2422	16.04	≤30.00	PASS
		2437	15.51	≤30.00	PASS
		2452	14.59	≤30.00	PASS


Test Graphs Peak




11G_Ant1_2412





11G_Ant1_2437



11G_Ant1_2462









Appendix D: Maximum power spectral density Test Result

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-14.68	≤8.00	PASS
		2437	-14.67	≤8.00	PASS
		2462	-15.75	≤8.00	PASS
11G	Ant1	2412	-15.86	≤8.00	PASS
		2437	-16.73	≤8.00	PASS
		2462	-17.12	≤8.00	PASS
11N20SISO	Ant1	2412	-15.12	≤8.00	PASS
		2437	-15.76	≤8.00	PASS
		2462	-17.25	≤8.00	PASS
11N40SISO	Ant1	2422	-18.44	≤8.00	PASS
		2437	-19.29	≤8.00	PASS
		2452	-20.12	≤8.00	PASS


Test Graphs




11G_Ant1_2412






11G_Ant1_2437




11G_Ant1_2462







11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452




Appendix E: Reference level measurement Test Result

Test Mode	Antenna	Freq (MHz)	Max.Point [MHz]	Result [dBm]
11B	Ant1	2412	2412.23	-0.32
		2437	2434.32	-0.27
		2462	2460.73	-1.53
11G	Ant1	2412	2419.51	-0.94
		2437	2439.52	-2.24
		2462	2458.89	-5.69
11N20SISO	Ant1	2412	2414.53	-1.43
		2437	2437.04	-0.58
		2462	2469.51	-3.64
11N40SISO	Ant1	2422	2425.80	-4.13
		2437	2432.05	-4.51
		2452	2447.05	-5.77


Test Graphs




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462







11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452




Appendix F: Band edge measurements


Test Result

Test Mode	Antenna	Ch Name	Frequency [MHz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	Low	2412	-0.32	-26.36	≤ -20.32	PASS
		High	2462	-1.53	-39.08	≤ -21.53	PASS
11G	Ant1	Low	2412	-0.94	-24.86	≤ -20.94	PASS
		High	2462	-5.69	-35.44	≤ -25.69	PASS
11N20SISO	Ant1	Low	2412	-1.43	-25.79	≤ -21.43	PASS
		High	2462	-3.64	-34.1	≤ -23.64	PASS
11N40SISO	Ant1	Low	2422	-4.13	-26.05	≤ -24.13	PASS
		High	2452	-5.77	-31.15	≤ -25.77	PASS


Test Graphs




11G_Ant1_High_2462




11N20SISO_Ant1_Low_2412




11N20SISO_Ant1_High_2462



11N40SISO_Ant1_Low_2422




11N40SISO_Ant1_High_2452




Appendix G: Conducted Spurious Emission Test Result

Test Mode	Antenna	Frequency [MHz]	Freq Range [Mhz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	30~26500	-0.32	-42.47	≤-20.32	PASS
		2437	30~26500	-0.27	-42.59	≤-20.27	PASS
		2462	30~26500	-1.53	-43.01	≤-21.53	PASS
11G	Ant1	2412	30~26500	-0.94	-41.49	≤-20.94	PASS
		2437	30~26500	-2.24	-42.46	≤-22.24	PASS
		2462	30~26500	-5.69	-43.64	≤-25.69	PASS
11N20SISO	Ant1	2412	30~26500	-1.43	-42.53	≤-21.43	PASS
		2437	30~26500	-0.58	-43.26	≤-20.58	PASS
		2462	30~26500	-3.64	-43.31	≤-23.64	PASS
11N40SISO	Ant1	2422	30~26500	-4.13	-43.03	≤-24.13	PASS
		2437	30~26500	-4.51	-43.32	≤-24.51	PASS
		2452	30~26500	-5.77	-42.36	≤-25.77	PASS


Test Graphs




11G_Ant1_2412_30~26500




11G_Ant1_2437_30~26500




11G_Ant1_2462_30~26500




11N20SISO_Ant1_2412_30~26500




11N20SISO_Ant1_2437_30~26500




11N20SISO_Ant1_2462_30~26500




11N40SISO_Ant1_2422_30~26500



11N40SISO_Ant1_2437_30~26500



11N40SISO_Ant1_2452_30~26500



11. ANTENNA REQUIREMENTS

11.1. Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

11.2. Test Result


The antennas used for this product is internal antenna, so compliance with antenna requirements. (Please refer to the EUT photo for details)

12. TEST SETUP PHOTO


Conducted Test



Radiated Test (Below 1GHz)



Radiated Test (Above 1GHz)





13. EUT PHOTO



External Photos
M/N: ETS-C-006





External Photos
M/N: ETS-C-006





External Photos
M/N: ETS-C-006




Internal Photos
M/N: ETS-C-006



Internal Photos
M/N: ETS-C-006





End of Test Report