

Report No.: KSCR220600092403

Page: 1 of 49

TEST REPORT

Application No.:KSCR2206000924ATFCC ID:2AL8S-0302C3XN-1

Applicant: ZHEJIANG UNIVIEW TECHNOLOGIES CO., LTD

Address of Applicant: 88 JIANGLING ROAD, XIXING TOWN, BINJIANG DISTRICT, HANGZHOU

CITY

Manufacturer: ZHEJIANG UNIVIEW TECHNOLOGIES CO., LTD

Address of Manufacturer: 88 JIANGLING ROAD, XIXING TOWN, BINJIANG DISTRICT, HANGZHOU

CITY

Factory: Zhejiang Uniview System Technology Co., Ltd.

Address of Factory: No.1277 Qingfeng South Road (South), Tongxiang Economic Development

Zone, 314500 TongxiangCity, Jiaxing City, PEOPLE'S REPUBLIC OF

CHINA

Equipment Under Test (EUT):

EUT Name: WiFi + BT Module **Model No.:** WF-M63B-USH1

Standard(s): 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2022-06-06

Date of Test: 2022-07-08 to 2022-07-11

Date of Issue: 2022-07-12

Test Result: Pass*

Eric Lin Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com.

No.10, Welye Road, Innovation Park, Kunshan, Jiangsu, China 215300 (186-512)57355888 (186-512)57370818 www.sgsgroup.com.cn 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 (186-512)57355888 (186-512)57370818 sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: KSCR220600092403

Page: 2 of 49

	Revision Record								
Version Chapter Date Modifier R									
01		2022-07-12		Original					

Authorized for issue by:			
	Cerii Lin		
	Eric_Liu/Project Engineer	_ _	
	Eni Li		
	Eric Lin/Reviewer	-	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 3 of 49

2 Test Summary

Radio Spectrum Technical Requirement							
Item	Requirement	Result					
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Customer Declaratio n			

Radio Spectrum Matter Part					
Item	Standard	Method	Requirement	Result	
Conducted Peak Output Power		ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass	
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass	
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass	
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass	
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass	
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass	
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass	
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 4 of 49

3 Contents

		Page
1	1 COVER PAGE	1
2	TEST SUMMARY	3
3	3 CONTENTS	4
4		
	4.1 DETAILS OF E.U.T.	
	4.2 POWER LEVEL SETTING USING IN TEST:	
	4.3 DESCRIPTION OF SUPPORT UNITS	
	4.4 MEASUREMENT UNCERTAINTY	
	4.5 TEST LOCATION	
	4.6 TEST FACILITY	
	4.7 DEVIATION FROM STANDARDS	
	4.8 ABNORMALITIES FROM STANDARD CONDITIONS	
5	5 EQUIPMENT LIST	10
_		
6	RADIO SPECTRUM TECHNICAL REQUIREMENT	12
	6.1 ANTENNA REQUIREMENT	12
	6.1.1 Test Requirement:	12
	6.1.2 Conclusion	12
7	7 RADIO SPECTRUM MATTER TEST RESULTS	13
	7.1 CONDUCTED PEAK OUTPUT POWER	13
	7.1.1 E.U.T. Operation	13
	7.1.2 Test Setup Diagram	
	7.1.3 Measurement Procedure and Data	
	7.2 MINIMUM 6dB BANDWIDTH	
	7.2.1 E.U.T. Operation	
	7.2.2 Test Mode Description	
	7.2.3 Test Setup Diagram	
	7.2.4 Measurement Procedure and Data	
	7.3 POWER SPECTRUM DENSITY	
	7.3.1 E.U.T. Operation	
	7.3.2 Test Mode Description	
	7.3.3 Test Setup Diagram7.3.4 Measurement Procedure and Data	
	7.4 CONDUCTED BAND EDGES MEASUREMENT	
	7.4.1 E.U.T. Operation	
	7.4.3 Test Setup Diagram	
	7.4.4 Measurement Procedure and Data	
	7.5 CONDUCTED SPURIOUS EMISSIONS	
	7.5.1 E.U.T. Operation	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 5 of 49

7.5.2	Test Mode Description	18
7.5.3	Test Setup Diagram	
7.5.4	Measurement Procedure and Data	19
7.6 F	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	
7.6.1	E.U.T. Operation	20
7.6.2	Test Mode Description	
7.6.3	Test Setup Diagram	
7.6.4	Measurement Procedure and Data	
7.7 F	RADIATED SPURIOUS EMISSIONS BELOW 1GHz	3 ²
7.7.1	E.U.T. Operation	3
7.7.2	Test Mode Description	
7.7.3	Test Setup Diagram	
7.7.4	Measurement Procedure and Data	32
7.8 F	RADIATED SPURIOUS EMISSIONS ABOVE 1GHz	35
7.8.1	E.U.T. Operation	3
7.8.2	Test Mode Description	
7.8.3	Test Setup Diagram	
7.8.4	Measurement Procedure and Data	36
8 TEST	SETUP PHOTO	49
9 EUT (CONSTRUCTIONAL DETAILS (EUT PHOTOS)	49



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 6 of 49

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.3V
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.1
Modulation Type:	GFSK
Data Rate:	1Mbps; 2Mbps
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	0.37dBi(Provided by the manufacturer)

4.2 Power level setting using in test:

Champal	BLE 1M	BLE 2M		
Channel	Ant 1	Ant 1		
0	default	default		
19	default	default		
39	default	default		

4.3 Description of Support Units

Description	Description Manufacturer		Serial No.
Notebook	Lenovo		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 7 of 49

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4 x 10 ⁻⁸
2	Timeout	2s
3	Duty Cycle	0.37%
4	Occupied Bandwidth	3%
5	RF Conducted Power	0.6dB
6	RF Power Density	2.9dB
7	Conducted Spurious Emissions	0.75dB
8	RF Radiated Power	5.2dB (Below 1GHz)
0	RF Radiated Power	5.9dB (Above 1GHz)
		4.2dB (Below 30MHz)
9	Radiated Spurious Emission Test	4.5dB (30MHz-1GHz)
9		5.1dB (1GHz-18GHz)
		5.4dB (Above 18GHz)
10	Temperature Test	1°C
11	Humidity Test	3%
12	Supply Voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300

Member of the SGS Group (SGS SA)



Report No.: KSCR220600092403

Page: 8 of 49

4.5 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1.SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc.) is provided by the applicant. (if applicable).

2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L4354)

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 2541.01)

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• FCC (Designation Number: CN1172)

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory.

Designation Number: CN1172.

• ISED (CAB identifier: CN0072)

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 2324EVCCI (Member No.: 1938)

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4.7 Deviation from Standards

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 9 of 49

4.8 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 10 of 49

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date		
RF Co	RF Conducted Test							
1	Spectrum Analyzer	Keysight	N9020A	KUS1911E004-2	10/11/2021	10/10/2022		
2	Spectrum Analyzer	Keysight	N9020A	KUS2001M001- 2	09/17/2021	09/16/2022		
3	Spectrum Analyzer	Keysight	N9030B	KSEM021-1	01/22/2022	01/21/2023		
4	Signal Generator	R&S	SMW200A	KSEM020-1	10/12/2021	10/11/2022		
5	Signal Generator	Agilent	N5182A	KUS2001M001- 1	08/27/2021	08/26/2022		
6	Radio Communication Test Station	Anritsu	MT8000A	KSEM001-1	09/23/2021	09/22/2022		
7	Radio Communication Analyzer	Anritsu	MT8821C	KSEM002-1	04/01/2022	03/31/2023		
8	Universal Radio Communication Tester	R&S	CMW500	KUS1911E004-1	10/12/2021	10/11/2022		
9	Switcher	CCSRF	FY562	KUS2001M001- 3	10/12/2021	10/11/2022		
10	AC Power Source	EXTECH	6605	KS301178	N.C.R	N.C.R		
11	DC Power Supply	Aglient	E3632A	KS301180	N.C.R	N.C.R		
12	Conducted Test Cable	Thermax	RF01-RF04	CZ301111- CZ301120	01/16/2022	01/15/2023		
13	Temp. / Humidity Chamber	TERCHY	MHK-120AK	KS301190	04/01/2021	03/31/2023		
14	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-5	04/01/2021	03/31/2023		
15	Software	BST	TST-PASS	/	N/A	N/A		
RF Ra	diated Test							
1	Spectrum Analyzer	R&S	FSV40	KUS1806E003	10/11/2021	10/10/2022		
2	Universal Radio Communication Tester	R&S	CMW500	KSEM009-1	04/01/2022	03/31/2023		
3	Signal Generator	Agilent	E8257C	KS301066	10/18/2021	10/17/2022		
4	Loop Antenna	COM-POWER	AL-130R	KUS1806E001	04/13/2021	04/12/2023		
5	Bilog Antenna	TESEQ	CBL 6112D	KUS1806E005	06/29/2021	06/28/2023		
6	Bilog Antenna	SCHWARZBECK	VULB9160	CZ301016	04/13/2021	04/12/2024		
7	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	KS301079	10/26/2020	10/25/2022		
8	Horn-antenna(1-18GHz)	ETS-LINDGREN	3117	KS301186	02/22/2021	02/21/2023		
9	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	CZ301058	03/22/2022	03/21/2023		
10	Amplifier(30MHz~18GHz)	PANSHAN TECHNOLOGY	LNA:1~18G	KSEM010-1	01/22/2022	01/21/2023		
11	Amplifier(18~40GHz)	COM-POWER	PAM-840A	KUS1710E001	01/22/2022	01/21/2023		
12	RE Test Cable	REBES MICROWAVE	1	CZ301097	11/14/2021	11/13/2022		
13	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-4	01/04/2022	31/03/2023		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 $\begin{array}{lll} t(86\text{-}512)57355888 & \textit{f}(86\text{-}512)57370818 & \textit{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & \textit{f}(86\text{-}512)57370818 & \textit{sgs.china@sgs.com} \\ \end{array}$



Report No.: KSCR220600092403

Page: 11 of 49

14	Software	Faratronic	EZ_EMC-v 3A1	/	N/A	N/A
----	----------	------------	--------------	---	-----	-----



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 12 of 49

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PCB antenna and no consideration of replacement. The best case gain of the antenna is 0.37dBi.

Antenna location: Refer to internal photo.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$



Report No.: KSCR220600092403

Page: 13 of 49

Radio Spectrum Matter Test Results 7

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3) Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:


Frequency range(MHz)	Output power of the intentional radiator(watt)				
	1 for ≥50 hopping channels				
902-928	0.25 for 25≤ hopping channels <50				
	1 for digital modulation				
	1 for ≥75 non-overlapping hopping channels				
2400-2483.5	0.125 for all other frequency hopping systems				
	1 for digital modulation				
5725-5850	1 for frequency hopping systems and digital modulation				

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C Atmospheric Pressure: 1010 mbar Humidity: 47.2 % RH

7.1.2 Test Setup Diagram



7.1.3 Measurement Procedure and Data

Please Refer to Appendix C for KSCR220600092403



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn

No.10, Weive Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300

t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



Report No.: KSCR220600092403

14 of 49 Page:

7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2) Test Method: ANSI C63.10 (2013) Section 11.8.1

I imit

≥500 kHz

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 23.6 °C Humidity: 47.2 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Please Refer to Appendix C for KSCR220600092403



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 83071443, or email: CN.Doccheck@sas.com

No.10, Weive Road, Innovation Park, Kunshan, Jiangsu, China 215300 t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn

中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300

t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



Report No.: KSCR220600092403

Page: 15 of 49

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 23.6 °C Humidity: 47.2 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description							
Final test	04	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.							
Final test	05	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.							

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

Please Refer to Appendix C for KSCR220600092403



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 83071443, or email: CN.Doccheck@sas.com

or email: <u>CN. Doccheck@sgs.com</u> Mo.10, Wejye Road, Innovation Park, Kunshan, Jiangsu, China 215300 (186-512)57355888 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 (186-512)57355888



Report No.: KSCR220600092403

Page: 16 of 49

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c).

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.7 °C Humidity: 47.2 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description								
Final test	04	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.								
Final test	05	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.								




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 17 of 49

7.4.3 Test Setup Diagram



Ground Reference Plane

7.4.4 Measurement Procedure and Data

Please Refer to Appendix C for KSCR220600092403



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 18 of 49

7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c).

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C Humidity: 47.2 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

	in the state of th									
Pre-scan / Final test	Mode Code	Description								
Final test	04	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.								
Final test	05	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.								




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 19 of 49

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix C for KSCR220600092403



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$



Report No.: KSCR220600092403

Page: 20 of 49

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C Humidity: 46.4 % RH Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms




Report No.: KSCR220600092403

Page: 21 of 49

7.6.3 Test Setup Diagram





30MHz-1GHz Above 1GHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 22 of 49

7.6.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$



Report No.: KSCR220600092403

Page: 23 of 49

Test Mode: 04; Polarity: Horizontal; Modulation: GFSK; Channel:Low



	Freq			Read Level	Over LevelFCC CLAFCC CLA			Remark
				dBuV				
1	2373.365	5.6/	26./1	59.48	42.10	74.00	-31.90	Peak
2	2390.000	5.69	26.73	55.80	38.48	74.00	-35.52	Peak
3	2402.340	5.71	26.75	111.75	94.48	74.00	20.48	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 24 of 49

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; Channel:Low



	Freq			Read Level	Over LevelFCC CLAFCC CLA		Remark	
				dBuV	•			
1	2372.700	5.67	26.70	61.85	44.46	74.00	-29.54	Peak
2	2373.745	5.67	26.71	63.69	46.31	74.00	-27.69	Peak
3	2401.960	5.71	26.75	105.70	88.43	74.00	14.43	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 25 of 49

Test Mode: 04; Polarity: Horizontal; Modulation: GFSK; Channel: High



	Freq		Ant Factor		Over LevelFCC CLAFCC CLA			Remark
2		5.82 5.83	27.03 27.04	55.29	95.81 38.50	74.00	-35.50	Peak
4	2500.000	5.85	27.10	52.93	36.23	74.00	-37.77	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 26 of 49

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:High



	Freq		Ant Factor		Over Leve1FCC CLAFCC CLA		Remark	
	MHz	dB	dB/m	dBuV	dBuV/m			
1	2480.000	5.82	27.03	105.11	88.30	74.00	14.30	Peak
2	2483.500	5.83	27.04	55.54	38.75	74.00	-35.25	Peak
3	2489.250	5.83	27.06	56.99	40.23	74.00	-33.77	Peak
4	2500.000	5.85	27.10	54.66	37.96	74.00	-36.04	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 27 of 49

Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; Channel:Low



	Freq			Read Level	Over LevelFCC CLAFCC CLA		Remark	
	MHz	dB	dB/m	dBuV	dBuV/m			
1	2374.315	5.67	26.71	58.75	41.37	74.00	-32.63	Peak
2	2390.000	5.69	26.73	56.46	39.14	74.00	-34.86	Peak
3	2402.530	5.71	26.75	111.71	94.44	74.00	20.44	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 28 of 49

Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel: Low



	Freq			Read Level	LevelF	CC CLAF	Over CC CLA	Remark
	MHz	dB	dB/m	dBuV	dBuV/m			
1	2373.270	5.67	26.71	64.13	46.75	74.00	-27.25	Peak
2	2390.000	5.69	26.73	54.53	37.21	74.00	-36.79	Peak
3	2402.625	5.71	26.75	105.35	88.08	74.00	14.08	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 29 of 49

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:High



	Freq		Ant Factor		LevelF	CC CLAF	Over	Remark
	MHz	dB	dB/m	dBuV	dBuV/m			
1	2479.625	5.82	27.03	112.88	96.07	74.00	22.07	Peak
2	2483.500	5.83	27.04	62.97	46.18	74.00	-27.82	Peak
3	2485.500	5.83	27.05	60.90	44.12	74.00	-29.88	Peak
4	2500.000	5.85	27.10	54.02	37.32	74.00	-36.68	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 30 of 49

Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel: High



	Freq		Ant Factor		LevelF	CC CLAF	Over	Remark
	MHz	dB	dB/m	dBuV	dBuV/m			
1	2480.625	5.82	27.03	104.93	88.12	74.00	14.12	Peak
2	2483.500	5.83	27.04	56.58	39.79	74.00	-34.21	Peak
3	2484.875	5.83	27.05	63.94	47.16	74.00	-26.84	Peak
4	2500.000	5.85	27.10	54.13	37.43	74.00	-36.57	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 31 of 49

7.7 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C Humidity: 46.4 % RH Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

	<u>=</u>						
Pre-scan / Final test	Mode Code	Description					
Final test	04	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.					
Final test	05	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 83071443, or email: CN.Doccheck@sas.com




Report No.: KSCR220600092403

Page: 32 of 49

7.7.3 Test Setup Diagram





Below 30MHz

30MHz-1GHz

7.7.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete. Remark:
- 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & www.sgsgroup.com.cn \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & sgs.china@sgs.com \\ \end{array}$



Report No.: KSCR220600092403

Page: 33 of 49





No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	37.7600	6.22	23.24	29.46	40.00	-10.54	100	158	QP
2	113.4200	9.28	18.87	28.15	43.50	-15.35	100	98	QP
3	184.2300	13.67	16.47	30.14	43.50	-13.36	100	133	QP
4	245.3400	16.17	19.32	35.49	46.00	-10.51	100	16	QP
5	263.7700	13.79	21.02	34.81	46.00	-11.19	100	121	QP
6	876.8100	29.42	2.30	31.72	46.00	-14.28	100	32	QP




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 34 of 49

Test Mode: 04; Polarity: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	38.7300	8.77	22.80	31.57	40.00	-8.43	100	46	QP
2	59.1000	15.80	15.07	30.87	40.00	-9.13	100	357	QP
3	184.2300	9.62	16.47	26.09	43.50	-17.41	100	49	QP
4	240.4900	9.55	18.79	28.34	46.00	-17.66	100	152	QP
5	804.0600	28.69	2.24	30.93	46.00	-15.07	100	73	QP
6	991.2700	29.78	2.40	32.18	54.00	-21.82	100	292	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 35 of 49

7.8 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 24.1 °C Humidity: 46.4 % RH Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.8.3 Test Setup Diagram





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 83071443, or email: CN.Doccheck@sas.com

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 36 of 49

7.8.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete. Remark:
- 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- 2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 37 of 49

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:Low



	Freq		Ant Factor		LevelF	CC CLAF	Remark	
2	MHz 4804.000 7206.000 9608.000	8.12 10.34	35.44	54.12 50.70	48.67 49.54	74.00	-24.46	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 38 of 49

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; Channel:Low



	Freq	Cable Ant Rea Loss Factor Leve			LevelF	CC CLAF	Remark	
	MHz	dB	dB/m	dBuV	dBuV/m			
1	4804.000	8.12	34.18	53.60	48.15	74.00	-25.85	Peak
2	7206.000	10.34	35.44	50.43	49.27	74.00	-24.73	Peak
3	9608.000	12.29	36.92	46.71	50.03	74.00	-23.97	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 39 of 49

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; Channel:middle



	Freq		Ant Factor		LevelF	Remark		
1	MHz 4880.000		dB/m 34 18			74 00	-25 26	Peak
2	7320.000							
3	9760.000	12.41	37.05	46.52	50.50	74.00	-23.50	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 40 of 49

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; Channel:middle



	Freq	Cable Ant Read Over Freq Loss Factor Level LevelFCC CLAFCC CLA					Remark	
			dB/m					
1	4880.000	8.1/	34.18	54.04	48./2	74.00	-25.28	Peak
2	7320.000	10.45	35.47	50.75	49.75	74.00	-24.25	Peak
3	9760.000	12.41	37.05	46.77	50.75	74.00	-23.25	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 41 of 49

Test Mode: 04; Polarity: Horizontal; Modulation: GFSK; Channel: High



	Freq		Ant Factor		LevelF	CC CLAF	Over CC CLA	Remark
2	MHz 4960.000 7440.000 9920.000	8.21 10.56	35.52	54.11 50.24	48.91 49.47	74.00	-24.53	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 42 of 49

Test Mode: 04; Polarity: Vertical; Modulation: GFSK; Channel: High



	Freq		Ant Factor		LevelF	CC CLAF	Over CC CLA	Remark
			dB/m			74.00	25.52	
	4960.000							
2	7440.000	10.56	35.52	49.79	49.02	74.00	-24.98	Peak
3	9920.000	12.50	37.18	45.94	50.29	74.00	-23.71	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$



Report No.: KSCR220600092403

Page: 43 of 49

Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; Channel:Low



	Freq		Ant Factor		LevelF	CC CLAI	Over	Remark
	MHz	dB	dB/m	dBuV	dBuV/m			
1	4804.000	8.12	34.18	53.67	48.22	74.00	-25.78	Peak
2	7206.000	10.34	35.44	50.63	49.47	74.00	-24.53	Peak
3	9608.000	12.29	36.92	47.44	50.76	74.00	-23.24	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 44 of 49

Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel:Low



	Freq		Ant Factor		Level	CC CLAF	Over CC CLA	Remark
	MHz	dB	dB/m	dBuV	dBuV/m			
1	4804.000	8.12	34.18	53.85	48.40	74.00	-25.60	Peak
2	7206.000	10.34	35.44	50.22	49.06	74.00	-24.94	Peak
3	9608.000	12.29	36.92	47.25	50.57	74.00	-23.43	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 45 of 49

Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; Channel: middle



	Freq	Cable Ant Loss Factor			Read Over Level LevelFCC CLAFCC CLA Rem				
			dB/m				25.40		
1	4880.000	8.1/	34.18	54.13	48.81	74.00	-25.19	Peak	
2	7320.000	10.45	35.47	50.53	49.53	74.00	-24.47	Peak	
3	9760.000	12.41	37.05	46.04	50.02	74.00	-23.98	Peak	




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 46 of 49

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; Channel:middle



	Freq	Cable Ant Loss Factor			Over LevelFCC CLAFCC CLA R			Remark
	MHz	dB	dB/m	dBuV	dBuV/m			
1	4880.000	8.17	34.18	53.76	48.44	74.00	-25.56	Peak
2	7320.000	10.45	35.47	50.17	49.17	74.00	-24.83	Peak
3	9760.000	12.41	37.05	46.23	50.21	74.00	-23.79	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 47 of 49

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; Channel:High



	Freq		Ant Factor		LevelF	CC CLAF	Over CC CLA	Remark
	MHz	dB	dB/m	dBuV	dBuV/m			
1	4960.000	8.21	34.17	54.07	48.87	74.00	-25.13	Peak
2	7440.000	10.56	35.52	50.37	49.60	74.00	-24.40	Peak
3	9920.000	12.50	37.18	46.65	51.00	74.00	-23.00	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300



Report No.: KSCR220600092403

Page: 48 of 49

Test Mode: 05; Polarity: Vertical; Modulation: GFSK; Channel: High



		Cable	Ant	Read			0ver	
	Freq	Loss	Factor	Level	LevelF	CC CLAF	CC CLA	Remark
	MHz	dB	dB/m	dBuV	dBuV/m			
1	4960.000	8.21	34.17	53.73	48.53	74.00	-25.47	Peak
2	7440.000	10.56	35.52	50.51	49.74	74.00	-24.26	Peak
3	9920.000	12.50	37.18	46.25	50.60	74.00	-23.40	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms



Report No.: KSCR220600092403

Page: 49 of 49

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for KSCR2206000924AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix - Photographs of EUT Constructional Details for KSCR2206000924AT

- End of the Report -



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 83071443, or email: CN.Doccheck@sas.com

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300 $\begin{array}{lll} t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{www.sgsgroup.com.cn} \\ t(86\text{-}512)57355888 & f(86\text{-}512)57370818 & \text{sgs.china@sgs.com} \\ \end{array}$

Member of the SGS Group (SGS SA)