



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctest.com>



MEASUREMENT REPORT FCC Part 22 & 90

Applicant Name:

LG Electronics USA, Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

1/15/2019 - 2/7/2019

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M1901080002-04-R1.ZNF

FCC ID:

ZNFG820UM

APPLICANT:

LG Electronics USA, Inc.

Application Type:

Class II Permissive Change

Model:

LM-G820UM

Additional Model(s):

LMG820UM, G820UM, LM-G820TM, LMG820TM, G820TM,
LM-G820QM, LMG820QM, G820QM, LM-G820QM5, LMG820QM5,
G820QM5, LM-G820QM6, LMG820QM6, G820QM6

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part:

§2.1049, §22(H), §90.691, §90.543

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01
v03r01, KDB 648474 D03 v01r04


Class II Permissive Change:

Please see FCC Change Document



This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M1901080002-04-R1.ZNF) supersedes and replaces the previously issued test report (S/N: 1M1901080002-04.ZNF) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President



| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 1 of 23 |



© 2019 PCTEST Engineering Laboratory, Inc.


V 8.8 11/19/2018

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

TABLE OF CONTENTS


| | | |
|-----|--|----|
| 1.0 | INTRODUCTION | 4 |
| 1.1 | Scope | 4 |
| 1.2 | PCTEST Test Location..... | 4 |
| 1.3 | Test Facility / Accreditations..... | 4 |
| 2.0 | PRODUCT INFORMATION..... | 5 |
| 2.1 | Equipment Description | 5 |
| 2.2 | Device Capabilities..... | 5 |
| 2.3 | Test Configuration | 5 |
| 2.4 | EMI Suppression Device(s)/Modifications | 5 |
| 3.0 | DESCRIPTION OF TESTS | 6 |
| 3.1 | Evaluation Procedure | 6 |
| 3.2 | Radiated Power and Radiated Spurious Emissions | 6 |
| 4.0 | MEASUREMENT UNCERTAINTY | 7 |
| 5.0 | TEST EQUIPMENT CALIBRATION DATA | 8 |
| 6.0 | SAMPLE CALCULATIONS | 9 |
| 7.0 | TEST RESULTS..... | 10 |
| 7.1 | Summary..... | 10 |
| 7.2 | Radiated Power (ERP)..... | 12 |
| 7.3 | Radiated Spurious Emissions Measurements | 15 |
| 8.0 | CONCLUSION..... | 23 |

| | | | | |
|---|---|--|---|--|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 2 of 23 | |





MEASUREMENT REPORT

FCC Part 22(H) & 90



| Mode | Tx Frequency (MHz) | Measurement | Max. Power (W) | Max. Power (dBm) | Emission Designator | Modulation |
|-------------|--------------------|-------------|----------------|------------------|---------------------|------------|
| LTE Band 14 | 790.5 - 795.5 | ERP | 0.096 | 19.84 | 4M55G7D | QPSK |
| LTE Band 14 | 790.5 - 795.5 | ERP | 0.071 | 18.51 | 4M52W7D | 16-QAM |
| LTE Band 14 | 790.5 - 795.5 | ERP | 0.058 | 17.62 | 4M53W7D | 64-QAM |
| LTE Band 14 | 793 | ERP | 0.094 | 19.72 | 9M01G7D | QPSK |
| LTE Band 14 | 793 | ERP | 0.071 | 18.53 | 9M01W7D | 16-QAM |
| LTE Band 14 | 793 | ERP | 0.057 | 17.52 | 8M99W7D | 64-QAM |
| LTE Band 26 | 821.5 | ERP | 0.075 | 18.74 | 13M4G7D | QPSK |
| LTE Band 26 | 821.5 | ERP | 0.049 | 16.88 | 13M4W7D | 16-QAM |
| LTE Band 26 | 821.5 | ERP | 0.039 | 15.91 | 13M4W7D | 64-QAM |

EUT Overview

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 3 of 23 |

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISSED.

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 4 of 23 | |

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFG820UM**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 90.543, 22(H) and 90.691.

Test Device Serial No.: 03864, 03856

2.2 Device Capabilities

This device contains the following capabilities:

800/850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ac WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: PWMA-W815A while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

| | | | | |
|---|---|---|---|--|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 5 of 23 | |

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Radiated Power and Radiated Spurious Emissions

\$2.1053, \$90.635, \$90.691, \$90.543

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [\text{dBm}] = P_g [\text{dBm}] - \text{cable loss} [\text{dB}] + \text{antenna gain} [\text{dBd/dBi}]$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g [\text{dBm}] - \text{cable loss} [\text{dB}]$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power} [\text{Watts}])$ specified in 90.691.

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 6 of 23 | |

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution | Expanded Uncertainty (\pm dB) |
|-------------------------------|----------------------------------|
| Radiated Disturbance (<1GHz) | 4.98 |
| Radiated Disturbance (>1GHz) | 5.07 |
| Radiated Disturbance (>18GHz) | 5.09 |

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 7 of 23 | |

5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|-----------------|--------------|----------------------------------|------------|--------------|------------|---------------|
| - | LTx3 | Licensed Transmitter Cable Set | 8/23/2018 | Annual | 8/23/2019 | LTx3 |
| Agilent | E5515C | Wireless Communications Test Set | 1/29/2016 | Triennial | 2/29/2019 | GB46310798 |
| Agilent | E5515C | Wireless Communications Test Set | 3/4/2016 | Triennial | 3/4/2019 | GB45360985 |
| Agilent | N9020A | MXA Signal Analyzer | 1/24/2018 | Annual | 2/24/2019 | US46470561 |
| Com-Power | AL-130 | 9kHz - 30MHz Loop Antenna | 10/10/2017 | Biennial | 10/10/2019 | 121034 |
| Com-Power | PAM-103 | Pre-Amplifier (1-1000MHz) | 9/17/2018 | Annual | 9/17/2019 | 441119 |
| Espec | ESX-2CA | Environmental Chamber | 3/28/2018 | Annual | 3/28/2019 | 17620 |
| ETS Lindgren | 3164-08 | Quad Ridge Horn Antenna | 3/28/2018 | Biennial | 3/28/2020 | 128337 |
| Mini Circuits | TVA-11-422 | RF Power Amp | N/A | | | QA1317001 |
| Mini-Circuits | PWR-SEN-4RMS | USB Power Sensor | 3/30/2018 | Annual | 3/30/2019 | 11210140001 |
| Mini-Circuits | SSG-4000HP | Synthesized Signal Generator | N/A | | | 11208010032 |
| Mini-Circuits | SSG-4000HP | Synthesized Signal Generator | N/A | | | 11403100002 |
| Rohde & Schwarz | CMU200 | Base Station Simulator | 5/18/2018 | Annual | 5/18/2019 | 109892 |
| Rohde & Schwarz | CMW500 | Radio Communication Tester | 6/8/2018 | Annual | 6/8/2019 | 112347 |
| Rohde & Schwarz | ESU26 | EMI Test Receiver (26.5GHz) | 5/21/2018 | Annual | 5/21/2019 | 100342 |
| Rohde & Schwarz | ESU40 | EMI Test Receiver (40GHz) | 8/9/2018 | Annual | 8/9/2019 | 100348 |
| Rohde & Schwarz | SFUNIT-Rx | Shielded Filter Unit | 6/18/2018 | Annual | 6/18/2019 | 102134 |
| Rohde & Schwarz | TS-PR26 | 18-26.5 GHz Pre-Amplifier | 9/19/2018 | Annual | 9/19/2019 | 100040 |
| Schwarzbeck | UHA 9105 | Dipole Antenna (400 - 1GHz) Rx | 4/30/2018 | Biennial | 4/30/2020 | 9105-2404 |
| Schwarzbeck | UHA 9105 | Dipole Antenna (400 - 1GHz) Tx | 4/30/2018 | Biennial | 4/30/2020 | 9105-2403 |
| Seekonk | NC-100 | Torque Wrench (8" lb) | 5/10/2018 | Biennial | 5/10/2020 | N/A |
| Sunol | DRH-118 | Horn Antenna (1-18 GHz) | 8/11/2017 | Biennial | 8/11/2019 | A042511 |
| Sunol | JB5 | Bi-Log Antenna (30M - 5GHz) | 4/19/2018 | Biennial | 4/19/2020 | A051107 |

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

| | | | | |
|--|--|-------------------------------|---|---------------------------------|
| FCC ID: ZNFG820UM |  MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) | |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 8 of 23 |

6.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission – BC10

Example: Channel 476 CDMA BC10 Mode 3rd Harmonic (2453.70MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 2453.70 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc.

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated



7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 9 of 23 |



7.0 TEST RESULTS

7.1 Summary

Company Name: LG Electronics USA, Inc.
 FCC ID: ZNFG820UM
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): CDMA / EvDO / LTE
 Band: Band Class 10 / Band 26 / Band 14



| FCC Part Section(s) | Test Description | Test Limit | Test Condition | Test Result | Reference |
|----------------------------|------------------------------------|---|----------------|-------------|-------------|
| 22.913(a.2) | Effective Radiated Power (Band 26) | < 7 Watts max. ERP | RADIATED | PASS | Section 7.2 |
| 90.542 | Effective Radiated Power (Band 14) | < 3 Watts max. ERP | | PASS | Section 7.2 |
| 2.1053 90.691 90.543 | Radiated Spurious Emissions | > 43 + log ₁₀ (P[Watts]) for all out-of-band emissions except > 50 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge | | PASS | Section 7.3 |

Table 7-1. Summary of Test Results

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 10 of 23 | |

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

| | | | | |
|---|---|--|---|--|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 11 of 23 | |

7.2 Radiated Power (ERP)

§22.913(a.2) §90.542

Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 12 of 23 | |

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Radiated Test Setup <1GHz

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.



| Frequency [MHz] | Channel Bandwidth [MHz] | Mod. | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | RB Size/Offset | Substitute Level [dBm] | Ant. Gain [dBi] | ERP [dBm] | ERP [Watts] | ERP Limit [dBm] | Margin [dB] |
|-----------------|-------------------------|--------|-----------------|---------------------|----------------------------|----------------|------------------------|-----------------|--------------|--------------|-----------------|-------------|
| 821.50 | 15 | QPSK | V | 149 | 122 | 1 / 0 | 14.60 | 6.29 | 18.74 | 0.075 | 38.45 | -19.71 |
| 821.50 | 15 | 16-QAM | V | 149 | 122 | 1 / 0 | 12.74 | 6.29 | 16.88 | 0.049 | 38.45 | -21.57 |
| 821.50 | 15 | 64-QAM | V | 149 | 122 | 1 / 0 | 11.77 | 6.29 | 15.91 | 0.039 | 38.45 | -22.54 |
| 821.50 | 15 (WCP) | QPSK | V | 153 | 105 | 1 / 0 | 9.94 | 6.29 | 14.08 | 0.026 | 38.45 | -24.37 |

Table 7-1. ERP Data (Band 26)

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 13 of 23 |

| Frequency [MHz] | Channel Bandwidth [MHz] | Mod. | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | RB Size/Offset | Substitute Level [dBm] | Ant. Gain [dBi] | ERP [dBm] | ERP [Watts] | ERP Limit [dBm] | Margin [dB] |
|-----------------|-------------------------|--------|-----------------|---------------------|----------------------------|----------------|------------------------|-----------------|--------------|--------------|-----------------|-------------|
| 790.50 | 5 | QPSK | V | 171 | 126 | 1 / 24 | 15.06 | 6.46 | 19.37 | 0.086 | 34.77 | -15.40 |
| 793.00 | 5 | QPSK | V | 159 | 125 | 1 / 24 | 15.32 | 6.52 | 19.69 | 0.093 | 34.77 | -15.08 |
| 795.50 | 5 | QPSK | V | 167 | 128 | 1 / 24 | 15.40 | 6.59 | 19.84 | 0.096 | 34.77 | -14.94 |
| 795.50 | 5 | 16-QAM | V | 167 | 128 | 1 / 0 | 14.07 | 6.59 | 18.51 | 0.071 | 34.77 | -16.27 |
| 795.50 | 5 | 64-QAM | V | 167 | 128 | 1 / 24 | 13.18 | 6.59 | 17.62 | 0.058 | 34.77 | -17.16 |
| 793.00 | 10 | QPSK | V | 168 | 129 | 1 / 49 | 15.35 | 6.52 | 19.72 | 0.094 | 34.77 | -15.05 |
| 793.00 | 10 | 16-QAM | V | 168 | 129 | 1 / 49 | 14.16 | 6.52 | 18.53 | 0.071 | 34.77 | -16.24 |
| 793.00 | 10 | 64-QAM | V | 168 | 129 | 1 / 0 | 13.15 | 6.52 | 17.52 | 0.057 | 34.77 | -17.25 |
| 795.50 | 5 | QPSK | H | 245 | 89 | 1 / 24 | 15.27 | 6.59 | 19.71 | 0.093 | 34.77 | -15.07 |
| 795.50 | 5 (WCP) | QPSK | V | 174 | 107 | 1 / 24 | 9.63 | 6.59 | 14.07 | 0.026 | 34.77 | -20.71 |

Table 7-2. ERP Data (Band 14)

| | | | | |
|--|---|-------------------------------|---|---------------------------------|
| FCC ID: ZNFG820UM |  MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) | |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 14 of 23 |

7.3 Radiated Spurious Emissions Measurements

§2.1053 §90.691 §90.543

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.


Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | Page 15 of 23 | |

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes

1. For CDMA mode, this device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.
2. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. This unit was tested with its standard battery.
4. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
5. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
6. Per 90.543(f), emissions in the 1559 – 1610MHz band are subject to a limit of -40dBm/MHz for wideband signals. These emission measurements are shown in this section below.

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 16 of 23 |

OPERATING FREQUENCY: 817.90 MHz
 CHANNEL: 476
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm



| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 1635.80 | H | 134 | 214 | -67.10 | 3.00 | -64.10 | -51.1 |
| 2453.70 | H | 115 | 351 | -59.11 | 3.73 | -55.38 | -42.4 |
| 3271.60 | H | - | - | -69.54 | 5.98 | -63.56 | -50.6 |
| 4089.50 | H | - | - | -70.83 | 7.56 | -63.26 | -50.3 |

Table 7-2. CDMA BC10 Radiated Spurious Data (Ch. 476)

OPERATING FREQUENCY: 823.10 MHz
 CHANNEL: 684
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 1646.20 | H | 182 | 291 | -67.59 | 3.06 | -64.53 | -51.5 |
| 2469.30 | H | 117 | 10 | -62.06 | 3.78 | -58.28 | -45.3 |
| 3292.40 | H | - | - | -69.32 | 5.99 | -63.33 | -50.3 |
| 4115.50 | H | - | - | -70.73 | 7.65 | -63.08 | -50.1 |

Table 7-3. CDMA BC10 Radiated Spurious Data (Ch. 684)

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 17 of 23 |

OPERATING FREQUENCY: 817.90 MHz
 CHANNEL: 476
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm



| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 1635.80 | H | 151 | 212 | -66.30 | 3.00 | -63.30 | -50.3 |
| 2453.70 | H | 153 | 12 | -65.06 | 3.73 | -61.33 | -48.3 |
| 3271.60 | H | - | - | -69.79 | 5.98 | -63.81 | -50.8 |
| 4089.50 | H | - | - | -70.30 | 7.56 | -62.74 | -49.7 |

Table 7-4. CDMA BC10 Radiated Spurious Data with WCP (Ch. 684)

OPERATING FREQUENCY: 814.70 MHz
 CHANNEL: 26697
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 1629.40 | V | 216 | 262 | -66.27 | 2.98 | -63.30 | -50.3 |
| 2444.10 | V | 203 | 213 | -64.82 | 3.75 | -61.07 | -48.1 |
| 3258.80 | V | - | - | -68.03 | 5.97 | -62.06 | -49.1 |
| 4073.50 | V | - | - | -68.89 | 7.53 | -61.36 | -48.4 |

Table 7-5. Radiated Spurious Data (LTE Band 26 – Low Channel)

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 18 of 23 |

OPERATING FREQUENCY: 823.30 MHz
 CHANNEL: 26783
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 1646.60 | V | 220 | 308 | -64.97 | 3.06 | -61.91 | -48.9 |
| 2469.90 | V | 291 | 214 | -63.20 | 3.78 | -59.42 | -46.4 |
| 3293.20 | V | - | - | -67.87 | 6.00 | -61.88 | -48.9 |
| 4116.50 | V | - | - | -69.62 | 7.65 | -61.96 | -49.0 |

Table 7-6. Radiated Spurious Data (LTE Band 26 – High Channel)

OPERATING FREQUENCY: 823.30 MHz
 CHANNEL: 26783
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 1646.60 | V | 160 | 201 | -68.97 | 3.06 | -65.91 | -52.9 |
| 2469.90 | V | 264 | 114 | -67.20 | 3.78 | -63.42 | -50.4 |
| 3293.20 | V | - | - | -67.85 | 6.00 | -61.86 | -48.9 |
| 4116.50 | V | - | - | -70.04 | 7.65 | -62.38 | -49.4 |

Table 7-7. Radiated Spurious Data with WCP (LTE Band 26 - Ch. 26783)

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 19 of 23 |

OPERATING FREQUENCY: 790.50 MHz
 CHANNEL: 23305
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13 dBm



| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 2371.50 | H | 104 | 307 | -61.40 | 3.81 | -57.59 | -44.6 |
| 3162.00 | H | - | - | -68.61 | 5.83 | -62.78 | -49.8 |
| 3952.50 | H | - | - | -68.86 | 7.27 | -61.59 | -48.6 |

Table 7-8. Radiated Spurious Data (LTE Band 14 – Low Channel)

OPERATING FREQUENCY: 793.00 MHz
 CHANNEL: 23330
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13 dBm

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 2379.00 | H | 170 | 356 | -61.24 | 3.77 | -57.48 | -44.5 |
| 3172.00 | H | - | - | -68.55 | 5.86 | -62.69 | -49.7 |
| 3965.00 | H | - | - | -69.26 | 7.29 | -61.97 | -49.0 |

Table 7-9. Radiated Spurious Data (LTE Band 14 – Mid Channel)

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 20 of 23 |

OPERATING FREQUENCY: 795.50 MHz
 CHANNEL: 2335
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13 dBm



| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 2386.50 | H | 100 | 358 | -61.04 | 3.78 | -57.26 | -44.3 |
| 3182.00 | H | - | - | -68.23 | 5.88 | -62.35 | -49.4 |
| 3977.50 | H | - | - | -69.32 | 7.32 | -62.00 | -49.0 |

Table 7-10. Radiated Spurious Data (LTE Band 14 – High Channel)

MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.00 MHz
 DISTANCE: 3 meters
 NARROWBAND EMISSION LIMIT: -50 dBm
 WIDEBAND EMISSION LIMIT: -40 dBm/MHz

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 1581.00 | H | 167 | 290 | -67.30 | 2.70 | -64.61 | -24.6 |
| 1586.00 | H | 167 | 219 | -66.94 | 2.68 | -64.26 | -24.3 |
| 1591.00 | H | 163 | 214 | -66.59 | 2.67 | -63.91 | -23.9 |

Table 7-11. Radiated Spurious Data (LTE Band 14 – Wide Band)

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 21 of 23 |

OPERATING FREQUENCY: 795.50 MHz
 CHANNEL: 23355
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13 dBm

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 2386.50 | H | 165 | 129 | -57.12 | 3.78 | -53.34 | -40.3 |
| 3182.00 | H | - | - | -67.90 | 5.88 | -62.02 | -49.0 |
| 3977.50 | H | - | - | -69.68 | 7.32 | -62.36 | -49.4 |

Table 7-12. Radiated Spurious Data with WCP (LTE Band 14)

MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.00 MHz
 DISTANCE: 3 meters
 NARROWBAND EMISSION LIMIT: -50 dBm
 WIDEBAND EMISSION LIMIT: -40 dBm/MHz

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Level at Antenna Terminals [dBm] | Substitute Antenna Gain [dBi] | Spurious Emission Level [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------------------|-------------------------------|-------------------------------|-------------|
| 1591.00 | H | 282 | 29 | -63.34 | 2.67 | -60.66 | -20.7 |

Table 7-13. Radiated Spurious Data with WCP (LTE Band 14 – Wide Band)

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 22 of 23 |

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFG820UM** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

| | | | | |
|--|---|--|---|---------------------------------|
| FCC ID: ZNFG820UM |  | MEASUREMENT REPORT (CLASS II PERMISSIVE CHANGE) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1901080002-04-R1.ZNF | Test Dates: 1/15/2019 - 2/7/2019 | EUT Type: Portable Handset | | Page 23 of 23 |