

## SAR TEST REPORT

For

Bluebird Inc.

LTE Phone

Model No.: SF550

Prepared for : Bluebird Inc.  
Address : SEI Tower 13~14F, 467-14, Dogok-dong, Gangnam-gu,  
Seoul 135-856, Korea

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an  
Avenue, Bao'an District, Shenzhen, Guangdong, China  
Tel : (86)755-82591330  
Fax : (86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : December 16, 2015  
Number of tested samples : 1  
Serial number : Prototype  
Date of Test : December 16, 2015 –December 23, 2015  
Date of Report : January 15, 2016

**SAR TEST REPORT****Report Reference No. .... : LCS1512161382E**

Date Of Issue ..... : January 15, 2016

**Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.**Address ..... : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,  
Bao'an District, Shenzhen, Guangdong, ChinaTesting Location/ Procedure..... : Full application of Harmonised standards ☒  
Partial application of Harmonised standards ☐  
Other standard testing method ☐**Applicant's Name..... : Bluebird Inc.**Address ..... : SEI Tower 13~14F, 467-14, Dogok-dong, Gangnam-gu, Seoul  
135-856, Korea**Test Specification:**

Scaled SAR Max. Values is..... : 0.711 W/Kg (1g) for Head and 0.639 W/Kg (1g) for Body.

Standard ..... : IEEE 1528:2013/KDB865664  
47CFR §2.1093

Test Report Form No. .... : LCSEMC-1.0

TRF Originator ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF ..... : Dated 2014-09


**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description. .... : LTE Phone**

Trade Mark ..... : Bluebird

Model/Type Reference ..... : SF550

Operation Frequency ..... : GSM 850/PCS1900, WCDMA Band II/V, LTE Band2/4/5/17,  
WLAN2.4G/5G, Bluetooth4.0Modulation Type ..... : GSM(GMSK,8PSK), WCDMA/HSDPA/HSUPA(QPSK),  
LTE(QPSK,16QAM), WIFI(DSSS,OFDM),  
Bluetooth(GFSK,8DPSK,PI/4DQPSK)Ratings ..... : DC 3.8V by Lithium ion polymer battery(2600mAh)  
Recharged by DC 5V/1A Travel Charger**Result ..... : Positive****Compiled by:****Supervised by:****Approved by:**

Cherry Chen/ File administrators

Glin Lu/ Technique principal

Gavin Liang/ Manager

## SAR -- TEST REPORT

**Test Report No. : LCS1512161382E**January 15, 2016  
Date of issue

Type / Model..... : SF550

EUT..... : LTE Phone

**Applicant..... : Bluebird Inc.**Address..... : SEI Tower 13~14F, 467-14, Dogok-dong, Gangnam-gu,  
Seoul 135-856, Korea

Telephone..... : /

Fax..... : /

**Manufacturer..... : Bluebird Inc.**Address..... : SEI Tower 13~14F, 467-14, Dogok-dong, Gangnam-gu,  
Seoul 135-856, Korea

Telephone..... : /

Fax..... : /

**Factory..... : Bluebird Inc.**Address..... : SEI Tower 13~14F, 467-14, Dogok-dong, Gangnam-gu,  
Seoul 135-856, Korea

Telephone..... : /

Fax..... : /

**Test Result****Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Revision History

Revision	Issue Date	Revisions	Revised By
00	2016-01-15	Initial Issue	Gavin Liang

## TABLE OF CONTENTS

<b>1. TEST STANDARDS AND TEST DESCRIPTION.....</b>	<b>6</b>
1.1. TEST STANDARDS .....	6
1.2. TEST DESCRIPTION.....	6
1.3. GENERAL REMARKS .....	6
1.4. PRODUCT DESCRIPTION .....	6
1.5. STATEMENT OF COMPLIANCE .....	8
<b>2. TEST ENVIRONMENT .....</b>	<b>9</b>
2.1. TEST FACILITY .....	9
2.2. ENVIRONMENTAL CONDITIONS .....	9
2.3. SAR LIMITS .....	9
2.4. EQUIPMENTS USED DURING THE TEST .....	10
<b>3. SAR MEASUREMENTS SYSTEM CONFIGURATION .....</b>	<b>12</b>
3.1. SARMEASUREMENT SET-UP.....	12
3.2. OPENSAR E-FIELD PROBE SYSTEM.....	13
3.3. PHANTOMS .....	14
3.4. DEVICE HOLDER .....	14
3.5. SCANNING PROCEDURE .....	15
3.6. DATA STORAGE AND EVALUATION.....	16
3.7. POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM.....	17
3.8. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS .....	19
3.9. TISSUE EQUIVALENT LIQUID PROPERTIES .....	19
3.10. SYSTEM CHECK .....	20
3.11. SAR MEASUREMENT PROCEDURE .....	22
<b>4. TEST CONDITIONS AND RESULTS.....</b>	<b>28</b>
4.1. CONDUCTED POWER RESULTS .....	28
4.2. MANUFACTURING TOLERANCE .....	38
4.3. TRANSMIT ANTENNAS AND SAR MEASUREMENT POSITION.....	45
4.4. SAR MEASUREMENT RESULTS .....	46
4.5. SIMULTANEOUS TX SAR CONSIDERATIONS .....	54
4.6. SAR MEASUREMENT VARIABILITY .....	58
4.7. GENERAL DESCRIPTION OF TEST PROCEDURES .....	58
4.8. MEASUREMENT UNCERTAINTY (300MHZ-3GHz).....	59
4.9. SYSTEM CHECK RESULTS .....	60
5.1. SAR TEST GRAPH RESULTS.....	74
<b>6. CALIBRATION CERTIFICATES .....</b>	<b>96</b>
5.1 PROBE-EP220 CALIBRATION CERTIFICATE .....	96
5.2 PROBE-EP221 CALIBRATION CERTIFICATE .....	105
5.3 PROBE-EPG214 CALIBRATION CERTIFICATE .....	114
5.4 SID750DIPOLE CALIBRATION CERITICATE .....	124
5.5 SID835DIPOLE CALIBRATION CERITICATE .....	135
5.6 SID1800 DIPOLE CALIBRATION CERTIFICATE.....	146
5.7 SID1900 DIPOLE CALIBRATION CERITICATE.....	157
5.8 SID2450 DIPOLE CALIBRATION CERITICATE.....	168
5.9 SID5-6G DIPOLE CALIBRATION CERITICATE.....	179
<b>7. EUT PHOTOGRAPHS .....</b>	<b>192</b>

# 1. TEST STANDARDS AND TEST DESCRIPTION

## 1.1. Test Standards

[IEEE Std C95.1, 2005](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 KHz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

[IEEE Std 1528™-2013](#): IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

[FCC Part 2.1093 Radiofrequency Radiation Exposure Evaluation](#): Portable Devices

[KDB447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies

[KDB648474 D04, Handset SAR v01r03](#): SAR Evaluation Considerations for Wireless Handsets

[KDB865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04](#): SAR Measurement Requirements for 100 MHz to 6 GHz

[KDB865664 D02 RF Exposure Reporting v01r02](#): RF Exposure Compliance Reporting and Documentation Considerations

[KDB248227 D01 802.11 Wi-Fi SAR v02r02](#): SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

[KDB941225 D01 3G SAR Procedures v03r01](#): 3G SAR MEAUREMENT PROCEDURES

[KDB 941225 D06 Hotspot Mode v02r01](#): SAR EVALUATION PROCEDURES FOR PORTABLE DEVICES WITH WIRELESS ROUTER CAPABILITIES

[KDB 941225 D05 SAR for LTE Devices v02r05](#): SAR Evaluation Considerations for LTE Devices

## 1.2. Test Description

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power . And Test device is identical prototype.

## 1.3. General Remarks

Date of receipt of test sample	:	Dec 16, 2015
Testing commenced on	:	Dec 16, 2015
Testing concluded on	:	Dec 23, 2015

## 1.4. Product Description

The **Bluebird Inc.'s** Model: SF550 or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

General Description	
Product Name:	LTE Phone
Trade Mark:	Bluebird
Model/Type reference:	SF550
Listed Model(s):	SF550
Modulation Type:	GMSK for GSM/GPRS and 8PSK for EGPRS;QPSK for WCDMA; QPSK/16QAM for LTE; DSSS/OFDM for WIFI2.4G and OFDM for WIFI5G; GFSK/8DPSK/π/4DQPSK for Bluetooth
Device category:	Portable Device
Exposure category:	General population/uncontrolled environment
EUT Type:	Production Unit
Hardware Version	P1
Software Version:	B20151124_R0.07
Power supply:	DC 3.8V by Lithium ion polymer battery(2600mAh) Recharged by DC 5V/1A Travel Charger
Hotspot:	Supported, power not reduced when Hotspot open
The EUT is GSM,WCDMA,LTE, mobile phone. the mobile phone is intended for speech and Multimedia Message Service (MMS) transmission. It is equipped with GPRS/EDGE class 12 for GSM850, PCS1900, WCDMA Band II, Band V ,LTE Band2, Band4, Band5, Band17, and Bluetooth, Wi-Fi2.4G, Wi-Fi5.2G, Wi-Fi5.8G and camera functions. For more information see the following datasheet	

Technical Characteristics	
GSM	
Support Networks	GSM, GPRS, EDGE
Support Band	GSM850, PCS1900
Frequency	GSM850: 824.2~848.8MHz GSM1900: 1850.2~1909.8MHz
Power Class:	GSM850:Power Class 5 PCS1900:Power Class 0
Modulation Type:	GMSK for GSM/GPRS; GMSK/8PSK For EGPRS
Antenna Type	PIFA Antenna, -1.0dBi(max.) For GSM 850; -0.5dBi(max.) For GSM 1900
GSM Release Version	R99
GPRS Multislot Class	12
EGPRS Multislot Class	12
DTM Mode	Not Supported
UMTS	
Support Networks	WCDMA RMC12.2K,HSDPA,HSUPA
Operation Band:	WCDMA Band II, Band V
Frequency Range	WCDMA Band II: 1852.4~1907.6MHz WCDMA Band V: 826.4~846.6MHz
Modulation Type:	QPSK for WCDMA/HSUPA/HSDPA
Power Class:	Class 3
WCDMA Release Version:	R99
HSDPA Release Version:	R8
HSUPA Release Version:	R8
DC-HSUPA Release Version:	Not Supported
Antenna Type	PIFA Antenna, -1.0dBi(max.) For Band V; -0.5dBi(max.) For Band II
LTE	
Support Band	LTE Band2, Band4, Band5, Band17
Frequency Range	LTE Band2:1850 ~1910MHz LTE Band4:1710~1755MHz LTE Band5:824 ~849MHz LTE Band17:704~716MHz
Power Class:	Class 3
Modulation Type:	QPSK/16QAM
LTE Release Version:	R8
Antenna Type	PIFA Antenna -0.5dBi(max.) For LTE FDD Band 2;-0.5dBi(max.) For LTE FDD Band 4; -1.0dBi(max.) For LTE FDD Band 5;-1.0dBi(max.) For LTE FDD Band 17
WIFI 2.4G	
Supported Standards:	802.11b/802.11g/802.11n(HT20&HT40)
Operation frequency:	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Channel number:	802.11b/802.11g/802.11n(HT20): 11; 802.11n(HT40): 7
Channel separation:	5MHz
Antenna Description	PIFA Antenna, 0.5dBi(Max.)
WIFI 5G	
Channel Number:	9 Channels for 20MHz Bandwidth (802.11a/n(HT20)) 4 channels for 40MHz Bandwidth (802.11a/n(HT40))
Frequency Range :	5180—5240MHz; 5745—5825MHz
Type of Modulation:	OFDM
Antenna Description	PIFA Antenna, 0.8dBi(Max.)
Bluetooth	
Bluetooth Version:	V4.0
Modulation:	GFSK(1Mbps) , $\pi/4$ -DQPSK(2Mbps), 8DPSK(3Mbps)
Operation frequency:	2402MHz~2480MHz
Channel number:	40/79
Channel separation:	1MHz/2MHz
Antenna Description	PIFA Antenna, 0.5dBi(Max.)

## 1.5. Statement of Compliance

The maximum of results of SAR found during testing for SF550 are follows:

<Highest Reported standalone SAR Summary>

Classment Class	Frequency Band	Head (Report 1g SAR(W/Kg))	Hotspot (Report 1g SAR(W/Kg))	Body-worn (Report 1g SAR(W/Kg))
PCE	GSM 850	0.447	0.545	0.482
	GSM1900	0.586	0.656	0.468
	WCDMA Band V	0.322	0.453	0.453
	WCDMA Band II	0.729	0.588	0.588
	LTE Band2	0.423	0.392	0.392
	LTE Band4	<b>0.774</b>	<b>0.696</b>	<b>0.696</b>
	LTE Band5	0.284	0.391	0.391
	LTE Band17	0.205	0.361	0.361
DTS	WIFI2.4G	<b>0.617</b>	<b>0.262</b>	<b>0.262</b>
UNI	WIFI5.2G	0.371	0.125	0.125
	WIFI5.8G	0.413	0.207	0.207

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

<Highest Reported simultaneous SAR Summary>

Exposure Position	Frequency Band	Reported 1-g SAR (W/kg)	Classment Class	Highest Reported Simultaneous Transmission 1-g SAR (W/kg)
Head	LTE Band4	0.774	PCE	<b>1.375</b>
	WLAN2.4G	0.601	DTS	



## 2.TEST ENVIRONMENT

### 2.1. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Site Description

EMC Lab.

: CNAS Registration Number. is L4595.  
FCC Registration Number. is 899208.  
Industry Canada Registration Number. is 9642A-1.  
VCCI Registration Number. is C-4260 and R-3804.  
ESMD Registration Number. is ARCB0108.  
UL Registration Number. is 100571-492.  
TUV SUD Registration Number. is SCN1081.  
TUV RH Registration Number. is UA 50296516-001.

### 2.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	18-25 ° C
Humidity:	40-65 %
Atmospheric pressure:	950-1050mbar

### 2.3. SAR Limits

EXPOSURE LIMITS	FCC Limit (1g Tissue)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average(averaged over the whole body)	0.08	0.4
Spatial Peak(averaged over any 1 g of tissue)	1.6	8.0
Spatial Peak(hands/wrists/ feet/anklesaveraged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

## 2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Type/Model	Serial Number	Calibration	
				Calibration Date	Calibration Due
PC	Lenovo	G5005	MY42081102	N/A	N/A
Signal Generator	Angilent	E4438C	MY42081396	09/25/2015	09/24/2016
Multimeter	Keithley	MiltiMeter 2000	4059164	10/01/2015	09/30/2016
S-parameter Network Analyzer	Agilent	8753ES	US38432944	09/25/2015	09/24/2016
Wireless Communication Test Set	R & S	CMU200	105988	09/25/2015	09/24/2016
Wideband Radia Communication Tester	R&S	CMW500	1201.0002K50	03/06/2015	03/05/2016
Power Meter	Agilent	E4407B	MY41440754	09/25/2015	09/24/2016
E-Field PROBE	SATIMO	SSE5	SN 17/14 EP220	10/01/2015	09/30/2016
E-Field PROBE	SATIMO	SSE5	SN 17/14 EP221	09/01/2015	08/31/2016
E-Field PROBE	SATIMO	SSE5	SN 17/14 EPG214	10/01/2015	09/31/2016
DIPOLE 750	SATIMO	SID 750	SN 30/14 DIP 0G750-331	10/01/2015	09/30/2016
DIPOLE 835	SATIMO	SID 835	SN 07/14 DIP 0G835-303	10/01/2015	09/30/2016
DIPOLE 1800	SATIMO	SID 1800	SN 07/14 DIP 1G800-301	10/01/2015	9/30/2016
DIPOLE 1900	SATIMO	SID 1900	SN 30/14 DIP 1G900-333	09/01/2015	08/31/2016
DIPOLE 2450	SATIMO	SID 2450	SN 07/14 DIP 2G450-306	10/01/2015	09/30/2016
DIPOLE 5-6G	SATIMO	SID 5G	SN 13/14 WAG32	10/01/2015	09/30/2016
COMOSAR OPEN Coaxial Probe	SATIMO	OCPG 68	SN 40/14 OCPG68	10/01/2015	09/30/2016
Communication Antenna	SATIMO	ANTA57	SN 39/14 ANTA57	10/01/2015	09/30/2016
Mobile Phone POSITIONING DEVICE	SATIMO	MSH98	SN 40/14 MSH98	N/A	N/A
DUMMY PROBE	SATIMO	DP60	SN 03/14 DP60	N/A	N/A
SAM PHANTOM	SATIMO	SAM117	SN 40/14 SAM117	N/A	N/A
Simulated Tissue 900 MHz Body and Head	SATIMO	SAM-9-H	SN 21/14 HLD438	Each Time	N/A
Simulated Tissue 1800 MHz For Head	SATIMO	SAM-18-H	SN 21/14 HLF439	Each Time	N/A
Simulated Tissue 1900 MHz For Head	SATIMO	SAM-18-H	SN 21/14 HLF439	Each Time	N/A
Simulated Tissue 2450 MHz Body and Head	SATIMO	SAM-24-H	SN 21/14 HLJ445	Each Time	N/A
PHANTOM TABLE	SATIMO	TABP98	SN 40/14 TABP98	N/A	N/A

6 AXIS ROBOT	KUKA	KR6-R900	501217	N/A	N/A
High Power Solid State Amplifier (80MHz~1000MHz)	Instruments for Industry	CMC150	M631-0627	09/25/2015	09/24/2016
Medium Power Solid State Amplifier (0.8~4.2GHz)	Instruments for Industry	S41-25	M629-0539	09/25/2015	09/24/2016
Wave Tube Amplifier 48 GHz at 20Watt	Hughes Aircraft Company	1277H02F000	102	09/25/2015	09/24/2016

## Note:

- 1) Per KDB865664D01 requirements for dipole calibration, the test laboratory has adopted three year extended calibration interval. Each measured dipole is expected to evaluate with following criteria at least on annual interval.
  - a) There is no physical damage on the dipole;
  - b) System check with specific dipole is within 10% of calibrated values;
  - c) The most recent return-loss results, measured at least annually, deviates by no more than 20% from the previous measurement;
  - d) The most recent measurement of the real or imaginary parts of the impedance, measured at least annually is within  $5\Omega$  from the previous measurement.
- 2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

### 3.SAR MEASUREMENTS SYSTEM CONFIGURATION

#### 3.1. SARMeasurement Set-up

The OPENSAR system for performing compliance tests consist of the following items:

A standard high precision 6-axis robot (KUKA) with controller and software.

KUKA Control Panel (KCP)

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with a Video Positioning System(VPS).

The stress sensor is composed with mechanical and electronic when the electronic part detects a change on the electro-mechanical switch,It sends an "Emergency signal" to the robot controller that to stop robot's moves

A computer operating Windows XP.

OPENSAR software


Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.

The SAM phantom enabling testing left-hand right-hand and body usage.

The Position device for handheld EUT

Tissue simulating liquid mixed according to the given recipes .

System validation dipoles to validate the proper functioning of the system.



### 3.2. OPENSAR E-field Probe System

The SAR measurements were conducted with the dosimetric probe EP220 (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

#### Probe Specification

Construction Symmetrical design with triangular core

Interleaved sensors

Built-in shielding against static charges

PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

Calibration ISO/IEC 17025 calibration service available.


Frequency	700 MHz to 3 GHz; Linearity: 0.25dB(700 MHz to 3GHz)
Directivity	0.25 dB in HSL (rotation around probe axis) 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	0.01W/kg to > 100 W/kg; Linearity: 0.25 dB
Dimensions	Overall length: 330 mm (Tip: 16mm) Tip diameter: 5 mm (Body: 8 mm) Distance from probe tip to sensor centers: 2.5 mm
Application	General dosimetry up to 3 GHz Dosimetry in strong gradient fields Compliance tests of Mobile Phones



#### Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.


The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



### 3.3. Phantoms

The SAM Phantom SAM117 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is in compliance with the specification set in IEEE P1528 and CENELEC EN62209-1, EN62209-2:2010. The phantom enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.


System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.



SAM Twin Phantom

### 3.4. Device Holder

In combination with the Generic Twin Phantom SAM117, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).



Device holder supplied by SATIMO

### 3.5. Scanning Procedure

The procedure for assessing the peak spatial-average SAR value consists of the following steps

#### Power Reference Measurement

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

#### Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

#### Zoom Scan

Zoom Scans are used to estimate the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan is done by 7x7x7 points within a cube whose base is centered around the maxima found in the preceding area scan.

Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$			$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm*	3 – 4 GHz: $\leq 5$ mm* 4 – 6 GHz: $\leq 4$ mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm
	graded grid	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm
Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB Publication 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

### Power Drift measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have OPENSAR software stop the measurements if this limit is exceeded.

## 3.6. Data Storage and Evaluation

### Data Storage

The OPENSAR software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

### Data Evaluation

The OPENSAR software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
	- Conversion factor	ConvFi
	- Diode compression point	Dcpi
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the OPENSAR components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

With  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$U_i$  = input signal of channel  $i$  ( $i = x, y, z$ )

cf = crest factor of exciting field

dcp<sub>i</sub> = diode compression point

From the compensated input signals the primary field data for each channel can be evaluated:

$$E - \text{fieldprobes : } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$H - \text{fieldprobes : } H_i = \sqrt{V_i \cdot \frac{a_{i0} + c_{i1}f + a_{i2}f^2}{f}}$$

With  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$\text{Norm}_i$  = sensor sensitivity of channel  $i$  ( $i = x, y, z$ )  
[mV/(V/m)²] for E-field Probes

ConvF = sensitivity enhancement in solution



- $a_{ij}$  = sensor sensitivity factors for H-field probes  
 $f$  = carrier frequency [GHz]  
 $E_i$  = electric field strength of channel  $i$  in V/m  
 $H_i$  = magnetic field strength of channel  $i$  in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

- with SAR = local specific absorption rate in mW/g  
 $E_{tot}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

### 3.7. Position of the wireless device in relation to the phantom

#### General considerations

This standard specifies two handset test positions against the head phantom – the “cheek” position and the “tilt” position.


The power flow density is calculated assuming the excitation field as a free space field

$$P_{(pwe)} = \frac{E_{tot}^2}{3770} \text{ or } P_{(pwe)} = H_{tot}^2 \cdot 37.7$$

Where  $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>

$E_{tot}$  = total electric field strength in V/m

$H_{tot}$  = total magnetic field strength in A/m




$w_t$  Width of the handset at the level of the acoustic

$w_b$  Width of the bottom of the handset


A Midpoint of the width  $w_t$  of the handset at the level of the acoustic output

B Midpoint of the width  $w_b$  of the bottom of the handset

Picture 1-a Typical “fixed” case handset    Picture 1-b Typical “clam-shell” case handset



Picture 2 Cheek position of the wireless device on the left side of SAM



Picture 3 Tilt position of the wireless device on the left side of SAM

For body SAR test we applied to FCC KDB941225 D03v01, KDB447498 D01v06, KDB248227 D01v02r02, KDB616217 D04v01r03.

### 3.8. Tissue Dielectric Parameters for Head and Body Phantoms

The liquid is consisted of water,salt,Glycol,Sugar,Preventol and Cellulose.The liquid has previously been proven to be suited for worst-case.It's satisfying the latest tissue dielectric parameters requirements proposed by the KDB865664.

The composition of the tissue simulating liquid

Ingredient (% Weight)	750MHz		835MHz		1800 MHz		1900 MHz		2450MHz		5000MHz	
	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	39.28	51.3	41.45	52.5	54.5	40.2	54.9	40.4	62.7	73.2	65.5	78.6
Preventol	0.10	0.10	0.10	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
HEC	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
DGBE	0.00	0.00	0.00	0.00	45.33	59.31	44.92	59.10	36.80	26.70	0.00	0.00
Triton X-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	17.2	10.7

Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma(S/m)$	$\epsilon_r$	$\sigma(S/m)$
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
2600	39.0	1.96	52.5	2.16
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

### 3.9. Tissue equivalent liquid properties


Dielectric Performance of Head and Body Tissue Simulating Liquid

Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue				Liquid Temp.	Test Data
		$\epsilon_r$	$\sigma$	$\epsilon_r$	Dev.	$\sigma$	Dev.		
750H	750	0.89	42.06	0.86	-3.37	42.21	0.36	21.0	12/16/2015
835H	835	0.89	42.81	0.91	2.25	42.68	-0.30	21.0	12/17/2015
1800H	1800	1.38	41.31	1.36	-1.45	41.13	-0.44	21.0	12/18/2015
1900H	1900	1.42	41.09	1.41	-0.70	41.25	0.39	21.0	12/21/2015
2450H	2450	1.77	39.05	1.79	1.13	39.11	0.15	21.0	12/22/2015
5000H	5200	4.66	36.00	4.63	-0.64	36.18	0.50	21.0	12/23/2015
750B	750	0.99	56.57	0.95	-4.04	56.71	0.25	21.0	12/16/2015
835B	835	0.96	53.46	0.94	-2.08	53.24	-0.41	21.0	12/17/2015
1800B	1800	1.38	53.27	1.33	-3.62	53.09	-0.34	21.0	12/18/2015
1900B	1900	1.54	54.20	1.52	-1.30	54.46	0.48	21.0	12/21/2015
2450B	2450	1.93	52.97	1.94	0.52	52.78	-0.36	21.0	12/22/2015
5000B	5000	5.30	49.00	5.25	-0.94	49.66	1.35	21.0	12/23/2015

### 3.10. System Check

The purpose of the system check is to verify that the system operates within its specifications at the device test frequency. The system check is simple check of repeatability to make sure that the system works correctly at the time of the compliance test;

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ( $\pm 10\%$ ).



The output power on dipole port must be calibrated to 20 dBm (100mW) before dipole is connected.



Photo of Dipole Setup

Mixture Type	Frequency (MHz)	Power	SAR <sub>1g</sub> (W/Kg)	SAR <sub>10g</sub> (W/Kg)	Drift (%)	1W Target		Difference percentage		Liquid Temp	Date
						SAR <sub>1g</sub> (W/Kg)	SAR <sub>10g</sub> (W/Kg)	1g	10g		
Head	750	100 mW	0.840	0.551	2.15	8.38	5.53	0.24	-0.36	21.0	12/16/2015
		Normalize to 1 Watt	8.40	5.51							
Body	750	100 mW	0.875	0.574	-0.87	8.77	5.78	-0.23	-0.69	21.0	12/16/2015
		Normalize to 1 Watt	8.75	5.74							
Head	835	100 mW	0.955	0.623	3.01	9.60	6.20	-0.52	0.48	21.0	12/17/2015
		Normalize to 1 Watt	9.55	6.23							
Body	835	100 mW	0.987	0.634	1.45	9.90	6.39	-0.30	-0.78	21.0	12/17/2015
		Normalize to 1 Watt	9.87	6.34							
Head	1800	100 mW	3.816	2.027	0.78	38.13	20.20	0.08	0.35	21.0	12/18/2015
		Normalize to 1 Watt	38.16	20.27							
Body	1800	100 mW	3.895	2.059	-0.44	39.03	20.65	-0.20	-0.29	21.0	12/18/2015
		Normalize to 1 Watt	38.95	20.59							
Head	1900	100 mW	3.977	2.014	2.16	39.84	20.20	-0.18	-0.30	21.0	12/21/2015
		Normalize to 1 Watt	39.77	20.14							
Body	1900	100 mW	4.338	2.146	0.97	43.33	21.59	0.12	-0.60	21.0	12/21/2015
		Normalize to 1 Watt	43.38	21.46							
Head	2450	100 mW	5.392	2.422	-3.14	53.89	24.15	0.06	0.29	21.0	12/22/2015
		Normalize to 1 Watt	53.92	24.22							
Body	2450	100 mW	5.457	2.463	4.32	54.65	24.58	-0.15	0.20	21.0	12/22/2015
		Normalize to 1 Watt	54.57	24.63							
Head	5200	100 mW	16.264	5.614	-0.07	163.88	57.29	-0.76	-2.01	21.0	12/23/2015
		Normalize to 1 Watt	162.64	56.14							
Body	5200	100 mW	15.439	5.332	2.56	158.49	55.40	-2.59	-3.75	21.0	12/23/2015
		Normalize to 1 Watt	154.39	53.32							
Head	5800	100 mW	18.006	5.893	1.58	181.20	61.50	-0.63	-4.18	21.0	12/24/2015
		Normalize to 1 Watt	180.06	58.93							
Body	5800	100 mW	18.971	5.827	-0.33	183.06	61.62	3.63	-2.19	21.0	12/24/2015
		Normalize to 1 Watt	189.71	60.27							

### 3.11. SAR measurement procedure

The measurement procedures are as follows:

#### 3.11.1 Conducted power measurement

- a. For WWAN power measurement, use base station simulator connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- b. Read the WWAN RF power level from the base station simulator.
- c. For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously Transmission, at maximum RF power in each supported wireless interface and frequency band.
- d. Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power.

#### 3.11.2 GSM Test Configuration

SAR tests for GSM 850 and GSM 1900, a communication link is set up with a System Simulator (SS) by air link. Using CMU200 the power level is set to "5" for GSM 850, set to "0" for GSM 1900. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5. the EGPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5.

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. GSM voice and GPRS data use GMSK, which is a constant amplitude modulation with minimal peak to average power difference within the time-slot burst. For EDGE, GMSK is used for MCS 1 – MCS 4 and 8-PSK is used for MCS 5 – MCS 9; where 8-PSK has an inherently higher peak-to-average power ratio. The GMSK and 8-PSK EDGE configurations are considered separately for SAR compliance. The GMSK EDGE configurations are grouped with GPRS and considered with respect to time-averaged maximum output power to determine compliance. The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode.

### 3.11.3 UMTS Test Configuration

#### 3G SAR Test Reduction Procedure

In the following procedures, the mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq \frac{1}{4}$  dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the secondary mode.<sup>3</sup> This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as “otherwise” in the applicable procedures; SAR measurement is required for the secondary mode.

#### Output power Verification

Maximum output power is verified on the high, middle and low channels according to procedures described in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1’s” for WCDMA/HSDPA or by applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA) are required in the SAR report. All configurations that are not supported by the handset or cannot be measured due to technical or equipment limitations must be clearly identified.

#### Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

1)

#### 2) Body-Worn Accessory SAR

SAR for body-worn accessory configurations is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCHn, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When more than 2 DPDCHn are supported by the handset, it may be necessary to configure additional DPDCHn using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC.

#### 3) Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn accessory configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices” section of this document, for the highest reported SAR body-worn accessory exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

HSDPA should be configured according to the UE category of a test device. The number of HSDSCH/ HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors ( $\beta_c$ ,  $\beta_d$ ), and HS-DPCCH power offset parameters ( $\Delta_{ACK}$ ,  $\Delta_{NACK}$ ,  $\Delta_{CQI}$ ) should be set according to values indicated in the Table below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

**Table 2: Subtests for UMTS Release 5 HSDPA**

Sub-set	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}$ (note 1, note 2)	CM(dB) (note 3)	MPR(dB)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (note 4)	15/15 (note 4)	64	12/15 (note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Rightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Rightarrow \beta_{hs} = 30/15 * \beta_c$   
Note2: CM=1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ .  
Note3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TFC1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

**HSUPA Test Configuration**

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn accessory configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the "Release 6 HSPA Data Devices" section of this document, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn accessory measurements is tested for next to the ear head exposure.

Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the  $\beta$  values indicated in Table 2 and other applicable procedures described in the 'WCDMA Handset' and 'Release 5 HSDPA Data Devices' sections of this document

**Table 3: Sub-Test 5 Setup for Release 6 HSUPA**

Sub-set	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	$\beta_{ec}$	$\beta_{ed}$	$\beta_{ed}$ (SF)	$\beta_{ed}$ (codes)	CM <sup>(2)</sup> (dB)	MPR (dB)	AG <sup>(4)</sup> Index	E-TFCI
1	11/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	11/15 <sup>(3)</sup>	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 <sup>(4)</sup>	15/15 <sup>(4)</sup>	64	15/15 <sup>(4)</sup>	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Rightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Rightarrow \beta_{hs} = 30/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Figure 5.1g.

Note 6:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.



### 3.11.4 LTE Test Configuration

#### QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel.<sup>8</sup> When the reported SAR of a required test channel is  $> 1.45$  W/kg, SAR is required for all three RB offset configurations for that required test channel.

#### QPSK with 50% RB allocation

The procedures required for 1 RB allocation in section 4.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.<sup>9</sup>

#### QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in sections 4.2.1 and 4.2.2 are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.

### 3.11.5 WIFI Test Configuration

The SAR measurement and test reduction procedures are structured according to either the DSSS or OFDM transmission mode configurations used in each standalone frequency band and aggregated band. For devices that operate in exposure configurations that require multiple test positions, additional SAR test reduction may be applied. The maximum output power specified for production units, including tune-up tolerance, are used to determine initial SAR test requirements for the 802.11 transmission modes in a frequency band. SAR is measured using the highest measured maximum output power channel for the initial test configuration. SAR measurement and test reduction for the remaining 802.11 modes and test channels are determined according to measured or specified maximum output power and reported SAR of the initial measurements. The general test reduction and SAR measurement approaches are summarized in the following:

1. The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures. Channels with measured maximum output power within  $\frac{1}{4}$  dB are considered to have the same maximum output.
2. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, an "initial test configuration" is first determined for each standalone and aggregated frequency band according to the maximum output power and tune-up tolerance specified for production units.
  - a. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.
  - b. SAR is measured for OFDM configurations using the initial test configuration procedures. Additional frequency band specific SAR test reduction may be considered for individual frequency bands
  - c. Depending on the reported SAR of the highest maximum output power channel tested in the initial test configuration, SAR test reduction may apply to subsequent highest output channels in the initial test configuration to reduce the number of SAR measurements.
3. The Initial test configuration does not apply to DSSS. The 2.4 GHz band SAR test requirements and 802.11b DSSS procedures are used to establish the transmission configurations required for SAR measurement.
4. An "initial test position" is applied to further reduce the number of SAR tests for devices operating in next to the ear, UMPC mini-tablet or hotspot mode exposure configurations that require multiple test positions .
  - a. SAR is measured for 802.11b according to the 2.4 GHz DSSS procedure using the exposure condition established by the initial test position.
  - b. SAR is measured for 2.4 GHz and 5 GHz OFDM configurations using the initial test configuration. 802.11b/g/n operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g/n modes are tested on the maximum average output channel.
5. The Initial test position does not apply to devices that require a fixed exposure test position. SAR is measured in a fixed exposure test position for these devices in 802.11b according to the 2.4 GHz DSSS procedure or in 2.4 GHz and 5 GHz OFDM configurations using the initial test configuration procedures .
6. The "subsequent test configuration" procedures are applied to determine if additional SAR measurements are required for the remaining OFDM transmission modes that have not been tested in the initial test configuration.

SAR test exclusion is determined according to reported SAR in the initial test configuration and maximum output power specified or measured for these other OFDM configurations.

#### 2.4 GHz and 5GHz SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in section 5.2.2.

##### 1. 802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- a. When the reported SAR of the highest measured maximum output power channel (section 3.1) for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- b. When the reported SAR is  $> 0.8$  W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

##### 1. 2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3). SAR is not required for the following 2.4 GHz OFDM conditions.

- a. When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration
- b. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

##### 2. SAR Test Requirements for OFDM Configurations

When SAR measurement is required for 802.11 a/g/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements.<sup>20</sup> In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

##### 3. OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

The initial test configuration for 2.4 GHz and 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures (section 4). When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- a. The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- b. If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- c. If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- d. When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.

After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.

- a. Channels with measured maximum output power within  $\frac{1}{4}$  dB of each other are considered to have the same maximum output.
- b. When there are multiple test channels with the same measured maximum output power, the channel closest to mid-band frequency is selected for SAR measurement.

- c. When there are multiple test channels with the same measured maximum output power and equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

#### Initial Test Configuration Procedures

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required (see section 5.3.2). SAR test reduction of subsequent highest output test channels is based on the reported SAR of the initial test configuration. For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode.<sup>23</sup> For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration. When the reported SAR of the initial test configuration is  $> 0.8$  W/kg, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.

#### 4. Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, the procedures in section 5.3.2 are applied to determine the test configuration. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- a. When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- b. When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for that subsequent test configuration.
- c. The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
  - 1). SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
  - 2). SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is  $> 1.2$  W/kg or until all required channels are tested.
    - a) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
    - d. SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
      - 1) replace "subsequent test configuration" with "next subsequent test configuration" (i.e., subsequent next highest specified maximum output power configuration)
      - 2) replace "initial test configuration" with "all tested higher output power configurations."

## 4.TEST CONDITIONS AND RESULTS

### 4.1. Conducted Power Results

Max Conducted power measurement results and power drift from tune-up tolerance provide by manufacturer:

#### Conducted power measurement results for GSM850/PCS1900

GSM 850		Burst Conducted power (dBm)			/	Average power (dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8		128/824.2	190/836.6	251/848.8
GSM		33.08	33.25	33.10	-9.03dB	24.05	24.22	24.07
GPRS (GMSK)	1TX slot	32.97	33.08	33.07	-9.03dB	23.94	24.05	24.04
	2TX slot	30.57	30.62	30.52	-6.02dB	24.55	24.60	24.50
	3TX slot	28.61	28.79	28.73	-4.26dB	24.35	24.53	24.47
	4TX slot	27.44	27.44	27.44	-3.01dB	24.43	24.43	24.43
EGPRS (8PSK)	1TX slot	26.71	26.78	26.74	-9.03dB	17.68	17.75	17.71
	2TX slot	23.96	24.13	24.04	-6.02dB	17.94	18.11	18.02
	3TX slot	22.06	22.11	22.08	-4.26dB	17.80	17.85	17.82
	4TX slot	20.76	20.86	20.81	-3.01dB	17.75	17.85	17.80
GSM 1900		Burst Conducted power (dBm)			/	Average power (dBm)		
		Channel/Frequency(MHz)				Channel/Frequency(MHz)		
		512/ 1850.2	661/ 1880	810/ 1909.8		512/ 1850.2	661/ 1880	810/ 1909.8
GSM		30.05	30.13	30.08	-9.03dB	21.02	21.10	21.05
GPRS (GMSK)	1TX slot	29.96	29.97	29.87	-9.03dB	20.93	20.94	20.84
	2TX slot	27.69	27.88	27.85	-6.02dB	21.67	21.86	21.83
	3TX slot	26.13	26.22	26.19	-4.26dB	21.87	21.96	21.93
	4TX slot	24.70	24.82	24.73	-3.01dB	21.69	21.81	21.72
EGPRS (8PSK)	1TX slot	25.81	25.87	25.76	-9.03dB	16.78	16.84	16.73
	2TX slot	23.50	23.55	23.52	-6.02dB	17.48	17.53	17.50
	3TX slot	21.54	21.72	21.58	-4.26dB	17.28	17.46	17.32
	4TX slot	19.63	19.71	19.66	-3.01dB	16.62	16.70	16.65

#### Notes:

##### 1. Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.00dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.00dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.00dB

2. According to the conducted power as above, the GPRS measurements are performed with 2Txslot for GPRS850 and 3Txslot GPRS1900.

## Conducted Power Measurement Results(WCDMA Band II/V)

Item	band	WCDMA Band II result (dBm)			WCDMA Band V result (dBm)		
		Channel/Frequency(MHz)			Channel/Frequency(MHz)		
	ARFCN	9262/1852.4	9400/1880	9538/1907.6	4132/826.4	4183/836.6	4233/846.6
RMC	12.2kbps RMC	23.41	23.55	23.51	23.51	23.63	23.56
	64kbps RMC	23.35	23.50	23.46	23.42	23.57	23.48
	144kbps RMC	23.31	23.42	23.45	23.41	23.54	23.40
	384kbps RMC	23.28	23.36	23.44	23.36	23.46	23.36
HSDPA	Sub - Test 1	23.19	23.26	23.18	23.21	23.36	23.32
	Sub - Test 2	22.38	22.50	22.49	22.36	22.56	22.41
	Sub - Test 3	21.80	21.94	21.82	21.85	21.97	21.89
	Sub - Test 4	21.30	21.44	21.40	21.40	21.53	21.50
HSUPA	Sub - Test 1	22.46	22.52	22.42	22.51	22.63	22.51
	Sub - Test 2	21.18	21.22	21.18	21.23	21.30	21.25
	Sub - Test 3	21.86	21.87	21.90	21.89	21.95	21.91
	Sub - Test 4	20.74	20.81	20.78	20.75	20.95	20.89
	Sub - Test 5	21.21	21.32	21.27	21.23	21.32	21.26

**Note:** When the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq 1/2$ dB higher than the primary mode (RMC12.2kbps) or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the secondary mode.

## LTE Band2

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
1.4	1850.7	1	0	21.20	19.30
		1	3	21.26	19.36
		1	5	21.29	19.35
		3	0	21.20	19.64
		3	2	21.25	19.54
		3	3	21.18	19.49
		6	0	20.19	19.31
	1880.0	1	0	21.12	20.36
		1	3	21.19	20.73
		1	5	21.01	20.50
		3	0	21.16	20.78
		3	2	21.20	20.84
		3	3	21.14	20.79
		6	0	20.14	19.65
	1909.3	1	0	20.99	20.03
		1	3	20.99	20.06
		1	5	20.99	20.03
		3	0	21.08	20.74
		3	2	21.03	20.71
		3	3	21.01	20.73
		6	0	20.06	20.02

3	1851.5	1	0	21.35	20.21
		1	7	21.42	20.34
		1	14	21.54	20.32
		8	0	20.34	19.43
		8	4	20.48	19.52
		8	7	20.40	19.45
		15	0	20.35	19.41
	1880.0	1	0	21.67	20.51
		1	7	21.52	20.51
		1	14	21.55	20.46
		8	0	20.72	19.62
		8	4	20.73	19.64
		8	7	20.60	19.62
		15	0	20.68	19.58
	1908.5	1	0	21.35	20.19
		1	7	21.36	20.30
		1	14	21.46	20.40
		8	0	20.39	20.81
		8	4	20.41	20.86
		8	7	20.43	20.78
		15	0	20.35	20.96
5	1852.5	1	0	21.47	20.10
		1	12	21.55	20.16
		1	24	21.18	20.69
		12	0	20.18	19.08
		12	6	20.03	19.13
		12	13	21.51	20.57
		25	0	21.47	20.51
	1880.0	1	0	20.73	20.13
		1	12	21.28	20.77
		1	24	21.04	20.66
		12	0	20.14	19.37
		12	6	20.29	19.37
		12	13	20.13	19.19
		25	0	20.19	19.07
	1907.5	1	0	20.26	19.31
		1	12	20.10	19.66
		1	24	20.20	19.73
		12	0	20.28	19.13
		12	6	20.88	19.80
		12	13	20.14	19.05
		25	0	20.31	19.42
10	1855.0	1	0	20.99	19.95
		1	24	21.26	20.27
		1	49	21.76	20.12
		25	0	21.51	20.47
		25	12	21.23	20.29
		25	25	21.11	20.18
		50	0	21.27	20.32
	1880.0	1	0	21.02	19.36
		1	24	21.12	20.49
		1	49	20.66	20.14
		25	0	20.39	19.26
		25	12	20.13	19.11
		25	25	20.17	18.93
		50	0	20.07	19.03
	1905.0	1	0	20.10	19.40
		1	24	20.27	19.80
		1	49	20.11	19.23
		25	0	20.50	18.58
		25	12	20.22	19.39

		25	25	20.48	19.98
		50	0	20.23	19.24
15	1857.5	1	0	19.53	18.43
		1	37	20.90	18.63
		1	74	19.04	18.49
		37	0	19.77	18.80
		37	18	19.60	18.65
		37	38	19.70	18.89
		75	0	19.68	18.68
	1880.0	1	0	19.31	18.73
		1	37	20.45	19.51
		1	74	19.93	19.07
		37	0	19.90	18.88
		37	18	19.50	18.57
		37	38	19.33	18.28
		75	0	19.55	18.45
	1902.5	1	0	19.39	18.84
		1	37	18.99	18.42
		1	74	19.77	18.88
		37	0	19.00	18.14
		37	18	19.07	18.25
		37	38	19.72	18.99
		75	0	19.32	18.39
20	1860.0	1	0	19.16	17.98
		1	49	20.48	19.09
		1	99	20.25	19.30
		50	0	19.83	18.86
		50	25	20.17	19.17
		50	50	20.42	19.34
		100	0	20.18	19.12
	1880.0	1	0	20.85	19.04
		1	49	20.40	19.26
		1	99	20.26	18.97
		50	0	19.21	18.15
		50	25	19.21	18.09
		50	50	19.11	18.03
		100	0	19.16	18.14
	1900.0	1	0	20.56	19.50
		1	49	20.43	19.36
		1	99	19.92	19.08
		50	0	19.79	18.84
		50	25	20.14	19.24
		50	50	20.42	19.47
		100	0	20.01	18.97

## LTE Band4

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
1.4	1710.7	1	0	21.63	20.57
		1	3	21.66	20.57
		1	5	21.61	20.55
		3	0	21.64	20.70
		3	2	21.73	20.69
		3	3	21.59	20.67
		6	0	20.68	19.59
	1732.5	1	0	21.01	19.82
		1	3	21.02	19.88
		1	5	20.98	19.83
		3	0	21.03	20.04
		3	2	21.13	20.11
		3	3	21.01	20.02
		6	0	21.09	20.00
	1754.3	1	0	21.64	20.72
		1	3	21.65	20.75
		1	5	21.54	20.73
		3	0	21.64	20.53
		3	2	21.71	20.44
		3	3	21.68	20.47
		6	0	20.64	19.73
3	1711.5	1	0	21.56	20.06
		1	7	21.53	20.06
		1	14	21.65	20.11
		8	0	20.54	19.68
		8	4	20.65	19.71
		8	7	20.60	19.70
		15	0	20.67	19.68
	1732.5	1	0	20.94	19.87
		1	7	20.95	19.92
		1	14	21.08	19.99
		8	0	20.53	19.10
		8	4	20.51	19.08
		8	7	20.50	19.10
		15	0	20.53	19.08
	1753.5	1	0	21.72	20.11
		1	7	21.54	20.01
		1	14	21.56	20.01
		8	0	20.74	19.69
		8	4	20.73	19.63
		8	7	20.58	19.62
		15	0	20.65	19.63
5	1712.0	1	0	21.05	19.98
		1	12	21.09	20.02
		1	24	20.96	19.90
		12	0	20.68	19.78
		12	6	20.65	19.82
		12	13	20.63	19.79
		25	0	20.62	19.69
	1732.5	1	0	21.02	19.83
		1	12	20.99	19.97
		1	24	21.13	19.97
		12	0	20.09	19.14
		12	6	19.99	19.19
		12	13	20.10	19.21
		25	0	20.04	19.05
	1752.5	1	0	21.40	19.95
		1	12	21.29	19.82



		1	24	21.19	19.76
		12	0	20.72	19.73
		12	6	20.76	19.78
		12	13	20.64	19.67
		25	0	20.71	19.98
10	1715.0	1	0	21.04	20.05
		1	24	21.01	20.03
		1	49	20.59	19.75
		25	0	21.11	20.14
		25	12	21.03	20.11
		25	25	20.90	20.01
		50	0	20.96	20.07
	1732.5	1	0	21.20	20.41
		1	24	21.49	20.44
		1	49	21.66	20.59
		25	0	20.50	19.48
		25	12	20.55	19.54
		25	25	20.62	19.61
		50	0	20.43	19.51
	1750.0	1	0	21.63	19.57
		1	24	21.73	19.66
		1	49	21.50	19.47
		25	0	20.65	19.73
		25	12	20.65	19.69
		25	25	20.64	19.63
		50	0	20.56	19.59
15	1717.5	1	0	20.52	19.90
		1	37	20.31	19.79
		1	74	19.88	19.46
		37	0	19.50	19.05
		37	18	19.34	18.91
		37	38	19.14	18.73
		75	0	19.26	18.83
	1732.5	1	0	19.82	19.52
		1	37	20.00	19.46
		1	74	20.38	19.75
		37	0	19.87	18.42
		37	18	19.94	18.51
		37	38	20.17	18.70
		75	0	19.93	18.44
	1747.5	1	0	20.36	19.86
		1	37	20.57	19.07
		1	74	20.53	19.05
		37	0	19.41	19.02
		37	18	19.47	19.03
		37	38	19.56	19.02
		75	0	19.43	18.97
20	1720.0	1	0	20.87	19.61
		1	49	20.96	19.56
		1	99	20.08	19.18
		50	0	19.90	18.85
		50	25	19.71	18.67
		50	50	19.43	18.46
		100	0	19.69	18.69
	1732.5	1	0	20.42	19.51
		1	49	20.71	19.42
		1	99	21.07	19.71
		50	0	19.43	18.41
		50	25	19.52	18.43
		50	50	19.61	18.55

	1745.0	100	0	19.54	18.52
		1	0	20.18	19.77
		1	49	20.26	19.39
		1	99	20.04	19.15
		50	0	19.72	18.79
		50	25	19.95	19.04
		50	50	20.02	19.09
		100	0	19.91	18.97

**LTE Band5**

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
1.4	824.7	1	0	21.13	19.58
		1	3	21.07	19.61
		1	5	20.93	19.53
		3	0	21.04	19.71
		3	2	21.07	19.70
		3	3	21.02	19.69
		6	0	20.39	18.49
		1	0	20.98	19.44
	836.5	1	3	21.02	19.44
		1	5	20.92	19.46
		3	0	21.00	19.60
		3	2	20.99	19.55
		3	3	20.98	19.67
		6	0	20.12	18.50
		1	0	20.98	19.67
		1	3	21.04	19.76
	848.3	1	5	20.88	19.71
		3	0	21.09	19.56
		3	2	21.12	19.55
		3	3	20.96	19.50
		6	0	20.13	18.72
		1	0	21.58	20.48
		1	7	21.54	20.44
		1	14	21.40	20.40
3	825.5	8	0	20.54	19.49
		8	4	20.55	19.45
		8	7	20.49	19.47
		15	0	20.51	19.45
		1	0	21.52	20.51
		1	7	21.50	20.41
		1	14	21.54	20.43
		8	0	20.63	19.59
	836.5	8	4	20.54	19.59
		8	7	20.52	19.50
		15	0	20.64	19.60
		1	0	21.54	20.37
		1	7	21.49	20.36
		1	14	21.33	20.37
		8	0	20.63	19.52
		8	4	20.45	19.43
	847.5	8	7	20.57	19.44
		15	0	20.57	19.49

5	826.5	1	0	21.56	20.73
		1	12	21.57	20.49
		1	24	21.29	20.30
		12	0	20.52	19.63
		12	6	20.54	19.57
		12	13	20.53	19.52
		25	0	20.50	19.49
	836.5	1	0	21.50	20.46
		1	12	21.60	20.43
		1	24	21.50	20.39
		12	0	20.60	19.67
		12	6	20.60	19.70
		12	13	20.59	19.64
		25	0	20.61	19.53
	846.5	1	0	21.59	20.25
		1	12	21.54	20.19
		1	24	21.53	20.06
		12	0	20.62	19.52
		12	6	20.58	19.57
		12	13	20.39	19.42
		25	0	20.60	19.52
10	829.0	1	0	21.83	20.86
		1	24	21.81	20.86
		1	49	21.40	20.57
		25	0	20.91	19.98
		25	12	20.83	19.81
		25	25	20.73	19.81
		50	0	20.79	19.86
	836.5	1	0	21.00	20.23
		1	24	21.29	20.24
		1	49	21.46	20.39
		25	0	20.30	19.30
		25	12	20.34	19.33
		25	25	20.46	19.45
		50	0	20.27	19.32
	844.0	1	0	21.66	20.86
		1	24	21.71	20.89
		1	49	21.83	20.81
		25	0	20.96	20.04
		25	12	20.95	20.03
		25	25	20.98	19.93
		50	0	20.88	19.93

**LTE Band17**

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
5	706.5	1	0	21.83	20.73
		1	12	21.71	20.76
		1	24	21.74	20.70
		12	0	20.80	19.94
		12	6	20.84	19.94
		12	13	20.85	19.99
		25	0	20.80	19.89
	710.0	1	0	21.90	20.56
		1	12	21.93	20.54
		1	24	21.90	20.57
		12	0	20.84	19.96
		12	6	20.75	19.83
		12	13	20.88	19.88
		25	0	20.78	19.70
	713.5	1	0	21.73	20.75
		1	12	21.85	20.81
		1	24	21.82	20.86
		12	0	20.80	19.85
		12	6	20.83	19.84
		12	13	20.69	19.77
		25	0	20.74	19.85
10	709.0	1	0	21.41	20.39
		1	24	21.34	20.36
		1	49	20.91	20.06
		25	0	20.43	19.51
		25	12	20.39	19.38
		25	25	20.23	19.38
		50	0	20.32	19.35
	710.0	1	0	20.56	19.75
		1	24	20.85	19.77
		1	49	21.02	19.95
		25	0	19.87	18.80
		25	12	19.88	18.87
		25	25	19.93	18.93
		50	0	19.79	18.87
	711.0	1	0	21.46	20.43
		1	24	21.57	20.50
		1	49	21.35	20.29
		25	0	20.49	19.57
		25	12	20.51	19.55
		25	25	20.49	19.45
		50	0	20.38	19.43

**Conducted power measurement of WLAN2.4G**

Mode	Channel	Frequency (MHz)	Worst case Data rate of worst case	Conducted Output Power (dBm)	
				Peak	Average
802.11b	1	2412	1Mbps	17.66	14.43
	6	2437	1Mbps	16.43	13.47
	11	2462	1Mbps	16.71	13.64
802.11g	1	2412	6Mbps	18.85	13.34
	6	2437	6Mbps	16.69	12.64
	11	2462	6Mbps	17.90	13.04
802.11n HT20	1	2412	6.5 Mbps	19.24	13.43
	6	2437	6.5 Mbps	18.16	12.85
	11	2462	6.5 Mbps	18.97	13.33
802.11n HT40	3	2422	13.5 Mbps	21.25	12.93
	6	2437	13.5 Mbps	22.32	13.25
	9	2452	13.5 Mbps	20.57	12.86

**Note:** SAR is not required for the following 2.4 GHz OFDM conditions as the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

**The conducted power measurement results for WLAN(5.2G)**

Mode	Channel	Frequency (MHz)	Conducted Output Power(dBm)
802.11a	36	5180	15.81
	40	5200	15.05
	48	5240	14.97
802.11n(20MHz)	36	5180	14.66
	40	5200	14.53
	48	5240	14.56
802.11n(40MHz)	38	5190	14.89
	46	5230	14.55

**The conducted power measurement results for WLAN(5.8G)**

Mode	Channel	Frequency (MHz)	Conducted Output Power(dBm)
802.11a	149	5745	12.11
	157	5785	12.43
	165	5825	13.78
802.11n(20MHz)	149	5745	12.33
	157	5785	12.28
	165	5825	13.40
802.11n(40MHz)	151	5755	11.99
	159	5795	12.56

**Conducted power measurement of BluetoothV4.0**

Mode	channel	Frequency (MHz)	Conducted output power	
			Peak (dBm)	Average (dBm)
BLE	0	2402	-1.98	-3.05
	19	2440	-1.85	-2.93
	39	2480	-2.43	-3.80
GFSK	0	2402	4.47	3.21
	39	2441	4.13	3.05
	78	2480	5.44	4.19
$\pi/4$ -DQPSK	0	2402	3.50	2.78
	39	2441	3.03	2.64
	78	2480	4.01	3.03
8DPSK	0	2402	3.56	2.79
	39	2441	3.06	2.66
	78	2480	4.12	3.09

Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Bluetooth Turn up Power (dBm)	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
5.0	5	2.45	1.0

Per KDB 447498 D01v05r02, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 1.4 which is  $< 3$ , SAR testing is not required.

## 4.2. Manufacturing tolerance

### GSM Speech

GSM 850 (GMSK) (Burst Average Power)			
Channel	Channel 251	Channel 190	Channel 128
Target (dBm)	33.0	33.0	33.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GSM 1900 (GMSK) (Burst Average Power)			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	30.0	30.0	30.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

GSM 850 GPRS (GMSK) (Burst Average Power)				
Channel		128	190	251
1 Txslot	Target (dBm)	33.0	33.0	33.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
2 Txslot	Target (dBm)	30.0	30.0	30.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
3 Txslot	Target (dBm)	28.0	28.0	28.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
4 Txslot	Target (dBm)	27.0	27.0	27.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
GSM 850 EDGE (8PSK) (Burst Average Power)				
Channel		128	190	251
1 Txslot	Target (dBm)	26.0	26.0	26.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
2 Txslot	Target (dBm)	24.0	24.0	24.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
3 Txslot	Target (dBm)	22.0	22.0	22.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
4 Txslot	Target (dBm)	20.0	20.0	20.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
GSM 1900 GPRS (GMSK) (Burst Average Power)				
Channel		512	661	810
1 Txslot	Target (dBm)	30.0	30.0	30.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
2 Txslot	Target (dBm)	27.0	27.0	27.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
3 Txslot	Target (dBm)	26.0	26.0	26.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
4 Txslot	Target (dBm)	24.0	24.0	24.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
GSM 1900 EDGE (8PSK) (Burst Average Power)				

Channel		512	661	810
1 Txslot	Target (dBm)	25.0	25.0	25.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
2 Txslot	Target (dBm)	23.0	23.0	23.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
3 Txslot	Target (dBm)	21.0	21.0	21.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0
4 Txslot	Target (dBm)	19.0	19.0	19.0
	Tolerance $\pm$ (dB)	1.0	1.0	1.0

**UMTS****UMTS Band V**

Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	23.0	23.0	23.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSDPA(sub-test 1)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	23.0	23.0	23.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSDPA(sub-test 2)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	22.0	22.0	22.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSDPA(sub-test 3)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSDPA(sub-test 4)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSUPA(sub-test 1)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	22.0	22.0	22.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSUPA(sub-test 2)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSUPA(sub-test 3)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSUPA(sub-test 4)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	20.0	20.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band V HSUPA(sub-test 5)</b>			
Channel	Channel 4132	Channel 4183	Channel 4233
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	23.0	23.0	23.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSDPA(sub-test 1)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	23.0	23.0	23.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSDPA(sub-test 2)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538

Target (dBm)	22.0	22.0	22.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSDPA(sub-test 3)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSDPA(sub-test 4)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSUPA(sub-test 1)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	22.0	22.0	22.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSUPA(sub-test 2)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSUPA(sub-test 3)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSUPA(sub-test 4)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	20.0	20.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>UMTS Band II HSUPA(sub-test 5)</b>			
Channel	Channel 9262	Channel 9400	Channel 9538
Target (dBm)	21.0	21.0	21.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

**LTE Band 2**

<b>BW:1.4MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 18607		Channel 18900		Channel 19193	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:1.4MHz [&lt;RB=3&gt;, &lt;RB=6&gt;]</b>						
Channel	Channel 18607		Channel 18900		Channel 19193	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:3MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 18615		Channel 18900		Channel 19185	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:3MHz [&lt;RB=8&gt;, &lt;RB=15&gt;]</b>						
Channel	Channel 18615		Channel 18900		Channel 19185	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:5MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 18625		Channel 18900		Channel 19175	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:5MHz [&lt;RB=12&gt;, &lt;RB=25&gt;]</b>						
Channel	Channel 18625		Channel 18900		Channel 19175	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	20.0	19.0	20.0	19.0



Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:10MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 18650		Channel 18900		Channel 19150	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:10MHz [&lt;RB=25&gt;, &lt;RB=50&gt;]</b>						
Channel	Channel 18650		Channel 18900		Channel 19150	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:15MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 18675		Channel 18900		Channel 19125	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	19.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:15MHz [&lt;RB=37&gt;, &lt;RB=75&gt;]</b>						
Channel	Channel 18675		Channel 18900		Channel 19125	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	19.0	18.0	19.0	18.0	19.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:20MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 18700		Channel 18900		Channel 19100	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:20MHz [&lt;RB=50&gt;, &lt;RB=100&gt;]</b>						
Channel	Channel 18700		Channel 18900		Channel 19100	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	19.5	19.0	19.5	19.0	19.5	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

**LTE Band 4**

<b>BW:1.4MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 19957		Channel 20175		Channel 20393	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:1.4MHz [&lt;RB=3&gt;, &lt;RB=6&gt;]</b>						
Channel	Channel 19957		Channel 20175		Channel 20393	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:3MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 19965		Channel 20175		Channel 20385	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:3MHz [&lt;RB=8&gt;, &lt;RB=15&gt;]</b>						
Channel	Channel 19965		Channel 20175		Channel 20385	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:5MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 19975		Channel 20175		Channel 20375	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:5MHz [&lt;RB=12&gt;, &lt;RB=25&gt;]</b>						
Channel	Channel 19975		Channel 20175		Channel 20375	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM

Target (dBm)	20.0	19.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:10MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 20000		Channel 20175		Channel 20350	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:10MHz [&lt;RB=25&gt;, &lt;RB=50&gt;]</b>						
Channel	Channel 20000		Channel 20175		Channel 20350	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:15MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 20025		Channel 20175		Channel 20325	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:15MHz [&lt;RB=37&gt;, &lt;RB=75&gt;]</b>						
Channel	Channel 20025		Channel 20175		Channel 20325	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:20MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 20050		Channel 20175		Channel 20300	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.5	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:20MHz [&lt;RB=50&gt;, &lt;RB=100&gt;]</b>						
Channel	Channel 20050		Channel 20175		Channel 20300	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	19.0	18.0	19.0	18.0	19.5	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

**LTE Band 5**

<b>BW:1.4MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 20407		Channel 20525		Channel 20643	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	19.0	21.0	19.0	21.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:1.4MHz [&lt;RB=3&gt;, &lt;RB=6&gt;]</b>						
Channel	Channel 20407		Channel 20525		Channel 20643	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	19.0	21.0	19.0	21.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:3MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 20415		Channel 20525		Channel 20635	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:3MHz [&lt;RB=8&gt;, &lt;RB=15&gt;]</b>						
Channel	Channel 20415		Channel 20525		Channel 20635	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:5MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 20425		Channel 20525		Channel 20625	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:5MHz [&lt;RB=12&gt;, &lt;RB=25&gt;]</b>						
Channel	Channel 20425		Channel 20525		Channel 20625	

	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:10MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 20450		Channel 20525		Channel 20600	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:10MHz [&lt;RB=25&gt;, &lt;RB=50&gt;]</b>						
Channel	Channel 20450		Channel 20525		Channel 20600	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

**LTE Band 17**

<b>BW:5MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 23755		Channel 23790		Channel 23825	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:5MHz [&lt;RB=12&gt;, &lt;RB=25&gt;]</b>						
Channel	Channel 23755		Channel 23790		Channel 23825	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	20.0	19.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:10MHz [&lt;RB=1&gt;]</b>						
Channel	Channel 23780		Channel 23790		Channel 23800	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	21.0	20.0	21.0	20.0	21.0	20.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0
<b>BW:10MHz [&lt;RB=25&gt;, &lt;RB=50&gt;]</b>						
Channel	Channel 23780		Channel 23790		Channel 23800	
	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Target (dBm)	20.0	19.0	19.0	18.0	20.0	19.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0	1.0	1.0

**WiFi 2.4G**

<b>802.11b (Average)</b>			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>802.11g (Average)</b>			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>802.11n HT20 (Average)</b>			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>802.11n HT40 (Average)</b>			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	13.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

**WiFi 5.2G**

<b>802.11a (Average)</b>			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>802.11n HT20 (Average)</b>			
Channel	Channel 36	Channel 40	Channel 48

Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>802.11n HT40 (Average)</b>			
Channel	Channel 38	Channel 46	
Target (dBm)	14.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	


**WiFi 5.8G**

<b>802.11a (Average)</b>			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>802.11n HT20 (Average)</b>			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>802.11n HT40 (Average)</b>			
Channel	Channel 151	Channel 159	
Target (dBm)	12.0	12.0	
Tolerance $\pm$ (dB)	1.0	1.0	

**Bluetooth V4.0**

<b>BLE-GFSK (Average)</b>			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-3.0	-3.0	-3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>GFSK (Average)</b>			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	3.0	3.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b>8DPSK (Average)</b>			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	2.0	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
<b><math>\pi/4</math>DQPSK (Average)</b>			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	2.0	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

### 4.3. Transmit Antennas and SAR Measurement Position



Antenna information:

WWAN Main Antenna	GSM/UMTS/LTE TX/RX
LTEDiversity antenna	Only RX
WLAN/GPS/BT Antenna	WLAN/BT TX/RX

Note:

- 1). Per KDB648474 D04, because the overall diagonal distance of this devices is 164mm>160mm, it is considered as "Phablet" device.
- 2). Per KDB648474 D04, 10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR < 1.2 W/Kg.
- 3). According to the KDB941225 D06 Hot Spot SAR v02, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

Distance of The Antenna to the EUT surface and edge (mm)						
Antennas	Front	Back	Top Side	Bottom Side	Left Side	Right Side
WWAN	<5	<5	133	<5	<5	<25
BT/WLAN	<5	<5	<5	131	<5	65

Positions for SAR tests; Hotspot mode						
Antennas	Front	Back	Top Side	Bottom Side	Left Side	Right Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT/WLAN	Yes	Yes	Yes	No	Yes	No

**General Note:** Referring to KDB 941225 D06 v02, When the overall device length and width are  $\geq 9\text{cm} \times 5\text{cm}$ , the test distance is 10mm, SAR must be measured for all sides and surfaces with a transmitting antenna located with 25mm from that surface or edge.

#### 4.4. SAR Measurement Results

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{target}} - P_{\text{measured}})/10}$$

$$\text{Scaling factor} = 10^{(P_{\text{target}} - P_{\text{measured}})/10}$$

$$\text{Reported SAR} = \text{Measured SAR} \times \text{Scaling factor}$$

Where

$P_{\text{target}}$  is the power of manufacturing upper limit;

$P_{\text{measured}}$  is the measured power;

Measured SAR is measured SAR at measured power which including power drift)

Reported SAR which including Power Drift and Scaling factor

The product with 2 SIMs and 2 SIMs(SIM1 and SIM2) can not used Simultaneous, we tested 2 SIMs(SIM1 and SIM2) and recorded worst case at SIM 1

#### Duty Cycle

Test Mode	Duty Cycle
Speech for GSM850/1900	1:8
GPRS850	1:4
GPRS1900	1: 2.67
UMTS	1:1
LTE	1:1
WiFi2450/5200/5800	1:1

#### 5.3.1 SAR Results

#### SAR Values [GSM 850]

Ch.	Freq. (MHz)	Time slots	Test Position	Conducted Power (dBm)	Maximum Allowed Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
190	836.6	Voice	Left Cheek	33.25	34.00	-1.60	1.19	0.365	0.434	
190	836.6	Voice	Left Tilt	33.25	34.00	2.95	1.19	0.147	0.175	
190	836.6	Voice	Right Cheek	33.25	34.00	-3.56	1.19	<b>0.376</b>	<b>0.447</b>	Plot 1
190	836.6	Voice	Right Tilt	33.25	34.00	0.60	1.19	0.149	0.177	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
251	848.8	2Txslots	Front	30.62	31.00	1.77	1.09	<b>0.500</b>	<b>0.545</b>	Plot 2
251	848.8	2Txslots	Rear	30.62	31.00	1.96	1.09	0.421	0.459	
251	848.8	2Txslots	Left	30.62	31.00	-1.01	1.09	0.301	0.328	
251	848.8	2Txslots	Right	30.62	31.00	3.73	1.09	0.284	0.310	
251	848.8	2Txslots	Bottom	30.62	31.00	-4.06	1.09	0.297	0.324	
measured / reported SAR numbers – Body worn (distance 10mm)										
190	836.6	Voice	Front	33.25	34.00	0.06	1.19	0.405	0.482	
190	836.6	Voice	Rear	33.25	34.00	3.69	1.19	0.346	0.412	

**SAR Values [GSM 1900]**

Ch.	Freq. (MHz)	time slots	Test Position	Conducted Power (dBm)	Maximum Allowed Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
661	1880.0	Voice	Left Cheek	30.13	31.00	-0.75	1.22	0.461	0.562	Plot 3
661	1880.0	Voice	Left Tilt	30.13	31.00	0.74	1.22	0.233	0.284	
661	1880.0	Voice	Right Cheek	30.13	31.00	1.53	1.22	<b>0.480</b>	<b>0.586</b>	
661	1880.0	Voice	Right Tilt	30.13	31.00	-0.01	1.22	0.238	0.290	
measured / reported SAR numbers – Body (hotspot open, distance 10mm)										
661	1880.0	3Txslots	Front	26.22	27.00	-3.12	1.20	<b>0.547</b>	<b>0.656</b>	Plot 4
661	1880.0	3Txslots	Rear	26.22	27.00	-1.16	1.20	0.516	0.619	
661	1880.0	3Txslots	Left	26.22	27.00	3.18	1.20	0.342	0.410	
661	1880.0	3Txslots	Right	26.22	27.00	-1.39	1.20	0.316	0.379	
661	1880.0	3Txslots	Bottom	26.22	27.00	1.57	1.20	0.335	0.402	
measured / reported SAR numbers – Body worn (distance 10mm)										
661	1880.0	Voice	Front	30.13	31.00	-1.56	1.22	0.384	0.468	
661	1880.0	Voice	Rear	30.13	31.00	2.95	1.22	0.320	0.390	

**SAR Values [WCDMA Band V]**

Ch.	Freq. (MHz)	Channel Type	Test Position	Conducted Power (dBm)	Maximum Allowed Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
4183	836.6	RMC	Left Cheek	23.63	24.00	-3.37	1.09	0.277	0.302	
4183	836.6	RMC	Left Tilt	23.63	24.00	0.80	1.09	0.146	0.159	
4183	836.6	RMC	Right Cheek	23.63	24.00	-0.03	1.09	<b>0.295</b>	<b>0.322</b>	Plot 5
4183	836.6	RMC	Right Tilt	23.63	24.00	1.36	1.09	0.153	0.167	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
4183	836.6	RMC	Front	23.63	24.00	-0.35	1.09	<b>0.416</b>	<b>0.453</b>	Plot 6
4183	836.6	RMC	Rear	23.63	24.00	-0.02	1.09	0.324	0.353	
4183	836.6	RMC	Left	23.63	24.00	4.33	1.09	0.271	0.295	
4183	836.6	RMC	Right	23.63	24.00	1.07	1.09	0.246	0.268	
4183	836.6	RMC	Bottom	23.63	24.00	2.80	1.09	0.219	0.239	
measured / reported SAR numbers – Body worn (distance 10mm)										
4183	836.6	RMC	Front	23.63	24.00	-0.35	1.09	0.416	0.453	
4183	836.6	RMC	Rear	23.63	24.00	-0.02	1.09	0.324	0.353	

**SAR Values [WCDMA Band II]**

Ch.	Freq. (MHz)	Channel Type	Test Position	Conducted Power (dBm)	Maximum Allowed Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
9400	1800.0	RMC	Left Cheek	23.55	24.00	2.98	1.11	0.597	0.663	
9400	1800.0	RMC	Left Tilt	23.55	24.00	-0.29	1.11	0.324	0.360	
9400	1800.0	RMC	Right Cheek	23.55	24.00	-1.97	1.11	<b>0.657</b>	<b>0.729</b>	Plot 7
9262	1852.4	RMC	Right Tilt	23.55	24.00	2.07	1.11	0.331	0.367	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
9400	1800.0	RMC	Front	23.55	24.00	-3.47	1.11	<b>0.530</b>	<b>0.588</b>	Plot 8
9400	1800.0	RMC	Rear	23.55	24.00	2.11	1.11	0.489	0.543	
9400	1800.0	RMC	Left	23.55	24.00	-1.28	1.11	0.376	0.417	
9400	1800.0	RMC	Right	23.55	24.00	3.94	1.11	0.351	0.390	
9400	1800.0	RMC	Bottom	23.55	24.00	-0.05	1.11	0.324	0.360	
measured / reported SAR numbers – Body worn (distance 10mm)										
9400	1800.0	RMC	Front	23.55	24.00	-3.47	1.11	0.530	0.588	
9400	1800.0	RMC	Rear	23.55	24.00	2.11	1.11	0.489	0.543	

**SAR Values [LTE Band 2]**

Ch.	Freq. (MHz)	Channel Type (20M)	Test Position	Conducted Power (dBm)	Maximum Allowed Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
18900	1880	1RB	Left Cheek	20.85	21.00	-2.05	1.04	0.407	0.423	Plot 9
18900	1880	1RB	Left Tilt	20.85	21.00	-4.07	1.04	0.225	0.234	
18900	1880	1RB	Right Cheek	20.85	21.00	0.53	1.04	0.384	0.399	
18900	1880	1RB	Right Tilt	20.85	21.00	2.71	1.04	0.207	0.215	
18700	1860	50%RB	Left Cheek	20.42	20.50	-0.50	1.02	0.379	0.387	
18700	1860	50%RB	Left Tilt	20.42	20.50	0.81	1.02	0.206	0.210	
18700	1860	50%RB	Right Cheek	20.42	20.50	-0.33	1.02	0.366	0.373	
18700	1860	50%RB	Right Tilt	20.42	20.50	-2.74	1.02	0.193	0.197	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
18900	1880	1RB	Front	20.85	21.00	1.73	1.04	0.377	0.392	Plot 10
18900	1880	1RB	Rear	20.85	21.00	0.57	1.04	0.341	0.355	
18900	1880	1RB	Left	20.85	21.00	-3.31	1.04	0.274	0.285	
18900	1880	1RB	Right	20.85	21.00	4.00	1.04	0.267	0.278	
18900	1880	1RB	Bottom	20.85	21.00	-2.46	1.04	0.245	0.255	
18700	1860	50%RB	Front	20.42	20.50	1.52	1.02	0.351	0.358	
18700	1860	50%RB	Rear	20.42	20.50	-3.36	1.02	0.323	0.329	
18700	1860	50%RB	Left	20.42	20.50	0.18	1.02	0.253	0.258	
18700	1860	50%RB	Right	20.42	20.50	0.14	1.02	0.267	0.272	
18700	1860	50%RB	Bottom	20.42	20.50	-1.65	1.02	0.225	0.230	
measured / reported SAR numbers – Body worn (distance 10mm)										
18900	1880	1RB	Front	20.85	21.00	1.73	1.04	0.377	0.392	
18900	1880	1RB	Rear	20.85	21.00	0.57	1.04	0.341	0.355	
18700	1860	50%RB	Front	20.42	20.50	1.52	1.02	0.351	0.358	
18700	1860	50%RB	Rear	20.42	20.50	-3.36	1.02	0.323	0.329	



**SAR Values [LTE Band 4]**

Ch.	Freq. (MHz)	Channel Type (20M)	Test Position	Conducted Power (dBm)	Maximum Allowed Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results	
								Measured	Reported		
measured / reported SAR numbers - Head											
20175	1732.5	1RB	Left Cheek	21.07	21.50	-0.39	1.10	0.661	0.727	Plot 11	
20175	1732.5	1RB	Left Tilt	21.07	21.50	2.71	1.10	0.329	0.362		
20175	1732.5	1RB	Right Cheek	21.07	21.50	0.35	1.10	<b>0.704</b>	<b>0.774</b>		
20175	1732.5	1RB	Right Tilt	21.07	21.50	1.54	1.10	0.337	0.371		
20300	1745.0	50%RB	Left Cheek	20.02	20.50	-2.61	1.12	0.655	0.734		
20300	1745.0	50%RB	Left Tilt	20.02	20.50	1.77	1.12	0.316	0.354		
20300	1745.0	50%RB	Right Cheek	20.02	20.50	-0.99	1.12	0.687	0.769		
20300	1745.0	50%RB	Right Tilt	20.02	20.50	0.48	1.12	0.331	0.371		
measured / reported SAR numbers - Body (hotspot open, distance 10mm)											
20175	1732.5	1RB	Front	21.07	21.50	-1.15	1.10	<b>0.633</b>	<b>0.696</b>	Plot 12	
20175	1732.5	1RB	Rear	21.07	21.50	-0.74	1.10	0.588	0.647		
20175	1732.5	1RB	Left	21.07	21.50	-2.45	1.10	0.349	0.384		
20175	1732.5	1RB	Right	21.07	21.50	-2.83	1.10	0.301	0.331		
20175	1732.5	1RB	Bottom	21.07	21.50	3.14	1.10	0.226	0.249		
20050	1720.0	50%RB	Front	20.02	20.50	-4.61	1.12	0.606	0.679		
20050	1720.0	50%RB	Rear	20.02	20.50	0.74	1.12	0.575	0.644		
20050	1720.0	50%RB	Left	20.02	20.50	-0.67	1.12	0.332	0.372		
20050	1720.0	50%RB	Right	20.02	20.50	-4.31	1.12	0.287	0.321		
20050	1720.0	50%RB	Bottom	20.02	20.50	4.57	1.12	0.208	0.233		
measured / reported SAR numbers – Body worn (distance 10mm)											
20175	1732.5	1RB	Front	21.07	21.50	-1.15	1.10	0.633	0.696		
20175	1732.5	1RB	Rear	21.07	21.50	-0.74	1.10	0.588	0.647		
20050	1720.0	50%RB	Front	20.02	20.50	-4.61	1.12	0.606	0.679		
20050	1720.0	50%RB	Rear	20.02	20.50	0.74	1.12	0.575	0.644		

**SAR Values [LTE Band 5]**

Ch.	Freq. (MHz)	Channel Type (10M)	Test Position	Conducted Power (dBm)	Maximum Allowed Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
20450	829.0	1RB	Left Cheek	21.83	22.00	-3.53	1.04	0.248	0.258	Plot 13
20450	829.0	1RB	Left Tilt	21.83	22.00	-0.42	1.04	0.106	0.110	
20450	829.0	1RB	Right Cheek	21.83	22.00	-1.25	1.04	<b>0.273</b>	<b>0.284</b>	
20450	829.0	1RB	Right Tilt	21.83	22.00	-2.69	1.04	0.114	0.119	
20600	844.0	50%RB	Left Cheek	20.98	21.00	3.08	1.01	0.245	0.247	
20600	844.0	50%RB	Left Tilt	20.98	21.00	-0.72	1.01	0.091	0.092	
20600	844.0	50%RB	Right Cheek	20.98	21.00	-2.06	1.01	0.269	0.272	
20600	844.0	50%RB	Right Tilt	20.98	21.00	0.65	1.01	0.101	0.102	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
20450	829.0	1RB	Front	21.83	22.00	-1.63	1.04	<b>0.376</b>	<b>0.391</b>	Plot 14
20450	829.0	1RB	Rear	21.83	22.00	0.03	1.04	0.354	0.368	
20450	829.0	1RB	Left	21.83	22.00	-2.91	1.04	0.218	0.227	
20450	829.0	1RB	Right	21.83	22.00	-2.75	1.04	0.197	0.205	
20450	829.0	1RB	Bottom	21.83	22.00	-2.74	1.04	0.156	0.162	
20600	844.0	50%RB	Front	20.98	21.00	-3.93	1.01	0.372	0.376	
20600	844.0	50%RB	Rear	20.98	21.00	2.07	1.01	0.342	0.345	
20600	844.0	50%RB	Left	20.98	21.00	2.78	1.01	0.216	0.218	
20600	844.0	50%RB	Right	20.98	21.00	0.61	1.01	0.191	0.193	
20600	844.0	50%RB	Bottom	20.98	21.00	0.53	1.01	0.128	0.129	
measured / reported SAR numbers – Body worn (distance 10mm)										
20525	836.5	1RB	Front	21.83	22.00	-1.63	1.04	0.376	0.391	
20525	836.5	1RB	Rear	21.83	22.00	0.03	1.04	0.354	0.368	
20600	844.0	50%RB	Front	20.98	21.00	-3.93	1.01	0.372	0.376	
20600	844.0	50%RB	Rear	20.98	21.00	2.07	1.01	0.342	0.345	

**SAR Values [LTE Band 17]**

Ch.	Freq. (MHz)	Channel Type (20M)	Test Position	Conducted Power (dBm)	Maximum Allowed Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
23800	711.0	1RB	Left Cheek	21.57	22.00	-1.25	1.10	0.186	0.205	Plot 15
23800	711.0	1RB	Left Tilt	21.57	22.00	-0.55	1.10	0.101	0.111	
23800	711.0	1RB	Right Cheek	21.57	22.00	-3.58	1.10	0.175	0.193	
23800	711.0	1RB	Right Tilt	21.57	22.00	3.84	1.10	0.093	0.102	
23800	711.0	50%RB	Left Cheek	20.51	21.00	-0.84	1.12	0.163	0.183	
23800	711.0	50%RB	Left Tilt	20.51	21.00	-3.55	1.12	0.073	0.082	
23800	711.0	50%RB	Right Cheek	20.51	21.00	0.54	1.12	0.170	0.190	
23800	711.0	50%RB	Right Tilt	20.51	21.00	-0.47	1.12	0.089	0.100	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
23800	711.0	1RB	Front	21.57	22.00	-0.38	1.10	0.328	0.361	Plot 16
23800	711.0	1RB	Rear	21.57	22.00	2.15	1.10	0.309	0.340	
23800	711.0	1RB	Left	21.57	22.00	2.39	1.10	0.224	0.246	
23800	711.0	1RB	Right	21.57	22.00	4.90	1.10	0.237	0.261	
23800	711.0	1RB	Bottom	21.57	22.00	-2.75	1.10	0.251	0.276	
23800	711.0	50%RB	Front	20.51	21.00	-2.54	1.12	0.313	0.351	
23800	711.0	50%RB	Rear	20.51	21.00	-0.25	1.12	0.280	0.314	
23800	711.0	50%RB	Left	20.51	21.00	-3.87	1.12	0.198	0.222	
23800	711.0	50%RB	Right	20.51	21.00	-1.38	1.12	0.231	0.259	
23800	711.0	50%RB	Bottom	20.51	21.00	-0.25	1.12	0.222	0.249	
measured / reported SAR numbers – Body worn (distance 10mm)										
23800	711.0	1RB	Front	21.57	22.00	-0.38	1.10	0.328	0.361	
23800	711.0	1RB	Rear	21.57	22.00	2.15	1.10	0.309	0.340	
23800	711.0	50%RB	Front	20.51	21.00	-2.54	1.12	0.323	0.362	
23800	711.0	50%RB	Rear	20.51	21.00	-0.25	1.12	0.280	0.314	

**SAR Values [WIFI2.4G]**

Ch.	Freq. (MHz)	Service	Test Position	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
1	2412	DSSS	Left Cheek	14.43	15.00	-1.73	1.14	0.541	0.617	Plot 17
1	2412	DSSS	Left Tilt	14.43	15.00	-3.86	1.14	0.463	0.528	
1	2412	DSSS	Right Cheek	14.43	15.00	3.47	1.14	0.527	0.601	
1	2412	DSSS	Right Tilt	14.43	15.00	2.26	1.14	0.448	0.511	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
1	2412	DSSS	Front	14.43	15.00	-0.23	1.14	0.230	0.262	Plot 18
1	2412	DSSS	Rear	14.43	15.00	-2.11	1.14	0.214	0.244	
1	2412	DSSS	Left	14.43	15.00	-4.50	1.14	0.148	0.169	
1	2412	DSSS	Top	14.43	15.00	4.72	1.14	0.186	0.212	
measured / reported SAR numbers – Body worn (distance 10mm)										
1	2412	DSSS	Front	14.43	15.00	-0.23	1.14	0.230	0.262	
1	2412	DSSS	Rear	14.43	15.00	-2.11	1.14	0.214	0.244	

**SAR Values [WIFI5.2G]**

Ch.	Freq. (MHz)	Service	Test Position	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
36	5180	OFDM	Left Cheek	15.81	16.00	-0.57	1.04	0.357	0.371	Plot 19
36	5180	OFDM	Left Tilt	15.81	16.00	-2.75	1.04	0.336	0.349	
36	5180	OFDM	Right Cheek	15.81	16.00	4.98	1.04	0.351	0.365	
36	5180	OFDM	Right Tilt	15.81	16.00	3.91	1.04	0.329	0.342	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
36	5180	OFDM	Front	15.81	16.00	-0.99	1.04	0.120	0.125	Plot 20
36	5180	OFDM	Rear	15.81	16.00	1.96	1.04	0.111	0.115	
36	5180	OFDM	Left	15.81	16.00	1.72	1.04	0.100	0.104	
36	5180	OFDM	Top	15.81	16.00	2.71	1.04	0.089	0.093	
measured / reported SAR numbers – Body worn (distance 10mm)										
36	5180	OFDM	Front	15.81	16.00	-2.33	1.04	0.120	0.125	
36	5180	OFDM	Rear	15.81	16.00	-2.39	1.04	0.111	0.115	

**SAR Values [WIFI5.8G]**

Ch.	Freq. (MHz)	Service	Test Position	Maximum Allowed Power (dBm)	Conducted Power (dBm)	Power Drift (%)	Scaling Factor	SAR <sub>1-g</sub> results(W/kg)		Graph Results
								Measured	Reported	
measured / reported SAR numbers - Head										
165	5825	OFDM	Left Cheek	13.78	14.00	0.48	1.05	0.393	0.413	Plot 21
165	5825	OFDM	Left Tilt	13.78	14.00	2.81	1.05	0.354	0.372	
165	5825	OFDM	Right Cheek	13.78	14.00	-0.99	1.05	0.388	0.407	
165	5825	OFDM	Right Tilt	13.78	14.00	3.16	1.05	0.355	0.373	
measured / reported SAR numbers - Body (hotspot open, distance 10mm)										
165	5825	OFDM	Front	13.78	14.00	-2.15	1.05	0.197	0.207	Plot 22
165	5825	OFDM	Rear	13.78	14.00	-4.74	1.05	0.174	0.183	
165	5825	OFDM	Left	13.78	14.00	1.23	1.05	0.145	0.152	
165	5825	OFDM	Top	13.78	14.00	1.65	1.05	0.163	0.171	
measured / reported SAR numbers – Body worn (distance 10mm)										
165	5825	OFDM	Front	13.78	14.00	-2.15	1.05	0.197	0.207	
165	5825	OFDM	Rear	13.78	14.00	-4.74	1.05	0.174	0.183	

## Note:

1. The value with black color is the maximum Reported SAR Value of each test band.
2. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is optional for such test configuration(s).
3. Per KDB 941225 D02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/HSUPA output power is  $< 0.25$  dB higher than RMC, or reported SAR with RMC 12.2kbps setting is  $\leq 1.2$  W/kg, HSDPA/HSUPA SAR evaluation can be excluded.
4. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel
5. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
6. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
7. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
8. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.
9. Per KDB 248227-SAR is measured using the highest measured maximum output power channel for the initial test configuration.

10. Per KDB 248227- Channels with measured maximum output power within ¼ dB of each other are considered to have the same maximum output, When there are multiple test channels with the same measured maximum output power, the channel closest to mid-band frequency is selected for SAR measurement. And when there are multiple test channels with the same measured maximum output power and equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

11. Per KDB 248227- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg. So OFDM SAR test is not required.

12. Per KDB 648474 D04, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is  $\leq 1.2$  W/kg, SAR testing with a headset connected to the handset is not required.

### 5.3.3 Standalone SAR Test Exclusion Considerations and Estimated SAR

Per KDB447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion;

- (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [  $\sqrt{f(\text{GHz})/x}$  ] W/kg for test separation distances  $\leq 50$  mm;

where  $x = 7.5$  for 1-g SAR, and  $x = 18.75$  for 10-g SAR.

- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is  $> 50$  mm

Per FCC KD B447498 D01, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the transmitting antenna in a specific a physical test configuration is  $\leq 1.6$  W/Kg. When the sum is greater than the SAR limit, SAR test exclusion is determined by the SAR to peak location separation ratio.

$$\text{Ratio} = \frac{(\text{SAR}_1 + \text{SAR}_2)^{1.5}}{(\text{peak location separation, mm})} < 0.04$$

Estimated stand alone SAR					
Communication system	Frequency (MHz)	Configuration	Maximum Power (including tune-up tolerance) (dBm)	Separation Distance (mm)	Estimated SAR <sub>1-g</sub> (W/kg)
Bluetooth*	2450	Head	5.0	5	0.141
Bluetooth*	2450	Hotspot	5.0	10	0.071
Bluetooth*	2450	Body Worn	5.0	10	0.071

Bluetooth\*- Including Lower power Bluetooth

## 4.5. Simultaneous TX SAR Considerations

### 5.5.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g/n and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

For the DUT, the BT and WiFi modules sharing same antenna, GSM module sharing a single antenna;

Application Simultaneous Transmission information:

Air-Interface	Band (MHz)	Type	Simultaneous Transmissions	Voice over Digital Transport(Data)
GSM	850	VO	Yes, WLAN or BT/BLE	N/A
	1900	VO		
	GPRS/EDGE	DT	Yes, WLAN or BT/BLE	N/A
WCDMA	Band II/BandV	DT	Yes, WLAN or BT/BLE	N/A
LTE	Band2/Band4	DT	Yes, WLAN or BT/BLE	N/A
WLAN	2450	DT	Yes, GSM, GPRS, EDGE, UMTS, LTE	Yes
BT/BLE	2450	DT	Yes, GSM, GPRS, EDGE, UMTS, LTE	N/A

Note: VO-Voice Service only; DT-Digital Transport

Note: BT and WLAN can be active at the same time, but only with interleaving of packages switched on board level. That means that they don't transmit at the same time.

BLE-Bluetooth low energy;

BT- Classical Bluetooth

### 5.5.2 Evaluation of Simultaneous SAR

#### Head Exposure Conditions

#### Simultaneous transmission SAR for WiFi and GSM

Test Position	GSM850 Reported SAR <sub>1-g</sub> (W/Kg)	GSM1900 Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Left Cheek	0.434	0.562	<b>0.617</b>	<b>0.371</b>	<b>0.413</b>	<b>1.179</b>	1.6	no	no
Left Tilt	0.175	0.284	0.528	0.349	0.372	0.812	1.6	no	no
Right Cheek	<b>0.447</b>	<b>0.586</b>	0.601	0.365	0.407	0.993	1.6	no	no
Right Tilt	0.177	0.290	0.511	0.342	0.373	0.801	1.6	no	no

#### Simultaneous transmission SAR for WiFi and UMTS

Test Position	UMTS Band V Reported SAR <sub>1-g</sub> (W/Kg)	UMTS Band II Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Left Cheek	0.302	0.663	<b>0.617</b>	<b>0.371</b>	<b>0.413</b>	1.280	1.6	no	no
Left Tilt	0.159	0.360	0.528	0.349	0.372	0.888	1.6	no	no
Right Cheek	<b>0.322</b>	<b>0.729</b>	0.601	0.365	0.407	<b>1.330</b>	1.6	no	no
Right Tilt	0.167	0.367	0.511	0.342	0.373	0.878	1.6	no	no

## Simultaneous transmission SAR for WiFi and LTE

Test Position	LTE Band2 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band4 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band5 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band17 Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Left Cheek	<b>0.423</b>	0.727	0.258	<b>0.205</b>	<b>0.617</b>	<b>0.371</b>	<b>0.413</b>	1.344	1.6	no	no
Left Tilt	0.234	0.362	0.110	0.111	0.528	0.349	0.372	0.890	1.6	no	no
Right Cheek	0.399	<b>0.774</b>	<b>0.284</b>	0.193	0.601	0.365	0.407	<b>1.375</b>	1.6	no	no
Right Tilt	0.215	0.371	0.119	0.102	0.511	0.342	0.373	0.882	1.6	no	no

## Simultaneous transmission SAR for BT and GSM

Test Position	GSM850 Reported SAR <sub>1-g</sub> (W/Kg)	GSM1900 Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Left Cheek	0.434	0.562	0.141	0.703	1.6	no	no
Left Tilt	0.175	0.284	0.141	0.425	1.6	no	no
Right Cheek	<b>0.447</b>	<b>0.586</b>	0.141	<b>0.727</b>	1.6	no	no
Right Tilt	0.177	0.290	0.141	0.431	1.6	no	no

## Simultaneous transmission SAR for BT and UMTS

Test Position	UMTS Band V Reported SAR <sub>1-g</sub> (W/Kg)	UMTS Band II Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Left Cheek	0.302	0.663	0.141	0.804	1.6	no	no
Left Tilt	0.159	0.360	0.141	0.501	1.6	no	no
Right Cheek	<b>0.322</b>	<b>0.729</b>	0.141	<b>0.870</b>	1.6	no	no
Right Tilt	0.167	0.367	0.141	0.508	1.6	no	no

## Simultaneous transmission SAR for BT and LTE

Test Position	LTE Band2 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band4 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band5 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band17 Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Left Cheek	<b>0.423</b>	0.727	0.258	<b>0.205</b>	0.141	0.868	1.6	no	no
Left Tilt	0.234	0.362	0.110	0.111	0.141	0.503	1.6	no	no
Right Cheek	0.399	<b>0.774</b>	<b>0.284</b>	0.193	0.141	<b>0.915</b>	1.6	no	no
Right Tilt	0.215	0.371	0.119	0.102	0.141	0.485	1.6	no	no

## Body Hotspot Exposure Conditions

## Simultaneous transmission SAR for WiFi and GSM

Test Position	GSM850 Reported SAR <sub>1-g</sub> (W/Kg)	GSM1900 Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.545	0.656	0.262	0.125	0.207	<b>0.918</b>	1.6	no	no
Rear	0.459	0.619	0.244	0.115	0.183	0.863	1.6	no	no
Left	0.328	0.410	0.169	0.104	0.152	0.579	1.6	no	no
Right	0.310	0.379	/	/	/	0.379	1.6	no	no
Bottom	0.324	0.402	/	/	/	0.324	1.6	no	no
Top	/	/	0.212	0.0093	0.171	0.212	1.6	no	no

## Simultaneous transmission SAR for WiFi and UMTS

Test Position	UMTS Band V Reported SAR <sub>1-g</sub> (W/Kg)	UMTS Band II Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.453	0.588	0.262	0.125	0.207	0.850	1.6	no	no
Rear	0.353	0.543	0.244	0.115	0.183	0.787	1.6	no	no
Left	0.295	0.417	0.169	0.104	0.152	0.586	1.6	no	no
Right	0.268	0.390	/	/	/	0.390	1.6	no	no
Bottom	0.239	0.360	/	/	/	0.360	1.6	no	no
Top	/	/	0.212	0.0093	0.171	0.212	1.6	no	no

## Simultaneous transmission SAR for WiFi and LTE

Test Position	LTE Band2 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band4 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band5 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band17 Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.392	0.696	0.391	0.361	0.262	0.125	0.207	0.958	1.6	no	no
Rear	0.355	0.647	0.368	0.340	0.244	0.115	0.183	0.891	1.6	no	no
Left	0.285	0.384	0.227	0.246	0.169	0.104	0.152	0.553	1.6	no	no
Right	0.278	0.331	0.205	0.261	/	/	/	0.331	1.6	no	no
Bottom	0.358	0.249	0.162	0.276	/	/	/	0.358	1.6	no	no
Top	/	/	/	/	0.212	0.0093	0.171	0.212	1.6	no	no

## Simultaneous transmission SAR for BT and GSM

Test Position	GSM850 Reported SAR <sub>1-g</sub> (W/Kg)	GSM1900 Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.545	0.656	0.071	0.727	1.6	no	no
Rear	0.459	0.619	0.071	0.690	1.6	no	no
Left	0.328	0.410	0.071	0.481	1.6	no	no
Right	0.310	0.379	/	0.379	1.6	no	no
Bottom	0.324	0.402	/	0.402	1.6	no	no
Top	/	/	0.071	0.071	1.6	no	no

## Simultaneous transmission SAR for BT and UMTS

Test Position	UMTS Band V Reported SAR <sub>1-g</sub> (W/Kg)	UMTS Band II Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.453	0.588	0.071	0.659	1.6	no	no
Rear	0.353	0.543	0.071	0.614	1.6	no	no
Left	0.295	0.417	0.071	0.488	1.6	no	no
Right	0.268	0.390	/	0.390	1.6	no	no
Bottom	0.239	0.360	/	0.360	1.6	no	no
Top	/	/	0.071	0.071	1.6	no	no

## Simultaneous transmission SAR for BT and LTE

Test Position	LTE Band2 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band4 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band5 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band17 Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. ΣSAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.392	0.696	0.391	0.361	0.071	0.767	1.6	no	no
Rear	0.355	0.647	0.368	0.340	0.071	0.718	1.6	no	no
Left	0.285	0.384	0.227	0.246	0.071	0.455	1.6	no	no
Right	0.278	0.331	0.205	0.261	/	0.331	1.6	no	no
Bottom	0.358	0.249	0.162	0.276	/	0.358	1.6	no	no
Top	/	/	/	/	0.071	0.071	1.6	no	no



**Body Worn Exposure Conditions****Simultaneous transmission SAR for WiFi and GSM**

Test Position	GSM850 Reported SAR <sub>1-g</sub> (W/Kg)	GSM1900 Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. $\Sigma$ SAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.482	0.468	0.262	0.125	0.207	0.744	1.6	no	no
Rear	0.412	0.390	0.244	0.115	0.183	0.656	1.6	no	no

**Simultaneous transmission SAR for WiFi and UMTS**

Test Position	UMTS Band V Reported SAR <sub>1-g</sub> (W/Kg)	UMTS Band II Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. $\Sigma$ SAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.453	0.588	0.262	0.125	0.207	0.850	1.6	no	no
Rear	0.353	0.543	0.244	0.115	0.183	0.787	1.6	no	no

**Simultaneous transmission SAR for WiFi and LTE**

Test Position	LTE Band2 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band4 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band5 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band17 Reported SAR <sub>1-g</sub> (W/Kg)	WiFi2.4G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.2G Reported SAR <sub>1-g</sub> (W/Kg)	WiFi5.8G Reported SAR <sub>1-g</sub> (W/Kg)	MAX. $\Sigma$ SAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.392	0.696	0.391	0.361	0.262	0.125	0.207	0.958	1.6	no	no
Rear	0.355	0.647	0.368	0.340	0.244	0.115	0.183	0.891	1.6	no	no

**Simultaneous transmission SAR for BT and GSM**

Test Position	GSM850 Reported SAR <sub>1-g</sub> (W/Kg)	GSM1900 Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. $\Sigma$ SAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.482	0.468	0.071	0.553	1.6	no	no
Rear	0.412	0.390	0.071	0.483	1.6	no	no

**Simultaneous transmission SAR for BT and UMTS**

Test Position	UMTS Band V Reported SAR <sub>1-g</sub> (W/Kg)	UMTS Band II Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. $\Sigma$ SAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.453	0.588	0.071	0.659	1.6	no	no
Rear	0.353	0.543	0.071	0.614	1.6	no	no

**Simultaneous transmission SAR for BT and LTE**

Test Position	LTE Band2 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band4 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band5 Reported SAR <sub>1-g</sub> (W/Kg)	LTE Band17 Reported SAR <sub>1-g</sub> (W/Kg)	BT Estimated SAR <sub>1-g</sub> (W/Kg)	MAX. $\Sigma$ SAR <sub>1-g</sub> (W/Kg)	SAR <sub>1-g</sub> Limit (W/Kg)	Peak location separation ratio	Simut Meas. Required
Front	0.392	0.696	0.391	0.361	0.071	0.767	1.6	no	no
Rear	0.355	0.647	0.368	0.340	0.071	0.718	1.6	no	no

Note:

1. The WiFi and BT share same antenna, so cannot transmit at same time.
2. The value with black color is the maximum values of standalone
3. The value with blue color is the maximum values of  $\Sigma$ SAR<sub>1-g</sub>

#### 4.6. SAR Measurement Variability

According to KDB865664, Repeated measurements are required only when the measured SAR is  $\geq 0.80$  W/kg. If the measured SAR value of the initial repeated measurement is  $< 1.45$  W/kg with  $\leq 20\%$  variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. A second repeated measurement is required only if the measured result for the initial repeated measurement is within 10% of the SAR limit and vary by more than 20%, which are often related to device and measurement setup difficulties. The following procedures are applied to determine if repeated measurements are required. The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.<sup>19</sup> The repeated measurement results must be clearly identified in the SAR report. All measured SAR, including the repeated results, must be considered to determine compliance and for reporting according to KDB 690783. Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.

- 4) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 5) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 6) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .
- 7) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

#### 4.7. General description of test procedures

1. The DUT is tested using CMU 200 communications testers as controller unit to set test channels and maximum output power to the DUT, as well as for measuring the conducted peak power.
2. Test positions as described in the tables above are in accordance with the specified test standard.
3. Tests in body position were performed in that configuration, which generates the highest time based averaged output power (see conducted power results).
4. Tests in head position with GSM were performed in voice mode with 1 timeslot unless GPRS/EGPRS/DTM function allows parallel voice and data traffic on 2 or more timeslots.
5. UMTS was tested in RMC mode with 12.2 kbit/s and TPC bits set to 'all 1'.
6. WiFi was tested in 802.11b/g/n mode with 1 Mbit/s and 6 Mbit/s. According to KDB 248227 the SAR testing for 802.11g/n is not required since When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.
7. Required WiFi test channels were selected according to KDB 248227
8. According to FCC KDB pub 248227 D01, Channels with measured maximum output power within  $\frac{1}{4}$  dB of each other are considered to have the same maximum output, When there are multiple test channels with the same measured maximum output power, the channel closest to mid-band frequency is selected for SAR measurement and when there are multiple test channels with the same measured maximum output power and equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.
9. According to FCC KDB pub 941225 D06 this device has been tested with 10 mm distance to the phantom for operation in WiFi hot spot mode.
10. Per FCC KDB pub 941225 D06 the edges with antennas within 2.5 cm are required to be evaluated for SAR to cover WiFi hot spot function.
11. According to IEEE 1528 the SAR test shall be performed at middle channel. Testing of top and bottom channel is optional.
12. According to KDB 447498 D01 testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
  - $\leq 0.6$  W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - $\leq 0.4$  W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz
13. IEEE 1528-2003 require the middle channel to be tested first. This generally applies to wireless devices that are designed to operate in technologies with tight tolerances for maximum output power variations across channels in the band. When the maximum output power variation across the required test channels is  $> \frac{1}{2}$  dB, instead of the middle channel, the highest output power channel must be used.
14. Per KDB648474 D04 require when the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is  $< 1.2$  W/kg.

15. Per KDB648474 D04 require when the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, using the same wireless mode test configuration for voice and data, such as UMTS, LTE and Wi-Fi, and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface)
16. 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg.
17. Per KDB648474 D04 require for phablet SAR test considerations, For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.
18. 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg.

#### **4.8. Measurement Uncertainty (300MHz-3GHz)**

Not required as SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is  $\geq 1.5$  W/kg for 1-g SAR according to KDB865664D01.

#### 4.9. System Check Results

Test mode:750MHz(Head)




Product Description:Validation

Model:Dipole SID750

E-Field Probe:SSE5(SN17/14 EP221)




Test Date: December 16, 2015

Medium(liquid type)	HSL 750
Frequency (MHz)	750.000000
Relative permittivity (real part)	42.21
Conductivity (S/m)	0.86
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.53
Variation (%)	-0.9400000
SAR 10g (W/Kg)	0.6275682
SAR 1g (W/Kg)	0.9433641
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>






Test mode:750MHz(Body)  
 Product Description:Validation  
 Model:Dipole SID750  
 E-Field Probe:SSE5(SN17/14 EP221)  
 Test Date: December 16, 2015

Medium(liquid type)	MSL_750
Frequency (MHz)	750.0000
Relative permittivity (real part)	56.71
Conductivity (S/m)	0.95
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.70
Variation (%)	1.0800000
SAR 10g (W/Kg)	0.6611235
SAR 1g (W/Kg)	0.9756340

**SURFACE SAR****VOLUME SAR**




Test mode:835MHz(Head)  
 Product Description:Validation  
 Model:Dipole SID835  
 E-Field Probe:SSE5(SN17/14 EP220)  
 Test Date: December 17, 2015

Medium(liquid type)	HSL_900
Frequency (MHz)	835.000000
Relative permittivity (real part)	42.68
Conductivity (S/m)	0.91
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.86
Variation (%)	0.5100000
SAR 10g (W/Kg)	0.6341423
SAR 1g (W/Kg)	0.9548732
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>






Test mode:835MHz(Body)  
 Product Description:Validation  
 Model:Dipole SID835  
 E-Field Probe:SSE5(SN17/14 EP220)  
 Test Date: December 17, 2015

Medium(liquid type)	MSL_900
Frequency (MHz)	835.0000
Relative permittivity (real part)	53.24
Conductivity (S/m)	0.94
Input power	100mW
Crest Factor	1.0
Conversion Factor	5.04
Variation (%)	1.0600000
SAR 10g (W/Kg)	0.6348979
SAR 1g (W/Kg)	0.9768104
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



Test mode:1800MHz(Head)  
Product Description:Validation  
Model :Dipole SID1800  
E-Field Probe:SSE5(SN17/14 EP220)  
Test Date: December 18, 2015




Medium(liquid type)	HSL_1800
Frequency (MHz)	1800.000000
Relative permittivity (real part)	41.13
Conductivity (S/m)	1.36
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.25
Variation (%)	-1.5500000
SAR 10g (W/Kg)	1.8531472
SAR 1g (W/Kg)	4.0087396
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>








Test mode:1800MHz(Body)  
 Product Description:Validation  
 Model :Dipole SID1800  
 E-Field Probe:SSE5(SN17/14 EP220)  
 Test Date: December 18, 2015

Medium(liquid type)	MSL_1800
Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.09
Conductivity (S/m)	1.33
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.34
Variation (%)	4.0200000
SAR 10g (W/Kg)	2.1647896
SAR 1g (W/Kg)	4.2305571

**SURFACE SAR****VOLUME SAR**




Test mode:1900MHz(Head)  
 Product Description:Validation  
 Model :Dipole SID1900  
 E-Field Probe:SSE5(SN17/14 EP221)  
 Test Date: December 21, 2015

Medium(liquid type)	HSL_1900
Frequency (MHz)	1900.0000
Relative permittivity (real part)	41.25
Conductivity (S/m)	1.41
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.71
Variation (%)	2.3900000
SAR 10g (W/Kg)	2.2087497
SAR 1g (W/Kg)	3.9201154
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>






Test mode:1900MHz(Body)  
 Product Description:Validation  
 Model :Dipole SID1900  
 E-Field Probe:SSE5(SN17/14 EP221)  
 Test Date: December 21, 2015

Medium(liquid type)	MSL_1900
Frequency (MHz)	1900.0000
Relative permittivity (real part)	54.46
Conductivity (S/m)	1.52
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.85
Variation (%)	-0.3200000
SAR 10g (W/Kg)	1.9743882
SAR 1g (W/Kg)	4.0762697
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>






Test mode:2450MHz(Head)  
 Product Description:Validation  
 Model:Dipole SID2450  
 E-Field Probe:SSE5(SN17/14 EP221)  
 Test Date: December 22, 2015

Medium(liquid type)	HSL_2450
Frequency (MHz)	2450.000000
Relative permittivity (real part)	39.11
Conductivity (S/m)	1.79
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.11
Variation (%)	2.5900000
SAR 10g (W/Kg)	2.3768495
SAR 1g (W/Kg)	4.9673667

**SURFACE SAR****VOLUME SAR**




Test mode:2450MHz(Body)  
 Product Description:Validation  
 Model:Dipole SID2450  
 E-Field Probe:SSE5(SN17/14 EP221)  
 Test Date: December 22, 2015

Medium(liquid type)	MSL_2450
Frequency (MHz)	2450.000000
Relative permittivity (real part)	52.78
Conductivity (S/m)	1.94
Input power	100mW
Crest Factor	1.0
Conversion Factor	4.25
Variation (%)	4.1700000
SAR 10g (W/Kg)	2.3301966
SAR 1g (W/Kg)	5.0196472
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>






Test mode:5200MHz(Head)  
 Product Description:Validation  
 Model:Dipole SID5000  
 E-Field Probe:SSE5(SN13/14 EPG214)  
 Test Date: December 23, 2015

Medium(liquid type)	HSL_5000
Frequency (MHz)	5200.0000
Relative permittivity (real part)	36.18
Conductivity (S/m)	4.63
Input power	100mW
Crest Factor	1.0
Conversion Factor	16.88
Variation (%)	0.5400000
SAR 10g (W/Kg)	2.2461573
SAR 1g (W/Kg)	4.4687281
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



Test mode:5200MHz(Body)  
 Product Description:Validation  
 Model:Dipole SID5000  
 E-Field Probe:SSE5(SN13/14 EPG214)  
 Test Date: December 23, 2015




Medium(liquid type)	MSL_5000
Frequency (MHz)	5200.0000
Relative permittivity (real part)	49.66
Conductivity (S/m)	5.25
Input power	100mW
Crest Factor	1.0
Conversion Factor	17.36
Variation (%)	1.3700000
SAR 10g (W/Kg)	2.1976343
SAR 1g (W/Kg)	5.1987269

**SURFACE SAR****VOLUME SAR**



Test mode:5800MHz(Head)  
 Product Description:Validation  
 Model:Dipole SID5000  
 E-Field Probe:SSE5(SN13/14 EPG214)  
 Test Date: December 24, 2015




Medium(liquid type)	HSL_5000
Frequency (MHz)	5800.0000
Relative permittivity (real part)	36.18
Conductivity (S/m)	4.63
Input power	100mW
Crest Factor	1.0
Conversion Factor	16.24
Variation (%)	0.5400000
SAR 10g (W/Kg)	2.2461573
SAR 1g (W/Kg)	4.4687281

**SURFACE SAR****VOLUME SAR**



Test mode:5800MHz(Body)  
 Product Description:Validation  
 Model:Dipole SID5000  
 E-Field Probe:SSE5(SN13/14 EPG214)  
 Test Date: December 24, 2015

Medium(liquid type)	MSL_5000
Frequency (MHz)	5800.0000
Relative permittivity (real part)	49.66
Conductivity (S/m)	5.25
Input power	100mW
Crest Factor	1.0
Conversion Factor	16.79
Variation (%)	1.3700000
SAR 10g (W/Kg)	2.1976343
SAR 1g (W/Kg)	5.1987269
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## 5.1. SAR Test Graph Results

SAR plots for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination according to FCC KDB 865664 D02

#1




Test Mode: GSM 850MHz, Mid channel (Head Right Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 17, 2015

Medium (liquid type)	MSL_900
Frequency (MHz)	836.600000
Relative permittivity (real part)	42.81
Conductivity (S/m)	0.89
E-Field Probe	SN 17/14 EP220
Crest Factor	8.0
Conversion Factor	4.83
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm
Variation (%)	-3.560000
SAR 10g (W/Kg)	0.260445
SAR 1g (W/Kg)	0.375793
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #2




Test Mode: Hotspot GSM850MHz,Mid channel(Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 17, 2015

Medium(liquid type)	MSL_900
Frequency (MHz)	836.600000
Relative permittivity (real part)	53.46
Conductivity (S/m)	0.96
E-Field Probe	SN 17/14 EP220
Crest Factor	6.02
Conversion Factor	5.02
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	1.770000
SAR 10g (W/Kg)	0.344785
SAR 1g (W/Kg)	0.499974
SURFACE SAR	VOLUME SAR



## #3




Test Mode:GSM 1900MHz,Mid channel(Head Right Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 21, 2015

Medium(liquid type)	MSL 1900
Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.09
Conductivity (S/m)	1.42
E-Field Probe	SN17/14 EP221
Crest Factor	8.0
Conversion Factor	4.71
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	1.530000
SAR 10g (W/Kg)	0.253795
SAR 1g (W/Kg)	0.480022

**SURFACE SAR****VOLUME SAR**

## #4




Test Mode: Hotspot GPRS1900MHz,Mid channel(Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 21, 2015

Medium(liquid type)	MSL 1900
Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.20
Conductivity (S/m)	1.54
E-Field Probe	SN17/14 EP221
Crest Factor	4.06
Conversion Factor	4.85
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-3.120000
SAR 10g (W/Kg)	0.302368
SAR 1g (W/Kg)	0.546702
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #5




Test Mode:WCDMA Band V,Mid channel(Head Right Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 17, 2015

Medium(liquid type)	MSL_900
Frequency (MHz)	836.600000
Relative permittivity (real part)	42.81
Conductivity (S/m)	0.89
E-Field Probe	SN 17/14 EP220
Crest Factor	1.0
Conversion Factor	4.83
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.030000
SAR 10g (W/Kg)	0.215887
SAR 1g (W/Kg)	0.294696

**SURFACE SAR****VOLUME SAR**

## #6




Test Mode: Hotspot WCDMA Band V, Mid channel (Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 17, 2015

Medium (liquid type)	MSL_900
Frequency (MHz)	836.600000
Relative permittivity (real part)	53.46
Conductivity (S/m)	0.96
E-Field Probe	SN 17/14 EP220
Crest Factor	1.0
Conversion Factor	5.02
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm
Variation (%)	-0.350000
SAR 10g (W/Kg)	0.280171
SAR 1g (W/Kg)	0.416432
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>





## #7




Test Mode:WCDMA Band II,Mid channel(Head Right Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 21, 2015

Medium(liquid type)	MSL 1900
Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.09
Conductivity (S/m)	1.42
E-Field Probe	SN17/14 EP221
Crest Factor	1.0
Conversion Factor	4.71
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.970000
SAR 10g (W/Kg)	0.362703
SAR 1g (W/Kg)	0.656842
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>





## #8




Test Mode: Hotspot WCDMA Band II, Mid channel(Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 21, 2015

Medium(liquid type)	MSL 1900
Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.20
Conductivity (S/m)	1.54
E-Field Probe	SN17/14 EP221
Crest Factor	1.0
Conversion Factor	4.85
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-3.470000
SAR 10g (W/Kg)	0.374463
SAR 1g (W/Kg)	0.530445
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #9




Test Mode: LTE Band 2, Mid channel(Head Left Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 21, 2015

Medium(liquid type)	MSL 1900
Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.09
Conductivity (S/m)	1.42
E-Field Probe	SN17/14 EP221
Crest Factor	1.0
Conversion Factor	4.71
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-2.050000
SAR 10g (W/Kg)	0.224584
SAR 1g (W/Kg)	0.407217

**SURFACE SAR****VOLUME SAR**

## #10




Test Mode: Hotspot LTE Band 2, Mid channel(Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 21, 2015

Medium(liquid type)	MSL 1900
Frequency (MHz)	1880.000000
Relative permittivity (real part)	54.20
Conductivity (S/m)	1.54
E-Field Probe	SN 17/14 EP221
Crest Factor	1.0
Conversion Factor	4.85
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	1.730000
SAR 10g (W/Kg)	0.218661
SAR 1g (W/Kg)	0.377143
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #11




Test Mode:LTE Band 4, Mid channel(Head Right Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 18, 2015

Medium(liquid type)	MSL 1800
Frequency (MHz)	1732.500000
Relative permittivity (real part)	41.31
Conductivity (S/m)	1.38
E-Field Probe	SN17/14 EP221
Crest Factor	1.0
Conversion Factor	4.25
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.350000
SAR 10g (W/Kg)	0.430779
SAR 1g (W/Kg)	0.703954

**SURFACE SAR****VOLUME SAR**

## #12

Test Mode: Hotspot LTE Band 4, Middle channel(Body Front Side)


## Product Description: LTE Phone

Model: SF550



Test Date: December 18, 2015

Medium(liquid type)	MSL_1800
Frequency (MHz)	1732.500000
Relative permittivity (real part)	53.27
Conductivity (S/m)	1.51
E-Field Probe	SN 17/14 EP221
Crest Factor	1.0
Conversion Factor	4.34
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.150000
SAR 10g (W/Kg)	0.448712
SAR 1g (W/Kg)	0.632708

## SURFACE SAR



**VOLUME SAR**



## #13




Test Mode: LTE Band 5, Low channel(Head Right Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 17, 2015

Medium(liquid type)	MSL_900
Frequency (MHz)	829.00000000
Relative permittivity (real part)	42.15
Conductivity (S/m)	0.90
E-Field Probe	SN 17/14 EP220
Crest Factor	1.0
Conversion Factor	4.83
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.250000
SAR 10g (W/Kg)	0.213360
SAR 1g (W/Kg)	0.272815

**SURFACE SAR****VOLUME SAR**

## #14




Test Mode: Hotspot LTE Band 5, Low channel(Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 17, 2015

Medium(liquid type)	MSL_900
Frequency (MHz)	829.00000000
Relative permittivity (real part)	53.88
Conductivity (S/m)	0.98
E-Field Probe	SN 17/14 EP220
Crest Factor	1.0
Conversion Factor	5.02
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.630000
SAR 10g (W/Kg)	0.276866
SAR 1g (W/Kg)	0.375942
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>





## #15




Test Mode:LTE Band 17, High channel(Head Left Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 16, 2015

Medium(liquid type)	MSL_750
Frequency (MHz)	711.000000
Relative permittivity (real part)	42.06
Conductivity (S/m)	0.89
E-Field Probe	SN 17/14 EP221
Crest Factor	1.0
Conversion Factor	4.53
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.250000
SAR 10g (W/Kg)	0.148444
SAR 1g (W/Kg)	0.185939

**SURFACE SAR****VOLUME SAR**



## #16




Test Mode: Hotspot LTE Band 17, High channel(Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 16, 2015

Medium(liquid type)	MSL_750
Frequency (MHz)	710.000000
Relative permittivity (real part)	56.57
Conductivity (S/m)	0.99
E-Field Probe	SN 17/14 EP221
Crest Factor	1.0
Conversion Factor	4.70
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.380000
SAR 10g (W/Kg)	0.249996
SAR 1g (W/Kg)	0.328478

**SURFACE SAR****VOLUME SAR**

## #17




Test Mode:802.11b(WiFi2.4G),Low channel(Head Left Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 22, 2015

Medium(liquid type)	MSL 2450
Frequency (MHz)	2412.000000
Relative permittivity (real part)	38.78
Conductivity (S/m)	1.79
E-Field Probe	SN 17/14 EP221
Crest Factor	1.0
Conversion Factor	4.11
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.730000
SAR 10g (W/Kg)	0.250635
SAR 1g (W/Kg)	0.541400
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #18




Test Mode: Hotspot 802.11b(WiFi2.4G),Low channel ( Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 22, 2015

Medium(liquid type)	MSL 2450
Frequency (MHz)	2412.000000
Relative permittivity (real part)	52.55
Conductivity (S/m)	1.91
E-Field Probe	SN 17/14 EP221
Crest Factor	1.0
Conversion Factor	4.25
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.230000
SAR 10g (W/Kg)	0.115378
SAR 1g (W/Kg)	0.230263
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #19




Test Mode:802.11a(WiFi5.2G), Low channel(Head Left Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 23, 2015

Medium(liquid type)	MSL 5000
Frequency (MHz)	5180.000000
Relative permittivity (real part)	36.77
Conductivity (S/m)	4.94
E-Field Probe	SN13/14 EPG214
Crest Factor	1.0
Conversion Factor	16.88
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.570000
SAR 10g (W/Kg)	0.175561
SAR 1g (W/Kg)	0.357033
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #20




Test Mode: Hotspot 802.11a(WiFi5.2G), Low channel ( Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 23, 2015

Medium(liquid type)	MSL 5000
Frequency (MHz)	5180.000000
Relative permittivity (real part)	50.44
Conductivity (S/m)	4.97
E-Field Probe	SN13/14 EPG214
Crest Factor	1.0
Conversion Factor	17.36
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-0.990000
SAR 10g (W/Kg)	0.062304
SAR 1g (W/Kg)	0.120142
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #21




Test Mode:802.11a(WiFi5.8G), High channel(Head Left Cheek)

Product Description: LTE Phone

Model: SF550

Test Date: December 23, 2015

Medium(liquid type)	MSL 5000
Frequency (MHz)	5825.000000
Relative permittivity (real part)	35.36
Conductivity (S/m)	5.76
E-Field Probe	SN13/14 EPG214
Crest Factor	1.0
Conversion Factor	16.24
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	0.480000
SAR 10g (W/Kg)	0.186048
SAR 1g (W/Kg)	0.392871
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>



## #22




Test Mode: Hotspot 802.11a(WiFi5.8G), High channel ( Body Front Side)

Product Description: LTE Phone

Model: SF550

Test Date: December 23, 2015

Medium(liquid type)	MSL 5000
Frequency (MHz)	5825.000000
Relative permittivity (real part)	48.99
Conductivity (S/m)	6.46
E-Field Probe	SN13/14 EPG214
Crest Factor	1.0
Conversion Factor	16.79
Sensor	4mm
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-2.150000
SAR 10g (W/Kg)	0.097244
SAR 1g (W/Kg)	0.196666
<b>SURFACE SAR</b>	<b>VOLUME SAR</b>





## 6. CALIBRATION CERTIFICATES

### 5.1 Probe-EP220 Calibration Certificate



## COMOSAR E-Field Probe Calibration Report

Ref : ACR.287.1.14.SATU.A

**SHENZHEN LCS COMPLIANCE TESTING  
LABORATORY LTD.**  
**1F., XINGYUAN INDUSTRIAL PARK, TONGDA ROAD,  
BAO'AN BLVD**  
**BAO'AN DISTRICT, SHENZHEN, GUANGDONG, CHINA**  
**SATIMO COMOSAR DOSIMETRIC E-FIELD PROBE**  
**SERIAL NO.: SN 17/14 EP220**

**Calibrated at SATIMO US**  
**2105 Barrett Park Dr. - Kennesaw, GA 30144**



**10/01/2015**

#### *Summary:*

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed in SATIMO USA using the CALISAR / CALIBAIR test bench, for use with a SATIMO COMOSAR system only. All calibration results are traceable to national metrology institutions.





## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.287.1.14.SATU.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	10/14/2015	<i>JS</i>
Checked by :	Jérôme LUC	Product Manager	10/14/2015	<i>JS</i>
Approved by :	Kim RUTKOWSKI	Quality Manager	10/14/2015	<i>Kim Rutkowski</i>

	Customer Name
Distribution :	Shenzhen LCS Compliance Testing Laboratory Ltd.

Issue	Date	Modifications
A	10/14/2015	Initial release

Page: 2/9

This document shall not be reproduced, except in full or in part, without the written approval of SATIMO.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of SATIMO.



## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.287.1.14.SATU.A

## TABLE OF CONTENTS

1	Device Under Test .....	4
2	Product Description .....	4
2.1	General Information .....	4
3	Measurement Method .....	4
3.1	Linearity .....	4
3.2	Sensitivity .....	5
3.3	Lower Detection Limit .....	5
3.4	Isotropy .....	5
3.5	Boundary Effect .....	5
4	Measurement Uncertainty .....	5
5	Calibration Measurement Results .....	6
5.1	Sensitivity in air .....	6
5.2	Linearity .....	7
5.3	Sensitivity in liquid .....	7
5.4	Isotropy .....	8
6	List of Equipment .....	9

Page: 3/9

*This document shall not be reproduced, except in full or in part, without the written approval of SATIMO.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to  
be released in whole or part without written approval of SATIMO.*



## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.287.1.14.SATU.A

## 1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	Satimo
Model	SSE5
Serial Number	SN 17/14 EP220
Product Condition (new / used)	New
Frequency Range of Probe	0.7 GHz-3GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.179 MΩ Dipole 2: R2=0.175 MΩ Dipole 3: R3=0.180 MΩ

A yearly calibration interval is recommended.

## 2 PRODUCT DESCRIPTION

### 2.1 GENERAL INFORMATION

Satimo's COMOSAR E field Probes are built in accordance to the IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209 standards.



**Figure 1 – Satimo COMOSAR Dosimetric E field Dipole**

Probe Length	330 mm
Length of Individual Dipoles	4.5 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	5 mm
Distance between dipoles / probe extremity	2.7 mm

## 3 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

### 3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.

Page: 4/9

*This document shall not be reproduced, except in full or in part, without the written approval of SATIMO.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of SATIMO.*



## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.287.1.14.SATU.A

### 3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

### 3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

### 3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 - 360 degrees in 15 degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

### 3.5 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

## 4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Incident or forward power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Reflected power	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Liquid conductivity	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Liquid permittivity	4.00%	Rectangular	$\sqrt{3}$	1	2.309%
Field homogeneity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%
Field probe positioning	5.00%	Rectangular	$\sqrt{3}$	1	2.887%
Field probe linearity	3.00%	Rectangular	$\sqrt{3}$	1	1.732%

Page: 5/9

This document shall not be reproduced, except in full or in part, without the written approval of SATIMO.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of SATIMO.