

Test Report


Applicant : Jiangsu Fulian Communication Technology Co.,Ltd
Address : Yongan Community, the south of Lanling Road, Danyang Development District, Jiangsu Province, China.
Product Name : FLC8720FRA-B
Brand Mark : Fulian
Model : FLC8720FRA-B
FCC ID : 2AXS5-FLC8720FRA-B
Report Number : BLA-EMC-202503-A2703
Date of Receipt : Mar. 7, 2025
Date of Test : Mar. 7, 2025 to Apr. 2, 2025
Test Standard : 47 CFR Part 15, Subpart E 15.407
Test Result : Pass

Compiled by: *Hugh*Review by: *Sueels*Approved by: *Blue Zheng*

Issued Date: Apr. 2, 2025

BlueAsia of Technical Services(Shenzhen) Co.,Ltd

Address: Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1	General information	5
1.1	General information	5
1.2	General description of EUT	5
2	Test summary	7
3	Test Configuration	8
3.1	Test mode	8
3.2	Operation frequency and test channel	9
3.3	Configuration diagram of EUT	10
3.4	Auxiliary equipment	10
3.5	Test environment	10
4	Laboratory information	11
4.1	Laboratory and accreditations	11
4.2	Measurement uncertainty	11
5	Test equipment	12
6	Test result	14
6.1	Antenna requirement	14
6.2	Conducted emissions at AC power line (150 kHz-30 MHz)	15
6.3	Frequency Stability	19
6.4	Maximum conducted output Power	20
6.5	Peak power spectrum density	22
6.6	Minimum 6dB bandwidth (5.725-5.85 GHz band)	23
6.7	26dB Emission bandwidth	24
6.8	99% Bandwidth	25
6.9	Duty Cycle	26
6.10	Conducted Band Edges Measurement	27
6.11	Conducted spurious emissions	29
6.12	Radiated emissions	31
6.13	Radiated emissions which fall in the restricted bands	60
6.14	DFS: Channel Closing Transmission Time	79
6.15	DFS: Non-occupancy period	81

7	Appendix A	83
7.1	Duty Cycle	83
7.2	Maximum Conducted Output Power	101
7.3	-26dB Bandwidth	119
7.4	Occupied Channel Bandwidth	133
7.5	Maximum Power Spectral Density Level	151
7.6	Band Edge	169
7.7	Frequency Stability	182
7.8	Conducted RF Spurious Emission	200
7.9	-6dB Bandwidth	218
	Appendix B: photographs of test setup	223
	Appendix C: photographs of EUT	225

Revise Record

Version No.	Date	Description
01	Apr. 2, 2025	Original

1 General information

1.1 General information

Applicant	Jiangsu Fulian Communication Technology Co.,Ltd
Address	Yongan Community, the south of Lanling Road, Danyang Development District, Jiangsu Province, China.
Manufacturer	Jiangsu Fulian Communication Technology Co.,Ltd
Address	Yongan Community, the south of Lanling Road, Danyang Development District, Jiangsu Province, China.
Factory	Jiangsu Fulian Communication Technology Co.,Ltd
Address	Yongan Community, the south of Lanling Road, Danyang Development District, Jiangsu Province, China.

1.2 General description of EUT

Product Name	FLC8720FRA-B
Model No.	FLC8720FRA-B
Series model	N/A
Operation Frequency	Band 1: 5180MHz-5240MHz; Band 2: 5260MHz~5320MHz; Band 3: 5500MHz~5700MHz; Band 4: 5745MHz-5825MHz.
Channel numbers	Band 1: 802.11a/802.11n(HT20): 4, 802.11n(HT40):2
	Band 2: 802.11a/802.11n(HT20): 4, 802.11n(HT40):2
	Band 3: 802.11a/802.11n(HT20): 11, 802.11n(HT40):5
	Band 4: 802.11a/802.11(HT20): 5, 802.11n(HT40): 2,
Modulation Type	BPSK, QPSK, 16-QAM, 64-QAM
Channel Spacing	802.11a/n: 20MHz, 802.11n: 40MHz
Data speed	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps, Up to 433 Mbps
DFS type	Slave
Antenna Type:	External antenna
Antenna Gain:	Band1: 3.67dBi, Band2: 3.67 dBi Band3: 3.67dBi, Band4: 3.23 dBi(Provided by customer)
Power supply or adapter information	DC3.3V
Hardware Version	N/A
Software Version	N/A

Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

BlueAsia

2 Test summary

No.	Test item	FCC standard	Test Method (Clause)	Result
1	Antenna Requirement	§15.203	N/A	Pass
2	Conducted Emissions at AC Power Line (150kHz-30MHz)	§15.207	ANSI C63.10-2013 Clause 6.2	Pass
3	Frequency Stability	§15.407 (g)	ANSI C63.10-2013 Clause 6.8	Pass
4	Maximum Conducted output power	§15.407 (a)	KDB 789033 D02 II E	Pass
5	Transmitter Power Control	§15.407 (h)(1)	KDB 789033 D02 II E	N/A
6	Peak Power spectrum density	§15.407 (a)	KDB 789033 D02 II F	Pass
7	Minimum 6 dB bandwidth (5.725-5.85 GHz band)	§15.407 (e)	KDB 789033 D02 II C 2	Pass
8	26dB Emission bandwidth	§15.407 (a)	KDB 789033 D02 II C 1	Pass
9	99% Bandwidth	N/A	KDB 789033 II D	Pass
10	Duty Cycle	KDB 789033 D02 II B 1	KDB 789033 II B 1	Pass
11	Conducted Band Edges Measurement	§15.407 (b)(4)	ANSI C63.10-2013 Clause 11.13	Pass
12	Conducted spurious emissions	§15.407(b)	ANSI C63.10-2013 Clause 11.11	Pass
13	Radiated Emissions which fall in the restricted bands	§15.209 §15.407(b)	KDB 789033 D02 II G	Pass
14	Radiated Emissions	§15.209 §15.407(b)	KDB 789033 D02 II G	Pass
15	DFS: Channel Closing Transmission Time	§15.407((h)(2)	KDB 905462 D02 Clause 7.8.3	Pass
16	DFS: Non-occupancy period	§15.407((h)(2)	KDB 905462 D02 Clause 7.8.3	Pass

N/A: Not Applicable

3 Test Configuration

3.1 Test mode

Test Mode ^{Note 1}	Description
TX	Keep the EUT in continuously transmitting mode with modulation.

Note 1: The EUT was configured to measure its highest possible emission and/or immunity level. The test modes were adapted according to the operation manual for use; the EUT was operated in the engineering mode ^{Note 2} to fix the TX frequency that was for the purpose of the measurements.


Note 2: Serial port command is used.

3.2 Operation frequency and test channel

802.11a/n

Bandwidth Band	20(MHz)		40(MHz)	
	Channel number	frequency(MHz)	Channel number	frequency(MHz)
U-NII-1	36	5180	38	5190
	40	5200		
	44	5220	46	5230
	48	5240		
U-NII-2A	52	5260	54	5270
	56	5280		
	60	5300	62	5310
	64	5320		
U-NII-2C	100	5500	102	5510
	104	5520		
	108	5540	110	5550
	112	5560		
	116	5580	--	--
	132	5660	134	5670
	136	5680		
	140	5700	--	--
U-NII-3	149	5745	151	5755
	153	5765		
	157	5785	159	5795
	161	5805		
	165	5825	--	--

3.3 Configuration diagram of EUT



3.4 Auxiliary equipment

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	Lenovo	E460C	N/A	From lab (No.BLA-ZC-BS-2022005)
Note: "--" mean no any auxiliary device during testing.				

3.5 Test environment

Environment	Temperature	Voltage
Normal	25°C	DC 3.3V

4 Laboratory information

4.1 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Address:	Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
CNAS accredited No.:	L9788
A2LA Cert. No.:	5071.01
FCC Designation No.:	CN1252
ISED CAB identifier No.:	CN0028
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

4.2 Measurement uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

Parameter	Expanded Uncertainty
Radiated Emission(9kHz-30MHz)	$\pm 4.34\text{dB}$
Radiated Emission(30Mz-1000MHz)	$\pm 4.24\text{dB}$
Radiated Emission(1GHz-18GHz)	$\pm 4.68\text{dB}$
AC Power Line Conducted Emission(150kHz-30MHz)	$\pm 3.45\text{dB}$
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 1.5\text{ dB}$
Power Spectral Density, conducted	$\pm 3.0\text{ dB}$
Unwanted Emissions, conducted	$\pm 3.0\text{ dB}$
Temperature	$\pm 3\text{ }^{\circ}\text{C}$
Supply voltages	$\pm 3\%$
Time	$\pm 5\%$

5 Test equipment

Radiated Spurious Emissions (Below 1GHz)

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-002-01	Anechoic chamber	9*6*6 chamber	SKET	N/A	2024/3/27	2027/3/26
BLA-EMC-002-02	Control room	966 control room	SKET	N/A	2024/3/27	2027/3/26
BLA-EMC-009	EMI receiver	ESR7	R&S	101199	2024/08/08	2025/08/07
BLA-EMC-043	Loop antenna	FMZB1519B	Schwarzbeck	00102	2024/06/29	2026/06/28
BLA-EMC-065	Broadband antenna	VULB9168	Schwarzbeck	01065P	2024/06/29	2026/06/27
BLA-XC-01	Coaxial Cable	N/A	BlueAsia	V01	N/A	N/A
BLA-XC-02	Coaxial Cable	N/A	BlueAsia	V02	N/A	N/A

Radiated Spurious Emissions (Above 1GHz)

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-001-01	Anechoic chamber	9*6*6 chamber	SKET	N/A	2023/11/16	2026/11/15
BLA-EMC-001-02	Control Room	966 control room	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-008	Spectrum	FSP40	R&S	100817	2024/08/08	2025/08/07
BLA-EMC-012	Broadband antenna	VULB9168	Schwarzbeck	00836 P:00227	2022/10/12	2025/10/11
BLA-EMC-013	Horn Antenna	BBHA9120D	Schwarzbeck	01892	2024/06/29	2026/06/28
BLA-EMC-014	Amplifier	PA_000318G-45	SKET	PA201804 3003	2024/08/08	2025/08/07
BLA-EMC-046	Filter bank	2.4G/5G Filter bank	SKET	N/A	2024/06/28	2025/06/27
BLA-EMC-061	Receiver	ESPI7	R&S	101477	2024/06/28	2025/06/27
BLA-EMC-066	Amplifier	LNPA_30M01 G-30	SKET	SK202106 0801	2024/06/28	2025/06/27
BLA-EMC-086	Amplifier	LNPA_18G40 G-50dB	SKET	SK202207 1301	2024/06/28	2025/06/27
BLA-EMC-087	Horn Antenna	BBHA 9170	Schwarzbeck	1106	2024/06/29	2026/06/28
BLA-XC-03	Coaxial Cable	N/A	BlueAsia	V03	N/A	N/A
BLA-XC-04	Coaxial Cable	N/A	BlueAsia	V04	N/A	N/A

Conducted Emissions

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-003-001	Shield room	8*3*3	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-009	EMI receiver	ESR7	R&S	101199	2024/08/08	2025/08/07
BLA-EMC-011	LISN	ENV216	R&S	101372	2024/08/08	2025/08/07
BLA-EMC-033	Impedance transformer	DC-2GHz	DFXP	N/A	2024/06/28	2025/06/27
BLA-EMC-041	LISN	AT166-2	ATTEN	AKK180600003	2024/08/08	2025/08/07
BLA-EMC-045	Impedance stable network	ISNT8-cat 6	TESEQ	53580	2024/08/08	2025/08/07
BLA-EMC-095	Single-channel vehicle artificial power network	NNBM 8124	Schwarzbeck	01045	2024/06/28	2025/06/27
BLA-EMC-096	Single-channel vehicle artificial power network	NNBM 8124	Schwarzbeck	01075	2024/06/28	2025/06/27
BLA-XC-05	Coaxial Cable	N/A	BlueAsia	V05	N/A	N/A

RF conducted

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-003-003	Shield room	5*3*3	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-016	Signal Generator	N5182A	Agilent	MY52420567	2024/06/28	2025/06/27
BLA-EMC-038	Spectrum	N9020A	Agilent	MY49100060	2024/08/08	2025/08/07
BLA-EMC-042	Power sensor	RPR3006W	DARE	14I00889SN042	2024/08/08	2025/08/07
BLA-EMC-044	Radio communication tester	CMW500	R&S	132429	2024/08/08	2025/08/07
BLA-EMC-064	Signal Generator	N5182B	KEYSIGHT	MY58108892	2024/06/28	2025/06/27
BLA-EMC-079	Spectrum	N9020A	Agilent	MY54420161	2024/08/08	2025/08/07
BLA-EMC-088	Audio Analyzer	ATS-1	Audio Precision	ATS141094	2024/06/28	2025/06/27

Test software

Software No.	Software Name	Manufacture	Software version	Test site
BLA-EMC-S001	EZ-EMC	EZ	EEMC-3A1+	RE(Below 1GHz)
BLA-EMC-S002	EZ-EMC	EZ	EEMC-3A1+	RE(Above 1GHz)
BLA-EMC-S003	EZ-EMC	EZ	EEMC-3A1+	CE
BLA-EMC-S010	MTS 8310	MW	2.0.0.0	RF

6 Test result

6.1 Antenna requirement

Test Standard	47 CFR Part 15, Subpart C 15.203
Test Method	N/A

6.1.1 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of a so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is Band1: 3.67dBi, Band2: 3.67 dBi, Band3: 3.67dBi, Band4: 3.23 dBi.

6.2 Conducted emissions at AC power line (150 kHz-30 MHz)


Test Standard	47 CFR Part 15, Subpart C 15.207
Test Method	ANSI C63.10-2013 Clause6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.2.1 Limit

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

6.2.2 Test setup



Description of test setup connection:

- Connect the control PC to the receiver through a USB to GPIB cable;
- The receiver is connected to the LISN through a coaxial line;
- Connect the power port of LISN to the EUT.

6.2.3 Procedure

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

LISN=Read Level+ Cable Loss+ LISN Factor

6.2.4 Test data


[Test mode: TX]; [Line: Line];[Power:AC120V/60Hz]

Conducted Emission Measurement

Project No.: CE

Data :#6

2025/04/02



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Antenna Height cm	Table Degree	Comment
1	0.2660	28.05	9.85	37.90	61.24	-23.34	QP		
2	0.2660	18.65	9.85	28.50	51.24	-22.74	AVG		
3	0.5580	22.31	9.79	32.10	56.00	-23.90	QP		
4	0.5580	14.61	9.79	24.40	46.00	-21.60	AVG		
5	1.5020	19.67	9.86	29.53	56.00	-26.47	QP		
6	1.5020	14.70	9.86	24.56	46.00	-21.44	AVG		
7	2.3220	18.79	9.96	28.75	56.00	-27.25	QP		
8	2.3220	17.34	9.96	27.30	46.00	-18.70	AVG		
9	3.9740	21.92	10.14	32.06	56.00	-23.94	QP		
10 *	3.9740	20.12	10.14	30.26	46.00	-15.74	AVG		
11	6.8060	24.04	10.24	34.28	60.00	-25.72	QP		
12	6.8060	22.95	10.24	33.19	50.00	-16.81	AVG		

Test Result: Pass


[Test mode: TX]; [Line: Neutral];[Power:AC120V/60Hz]

Conducted Emission Measurement

Project No.: CE

Data :#5

2025/04/02



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV	dBuV	dB	cm	degree	Comment
1		0.5740	25.01	9.71	34.72	56.00	-21.28	QP		
2		0.5740	18.82	9.71	28.53	46.00	-17.47	AVG		
3		1.6820	19.55	9.79	29.34	56.00	-26.66	QP		
4		1.6820	16.15	9.79	25.94	46.00	-20.06	AVG		
5		4.2580	21.14	10.06	31.20	56.00	-24.80	QP		
6	*	4.2580	20.74	10.06	30.80	46.00	-15.20	AVG		
7		6.3460	22.53	10.23	32.76	60.00	-27.24	QP		
8		6.3460	21.60	10.23	31.83	50.00	-18.17	AVG		
9		10.7540	33.30	0.10	33.40	60.00	-26.60	QP		
10		10.7540	29.02	0.10	29.12	50.00	-20.88	AVG		
11		15.5180	18.01	11.93	29.94	60.00	-30.06	QP		
12		15.5180	15.43	11.93	27.36	50.00	-22.64	AVG		

Test Result: Pass


6.3 Frequency Stability

Test Standard	47 CFR Part 15, Subpart E 15.407(g)
Test Method	ANSI C63.10-2013 Clause 6.8
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.3.1 Limit

The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 35 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

6.3.2 Test setup



6.3.3 Test data

Pass: Please refer to appendix A for details

6.4 Maximum conducted output Power

Test Standard	47 CFR Part 15, Subpart E 15.407 (a)
Test Method	KDB 789033 D02 II E
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX


6.4.1 Limit

Frequency band(MHz)	Limit
5150-5250	$\leq 1\text{W}(30\text{dBm})$ for master device
	$\leq 250\text{mW}(24\text{dBm})$ for client device
5250-5350	$\leq 250\text{mW}(24\text{dBm})$ for client device or $11\text{dBm}+10\log B^*$
5470-5725	$\leq 250\text{mW}(24\text{dBm})$ for client device or $11\text{dBm}+10\log B^*$
5725-5850	$\leq 1\text{W}(30\text{dBm})$

Remark:* Where B is the 26dB emission bandwidth in MHz.

The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

6.4.2 Test setup



6.4.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.5 Peak power spectrum density


Test Standard	47 CFR Part 15, Subpart E 15.407 (a)
Test Method	KDB 789033 D02 II F
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.5.1 Limit

Frequency band(MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500 kHz

Remark: The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.

6.5.2 Test setup



6.5.3 Test data

Pass: Please refer to appendix A for details

BlueAsia of Technical Services (Shenzhen) Co., Ltd.

Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Report version : V1.3


6.6 Minimum 6dB bandwidth (5.725-5.85 GHz band)

Test Standard	47 CFR Part 15, Subpart E 15.407 (e)
Test Method	KDB 789033 D02 II C 2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.6.1 Limit

≥500 kHz

6.6.2 Test setup



6.6.3 Test data


Pass: Please refer to appendix A for details

6.7 26dB Emission bandwidth

Test Standard	47 CFR Part 15, Subpart E 15.407 (a)
Test Method	KDB 789033 D02 II C 1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.7.1 Limit

6.7.2 Test setup



6.7.3 Test data


Pass: Please refer to appendix A for details

6.8 99% Bandwidth

Test Standard	N/A
Test Method	KDB 789033 II D
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.8.1 Limit

6.8.2 Test setup




6.8.3 Test data

Pass: Please refer to appendix A for details

6.9 Duty Cycle

Test Standard	47 CFR Part 15, Subpart E 15.407
Test Method	KDB 789033 II B 1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.9.1 Test setup



6.9.2 Test data

Pass: Please refer to appendix A for details

6.10 Conducted Band Edges Measurement

Test Standard	47 CFR Part 15, Subpart C 15.407(b)(4)
Test Method	ANSI C63.10-2013 Clause 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.10.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.10.2 Test setup



6.10.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.11 Conducted spurious emissions

Test Standard	47 CFR Part 15, Subpart C 15.407
Test Method	ANSI C63.10-2013 Clause 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.11.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.11.2 Test setup



6.11.3 Test data

Pass: Please refer to appendix A for details

BlueAsia