

**FCC PART 15.247**  
**RSS-GEN, ISSUE 4, NOVEMBER 2014**  
**RSS-247, ISSUE 2, FEBRUARY 2017**  
**TEST REPORT**

For

**SZ DJI Osmo Technology Co.,Ltd.**

12th floor, West Wing, Skyworth Semiconductor Design Building NO.18 Gaoxin South 4th Ave,  
Nanshan District, Shenzhen, China

**FCC ID: 2ANDR-RS11804**  
**IC: 23060-RS11804**

<b>Report Type:</b> Original Report	<b>Product Name:</b> Ronin-S
<b>Report Number:</b>	RDG180414002-00A
<b>Report Date:</b>	2018-04-24
<b>Reviewed By:</b>	Jerry Zhang EMC Manager
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	6
EUT EXERCISE SOFTWARE .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	7
SUPPORT CABLE LIST AND DETAILS .....	7
BLOCK DIAGRAM OF TEST SETUP .....	8
<b>SUMMARY OF TEST RESULTS.....</b>	<b>9</b>
<b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1093- RF EXPOSURE.....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
<b>RSS-102 § 2.5.1 EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION .....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
<b>FCC §15.203 ,RSS-GEN§8.3- ANTENNA REQUIREMENT.....</b>	<b>12</b>
APPLICABLE STANDARD .....	12
ANTENNA INFORMATION AND CONNECTOR CONSTRUCTION.....	12
<b>FCC §15.207 (a),RSS-Gen §8.8– AC LINE CONDUCTED EMISSIONS.....</b>	<b>13</b>
APPLICABLE STANDARD .....	13
EUT SETUP .....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE .....	14
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST DATA .....	15
<b>FCC §15.209, §15.205 , §15.247(d) &amp; RSS-247 §5.5&amp;RSS-GEN§8.10- SPURIOUS EMISSIONS .....</b>	<b>17</b>
APPLICABLE STANDARD .....	17
EUT SETUP .....	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	18
TEST PROCEDURE .....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	18
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST DATA .....	19
<b>FCC §15.247(a) (2)&amp; RSS-247 §5.2 a) &amp;RSS-247 §5.2 a) &amp;RSS-GEN§6.6 –6 dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</b>	<b>25</b>
APPLICABLE STANDARD .....	25
TEST PROCEDURE .....	25
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA .....	26

<b>FCC §15.247(b) (3)&amp;RSS-247 §5.4 d) - MAXIMUM CONDUCTED OUTPUT POWER .....</b>	<b>30</b>
APPLICABLE STANDARD .....	30
TEST PROCEDURE .....	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST DATA .....	31
<b>FCC §15.247(d)&amp;RSS-247 §5.5 – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>33</b>
APPLICABLE STANDARD .....	33
TEST PROCEDURE .....	33
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA .....	34
<b>FCC §15.247(e) &amp;RSS-247 §5.2 b)- POWER SPECTRAL DENSITY .....</b>	<b>36</b>
APPLICABLE STANDARD .....	36
TEST PROCEDURE .....	36
TEST EQUIPMENT LIST AND DETAILS.....	36
TEST DATA .....	36

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>		Ronin-S
<b>EUT Model:</b>		RS1
<b>FCC ID:</b>		2ANDR-RS11804
<b>IC:</b>		23060-RS11804
<b>Rated Input Voltage:</b>		12Vdc from adapter and 14.4V from battery
<b>Adapter Information</b>	<b>Manufacturer:</b>	DJI
	<b>Model:</b>	QC24-US
	<b>Input:</b>	100-240VAC~50/60Hz Max 0.8A
	<b>Output:</b>	3.6~8V/3A or 12V/2A
<b>External Dimension:</b>		293 mm (L) x 256 mm (W) x 590 mm (H)
<b>Serial Number:</b>		180414002
<b>EUT Received Date:</b>		2018.04.14

### Objective

This report is prepared on behalf of *SZ DJI Osmo Technology Co.,Ltd.* in accordance with Part 2, Subpart J, Part 15, Subparts A, and C of the Federal Communications Commission's rules and RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada, RSS-Gen Issue 4, November 2014 of the Innovation, Science and Economic Development Canada.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.209, 15.247 rules and RSS-247, Issue 2, February 2017, RSS-Gen Issue 4, November 2014 of the Innovation, Science and Economic Development Canada.

### Related Submittal(s)/Grant(s)

N/A.

### Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices", RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada, RSS-Gen Issue 4, November 2014 of the Innovation, Science and Economic Development Canada.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

**Measurement Uncertainty**

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~26.5GHz: 5.23 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

### Equipment Modifications


No modification was made to the EUT tested.

### EUT Exercise Software

The worst condition (maximum power) was configured by system default setting, the software RF 'Certification.exe' was use for change the test mode and channels.

The duty cycle as below:

T <sub>on</sub> (ms)	T <sub>on+off</sub> (ms)	Duty Cycle (%)	Minimum Transmission Duration (T) (ms)
100	100	100	100



Date: 14.APR.2018 14:23:29


### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
MLF	adapter	S005AYU0500100	N/A

### Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	yes	no	0.6	adapter	EUT

## Block Diagram of Test Setup





**SUMMARY OF TEST RESULTS**

Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
RSS-102 §2.5.1	Exemption Limits for Routine Evaluation -SAR Evaluation	Compliance
FCC§15.203 RSS-GEN§8.3	Antenna Requirement	Compliance
§15.207 (a) RSS-Gen §8.8	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d) RSS-247 §5.5 RSS-Gen §8.10	Spurious Emissions	Compliance
§15.247 (a)(2) RSS-247 §5.2 a)	6 dB Emission Bandwidth And 99% Occupied Bandwidth	Compliance
§15.247(b)(3) RSS-247 §5.4 d)	Maximum conducted output power	Compliance
§15.247(d) RSS-247 §5.5	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247 (e) RSS-247 §5.2 b)	Power Spectral Density	Compliance

---

**FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**

---

**Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

**Measurement Result**

The max conducted power including tune-up tolerance is -2.0 dBm (0.63 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$   
 $= 0.63/5 \cdot (\sqrt{2.480}) = 0.2 < 3.0$

**So the stand-alone SAR evaluation is not necessary.**

## RSS-102 § 2.5.1 EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION

### Applicable Standard

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5.

**Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>45</sup>**

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

### Measurement Result:

The maximum output power including tune up tolerance is -2.0 dBm, which was declared by manufacturer. The antenna gain is 0.3 dBi, so the EIRP=-2.0+0.3= -1.7 dBm(0.68mW)

The exemption power(P) limits for routine evaluation in 2402-2480MHz is:

$$(2480-2450)/(3500-2450)=(4-P)/(4-2)$$

$$\Rightarrow P=3.96 \text{ mW}@2480\text{MHz}$$

$$> 0.68 \text{ mW}$$

So the SAR evaluation can be exempted.

## **FCC §15.203 ,RSS-GEN§8.3- ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
  - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

According to RSS-Gen §8.3, The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the licence-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.

Licence-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (e.i.r.p.) limits specified in the applicable standard (RSS) for the licence-exempt apparatus.

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.<sup>9</sup> When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

User manuals for transmitters equipped with detachable antennas shall also contain the following notice in a conspicuous location:

*This radio transmitter (identify the device by certification number or model number if Category II) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.*

Immediately following the above notice, the manufacturer shall provide a list of all antenna types approved for use with the transmitter, indicating the maximum permissible antenna gain (in dBi).

### **Antenna Information And Connector Construction**

The EUT has one internal antenna arrangement for BLE mode, the antenna gain is 0.3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliance.

## FCC §15.207 (a), RSS-Gen §8.8– AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207(a) and RSS-Gen§8.8

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 and RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

## Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

$V_C$ : corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2017-12-11	2018-12-11
R&S	L.I.S.N	ESH2-Z5	892107/021	2017-09-25	2018-09-25
R&S	Two-line V-network	ENV 216	3560.6550.12	2017-12-08	2018-12-08
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2017-09-05	2018-09-05

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**


<b>Temperature:</b>	25.2 °C
<b>Relative Humidity:</b>	52 %
<b>ATM Pressure:</b>	101.2 kPa

The testing was performed by Ade Xiao on 2018-04-17.

**Test Mode: Transmitting****AC120V, 60 Hz, Line:**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.415949	31.7	9.000	L1	10.0	25.8	57.5	Compliance
0.432855	33.0	9.000	L1	9.9	24.2	57.2	Compliance
0.515791	36.6	9.000	L1	9.9	19.4	56.0	Compliance
0.541050	43.3	9.000	L1	9.9	12.7	56.0	Compliance
0.563041	37.4	9.000	L1	9.9	18.6	56.0	Compliance
0.991374	29.6	9.000	L1	9.8	26.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.454052	22.4	9.000	L1	9.9	24.4	46.8	Compliance
0.499611	25.9	9.000	L1	9.9	20.1	46.0	Compliance
0.519918	31.8	9.000	L1	9.9	14.2	46.0	Compliance
0.541050	34.1	9.000	L1	9.9	11.9	46.0	Compliance
0.563041	29.6	9.000	L1	9.9	16.4	46.0	Compliance
1.190776	26.0	9.000	L1	9.8	20.0	46.0	Compliance

**AC120V, 60 Hz, Neutral:**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.457684	33.0	9.000	N	9.9	23.7	56.7	Compliance
0.499611	35.7	9.000	N	9.9	20.3	56.0	Compliance
0.519918	38.8	9.000	N	9.9	17.2	56.0	Compliance
0.545378	37.7	9.000	N	9.9	18.3	56.0	Compliance
0.563041	37.7	9.000	N	9.8	18.3	56.0	Compliance
1.239175	30.0	9.000	N	9.8	26.0	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.499611	25.7	9.000	N	9.9	20.3	46.0	Compliance
0.519918	28.4	9.000	N	9.9	17.6	46.0	Compliance
0.541050	35.2	9.000	N	9.9	10.8	46.0	Compliance
0.563041	28.7	9.000	N	9.8	17.3	46.0	Compliance
1.117238	26.4	9.000	N	9.8	19.6	46.0	Compliance
1.259081	23.3	9.000	N	9.8	22.7	46.0	Compliance




## FCC §15.209, §15.205 , §15.247(d) & RSS-247 §5.5&RSS-GEN§8.10- SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205; and RSS-247 §5.5, RSS-GEN §8.10

### EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 and RSS-247 §5.5,RSS-Gen §8.10 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-12-11	2018-12-11
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
HP	Amplifier	8447D	2727A05902	2017-09-05	2018-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2018-01-04	2019-01-04
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-04
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2017-06-16	2020-06-15
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2017-09-05	2018-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2017-06-27	2018-06-27
Agilent	Spectrum Analyzer	E4440A	SG43360054	2018-01-04	2019-01-04
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2017-06-27	2018-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2017-06-16	2018-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2017-06-16	2018-06-16
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A


\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**


<b>Temperature:</b>	24.3 °C
<b>Relative Humidity:</b>	40 %
<b>ATM Pressure:</b>	100.5 kPa

*The testing was performed by Sunny Cen on 2018-04-14.*

*Test Mode: Transmitting*

**1) 30MHz-1GHz(Low Channel was the worst):****Horizontal:**

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	24.96	QP	1.54	26.50	40.00	13.50
101.7800	29.61	QP	-8.41	21.20	43.50	22.30
248.2500	28.03	QP	-6.13	21.90	46.00	24.10
262.8000	26.87	QP	-4.77	22.10	46.00	23.90
380.1700	28.32	QP	-2.52	25.80	46.00	20.20
405.3900	30.84	QP	-1.94	28.90	46.00	17.10

**Vertical:**

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
42.6100	42.88	QP	-7.68	35.20	40.00	4.80
110.5100	37.07	QP	-6.37	30.70	43.50	12.80
143.4900	37.97	QP	-5.97	32.00	43.50	11.50
158.0400	39.49	QP	-5.89	33.60	43.50	9.90
248.2500	31.23	QP	-6.13	25.10	46.00	20.90
405.3900	29.74	QP	-1.94	27.80	46.00	18.20




**2) 1-25GHz:**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402.00	53.25	PK	H	28.10	1.80	0.00	83.15	N/A	N/A
2402.00	52.14	AV	H	28.10	1.80	0.00	82.04	N/A	N/A
2402.00	57.88	PK	V	28.10	1.80	0.00	87.78	N/A	N/A
2402.00	56.54	AV	V	28.10	1.80	0.00	86.44	N/A	N/A
2390.00	23.47	PK	V	28.08	1.80	0.00	53.35	74.00	20.65
2390.00	13.82	AV	V	28.08	1.80	0.00	43.70	54.00	10.30
4804.00	47.54	PK	V	32.91	3.17	37.20	46.42	74.00	27.58
4804.00	45.36	AV	V	32.91	3.17	37.20	44.24	54.00	9.76
7206.00	43.54	PK	V	35.74	4.82	37.23	46.87	74.00	27.13
7206.00	41.05	AV	V	35.74	4.82	37.23	44.38	54.00	9.62
Middle Channel: 2440 MHz									
2440.00	54.25	PK	H	28.18	1.82	0.00	84.25	N/A	N/A
2440.00	52.47	AV	H	28.18	1.82	0.00	82.47	N/A	N/A
2440.00	56.98	PK	V	28.18	1.82	0.00	86.98	N/A	N/A
2440.00	54.87	AV	V	28.18	1.82	0.00	84.87	N/A	N/A
4880.00	45.59	PK	V	33.06	3.27	37.21	44.71	74.00	29.29
4880.00	43.22	AV	V	33.06	3.27	37.21	42.34	54.00	11.66
7320.00	43.26	PK	V	36.03	4.62	37.37	46.54	74.00	27.46
7320.00	40.47	AV	V	36.03	4.62	37.37	43.75	54.00	10.25
High Channel: 2480 MHz									
2480.00	54.56	PK	H	28.26	1.84	0.00	84.66	N/A	N/A
2480.00	52.55	AV	H	28.26	1.84	0.00	82.65	N/A	N/A
2480.00	57.54	PK	V	28.26	1.84	0.00	87.64	N/A	N/A
2480.00	54.71	AV	V	28.26	1.84	0.00	84.81	N/A	N/A
2483.50	25.49	PK	V	28.27	1.84	0.00	55.60	74.00	18.40
2483.50	13.57	AV	V	28.27	1.84	0.00	43.68	54.00	10.32
4960.00	45.65	PK	V	33.22	3.23	37.25	44.85	74.00	29.15
4960.00	43.26	AV	V	33.22	3.23	37.25	42.46	54.00	11.54
7440.00	42.58	PK	V	36.34	4.41	37.52	45.81	74.00	28.19
7440.00	40.13	AV	V	36.34	4.41	37.52	43.36	54.00	10.64

## Worst plots (Low Channel)




### Horizontal

Fundamental  
Test with Band  
Rejection Filter



# Vertical

Fundamental  
Test with Band  
Rejection Filter





## **FCC §15.247(a) (2)& RSS-247 §5.2 a) &RSS-247 §5.2 a) &RSS-GEN§6.6 –6 dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH**

### **Applicable Standard**

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

According to RSS-247 §5.2 a)

The minimum 6 dB bandwidth shall be 500 kHz.


According to RSS-Gen §6.6

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

When the occupied bandwidth limit is not stated in the applicable RSS or reference measurement method, the transmitted signal bandwidth shall be reported as the 99% emission bandwidth, as calculated or measured.

### **Test Procedure**

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times \text{RBW}$ .
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- h) Measure the 99% bandwidth use OBW test function.



**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESPI	100120	2017-12-11	2018-12-11
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

Temperature:	26.8 °C
Relative Humidity:	58 %
ATM Pressure:	100.5 kPa

*The testing was performed by Kami Zhou on 2018-04-14.*


*Test Mode: Transmitting*

*Test Result: Compliant. Please refer to the following table and plots.*

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Occupied bandwidth (MHz)	Limit (MHz)
Low	2402	0.69	1.05	$\geq 0.5$
Middle	2440	0.68	1.06	$\geq 0.5$
High	2480	0.69	1.06	$\geq 0.5$


## 6dB Bandwidth:

### Low Channel




Date: 14.APR.2018 13:27:36


### Middle Channel



Date: 14.APR.2018 13:29:59


**High Channel**

Date: 14.APR.2018 13:32:15

**99% Occupied Bandwidth:****Low Channel**


Date: 14.APR.2018 13:27:49

## Middle Channel



Date: 14.APR.2018 13:30:11

## High Channel



Date: 14.APR.2018 13:32:29

## FCC §15.247(b) (3)&RSS-247 §5.4 d) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to RSS-247§5.4 d) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. Except as provided in Section 5.4(e), the e.i.r.p. shall not exceed 4 W.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESPI	100120	2017-12-11	2018-12-11
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**


Temperature:	26.8 °C
Relative Humidity:	58 %
ATM Pressure:	100.5 kPa

The testing was performed by Kami Zhou on 2018-04-14.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table.

Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Limit (dBm)
Low	2402	-2.56	30
Middle	2440	-2.76	30
High	2480	-2.13	30

**Low Channel**


Date: 14.APR.2018 13:28:02

### Middle Channel



Date: 14.APR.2018 13:30:24

### High Channel



Date: 14.APR.2018 13:32:42



## **FCC §15.247(d)&RSS-247 §5.5 – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

---

### **Applicable Standard**

According to FCC §15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to RSS-247 §5.5:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESPI	100120	2017-12-11	2018-12-11
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**


Temperature:	26.8 °C
Relative Humidity:	58 %
ATM Pressure:	100.5 kPa

*The testing was performed by Kami Zhou on 2018-04-14.*

*Test mode: Transmitting*


*Test Result: Compliant. Please refer to following plots.*

## Band Edge, Left Side



Date: 14.APR.2018 13:29:00

## Band Edge, Right Side



Date: 14.APR.2018 13:33:40

## **FCC §15.247(e) & RSS-247 §5.2 b)- POWER SPECTRAL DENSITY**

### **Applicable Standard**

According to FCC§15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-247 §5.2 b):

- b) The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

### **Test Procedure**

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set the VBW  $\geq 3 \times \text{RBW}$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESPI	100120	2017-12-11	2018-12-11
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### **Test Data**

#### **Environmental Conditions**

Temperature:	25.5 °C
Relative Humidity:	54 %
ATM Pressure:	101.1 kPa


*The testing was performed by Kami Zhou on 2018-04-16.*

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-13.49	$\leq 8$
Middle	2440	-14.06	$\leq 8$
High	2480	-13.67	$\leq 8$

### Power Spectral Density, Low Channel




Date: 16.APR.2018 15:49:13

### Power Spectral Density, Middle Channel



Date: 16.APR.2018 15:52:36

### Power Spectral Density, High Channel



Date: 16.APR.2018 15:50:25

\*\*\*\*\* END OF REPORT \*\*\*\*\*