

KDB 447498 D03
IEEE C95.1
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

IoT Gateway

Model: XI*(*=0~9, A~Z or Blank)

Trade Name: N/A

Issued to

Quanta Computer Inc.
No.188, Wenhua 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan
(R.O.C.)

Issued by

Compliance Certification Services Inc.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
<http://www.ccsrf.com>
service@ccsrf.com
Issued Date: January 14, 2016



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2016/1/14	Initial Issue	ALL	Becca Chen

TABLE OF CONTENTS

1. LIMIT	4
2. EUT SPECIFICATION	4
3. TEST RESULTS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE	6

1. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT SPECIFICATION

EUT	IoT Gateway		
Model	XI*(*=0~9, A~Z or Blank)		
RF Module	Broadcom	Model:	BCM43438
Model Discrepancy	All the above models are identical except for the designation of model numbers. The suffix of (*=0~9, A~Z or Blank) on model number is just for marketing purpose only.		
Frequency band (Operating)	<input checked="" type="checkbox"/> 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> Bluetooth 2.1 + EDR: 2402 ~ 2480 MHz <input checked="" type="checkbox"/> Bluetooth 4.0: 2402 ~ 2480 MHz <input type="checkbox"/> Others		
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others		
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)		
Antenna Specification	Monopole-coupled Antenna: 2.4GHz: Antenna Gain : 2.19 dBi (Numeric gain 1.66)		
Maximum Average output power	IEEE 802.11b Mode: 16.49 dBm (44.566 mW) IEEE 802.11g Mode: 15.77 dBm (37.757 mW) IEEE 802.11n HT 20 Mode: 14.78 dBm (30.061 mW) Bluetooth 2.1 + EDR: 9.14 dBm (8.204 mW) Bluetooth 4.0: 7.47 dBm (5.585 mW)		
Maximum Tune up Power	IEEE 802.11b Mode: 18.00 dBm (63.096 mW) IEEE 802.11g Mode: 17.00 dBm (50.119 mW) IEEE 802.11n HT 20 Mode: 16.00 dBm (39.811 mW) Bluetooth 2.1 + EDR: 11.00 dBm (12.589 mW) Bluetooth 4.0: 9.00 dBm (7.943 mW)		
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A		

3. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

4. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2412	63.096	1.66	20	0.0208	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2412	50.119	1.66	20	0.0166	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	39.811	1.66	20	0.0132	1

Bluetooth 2.1 + EDR: :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
1	2402	12.589	1.66	20	0.0042	1

Bluetooth 4.0 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
0	2402	7.943	1.66	20	0.0026	1