

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Guangzhou Panyu Juda Car Audio Equipment Co.,Ltd.

Bluetooth Speaker

Model Number: UB-SPB4M-101

FCC ID: ESXSPB4M

Prepared for : Guangzhou Panyu Juda Car Audio Equipment Co.,Ltd.
Vtrek Dewei Industrial Garden,Shibei Industrial Road,
Dashi Town, Panyu Borough, Guangzhou , Guangdong
, China

Prepared By : EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City,
GuangDong, China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1408006
Date of Test : July 24,2014~ Aug 10, 2014
Date of Report : Aug 11, 2014

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT)	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities	7
2.3. Assistant equipment used for test	8
2.4. Block Diagram	8
2.5. Test mode	8
2.6. Channel List for Bluetooth.....	8
2.7. Test Equipment.....	9
3 POWER LINE CONDUCTED EMISSION TEST.....	10
3.1. Limit.....	10
3.2. Block Diagram of Test Setup	10
3.3. Test Procedure	10
3.4. Test Result.....	10
3.5. Test data	11
4 RADIATED EMISSION TEST	13
4.1 Limit.....	13
4.2. Test Procedure	14
4.3 Block Diagram of Test setup.....	14
4.4 Test Result.....	14
4.5 Test Data	15
5 CONDUCTED SPURIOUS EMISSION.....	33
5.1 Limit	33
5.2 Test Procedure.....	33
5.3 Test Result.....	33
5.4 Test Data	34
6 BAND EDGE COMPLIANCE TEST	40
6.1 Limit	40
6.2 Test Procedure	40
6.3 Test Result.....	40
6.4 Test Data	41
7 6dB Bandwidth Test.....	45
7.1 Limit	45
7.2 Test Procedure	45
7.3 Test Result.....	45
7.4 Test Data	46
8 OUTPUT POWER TEST	48
8.1 Limit	48
8.2 Test Procedure.....	48
8.3 Test Procedure	48

8.4 Test Result.....49

8.5 Test Data50

9 POWER SPECTRAL DENSITY TEST52

9.1 Limit52

9.2 Test Procedure.....52

9.3 Test Result.....53

9.4 Test Data54

10 ANTENNA REQUIREMENTS56




10.1 Limit56

10.2 Result.....56

11 TEST SETUP PHOTO.....57

12 PHOTOS OF EUT60

Test Report Verification

Applicant:	Guangzhou Panyu Juda Car Audio Equipment Co.,Ltd.		
Address:	Vtrek Dewei Industrial Garden,Shibei Industrial Road, Dashi Town, Panyu Borough Guangzhou, Guangdong , China		
Manufacturer Address:	Guangzhou Panyu Juda Car Audio Equipment Co.,Ltd. Vtrek Dewei Industrial Garden,Shibei Industrial Road, Dashi Town, Panyu Borough Guangzhou, Guangdong , China		
E.U.T:	Bluetooth Speaker		
Model Number:	UB-SPB4M-101		
Power Supply:	DC 10V From Adapter Input AC 100-240V~50/60Hz ; 1.5A DC 7.4V From Internal Battery		
Test Voltage:	DC 10V From Adapter Input AC 120V/60Hz		
Trade Name:	URBAN BEATZ	Serial No.:	-----
Date of Receipt:	July 24, 2014	Date of Test:	July 24,2014~ Aug 10, 2014
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2013 ANSI C63.4:2009		
Test Result:	The device described above is tested by EST Technology Co., Ltd.. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the ETSI EN FCC Rules and Regulations Part 15 Subpart C requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd. Date: Aug 11, 2014		
Prepared by:	Tested by:	Approved by:	
			
Ada / Assistant	Tony.Tang/ Engineer	IcemanHu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	: Bluetooth Speaker
Model Number	: UB-SPB4M-101
FCC ID	: ESXSPB4M
Operation frequency	: 2402MHz~2480MHz
Number of channel	: 40
Antenna	: Internal antenna, 0 dBi gain
Modulation	: Bluetooth V4.0 BLE: GFSK
Power Supply	: DC 10V From Adapter Input AC 120V/60Hz
Sample Type	: Prototype production

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.4:2009	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.4:2009 KDB 558074	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
Conducted spurious emissions	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

2.2. Test Facilities

EMC Lab : Certificated by CNAL, CHINA
 Registration No.: L5288
 Date of registration: October 28, 2011

 Certificated by FCC, USA
 Registration No.: 989591
 Date of registration: November 20, 2013

 Certificated by Industry Canada
 Registration No.: 9405A-1
 Date of registration: January 03, 2013

 Certificated by VCCI, Japan
 Registration No.: R-3663 & C-4103
 Date of registration: July 25, 2011

 Certificated by TUV Rheinland, Germany
 Registration No.: UA 50195514 0001
 Date of registration: January 07, 2011

 Certificated by TUV/PS, Shenzhen
 Registration No.: SCN1017
 Date of registration: January 27, 2011

 Certificated by Intertek ETL SEMKO
 Registration No.: 2011-RTL-L1-18
 Date of registration: April 28, 2011

 Certificated by Siemic, Inc.
 Registration No.: SLCN021
 Date of registration: November 8, 2011

 Certificated by Nemko, Hong Kong
 Registration No.: 175193
 Date of registration: May 4, 2011

Name of Firm : EST Technology Co., Ltd.

Site Location : San Tun Management Zone, Houjie Town, Dongguan,
 Guangdong, China


2.3. Assistant equipment used for test

2.3.1. Adapter

M/N : DYS152-100150W-1
 Input : AC 100-240V~50/60Hz 1.5A Max
 Output : DC 10V/1.5A

2.4. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 meter high above ground. EUT was set into BT test mode by Bluesuite software before test.



(EUT: Bluetooth Speaker)

2.5. Test mode

A special test software was used to control EUT work in Continuous TX mode(100% duty cycle), and select test channel, wireless mode and data rate.

Mode	Channel	Frequency
BT 4.0-BLE GFSK	Low	2402MHz
	Middle	2440MHz
	High	2480MHz

2.6. Channel List for Bluetooth

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2404
3	2406	4	2408
5	2410	6	2412
7	2414	8	2416
9	2418	10	2420
11	2422	12	2424
13	2426	14	2428
15	2430	16	2432
17	2434	18	2436
19	2438	20	2440
21	2442	22	2444
23	2446	24	2448
25	2450	26	2452
27	2454	28	2456
29	2458	30	2460
31	2462	32	2464
33	2466	34	2468
35	2470	36	2472
37	2474	38	2476
39	2478	40	2480

2.7. Test Equipment

2.7.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	June,28,14	1 Year
Artificial Mains Networ	Rohde & Schwarz	ENV216	101260	June,28,14	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	June,28,14	1 Year

2.7.2. For radiated emission test(30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	June,28,14	1 Year
Spectrum Analyzer	Agilent	E4411B	MY50140697	June,28,14	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	June,28,14	1 Year
Signal Amplifier	Agilent	310N	187037	June,28,14	1 Year
RF Cable	Hubersuhner	W10.02	534123	June,28,14	1 Year

2.7.3. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA9120D1 002	June,28,14	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	June,28,14	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	June,28,14	1 Year
RF Cable	Hubersuhner	RG 214/U	513423	June,28,14	1 Year

3 POWER LINE CONDUCTED EMISSION TEST


3.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.2. Block Diagram of Test Setup



3.3 Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2009 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Result


PASS. (All emissions not reported below are too low against the prescribed limits.)

3.5. Test data



Site no. : EST Conduction Shielded RoomData no. : 361
 Limit : FCC PART 15B QP LINE Phase : LINE
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa
 Engineer : Dick
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : TX Mode

	Freq.	LISN	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.16	9.61	9.81	30.34	49.76	65.25	15.49	QP
2	0.16	9.61	9.81	8.34	27.76	55.25	27.49	Average
3	0.28	9.61	9.83	26.46	45.90	60.68	14.78	QP
4	0.28	9.61	9.83	14.46	33.90	50.68	16.78	Average
5	0.35	9.61	9.83	24.59	44.03	58.91	14.88	QP
6	0.35	9.61	9.83	7.59	27.03	48.91	21.88	Average
7	0.90	9.63	9.82	21.56	41.01	56.00	14.99	QP
8	0.90	9.63	9.82	14.56	34.01	46.00	11.99	Average
9	1.39	9.63	9.82	19.39	38.84	56.00	17.16	QP
10	1.39	9.63	9.82	8.39	27.84	46.00	18.16	Average
11	2.71	9.62	9.84	17.99	37.45	56.00	18.55	QP
12	2.71	9.62	9.84	10.99	30.45	46.00	15.55	Average



Site no. : EST Conduction Shielded Room
 Data no. : 363
 Limit : FCC PART 15B QP
 LINE Phase : NEUTRAL
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa
 Engineer : Dick
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : TX Mode

	Freq.	LISN	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.18	9.55	9.80	24.91	44.26	64.42	20.16	QP
2	0.18	9.55	9.80	8.91	28.26	54.42	26.16	Average
3	0.28	9.60	9.83	22.80	42.23	60.90	18.67	QP
4	0.28	9.60	9.83	17.80	37.23	50.90	13.67	Average
5	0.83	9.62	9.81	21.30	40.73	56.00	15.27	QP
6	0.83	9.62	9.81	19.30	38.73	46.00	7.27	Average
7	0.90	9.62	9.82	21.43	40.87	56.00	15.13	QP
8	0.90	9.62	9.82	14.43	33.87	46.00	12.13	Average
9	1.39	9.61	9.82	21.22	40.65	56.00	15.35	QP
10	1.39	9.61	9.82	11.22	30.65	46.00	15.35	Average
11	2.72	9.63	9.84	18.04	37.51	56.00	18.49	QP
12	2.72	9.63	9.84	9.04	28.51	46.00	17.49	Average

4 RADIATED EMISSION TEST

4.1 Limit

4.1.1 15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

- Remark : (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V/m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.1.2 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.2. Test Procedure


EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the EMI test receiver is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

4.3 Block Diagram of Test setup



4.4 Test Result

PASS.


All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

2、 The frequency 2402MHz 、 2440MHz and 2480 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.


4.5 Test Data

30-1000 MHz




Site no. : 3m Chamber Data no. : 797
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Dick
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark
					Level (dBuV/m)	Limits (dBuV/m)		
1	38.73	13.48	0.79	12.59	26.86	40.00	13.14	QP
2	56.19	5.21	0.96	18.70	24.87	40.00	15.13	QP
3	101.78	9.65	1.31	16.72	27.68	43.50	15.82	QP
4	128.94	11.33	1.47	16.66	29.46	43.50	14.04	QP
5	180.35	8.95	1.70	19.26	29.91	43.50	13.59	QP
6	221.09	9.26	2.01	10.79	22.06	46.00	23.94	QP




Site no. : 3m Chamber Data no. : 798
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Dick
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	104.69	9.95	1.44	12.20	23.59	43.50	19.91	QP
2	133.79	11.36	1.56	11.66	24.58	43.50	18.92	QP
3	182.29	8.76	1.67	16.80	27.23	43.50	16.27	QP
4	218.18	9.00	1.90	18.24	29.14	46.00	16.86	QP
5	269.59	12.56	2.25	9.30	24.11	46.00	21.89	QP
6	322.94	13.65	2.43	6.29	22.37	46.00	23.63	QP




Site no. : 3m Chamber	Data no. : 799
Dis. / Ant. : 3m 27137	Ant. pol. : HORIZONTAL
Limit : FCC PART 15 B	
Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa	
Engineer : Dick	
EUT : Bluetooth Speaker	
Power : DC 10V From Adapter Input AC 120V/60Hz	
M/N : UB-SPB4M-101	
Test Mode : GFSK TX 2440MHz	

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission			Remark
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	109.54	10.44	1.40	10.90	22.74	43.50	20.76	QP
2	133.79	11.36	1.56	10.09	23.01	43.50	20.49	QP
3	159.98	10.36	1.71	9.25	21.32	43.50	22.18	QP
4	177.44	8.97	1.67	13.82	24.46	43.50	19.04	QP
5	216.24	8.80	1.95	12.81	23.56	46.00	22.44	QP
6	347.19	14.38	2.56	3.50	20.44	46.00	25.56	QP




Site no. : 3m Chamber Data no. : 800
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Dick
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2440MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	33.88	16.11	0.70	10.22	27.03	40.00	12.97	QP
2	65.89	5.17	1.00	18.01	24.18	40.00	15.82	QP
3	114.39	10.85	1.42	17.87	30.14	43.50	13.36	QP
4	133.79	11.36	1.56	21.70	34.62	43.50	8.88	QP
5	155.13	10.67	1.69	17.94	30.30	43.50	13.20	QP
6	179.38	8.96	1.72	19.09	29.77	43.50	13.73	QP



Site no. : 3m Chamber Data no. : 801
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Dick
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2480MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	33.88	16.11	0.70	8.62	25.43	40.00	14.57	QP
2	104.69	9.95	1.44	18.30	29.69	43.50	13.81	QP
3	130.88	11.33	1.47	19.89	32.69	43.50	10.81	QP
4	155.13	10.67	1.69	18.08	30.44	43.50	13.06	QP
5	179.38	8.96	1.72	18.58	29.26	43.50	14.24	QP
6	196.84	7.72	1.81	13.77	23.30	43.50	20.20	QP



Site no. : 3m Chamber Data no. : 802
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Dick
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission			Remark
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	101.78	9.65	1.31	16.84	27.80	43.50	15.70	QP
2	128.94	11.33	1.47	13.21	26.01	43.50	17.49	QP
3	179.38	8.96	1.72	16.22	26.90	43.50	16.60	QP
4	211.39	8.51	1.85	16.75	27.11	43.50	16.39	QP
5	264.74	12.94	2.28	8.79	24.01	46.00	21.99	QP
6	313.24	13.31	2.44	4.99	20.74	46.00	25.26	QP


1000-18000 MHz



Site no. : 3m Chamber Data no. : 743
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2402MHz

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2402.00	27.61	6.62	34.18	96.12	96.17	74.00	-22.17	Peak
2	4043.00	29.74	10.84	32.25	39.05	47.38	74.00	26.62	Peak
3	6168.00	33.15	12.16	32.06	35.97	49.22	74.00	24.78	Peak
4	7834.00	36.68	11.47	31.40	34.16	50.91	74.00	23.09	Peak
5	10588.00	39.07	11.31	32.88	30.67	48.17	74.00	25.83	Peak
6	14498.00	41.88	10.93	33.08	31.13	50.86	74.00	23.14	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 744
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2402MHz

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2402.00	27.61	6.62	34.18	100.10	100.15	74.00	-26.15	Peak
2	4213.00	29.98	10.69	32.00	39.42	48.09	74.00	25.91	Peak
3	7511.00	36.47	11.61	31.85	33.41	49.64	74.00	24.36	Peak
4	9194.00	37.75	11.55	32.35	32.79	49.74	74.00	24.26	Peak
5	10333.00	38.68	11.40	32.40	33.08	50.76	74.00	23.24	Peak
6	14328.00	41.74	10.92	32.98	30.56	50.24	74.00	23.76	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 747
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2440MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission				Remark
					Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	2440.00	27.60	6.67	34.12	97.07	97.22	74.00	-23.22	Peak
2	5029.00	31.56	12.55	32.06	37.78	49.83	74.00	24.17	Peak
3	8004.00	37.01	11.40	31.22	33.09	50.28	74.00	23.72	Peak
4	10248.00	38.53	11.45	32.24	32.83	50.57	74.00	23.43	Peak
5	13223.00	39.42	11.46	34.68	31.64	47.84	74.00	26.16	Peak
6	14481.00	41.86	10.93	33.02	30.67	50.44	74.00	23.56	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 748
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2440MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	27.60	6.67	34.12	102.43	102.58	74.00	-28.58	Peak
2	4893.00	31.40	12.14	31.92	38.31	49.93	74.00	24.07	Peak
3	6389.00	33.93	12.20	31.91	36.59	50.81	74.00	23.19	Peak
4	8633.00	37.24	11.45	32.31	34.82	51.20	74.00	22.80	Peak
5	11013.00	39.51	11.28	33.68	31.64	48.75	74.00	25.25	Peak
6	14328.00	41.74	10.92	32.98	29.65	49.33	74.00	24.67	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 749
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	34.03	101.50	101.76	74.00	-27.76	Peak
2	4910.00	31.42	12.22	31.93	38.44	50.15	74.00	23.85	Peak
3	6593.00	34.46	12.10	32.17	35.60	49.99	74.00	24.01	Peak
4	8463.00	36.87	11.45	31.86	35.01	51.47	74.00	22.53	Peak
5	11319.00	39.31	11.06	34.26	32.11	48.22	74.00	25.78	Peak
6	14464.00	41.85	10.93	32.96	28.60	48.42	74.00	25.58	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 750
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.58	6.71	34.03	104.42	104.68	74.00	-30.68	Peak
2	4944.00	31.47	12.37	31.96	39.16	51.04	74.00	22.96	Peak
3	7443.00	36.54	11.61	31.93	35.39	51.61	74.00	22.39	Peak
4	9143.00	37.65	11.53	32.39	35.17	51.96	74.00	22.04	Peak
5	10809.00	39.31	11.30	33.30	31.31	48.62	74.00	25.38	Peak
6	14498.00	41.88	10.93	33.08	29.61	49.34	74.00	24.66	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


18000-25000 MHz



Site no. : 3m Chamber Data no. : 753
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2402MHz

		Ant.	Cable	Amp	Emission				
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 19869.00	46.05	19.54	36.59	13.46	42.46	74.00	31.54	Peak	
2 22697.00	45.72	20.97	34.17	12.28	44.80	74.00	29.20	Peak	


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 754
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2402MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)			
1 20590.00	46.05	19.95	36.16	12.06	41.90	74.00	32.10	Peak
2 23509.00	45.70	21.60	33.33	11.51	45.48	74.00	28.52	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 755
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2440MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission				Remark
					Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	20653.00	46.10	19.98	36.12	12.61	42.57	74.00	31.43	Peak
2	23411.00	45.68	21.51	33.43	10.90	44.66	74.00	29.34	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 756
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2440MHz

		Ant.	Cable	Amp	Emission				
	Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	20569.00	46.04	19.94	36.18	11.76	41.56	74.00	32.44	Peak
2	22193.00	45.74	20.68	34.69	11.07	42.80	74.00	31.20	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 757
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
					Level (dBuV/m)				
1 20716.00	46.12	20.00	36.05	12.33	42.40		74.00	31.60	Peak
2 23761.00	45.65	21.83	33.06	10.69	45.11		74.00	28.89	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 758
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2480MHz

		Ant.	Cable	Amp	Emission				
	Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	20338.00	46.03	19.83	36.39	8.24	37.71	74.00	36.29	Peak
2	22690.00	45.73	20.97	34.17	8.20	40.73	74.00	33.27	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

5 CONDUCTED SPURIOUS EMISSION

5.1 Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.2 Test Procedure



The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz for frequency range from 30MHz to 1000 MHz; The resolution bandwidth is set to 1 MHz, The video bandwidth is set to 3 MHz for frequency range from 1000MHz to 25000 MHz..



5.3 Test Result

PASS (The testing data was attached in the next pages.)



5.4 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz









Test Mode: BT 4.0-BLE GFSK 2440MHz





Test Mode: BT 4.0-BLE GFSK 2480MHz





6 BAND EDGE COMPLIANCE TEST

6.1 Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits

6.2 Test Procedure


1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO

6.3 Test Result

Pass (The testing data was attached in the next pages.)

- Note:
- 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
 - 2、 The frequency 2402MHz and 2480 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.


6.4 Test Data



Site no. : 3m Chamber Data no. : 745
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2402MHz

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2323.87	27.73	6.54	34.23	42.35	42.39	74.00	31.61	Peak
2	2390.00	27.64	6.62	34.19	40.73	40.80	74.00	33.20	Peak
3	2402.19	27.61	6.62	34.18	101.85	101.90	74.00	-27.90	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 746
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2402MHz

	Freq.	Ant.	Cable	Amp	Emission		Limits	Margin	Remark
	(MHz)	Factor	Loss	Factor	Reading	Level	(dBuV/m)	(dB)	
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)			
1	2324.09	27.73	6.54	34.23	42.32	42.36	74.00	31.64	Peak
2	2390.00	27.64	6.62	34.19	42.95	43.02	74.00	30.98	Peak
3	2402.19	27.61	6.62	34.18	100.71	100.76	74.00	-26.76	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 751
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.23	27.58	6.71	34.03	106.02	106.28	74.00	-32.28	Peak
2	2483.50	27.58	6.71	34.03	49.72	49.98	74.00	24.02	Peak
3	2487.83	27.58	6.73	34.03	46.39	46.67	74.00	27.33	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 752
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 10V From Adapter Input AC 120V/60Hz
 M/N : UB-SPB4M-101
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.93	27.58	6.71	34.03	99.82	100.08	74.00	-26.08	Peak
2	2483.50	27.58	6.71	34.03	45.21	45.47	74.00	28.53	Peak
3	2492.68	27.58	6.73	34.03	44.41	44.69	74.00	29.31	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

7 6dB Bandwidth Test

7.1 Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

7.2 Test Procedure


- 1, Connected the EUT's antenna port to spectrum analyzer device.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set resolution bandwidth (RBW) = 100 kHz.
 - (2). Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - (3). Detector = Peak.
 - (4). Trace mode = max hold.
 - (5). Sweep = auto couple.
 - (6). Allow the trace to stabilize.
 - (7). Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 Test Result


EUT: Bluetooth Speaker			
M/N: UB-SPB4M-101			
Test date: July 27, 2014		Tested by: Tony.Tang	Test site: RF Site
Test Mode	CH	6dB bandwidth (MHz)	Limit (KHz)
BT 4.0-BLE GFSK	CH1	0.742	>500
	CH20	0.760	>500
	CH40	0.752	>500
Conclusion : PASS			

7.4 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



8 OUTPUT POWER TEST

8.1 Limit

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

8.2 Test Procedure

8.3 Test Procedure

- 1, Connected the EUT's antenna port to spectrum analyzer device.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set the RBW $\geq$ DTS bandwidth.
 - (2). Set VBW $\geq$ 3 x RBW.
 - (3). Set span $\geq$ 3 x RBW.
 - (4). Sweep time = auto couple.
 - (5). Detector = peak.
 - (6). Trace mode = max hold.
 - (7). Allow trace to fully stabilize.
 - (8). Use peak marker function to determine the peak amplitude level.


Note: The cable loss and attenuator loss were offset into measure device as an amplitude offs

8.4 Test Result


EUT: Bluetooth Speaker			
M/N:UB-SPB4M-101			
Test date: July 27,2014		Test site: 3m Chamber	Tested by: Tony Tang
Pass			
Test Mode	CH	Peak output Power (dBm)	Limit (dBm)
BT 4.0-BLE GFSK	CH1	1.96	30
	CH20	2.45	30
	CH40	1.81	30
Conclusion : PASS			

8.5 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



9 POWER SPECTRAL DENSITY TEST

9.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

9.2 Test Procedure


- 1, Connected the EUT's antenna port to spectrum analyzer device.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set analyzer center frequency to DTS channel center frequency.
 - (2). Set the span to 1.5 times the DTS bandwidth.
 - (3). Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
 - (4). Set the VBW $\geq 3 \text{ RBW}$.
 - (5). Detector = peak.
 - (6). Sweep time = auto couple.
 - (7). Trace mode = max hold.
 - (8). Allow trace to fully stabilize.
 - (9). Use the peak marker function to determine the maximum amplitude level.
 - (10). If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

9.3 Test Result


EUT: Bluetooth Speaker			
M/N: UB-SPB4M-101			
Test date: July 27, 2014		Test site: 3m Chamber	Tested by: Tony Tang
Pass			
Test Mode	CH	Power density (dBm/3kHz)	Limit (dBm/3kHz)
BT 4.0-BLE GFSK	CH1	-7.941	8
	CH20	-6.675	8
	CH40	-5.948	8
Conclusion : PASS			

9.4 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



10 ANTENNA REQUIREMENTS

10.1 Limit



For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2 Result



The antennas used for this product are integral Patch Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0 dBi.

11 TEST SETUP PHOTO



Conducted Test



Radiated Test (30-1000 MHz)




Radiated Test (1000-25000 MHz)




12 PHOTOS OF EUT

External Photos
M/N: UB-SPB4M-101




External Photos
M/N: UB-SPB4M-101





External Photos
M/N: UB-SPB4M-101



Internal Photos
M/N: UB-SPB4M-101




Internal Photos
M/N: UB-SPB4M-101





Bluetooth
Antenna



Internal Photos
M/N: UB-SPB4M-101



Internal Photos
M/N: UB-SPB4M-101



Internal Photos
M/N: UB-SPB4M-101



Adapter Photos

