

TEST REPORT

Reference No..... : WTX21X03018731W-1
FCC ID : 2ARO3-W55SE
Applicant : Worldwide telecom limited
Address..... : 2F Block C; Shenfang Building, Zhen Hualu, Futian, Shenzhen.
Product Name : SmartPhone
Test Model. : W55SE
Standards : FCC Part 22H, FCC Part 24E
Date of Receipt sample : Mar.11, 2021
Date of Test..... : Mar.11, 2021 to Mar.23, 2021
Date of Issue : Mar.23, 2021
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308

Fax.: +86-755-33663309


Tested by:

Reviewed By:

Approved & Authorized By:



Jason Su / Project Engineer



Lion Cai / RF Manager



Silin Chen / Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TEST FACILITY	6
1.5 EUT SETUP AND TEST MODE	7
1.6 MEASUREMENT UNCERTAINTY	8
1.7 TEST EQUIPMENT LIST AND DETAILS	9
2. SUMMARY OF TEST RESULTS	11
3. RF OUTPUT POWER	12
3.1 STANDARD APPLICABLE	12
3.2 TEST PROCEDURE	12
3.3 SUMMARY OF TEST RESULTS/PLOTS	12
4. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER	15
4.1 STANDARD APPLICABLE	15
4.2 TEST PROCEDURE	15
4.3 SUMMARY OF TEST RESULTS	15
5. EMISSION BANDWIDTH	16
5.1 STANDARD APPLICABLE	16
5.2 TEST PROCEDURE	16
5.3 SUMMARY OF TEST RESULTS/PLOTS	16
6. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL	17
6.1 STANDARD APPLICABLE	17
6.2 TEST PROCEDURE	17
6.3 SUMMARY OF TEST RESULTS/PLOTS	17
7. SPURIOUS RADIATED EMISSIONS	18
7.1 STANDARD APPLICABLE	18
7.2 TEST PROCEDURE	18
7.3 SUMMARY OF TEST RESULTS/PLOTS	18
8. FREQUENCY STABILITY	29
8.1 STANDARD APPLICABLE	29
8.2 TEST PROCEDURE	29
8.3 SUMMARY OF TEST RESULTS/PLOTS	29
9. MODULATION CHARACTERISTICS	30
9.1 STANDARD APPLICABLE	30
9.2 TEST PROCEDURE	30
9.3 SUMMARY OF TEST RESULTS/PLOTS	30
APPENDIX SUMMARY	31
APPENDIX A	32
APPENDIX B	33
APPENDIX C	34
APPENDIX D	46
APPENDIX E	81
APPENDIX F	84
APPENDIX PHOTOGRAPHS	86

Report version

Version No.	Date of issue	Description
Rev.00	Mar.23, 2021	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Worldwide telecom limited
Address of applicant: 2F Block C; Shenfang Building, Zhen Hualu, Futian, Shenzhen.

Manufacturer: Worldwide telecom limited
Address of manufacturer: 2F Block C; Shenfang Building, Zhen Hualu, Futian, Shenzhen.

General Description of EUT:	
Product Name:	SmartPhone
Trade Name:	WOLKI
Model No.:	W55SE
Adding Model(s):	/
Rated Voltage:	DC3.8V
Battery:	1650mAh
Adapter Model:	WCH05 Input: AC100-240V, 50/60Hz , 0.15A Output: DC5.0V , 1000mA
Software Version:	WOLKI_W55SE_V01_20210301
Hardware Version:	V130M3_MB
Note: The test data is gathered from a production sample provided by the manufacturer.	

Technical Characteristics of EUT:	
2G	
Support Networks:	GSM, GPRS
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS 850: 824~849MHz GSM/GPRS 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS 850: 869~894MHz GSM/GPRS 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 32.08dBm, GSM1900: 28.98dBm
Type of Emission:	GSM850: 249KGXW, GSM1900: 255KGXW
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: -0.5dBi; GSM1900: 0.5dBi
GPRS Class:	Class 12
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 22.42dBm, WCDMA Band 5: 22.57dBm
Type of Emission:	WCDMA Band 2: 4M18F9W WCDMA Band 5: 4M19F9W
Type of Modulation:	BPSK
Antenna Type:	Integral Antenna
Antenna Gain:	WCDMA Band 2: 0.5dBi, WCDMA Band 5: -0.5dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 2: FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS.

FCC Rules Part 22: PRIVATE LAND MOBILE RADIO SERVICES.

FCC Rules Part 24: PUBLIC MOBILE SERVICES.

TIA/EIA 603 E March 2016: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

ANSI C63.26-2015: American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services

KDB 971168 D01 Power Meas License Digital Systems v03r01: MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603 E/ KDB 971168/ ANSI C63.26. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	GSM 1900	Low, Middle, High Channels
TM4	GPRS 1900	Low, Middle, High Channels
TM5	WCDMA Band 5	Low, Middle, High Channels
TM6	HSDPA Band 5	Low, Middle, High Channels
TM7	HSUPA Band 5	Low, Middle, High Channels
TM8	WCDMA Band 2	Low, Middle, High Channels
TM9	HSDPA Band 2	Low, Middle, High Channels
TM10	HSUPA Band 2	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency(MHz)	Channel Number
GSM 850	GSM/GPRS	824.2	128
		836.6	190
		848.8	251
PCS 1900	GSM/GPRS	1850.2	512
		1880.0	661
		1909.8	810
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4	4132
		836.6	4183
		846.6	4233
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4	9262
		1880.0	9400
		1907.6	9538
Note: the transmitter has been tested on the communications mode of GSM, GPRS, WCDMA, HSDPA, HSUPA compliance test and record the worst case.			

Test Conditions	
Temperature:	23.5 °C
Relative Humidity:	51 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	1.0	Unshielded	Without Ferrite
Earphone Cable	1.24	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	TianYi310-14ISK	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Frequency Stability	Conducted	2.3%
Transmitter Spurious Emissions	Conducted	$\pm 0.42\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2020-04-28	2021-04-27
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2020-04-28	2021-04-27
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2020-04-28	2021-04-27
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2020-04-28	2021-04-27
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2020-04-28	2021-04-27
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2020-04-28	2021-04-27
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1068	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1055	RF Limiter	ATTEN	AT-BSF-0820~0920	/	2020-04-28	2021-04-27
SEMT-1056	RF Limiter	ATTEN	AT-BSF-1710~1910	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	/	/
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	/	/

SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	/	/
SEMT-C004	Cable	Zheng DI	2M0RFC	/	/	/
SEMT-C005	Cable	Zheng DI	1M0RFC	/	/	/
SEMT-C006	Cable	Zheng DI	1M0RFC	/	/	/

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§22.913(a), §24.232(c)	RF Output Power	Compliant
§24.51	Peak-to-average Ratio (PAR) of Transmitter	Compliant
§22.917(b), §24.238(b)	Emission Bandwidth	Compliant
§22.917(a), §24.238(a)	Spurious Emissions at Antenna Terminal	Compliant
§22.917(a), §24.238(a)	Spurious Radiation Emissions	Compliant
§22.917(a), §24.238(a)	Out of Band Emissions	Compliant
§22.355, §24.235	Frequency Stability	Compliant
§2.1047	Modulation characteristics	Compliant

3. RF Output Power


3.1 Standard Applicable

According to §22.913(a)(2), the ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

3.2 Test Procedure

- Conducted output power test method:



- Radiated power test method:

1. The setup of EUT is according with per ANSI/TIA Standard 603E and ANSI C63.26 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

3.3 Summary of Test Results/Plots

➤ **Max. Radiated Power**

Mode	Channel	Antenna Polar	ERP (dBm)	Limit (dBm)	Result
GSM850	128	V	28.42	<38.45	Pass
		H	23.35		
	190	V	28.12		
		H	23.57		
	251	V	28.39		
		H	23.41		
GPRS850	128	V	28.69	<38.45	Pass
		H	22.97		
	190	V	28.31		
		H	22.35		
	251	V	28.49		
		H	22.92		

Mode	Channel	Antenna Polar	EIRP (dBm)	Limit (dBm)	Result
PCS1900	512	V	25.87	<33.00	Pass
		H	20.12		
	661	V	25.36		
		H	20.57		
	810	V	25.35		
		H	20.49		
GPRS1900	512	V	25.06	<33.00	Pass
		H	20.13		
	661	V	25.36		
		H	19.79		
	810	V	25.65		
		H	20.42		

Mode	Channel	Antenna Polar	ERP	Limit (dBm)	Result
WCDMA Band V	4132	V	20.14	<38.45	Pass
		H	15.36		
	4183	V	20.79		
		H	15.97		
	4233	V	20.36		
		H	15.12		

Mode	Channel	Antenna Polar	EIRP	Limit (dBm)	Result
WCDMA Band II	9262	V	19.69	<33.00	Pass
		H	14.32		
	9400	V	19.57		
		H	15.32		
	9538	V	20.11		
		H	15.90		

Note: Pre-scan mode WCDMA/HSDPA/HSUPA find the worst case at WCDMA mode and recorded in the test report.

➤ **Max. Conducted Power (Average power)**

Please refer to Appendix A

4. Peak-to-average Ratio (PAR) of Transmitter

4.1 Standard Applicable


According to §24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51, in measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.2 Test Procedure

According with KDB 971168

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Configuration for the emission bandwidth testing:



4.3 Summary of Test Results

Please refer to Appendix B.

5. Emission Bandwidth

5.1 Standard Applicable


According to §22.917(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 10kHz for GSM mode and 100kHz for WCDMA mode, VBW shall be at least 3 times the RBW, and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



5.3 Summary of Test Results/Plots

Please refer to Appendix C

6. Out of Band Emissions at Antenna Terminal

6.1 Standard Applicable


According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10^{th} harmonic.

Test Configuration for the out of band emissions testing:



6.3 Summary of Test Results/Plots

Note: Pre-scan mode WCDMA/HSDPA/HSUPA find the worst case at WCDMA mode and recorded in the test report.

Please refer to Appendix D

7. Spurious Radiated Emissions

7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

7.2 Test Procedure

1. The setup of EUT is according with per ANSI/TIA Standard 603E and ANSI C63.26 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.


Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

7.3 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

For Cellular Band			
Test Channel	GSM850	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.4089	-70.45	0.15	-70.30	-13.00	-57.30	-	-	QP
2	97.4560	-71.56	-1.95	-73.51	-13.00	-60.51	-	-	QP
3	543.2742	-73.74	7.90	-65.84	-13.00	-52.84	-	-	QP

For Cellular Band			
Test Channel	GSM850	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.6585	-69.87	-0.04	-69.91	-13.00	-56.91	-	-	QP
2	117.7725	-71.45	-2.27	-73.72	-13.00	-60.72	-	-	QP
3	603.5392	-74.58	9.83	-64.75	-13.00	-51.75	-	-	QP

For Cellular Band			
Test Channel	GSM1900	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.6584	-69.72	-0.04	-69.76	-13.00	-56.76	-	-	QP
2	100.9339	-71.06	-1.52	-72.58	-13.00	-59.58	-	-	QP
3	601.4265	-74.35	9.86	-64.49	-13.00	-51.49	-	-	QP


For Cellular Band			
Test Channel	GSM1900	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.8747	-63.60	-1.74	-65.34	-13.00	-52.34	-	-	QP
2	97.1148	-70.79	-2.00	-72.79	-13.00	-59.79	-	-	QP
3	616.3718	-74.97	9.73	-65.24	-13.00	-52.24	-	-	QP


Note: Margin= (Reading+ Correct)- Limit

Test Channel	band 5	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.5348	-69.56	0.03	-69.53	-13.00	-56.53	-	-	QP
2	96.7749	-70.63	-2.06	-72.69	-13.00	-59.69	-	-	QP
3	595.1329	-74.25	9.75	-64.50	-13.00	-51.50	-	-	QP

Test Channel	band 5	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.0583	-69.62	0.00	-69.62	-13.00	-56.62	-	-	QP
2	102.0014	-71.62	-1.52	-73.14	-13.00	-60.14	-	-	QP
3	704.2261	-74.42	10.09	-64.33	-13.00	-51.33	-	-	QP

Test Channel	band 2	Polarity:	Horizontal
--------------	--------	-----------	------------



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.5868	-69.98	-0.02	-70.00	-13.00	-57.00	-	-	QP
2	98.1419	-71.79	-1.82	-73.61	-13.00	-60.61	-	-	QP
3	668.1423	-74.59	9.79	-64.80	-13.00	-51.80	-	-	QP

Test Channel	band 2	Polarity:	Vertical
--------------	--------	-----------	----------



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.8746	-65.77	-1.74	-67.51	-13.00	-54.51	-	-	QP
2	71.8320	-67.91	-3.35	-71.26	-13.00	-58.26	-	-	QP
3	408.9460	-74.07	5.54	-68.53	-13.00	-55.53	-	-	QP

Note: $Margin = (Reading + Correct) - Limit$

Remark: ‘-’ Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

- Spurious Emissions Above 1GHz
- For Cellular Band_GSM850 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.2MHz)						
1648.4	-36.01	4.94	-31.07	-13	-18.07	H
2472.6	-41.78	8.46	-33.32	-13	-20.32	H
1648.4	-37.66	4.94	-32.72	-13	-19.72	V
2472.6	-41.59	8.46	-33.13	-13	-20.13	V
Middle Channel (836.6MHz)						
1673.2	-35.87	5.11	-30.76	-13	-17.76	H
2509.8	-42.96	8.54	-34.42	-13	-21.42	H
1673.2	-36.68	5.11	-31.57	-13	-18.57	V
2509.8	-43.94	8.54	-35.4	-13	-22.4	V
High Channel (848.8MHz)						
1697.6	-34.85	5.25	-29.6	-13	-16.6	H
2546.4	-44.02	8.57	-35.45	-13	-22.45	H
1697.6	-35.97	5.25	-30.72	-13	-17.72	V
2546.4	-42.54	8.57	-33.97	-13	-20.97	V

- For PCS Band_GSM1900 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-40.46	10.54	-29.92	-13	-16.92	H
5550.6	-49.72	13.37	-36.35	-13	-23.35	H
3700.4	-39.92	10.54	-29.38	-13	-16.38	V
5550.6	-46.58	13.37	-33.21	-13	-20.21	V
Middle Channel (1880MHz)						
3760.0	-40.49	10.64	-29.85	-13	-16.85	H
5640.0	-48.34	13.54	-34.8	-13	-21.8	H
3760.0	-39.41	10.64	-28.77	-13	-15.77	V
5640.0	-46.68	13.54	-33.14	-13	-20.14	V
High Channel (1909.8MHz)						
3819.6	-40.08	10.74	-29.34	-13	-16.34	H
5729.4	-48.27	13.71	-34.56	-13	-21.56	H
3819.6	-41.25	10.74	-30.51	-13	-17.51	V
5729.4	-48.52	13.71	-34.81	-13	-21.81	V

➤ For WCDMA Band V Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (826.4MHz)						
1652.8	-36.61	4.94	-31.67	-13	-18.67	H
2479.2	-41.01	8.46	-32.55	-13	-19.55	H
1652.8	-36.63	4.94	-31.69	-13	-18.69	V
2479.2	-41.63	8.46	-33.17	-13	-20.17	V
Middle Channel (836.6MHz)						
1672.8	-36.87	5.11	-31.76	-13	-18.76	H
2509.2	-42.87	8.54	-34.33	-13	-21.33	H
1672.8	-34.33	5.11	-29.22	-13	-16.22	V
2509.2	-42.92	8.54	-34.38	-13	-21.38	V
High Channel (846.6MHz)						
1693.2	-34.64	5.25	-29.39	-13	-16.39	H
2539.8	-43.61	8.57	-35.04	-13	-22.04	H
1693.2	-35.88	5.25	-30.63	-13	-17.63	V
2539.8	-42.3	8.57	-33.73	-13	-20.73	V

➤ For WCDMA Band II Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1852.4MHz)						
3704.8	-39.5	10.54	-28.96	-13	-15.96	H
5557.2	-49.27	13.37	-35.9	-13	-22.9	H
3704.8	-40.96	10.54	-30.42	-13	-17.42	V
5557.2	-46.79	13.37	-33.42	-13	-20.42	V
Middle Channel (1880MHz)						
3760.0	-41.31	10.64	-30.67	-13	-17.67	H
5640.0	-48.02	13.54	-34.48	-13	-21.48	H
3760.0	-41.65	10.64	-31.01	-13	-18.01	V
5640.0	-49.29	13.54	-35.75	-13	-22.75	V
High Channel (1907.6MHz)						
3815.2	-39.94	10.74	-29.2	-13	-16.2	H
5722.8	-47.74	13.71	-34.03	-13	-21.03	H
3815.2	-41.08	10.74	-30.34	-13	-17.34	V
5722.8	-49.22	13.71	-35.51	-13	-22.51	H

Note: Result=Reading+ Correct, Margin= Result- Limit

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Frequency Stability

8.1 Standard Applicable

According to §22.355, §24.235 the limit is 2.5ppm.

8.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

8.3 Summary of Test Results/Plots

Please refer to Appendix E

9. Modulation characteristics


9.1 Standard Applicable

According to §2.1047, measurements required: Modulation characteristics is given below:

- (a) Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.
- (b) Equipment which employs modulation limiting. A curve or family of curves showing the percentage of modulation versus the modulation input voltage shall be supplied. The information submitted shall be sufficient to show modulation limiting capability throughout the range of modulating frequencies and input modulating signal levels employed.
- (c) Single sideband and independent sideband radiotelephone transmitters which employ a device or circuit to limit peak envelope power. A curve showing the peak envelope power output versus the modulation input voltage shall be supplied. The modulating signals shall be the same in frequency as specified in paragraph (c) of §2.1049 for the occupied bandwidth tests.
- (d) Other types of equipment. A curve or equivalent data which shows that the equipment will meet the modulation requirements of the rules under which the equipment is to be licensed.

9.2 Test Procedure

According to ANSI C63.26-2015 section 5.3.2, the following test setup was performed.



9.3 Summary of Test Results/Plots

Only the worst case was selected to record

Please refer to Appendix F

APPENDIX SUMMARY

Project No.	WTX21X03018731W	Test Engineer	Moon
Start date	2021/03/15	Finish date	2021/03/15
Temperature	23.5℃	Humidity	51%
RF specifications	GSM/WCDMA		

APPENDIX	Description of Test Item	Result
A	RF Output Power	Compliant
B	Peak-to-average Ratio (PAR) of Transmitter	Compliant
C	Emission Bandwidth	Compliant
D	Out of Band Emissions at Antenna Terminal	Compliant
E	Frequency Stability	Compliant
F	Modulation characteristics	Compliant

APPENDIX A

Conducted Average power

Conducted Average power (dBm)						
Band	GSM850			PCS1900		
Channel	128	190	251	512	661	810
Frequency(MHz)	824.20	836.60	848.80	1850.20	1880.00	1909.80
GSM	31.46	31.78	32.04	28.58	28.10	28.40
GPRS(1Slot)	31.47	31.79	32.08	28.32	28.98	28.68

Conducted Average power (dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4183	4233	9262	9400	9538
Frequency(MHz)	826.4	836.6	846.6	1852.4	1880.0	1907.6
RMC 12.2k	22.57	22.32	21.54	22.42	22.39	21.91
HSDPA Subtest-1	21.78	21.41	20.84	21.47	21.38	21.06
HSDPA Subtest-2	21.75	21.39	20.82	21.45	21.35	21.02
HSDPA Subtest-3	21.74	21.38	20.81	21.43	21.34	21.03
HSDPA Subtest-4	21.74	21.38	20.83	21.44	21.35	21.04
HSUPA Subtest-1	21.71	21.41	20.87	21.40	21.40	21.03
HSUPA Subtest-2	21.68	21.38	20.84	21.38	21.38	21.01
HSUPA Subtest-3	21.67	21.35	20.83	21.37	21.36	21.02
HSUPA Subtest-4	21.69	21.36	20.84	21.35	21.37	21.01
HSUPA Subtest-5	21.67	21.37	20.85	21.36	21.36	21.02

APPENDIX B

Peak-to-average Ratio (PAR) of Transmitter

PCS1900				
Test Mode	Channel	Frequency (MHz)	PAR (dB)	Limit (dB)
GSM	661	1850.2	4.87	13
GPRS(1 Slot)	661	1850.2	5.32	13




WCDMA Band II				
Test Mode	Channel	Frequency (MHz)	PAR (dB)	Limit (dB)
WCDMA	9262	1852.4	4.35	13
	9400	1880.0	4.17	13
	9538	1907.6	4.62	13




Note: Only the worst case was selected to record.

APPENDIX C


EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (kHz)	-26dB bandwidth (kHz)
GSM 850 (GMSK)	128	824.20	244.139	314.567
	190	836.60	244.910	320.389
	251	848.80	246.336	323.780
GPRS850 (GMSK,1Slot)	128	824.20	244.498	312.240
	190	836.60	248.900	313.774
	251	848.80	244.991	315.295
PCS1900 (GMSK)	512	1850.20	246.557	323.546
	661	1880.00	246.048	316.759
	810	1909.80	254.607	316.073
GPRS1900 (GMSK,1Slot)	512	1850.20	249.571	314.145
	661	1880.00	242.544	319.495
	810	1909.80	246.422	315.362

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
WCDMA Band V	4132	826.40	4.161	4.709
	4183	836.60	4.146	4.714
	4233	846.60	4.187	4.698
HSDPA	4132	826.40	4.184	4.693
	4183	836.60	4.180	4.669
	4233	846.60	4.167	4.706
HSUPA	4132	826.40	4.181	4.683
	4183	836.60	4.151	4.672
	4233	846.60	4.162	4.670
WCDMA Band II	9262	1852.40	4.168	4.722
	9400	1880.00	4.156	4.688
	9538	1907.60	4.163	4.715
HSDPA	9262	1852.40	4.173	4.707
	9400	1880.00	4.169	4.693
	9538	1907.60	4.133	4.684
HSUPA	9262	1852.40	4.184	4.712
	9400	1880.00	4.167	4.705
	9538	1907.60	4.150	4.716

GSM 850 (GMSK)-Low	 Agilent R T Ch Freq 824.2 MHz Trig Free Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/ Offst 6.5 dB Center 824.2 MHz Span 1 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 244.1393 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -1.696 kHz x dB Bandwidth 314.567 kHz Freq/Channel Center Freq 824.200000 MHz Start Freq 823.700000 MHz Stop Freq 824.700000 MHz CF Step 100.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
GSM 850 (GMSK)-Middle	 Agilent R T Ch Freq 836.6 MHz Trig Free Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/ Offst 6.5 dB Center 836.6 MHz Span 1 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 244.9105 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -855.022 Hz x dB Bandwidth 320.389 kHz Freq/Channel Center Freq 836.600000 MHz Start Freq 836.100000 MHz Stop Freq 837.100000 MHz CF Step 100.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
GSM 850 (GMSK)-High	 Agilent R T Ch Freq 848.8 MHz Trig Free Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/ Offst 6.5 dB Center 848.8 MHz Span 1 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 246.3356 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -1.635 kHz x dB Bandwidth 323.780 kHz Freq/Channel Center Freq 848.800000 MHz Start Freq 848.300000 MHz Stop Freq 849.300000 MHz CF Step 100.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

GPRS850 (GMSK,1Slot)-Low	 Agilent R T Ch Freq 824.2 MHz Trig Free Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/Offset 6.5 dB Center 824.2 MHz Span 1 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 244.4982 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error 38.612 Hz x dB Bandwidth 312.240 kHz Freq/Channel Center Freq 824.200000 MHz Start Freq 823.700000 MHz Stop Freq 824.700000 MHz CF Step 100.000000 kHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Scale Type Log Lin
GPRS850 (GMSK,1Slot)-Middle	 Agilent R T Ch Freq 836.6 MHz Trig Free Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/Offset 6.5 dB Center 836.6 MHz Span 1 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 248.9002 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -1.707 kHz x dB Bandwidth 313.774 kHz Freq/Channel Center Freq 836.600000 MHz Start Freq 836.100000 MHz Stop Freq 837.100000 MHz CF Step 100.000000 kHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Scale Type Log Lin
GPRS850 (GMSK,1Slot)-High	 Agilent R T Ch Freq 848.8 MHz Trig Free Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/Offset 6.5 dB Center 848.8 MHz Span 1 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 244.9907 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -894.722 Hz x dB Bandwidth 315.295 kHz Freq/Channel Center Freq 848.800000 MHz Start Freq 848.300000 MHz Stop Freq 849.300000 MHz CF Step 100.000000 kHz Auto Man Freq Offset 0.0000000 Hz Signal Track On Off Scale Type Log Lin

PCS1900 (GMSK)-Low	Agilent Ch Freq 1.8502 GHz Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/ Offset 6.5 dB Center 1.85 GHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 246.5569 kHz Transmit Freq Error 1.077 kHz x dB Bandwidth 323.546 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Freq/Channel Center Freq 1.85020000 GHz Start Freq 1.84970000 GHz Stop Freq 1.85070000 GHz CF Step 100.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
PCS1900 (GMSK)-Middle	Agilent Ch Freq 1.88 GHz Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/ Offset 6.5 dB Center 1.88 GHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 246.0481 kHz Transmit Freq Error -781.222 Hz x dB Bandwidth 316.759 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Freq/Channel Center Freq 1.88000000 GHz Start Freq 1.87950000 GHz Stop Freq 1.88050000 GHz CF Step 100.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
PCS1900 (GMSK)-High	Agilent Ch Freq 1.9098 GHz Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/ Offset 6.5 dB Center 1.91 GHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 254.6067 kHz Transmit Freq Error 1.510 kHz x dB Bandwidth 316.073 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Freq/Channel Center Freq 1.90980000 GHz Start Freq 1.90930000 GHz Stop Freq 1.91030000 GHz CF Step 100.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

GPRS1900 (GMSK,1Slot)-Low	Agilent R T Ch Freq 1.8502 GHz Trig Free Occupied Bandwidth Ref 40.5 dBm Atten 45 dB #Peak Log 10 dB/ Offset 6.5 dB  Center 1.85 GHz Span 1 MHz #Res BW 10 kHz #VBW 30 kHz Sweep 10.36 ms (1001 pts) Occupied Bandwidth 249.5710 kHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error 940.097 Hz x dB Bandwidth 324.145 kHz Freq/Channel Center Freq 1.85020000 GHz Start Freq 1.84970000 GHz Stop Freq 1.85070000 GHz CF Step 100.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
--	---




WCDMA Band V-Low	Agilent R T Ch Freq 826.4 MHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB Center 826.4 MHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1613 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error 4.197 kHz x dB Bandwidth 4.709 MHz Freq/Channel Center Freq 826.400000 MHz Start Freq 821.400000 MHz Stop Freq 831.400000 MHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
WCDMA Band V-Middle	Agilent R T Ch Freq 836.6 MHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB Center 836.6 MHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1459 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -17.116 kHz x dB Bandwidth 4.714 MHz Freq/Channel Center Freq 836.600000 MHz Start Freq 831.600000 MHz Stop Freq 841.600000 MHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
WCDMA Band V-High	Agilent R T Ch Freq 846.6 MHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB Center 846.6 MHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1872 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -132.477 Hz x dB Bandwidth 4.698 MHz Freq/Channel Center Freq 846.600000 MHz Start Freq 841.600000 MHz Stop Freq 851.600000 MHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

HSDPA-Low	Agilent R T Ch Freq 826.4 MHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB Center 826.4 MHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1837 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error 6.322 kHz x dB Bandwidth 4.693 MHz Freq/Channel Center Freq 826.400000 MHz Start Freq 821.400000 MHz Stop Freq 831.400000 MHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
HSDPA-Middle	Agilent R T Ch Freq 836.6 MHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB Center 836.6 MHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1797 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -26.814 kHz x dB Bandwidth 4.669 MHz Freq/Channel Center Freq 836.600000 MHz Start Freq 831.600000 MHz Stop Freq 841.600000 MHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
HSDPA-High	Agilent R T Ch Freq 846.6 MHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB Center 846.6 MHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1669 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -2.205 kHz x dB Bandwidth 4.706 MHz Trace/View 1 2 3 Trace Clear Write Max Hold Min Hold View Blank More 1 of 2

Waltek Testing Group (Shenzhen) Co., Ltd.
http://www.semtest.com.cn


WCDMA Band II-Low	Agilent Ch Freq 1.8524 GHz Occupied Bandwidth Ref 30 dBm #Peak Log dB/ Offset 6.5 dB Center 1.852 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1678 MHz Transmit Freq Error -11.244 kHz x dB Bandwidth 4.722 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Freq/Channel Center Freq 1.85240000 GHz Start Freq 1.84740000 GHz Stop Freq 1.85740000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
WCDMA Band II-Middle	Agilent Ch Freq 1.88 GHz Occupied Bandwidth Ref 30 dBm #Peak Log dB/ Offset 6.5 dB Center 1.88 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1562 MHz Transmit Freq Error -673.066 Hz x dB Bandwidth 4.688 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Freq/Channel Center Freq 1.88000000 GHz Start Freq 1.87500000 GHz Stop Freq 1.88500000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
WCDMA Band II-High	Agilent Ch Freq 1.9076 GHz Occupied Bandwidth Ref 30 dBm #Peak Log dB/ Offset 6.5 dB Center 1.908 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1628 MHz Transmit Freq Error -26.659 kHz x dB Bandwidth 4.715 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Freq/Channel Center Freq 1.90760000 GHz Start Freq 1.90260000 GHz Stop Freq 1.91260000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

HSDPA-Low	Agilent Ch Freq 1.8524 GHz Occupied Bandwidth Ref 30 dBm #Peak Log 10 dB/ Offset 6.5 dB Center 1.852 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1726 MHz Transmit Freq Error -12.896 kHz x dB Bandwidth 4.707 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Trace/View Trace 1 2 3 Clear Write Max Hold Min Hold View Blank More 1 of 2
HSDPA-Middle	Agilent Ch Freq 1.88 GHz Occupied Bandwidth Ref 30 dBm #Peak Log 10 dB/ Offset 6.5 dB Center 1.88 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1685 MHz Transmit Freq Error -5.579 kHz x dB Bandwidth 4.693 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Freq/Channel Center Freq 1.88000000 GHz Start Freq 1.87500000 GHz Stop Freq 1.88500000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
HSDPA-High	Agilent Ch Freq 1.9076 GHz Occupied Bandwidth Ref 30 dBm #Peak Log 10 dB/ Offset 6.5 dB Center 1.908 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1334 MHz Transmit Freq Error -30.478 kHz x dB Bandwidth 4.684 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Freq/Channel Center Freq 1.90760000 GHz Start Freq 1.90260000 GHz Stop Freq 1.91260000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin



HSUPA-Low	Agilent R T Ch Freq 1.8524 GHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB  Center 1.852 GHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1842 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -12.628 kHz x dB Bandwidth 4.712 MHz Freq/Channel Center Freq 1.85240000 GHz Start Freq 1.84740000 GHz Stop Freq 1.85740000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
HSUPA-Middle	Agilent R T Ch Freq 1.88 GHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB  Center 1.88 GHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1667 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -6.738 kHz x dB Bandwidth 4.705 MHz Freq/Channel Center Freq 1.88000000 GHz Start Freq 1.87500000 GHz Stop Freq 1.88500000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin
HSUPA-High	Agilent R T Ch Freq 1.9076 GHz Trig Free Occupied Bandwidth Ref 30 dBm Atten 35 dB #Peak Log 10 dB/ Offset 6.5 dB  Center 1.908 GHz Span 10 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts) Occupied Bandwidth 4.1496 MHz Occ BW % Pwr 99.00 % x dB -26.00 dB Transmit Freq Error -30.720 kHz x dB Bandwidth 4.716 MHz Freq/Channel Center Freq 1.90760000 GHz Start Freq 1.90260000 GHz Stop Freq 1.91260000 GHz CF Step 1.00000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

APPENDIX D


Out of Band Emissions at Antenna Terminal






GSM 850
(GMSK)-Middle




GSM 850
(GMSK)-High





	
Bandedge	
	

GPRS850
(GMSK,1Slot)-Low





GPRS850
(GMSK,1Slot)-Middle











Bandedge






PCS1900
(GMSK)-Low





PCS1900
(GMSK)-Middle






PCS1900
(GMSK)-High






Bandedge






GPRS1900
(GMSK,1Slot)-Low





GPRS1900
(GMSK,1Slot)-Middle









GPRS1900
(GMSK,1Slot)-High





Bandedge




WCDMA Band V-Low	
	
WCDMA Band V-Middle	

	
WCDMA Band V-High	
	


Bandedge






HSDPA Band V-Low





HSDPA Band V-Middle




	
HSDPA Band V-High	
	


Bandedge



HSUPA Band V-Low





HSUPA Band V-Middle






	Agilent R T Ref 20 dBm Atten 25 dB Mkr1 2.986 GHz -35.44 dBm #Peak Log 10 dB/ Offset 6.5 dB DI -13.0 dBm M1 S2 S3 FC AA Marker 2.985750000 GHz -35.44 dBm Start 1 GHz Stop 12.75 GHz #Res BW 1 MHz #VBW 3 MHz Sweep 29.38 ms (1001 pts) Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
HSUPA Band V-High	Agilent R T Ref 25 dBm Atten 30 dB Mkr1 442.3 MHz -42.98 dBm #Peak Log 10 dB/ Offset 6.5 dB DI -13.0 dBm M1 S2 S3 FC AA Marker 442.250000 MHz -42.98 dBm Start 30 MHz Stop 1 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 100.5 ms (1001 pts) Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2
	Agilent R T Ref 20 dBm Atten 25 dB Mkr1 2.974 GHz -35.18 dBm #Peak Log 10 dB/ Offset 6.5 dB DI -13.0 dBm M1 S2 S3 FC AA Marker 2.974000000 GHz -35.18 dBm Start 1 GHz Stop 12.75 GHz #Res BW 1 MHz #VBW 3 MHz Sweep 29.38 ms (1001 pts) Peak Search Meas Tools ▶ Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2




Bandedge






WCDMA Band II-Low





WCDMA Band II-Low






WCDMA Band II-Low






Bandedge






HSDPA Band II-Low





HSDPA Band II-Low






HSDPA Band II-Low






Bandedge






HSUPA Band II-Low





HSUPA Band II-Low



HSUPA Band II-Low



Bandedge



APPENDIX E

Frequency Stability

Note: 1. Worst case at GSM850/PCS1900/WCDMA B2/B5 middle channel

2. Normal Voltage NV=DC3.8V; Low Voltage LV=DC3.5V; High Voltage HV=DC4.35V

➤ Frequency stability V.S. Temperature measurement

Reference Frequency: GSM850 Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
NV	-30	70	0.0837	2.50	Pass
	-20	61	0.0726		
	-10	50	0.0598		
	0	43	0.0515		
	10	37	0.0441		
	20	33	0.0395		
	30	39	0.0469		
	40	45	0.0542		
	50	52	0.0625		
Reference Frequency: PCS1900 Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
NV	-30	70	0.0372	2.50	Pass
	-20	56	0.0299		
	-10	47	0.0250		
	0	43	0.0229		
	10	39	0.0209		
	20	35	0.0188		
	30	41	0.0217		
	40	46	0.0245		
	50	54	0.0286		


Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
NV	-30	76	0.0910	2.50	Pass
	-20	62	0.0745		
	-10	53	0.0634		
	0	46	0.0552		
	10	42	0.0506		
	20	35	0.0414		
	30	38	0.0460		
	40	43	0.0515		
	50	51	0.0607		
Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880MHz					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
NV	-30	64	0.0340	2.50	Pass
	-20	56	0.0299		
	-10	52	0.0278		
	0	45	0.0241		
	10	41	0.0217		
	20	35	0.0184		
	30	39	0.0209		
	40	45	0.0237		
	50	50	0.0266		


➤ Frequency stability V.S. Voltage measurement

Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	HV	54	0.0644	2.50	Pass
	NV	43	0.0515		
	LV	38	0.0460		
Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	HV	65	0.0348	2.50	Pass
	NV	57	0.0303		
	LV	49	0.0262		
Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	
		Hz	ppm	Result	
25	HV	25	0.0294	2.50	Pass
	NV	28	0.0340		
	LV	33	0.0395		
Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	HV	61	0.0323	2.50	Pass
	NV	56	0.0299		
	LV	45	0.0241		

APPENDIX F

Modulation characteristics





APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

******* END OF REPORT *******