

FCC TEST REPORT
for
Wahoo Fitness LLC

GEM RETRO
Model No.: GEMRET0101

Prepared for : Wahoo Fitness LLC
Address : 90 W. Wieuca Road #110 Atlanta, GA 30342

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited
Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road,
Nanshan District, Shenzhen, Guangdong, China
Tel: (86) 755-26066544
Fax: (86) 755-26014772

Report Number : R0116011253Z
Date of Test : Jan. 27~ Mar. 04, 2016
Date of Report : Mar. 08, 2016

TABLE OF CONTENTS

Description

Page

Test Report

1. GENERAL INFORMATION.....	4
1.1. Description of Device (EUT).....	4
1.2. Auxiliary Equipment Used during Test.....	5
1.3. Description of Test Facility.....	6
1.4. Measurement Uncertainty.....	6
2. TEST METHODOLOGY.....	7
2.1. Summary of Test Results.....	7
2.2. Description of Test Modes.....	7
3. TEST PROCEDURE.....	8
4. RADIATION INTERFERENCE.....	9
4.1. Requirements (15.249, 15.209):.....	9
4.2. Test Procedure.....	9
4.3 Test Equipment.....	10
4.4. Test Results.....	10
5. BANDEDGE.....	14
5.1. Requirements (15.249):.....	14
5.2. Test Procedure.....	14
5.3. Test Configuration:.....	14
5.4. Test Results.....	15
6. OCCUPIED BANDWIDTH.....	24
6.1. Requirements :.....	24
6.2. Test SET-UP.....	24
6.3 Test Equipment.....	24
6.4. Test Results.....	24
7. ANTENNA APPLICATION.....	26
7.1. Antenna requirement.....	26
7.2. Result.....	26
8. PHOTOGRAPH.....	27
8.1. Photo of Radiation Emission Test.....	27

TEST REPORT

Applicant : Wahoo Fitness LLC
Manufacturer : Wahoo Fitness LLC
EUT : GEM RETRO
Model No. : GEMRET0101
Serial No. : N.A.
Trade Mark : N.A.
Rating : DC 3.6V Max.

Measurement Procedure Used:

FCC Part15 Subpart C, Paragraph 15.207, 15.249 & 15.209

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test : Jan. 27~ Mar. 04, 2016

Prepared by :

Kebo Zhang

(Tested Engineer / Kebo Zhang)

Reviewer :

Amy Ding

(Project Manager / Amy Ding)

Approved & Authorized Signer :

Tom Chen

(Manager / Tom Chen)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: GEM RETRO
Model Number	: GEMRET0101
Test Power Supply	: DC 4.75V for POE Power Supply/ DC 10.0V for POE Power Supply
Frequency	: BT: 2402~2480MHz 2.4GHz: 2457MHz
Modulation	: BT/2.4GHz: GFSK
Channel Spacing	: BT: 2MHz
Number of Channels	: BT: 40 2.4GHz: 1
Antenna Type	: Integrated monopole chip antenna
Antenna Gain	: 3.45 dBi
Applicant Address	: Wahoo Fitness LLC 90 W. Wieuca Road #110 Atlanta, GA 30342
Manufacturer Address	: Wahoo Fitness LLC 90 W. Wieuca Road #110 Atlanta, GA 30342
Factory Address	: Flextronics Electronics Technology (Suzhou) Co., Ltd. No.268 Suhong Road, Suzhou Industrial Park, Suzhou City, Jiangsu Province, China
Date of receipt	: Jan. 27, 2016
Date of Test	: Jan. 27~ Mar. 04, 2016

1.2. Auxiliary Equipment Used during Test

POE Power Supply : DC 4.75V/DC 10.0V

PC : Manufacturer: DELL
M/N: Optiplex 3020 MT
S/N: CN-079V51-70163-4AD-089K-A00
Input Rating: AC 100-240V, 50-60Hz 5.4A
CE , FCC DOC, CCC

MONITOR : Manufacturer: DELL
M/N: UZ2215Hf
S/N: CN-035VN6-72872-45A-A3AB
Input Rating: AC 100-240V, 50-60Hz, 1.5A
Output Rating: DC 19.5V, 4.62A
TUV-GS FCC CE KCC VCCI

KEYBOARD : Manufacturer: DELL
M/N: SK-8120
S/N: CN-0DJ365-71616-49J-0MVR-A00
Input Rating: DC 5V,0.05A
CE FCC VCCI KCC TUV-GS
Cable: 1.8m, unshielded

MOUSE : Manufacturer: DELL
M/N: MS111-T
S/N: CN-0KW2YH-71616-488-1CBJ
Input Rating: DC 5V,0.1A
Cable: 1.8m, unshielded
CE FCC VCCI KCC TUV-GS

Printer : Manufacturer: Brother
M/N: MFC-3360C
S/N: N/A
CE, FCC:DOC

Power Line : Non-Shielded, 1.5m

VGA Cable : Non-Shielded, 1.5m

1.3. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 752021

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 10, 2013.

IC-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A-1, February 22, 2013.

Test Location

All Emissions tests were performed at
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC
Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong,
China

1.4. Measurement Uncertainty

Radiation Uncertainty : Ur = 4.1 dB (Horizontal)
Ur = 4.3 dB (Vertical)

Conduction Uncertainty : Uc = 3.4dB

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC Part 15, Paragraph 15.249.

2.1. Summary of Test Results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
§15.207 (a)	Conducted Emission	-	N/A
§15.205	Restricted Band of Operation	PASS	Complies
§15.209 §15.249(a)	Radiated Emission	PASS	Complies
§15.215(c)	20dB Bandwidth Test	PASS	Complies
§15.203	Antenna Requirement	PASS	Complies

2.2. Description of Test Modes

The EUT has been tested under operating condition.

Manual control the EUT for staying in continuous transmitting mode.

3. Test Procedure

GENERAL: This report shall NOT be reproduced except in full without the written approval of Shenzhen Anbotek Compliance Laboratory Limited. The EUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.10-2013 using a spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the EUT was 74.3oF with a humidity of 69%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.10-2013 10.1.7 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

4. Radiation Interference

4.1. Requirements (15.249, 15.209):

FIELD STRENGTH of Fundamental: @3M	FIELD STRENGTH of Harmonics	S15.209	
902-928 MHZ		30 - 88 MHz	40 dBuV/m
2.4-2.4835 GHz		88 - 216 MHz	43.5
94 dBuV/m @3m	54 dBuV/m @3m	216 - 960 MHz	46
		ABOVE 960 MHz	54dBuV/m

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in 15.209, whichever is the lesser attenuation.

4.2. Test Procedure

For below 1GHz, the EUT is placed on a turn table which is 0.8 meter high above the ground. For above 1GHz, the EUT is placed on a turn table which is 1.5 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

All readings from 30MHz to 1GHz are quasi-peak values with a resolution bandwidth of 120kHz. All reading are above 1GHz, peak & average values with a resolution bandwidth of 1MHz. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation. The test results are listed in Section 4.3.

4.3 Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analysis	Agilent	E4407B	US39390582	Apr. 17, 2015	1 Year
2.	Preamplifier	Instruments corporation	EMC011830	980100	Apr. 17, 2015	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESPI	101604	Apr. 17, 2015	1 Year
4.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Apr. 20, 2015	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Apr. 20, 2015	1 Year
6.	Pre-amplifier	SONOMA	310N	186860	Apr. 17, 2015	1 Year
7.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
8	Power Sensor	DAER	RPR3006W	15I00041SN046	Jun 30, 2015	1 Year
9	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Jun 30, 2015	1 Year
10	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Jun 30, 2015	1 Year
11	Signal Generator	Agilent	E4421B	MY41000743	Jun 30, 2015	1 Year
12	DC Power supply	IV	IV-8080	YQSB0096	Jun 30, 2015	1 Year
13	TEMP&HUMI PROGRAMMABLE CHAMBER	Bell Group	BE-THK-150M8	SE-0137	Mar 16, 2015	1 Year

4.4. Test Results


PASS.

The EUT was tested on (On(DC 4.75V), On(DC 10.0V)) modes, only the worst data of (On(DC 10.0V)) is attached in the following pages.

Only the worst case (x orientation).


Below 1GHz:

Job No.:	0116011253I	Polarziation:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10.0V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Mode:	ON	Distance:	3m
Note:	30-1000MHz		



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	35.4993	43.22	-13.90	29.32	40.00	-10.68	QP	300	360	
2	47.9940	34.90	-13.67	21.23	40.00	-18.77	QP	300	0	
3	95.7622	42.00	-20.98	21.02	43.50	-22.48	QP	300	360	
4	119.8556	45.79	-21.32	24.47	43.50	-19.03	QP	300	0	
5	180.0165	41.59	-21.85	19.74	43.50	-23.76	QP	300	360	
6	349.2500	32.41	-14.00	18.41	46.00	-27.59	QP	300	0	

Job No.: 0116011253I Polarization: Vertical
Standard: (RE)FCC PART15 C _3m Power Source: DC 10.0V
Test item: Radiation Test Temp.(C)/Hum.(%RH): 24.3(C)/55%RH
Mode: ON Distance: 3m
Note: 30-1000MHz



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.3173	50.33	-16.77	33.56	40.00	-6.44	QP	100	0	
2	47.9938	50.49	-13.67	36.82	40.00	-3.18	QP	100	360	
3	95.7622	48.43	-15.98	32.45	43.50	-11.05	QP	100	0	
4	119.8556	52.77	-16.32	36.45	43.50	-7.05	QP	100	360	
5	202.8103	47.01	-15.77	31.24	43.50	-12.26	QP	100	0	
6	239.9874	45.82	-14.09	31.73	46.00	-14.27	QP	100	0	

Above 1 GHz:

Horizontal CH Middle (2457MHz)								
Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dBμV	Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
2457.000	2.19	31.22	34.60	89.52	88.33	114.0	-25.67	Peak
2457.000	2.19	31.22	34.60	80.36	79.17	94.0	-14.83	AV
4914.250	2.57	35.00	34.58	42.76	45.75	74.0	-28.25	Peak
4914.250	2.57	35.00	34.58	34.89	37.88	54.0	-16.12	AV
7371.630	3.00	36.17	35.14	39.67	43.70	74.0	-30.30	Peak
7371.630	3.00	36.17	35.14	34.58	38.61	54.0	-15.39	AV
9828.000	---	---	---	---	---	---	---	---
12285.00	---	---	---	---	---	---	---	---
14742.00	---	---	---	---	---	---	---	---
17199.00	---	---	---	---	---	---	---	---

Vertical CH Middle (2457MHz)								
Frequency MHz	Cable Loss dB	Ant Factor dB/m	Preamp Factor dB	Read Level dBμV	Level dBμV/m	Limit dBμV/m	Over Limit dB	Remark
2457.000	2.19	31.22	34.60	91.94	90.75	114.0	-23.25	Peak
2457.000	2.19	31.22	34.60	82.20	81.01	94.0	-12.99	AV
4914.460	2.57	35.00	34.58	47.53	50.52	74.0	-23.48	Peak
4914.460	2.57	35.00	34.58	39.64	42.63	54.0	-11.37	AV
7371.870	3.00	36.17	35.14	42.38	46.41	74.0	-27.59	Peak
7371.870	3.00	36.17	35.14	35.91	39.94	54.0	-14.06	AV
9828.000	---	---	---	---	---	---	---	---
12285.00	---	---	---	---	---	---	---	---
14742.00	---	---	---	---	---	---	---	---
17199.00	---	---	---	---	---	---	---	---

**NOTE: “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
The results of different modulations are the same.**

5. Bandedge

5.1. Requirements (15.249):

The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

5.2. Test Procedure


The EUT is placed on a turn table which is 1.5 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test. The device is evaluated in xyz orientation.

Test Equipment


Same as the equipment listed in 4.3.

5.3. Test Configuration:

30M to 1G emissions:



1G to 40G emissions:




5.4. Test Results

Pass.


Please refer the following plot. Only the worst case (x orientation).

Job No.:	0116011253I	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55% RH
Note:	PEAK	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2374.325	46.45	-2.55	43.90	74.00	-30.10	peak			
2	2390.000	44.86	-2.51	42.35	74.00	-31.65	peak			
3	2400.000	45.77	-2.49	43.28	74.00	-30.72	peak			

Job No.:	0116011253I	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Note:	PEAK	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2375.875	43.49	-2.55	40.94	74.00	-33.06	peak			
2	2390.000	42.68	-2.51	40.17	74.00	-33.83	peak			
3	2400.000	44.26	-2.49	41.77	74.00	-32.23	peak			

Job No.:	0116011253I	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55% RH
Note:	AV	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2377.813	42.06	-2.54	39.52	54.00	-14.48	AVG			
2	2390.000	40.98	-2.51	38.47	54.00	-15.53	AVG			
3	2400.000	41.41	-2.49	38.92	54.00	-15.08	AVG			

Job No.:	0116011253I	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10V
Test item:	Radiation Test	Temp.(C)/Hum.(% RH):	24.3(C)/55% RH
Note:	AV	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2375.488	39.58	-2.55	37.03	54.00	-16.97	AVG			
2	2390.000	38.42	-2.51	35.91	54.00	-18.09	AVG			
3	2400.000	38.38	-2.49	35.89	54.00	-18.11	AVG			

Job No.:	0116011253I	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55% RH
Note:	PEAK	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	46.40	-2.31	44.09	74.00	-29.91	peak			
2	2487.900	46.41	-2.30	44.11	74.00	-29.89	peak			

Job No.:	0116011253I	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Note:	PEAK	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	44.90	-2.31	42.59	74.00	-31.41	peak			
2	2488.313	45.30	-2.30	43.00	74.00	-31.00	peak			

Job No.:	0116011253I	Polarization:	Horizontal
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10V
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55% RH
Note:	AV	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	41.55	-2.31	39.24	54.00	-14.76	AVG			
2	2485.287	41.59	-2.30	39.29	54.00	-14.71	AVG			

Job No.:	0116011253I	Polarization:	Vertical
Standard:	(RE)FCC PART15 C _3m	Power Source:	DC 10V
Test item:	Radiation Test	Temp.(C)/Hum.(% RH):	24.3(C)/55% RH
Note:	AV	Distance:	3m




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	2483.500	39.55	-2.31	37.24	54.00	-16.76	AVG			
2	2486.800	39.05	-2.30	36.75	54.00	-17.25	AVG			

6. Occupied Bandwidth

6.1. Requirements :

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2. Test SET-UP



6.3 Test Equipment


Same as the equipment listed in 4.3.

6.4. Test Results

Pass.

Please refer the following plot.

20dB Down:



7. ANTENNA APPLICATION


7.1. Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.



7.2. Result

The EUT's antenna used a Integrated monopole chip antenna which is permanently attached, The antenna's gain is 3.45dBi and meets the requirement.




8. PHOTOGRAPH

8.1. Photo of Radiation Emission Test



APPENDIX I (External Photos)


1. Figure
The EUT-Top View




2. Figure
The EUT-Bottom View




3. Figure
The EUT-FrontView




4. Figure
The EUT-Back View



5. Figure
The EUT-Right View



6. Figure
The EUT-Left View




APPENDIX II (Internal Photos)


1. Figure
The EUT-Inside View



2. Figure
PCB of the EUT-Front View



3. Figure
PCB of the EUT-Back View




4. Figure
PCB of the EUT-Front View



5. Figure
PCB of the EUT-Back View



6. Figure
PCB of the EUT-Front View



7. Figure
PCB of the EUT-Back View

