

# FCC Test Report

Report No.: AGC01741230307FE08

FCC ID	:	2AYT3-AC60
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Portable Power Station
BRAND NAME	:	BLUETTI
MODEL NAME	:	AC60
APPLICANT	:	SHENZHEN POWEROAK NEWENER CO., LTD
DATE OF ISSUE	:	Apr. 21, 2023
STANDARD(S)	:	FCC Part 15.247
REPORT VERSION	:	V1.0
		milian







#### **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Apr. 21, 2023	Valid	Initial Release	



## TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RELATED SUBMITTAL(S)/GRANT(S)	7
2.4. TEST METHODOLOGY	7
2.5. SPECIAL ACCESSORIES	7
2.6. EQUIPMENT MODIFICATIONS	
2.7. ANTENNA REQUIREMENT	7
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	
5.1. CONFIGURATION OF TESTED SYSTEM	
5.2. EQUIPMENT USED IN TESTED SYSTEM	
5.3. SUMMARY OF TEST RESULTS	
6. TEST FACILITY	
7. PEAK OUTPUT POWER	
7.1. MEASUREMENT PROCEDURE	
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
7.3. LIMITS AND MEASUREMENT RESULT	
8. BANDWIDTH	
8.1. MEASUREMENT PROCEDURE	
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
8.3. LIMITS AND MEASUREMENT RESULTS	
9. CONDUCTED SPURIOUS EMISSION	24
9.1. MEASUREMENT PROCEDURE	
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
9.3. MEASUREMENT EQUIPMENT USED	24
9.4. LIMITS AND MEASUREMENT RESULT	24
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	
10.1. MEASUREMENT PROCEDURE	
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	



10.3. MEASUREMENT EQUIPMENT USED	37
10.4. LIMITS AND MEASUREMENT RESULT	
11. RADIATED EMISSION	41
11.1. MEASUREMENT PROCEDURE	41
11.2. TEST SETUP	42
11.3. LIMITS AND MEASUREMENT RESULT	43
11.4. TEST RESULT	43
12. LINE CONDUCTED EMISSION TEST	57
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	57
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	57
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	58
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	58
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	58
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	61
APPENDIX B: PHOTOGRAPHS OF EUT	61



## **1. VERIFICATION OF COMPLIANCE**

Applicant	SHENZHEN POWEROAK NEWENER CO., LTD		
Address	F19, BLD No.1, Kaidaer Tongsha Rd No.168, Xili Street, Nanshan, Shenzhen, China		
Manufacturer	SHENZHEN POWEROAK NEWENER CO., LTD		
Address	F19, BLD No.1, Kaidaer Tongsha Rd No.168, Xili Street, Nanshan, Shenzhen, China		
Factory	Huizhou PowerOak Innovation Co., Ltd		
Address	No.1 Workshop) Longsheng 5th Road, Laoshe Village, Dayawan West Zone, Iuizhou, Guangdong, China		
Product Designation	Portable Power Station		
Brand Name	BLUETTI		
Test Model	AC60		
Date of receipt of test item	Mar. 16, 2023		
Date of Test:	Mar. 16, 2023~Apr. 21, 2023		
Deviation	No any deviation from the test method		
Condition of Test Sample	Normal		
Test Result	Pass		
Report Template	AGCRT-US-BLE/RF		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By

an Duan

Alan Duan (Project Engineer)

Apr. 21, 2023

**Reviewed By** 

vin Lin \_\_\_\_\_

Calvin Liu (Reviewer)

Apr. 21, 2023

Approved By

Max Zhang

Max Zhang Authorized Officer

Apr. 21, 2023



# 2. GENERAL INFORMATION

## 2.1. PRODUCT DESCRIPTION

The EUT is designed as a "Portable Power Station". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	Frequency 2.402 GHz to 2.480GHz					
RF Output Power	1Mbps: 1.182dBm (Max) 2Mbps: 0.905dBm (Max)					
Bluetooth Version	V5.0					
Modulation	BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE ⊠GFSK 1Mbps ⊠GFSK 2Mbps					
Number of channels	40 Channel					
Antenna Designation	PCB Antenna (Comply with requirements of the FCC part 15.203)					
Antenna Gain	-2.31dBi					
Hardware Version	AC60_U2 V4.0					
Software Version	V2073					
Input Rating	<ul> <li>AC: 120V~50/60Hz, 10A Max</li> <li>DC/PV:12V-28V=8A, 200W Max</li> </ul>					
Output Rating	<ul> <li>AC: 120V~50/60Hz, 600W Max.</li> <li>USB-A: 5V=3A</li> <li>USB-C: 5/9/12/15/20V=3A; 20V=5A(E-Marker chip built-in)</li> <li>Wireless Charge: 5/7.5/10/15W</li> <li>Cigarette Lighter Socket: 12V=10A</li> <li>AC and DC output: 600W Total</li> <li>Battery Expansion: 22.4V=30A Total</li> </ul>					

## 2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency		
	0	2402 MHz		
	1	2404 MHz		
2400~2483.5MHz	:	:		
	38	2478 MHz		
	39	2480 MHz		



#### 2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for FCC ID: 2AYT3-AC60 filing to comply with the FCC Part 15.247 requirements.

#### 2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### **2.5. SPECIAL ACCESSORIES**

Refer to section 5.2.

#### 2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



# **3. MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement y  $\pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$		
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$		



## 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX_CH00_1Mbps
2	Middle channel TX_CH19_1Mbps
3	High channel TX_CH39_1Mbps
4	Low channel TX_CH00_2Mbps
5	Middle channel TX_CH19_2Mbps
6	High channel TX_CH39_2Mbps

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.

2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting

									<u> </u>			
🎼 ssco	M V5.13.1	串口/网	络数据	调试器,作者	前大虾丁丁	,26180	058@qq.co	m. QQ群:	52502449(最新版本)	-		$\times$
通讯端口	串口设置	显示	发送	多字符串	小工具	帮助	联系作者	大虾论坛				
10:26:19.	548]发→◇	AT#Ab2	402_00_	00								^
10:26:19. 10:33:30.	563]收 <del>←</del> ◆ 188]发→◇	OK AT#Ab2	480_00_	00								
10:36:22.	203]收 <del>←</del> ◆ 693]发→◇		402_00_	01								
10:41:08. 10:42:08.	693]收←◆ 820]收←◆ 798]发→◇	·\0\0\0		00								
] 10:42:08. 10:42:19. ]	798]收 <del>←</del> ♦ 362]发→◇	OK AT#Ab2	402_00_	00								
	362]收✦✦ 486]发→◇		402_00_	01								- 1
10:42:27. 10:43:18. 1	486]收←◆ 256]发→◇	OK AT#Ab2	402_00_	00								
10:43:18. 10:47:26. 7	266]收 <del>←</del> ◆ 848]发→◇	OK AT#Ab2	440_00_	00								
10:47:26.	848]收←◆ 171]发→◇	OK AT#Ab2	480_00_	,00								
10:49:27.	186]收 <del>←</del> ◆ 318]发→◇	OK AT#Ab2	402_00_	01								
」 10:53:37.	324]收←◆	OK										
清除窗口	1 打开文件	ŧ .					发;	送文件 停	止 清发送区 □ 最前	🕅 English	保存参数	扩展 -
第11日号 CO	MG USB-SER	IAL CH3	340	- н	13显示	呆存数排	■ □ 接收	数据到文件	□ HEX发送 □ 定时发送	£: 10 ms/	次 🔽 加	回车换行
● 关闭	串口 👌	更	多串口词	日本 🔽 🗹	时间戳和	分包显示	■ 超时时间	a):20 ms	第1 字节 至 末尾 ▼ カ	n校验 None	•	
~	DTR 波特	窿: 11	5200	▼ AT#Ab	2402_00_0	)1						
的了更好地	发展SSCOM 立创F结尾客	欠件	发	Ě								
【升级到V	5. 13. 1 ] 🛨	合宙高	生价比40	模块值得-	-i式 ★RT-	Thread	中国人的开	原免费操作	系统 ★新一代WiFi芯片新	兼容8266支持I	T-Thread	★8KMjž
www.daxia	a.com S:3	74	R:5	2	COM6	助开	115200bps	,8,1,None	None,			



# **5. SYSTEM TEST CONFIGURATION**

## **5.1. CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:

EUT

Conducted Emission Configure:

EUT	AE

## **5.2. EQUIPMENT USED IN TESTED SYSTEM**

ltem	Equipment	Model No.	ID or Specification	Remark	
1	Portable Power Station	AC60	2AYT3-AC60	EUT	

#### **5.3. SUMMARY OF TEST RESULTS**

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



# 6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA

## TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Aug. 04, 2022	Aug. 03, 2023
LISN	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test software	R&S	ES-K1 (Ver.V1.71)	N/A	N/A	N/A

## TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	N/A	N/A
Attenuator	ZHINAN	E-002	N/A	Sep. 01, 2022	Aug. 31, 2023
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 01, 2022	Aug. 31, 2023
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 05, 2023	Jan. 04, 2025
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A



# 7. PEAK OUTPUT POWER


## 7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW≥DTS bandwidth
- 3. VBW≥3\*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

## 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP






#### 7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power						
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail		
	2402	0.617	≪30	Pass		
GFSK 1Mbps	2440	0.641	≪30	Pass		
	2480	1.182	≪30	Pass		
	2402	0.365	≪30	Pass		
GFSK 2Mbps	2440	0.397	≪30	Pass		
	2480	0.905	≪30	Pass		


#### **Test Graphs of Conducted Output Power**











#### **Test Graphs of Conducted Output Power**



R   enter F	RF 50 Ω AC req 2.48000000		SENSE:INT	ALIGN AUTO Avg Type: Log-Pwr	07:31:23 PM Apr 18, 2023 TRACE 1 2 3 4 5 6	Frequency
		PNO: Fast ↔ IFGain:Low	Trig: Free Run #Atten: 40 dB	Avg Hold: 100/100	TYPE MWWWWW DET PNNNNN	
) dB/div	Ref 20.00 dBm			Mkr1	2.480 203 GHz 0.905 dBm	Auto Tun
						Center Fre
0.0			<b>_</b> 1			2.480000000 GH
.00		and the second				Start Fre
0.0						2.477500000 GH
0.0						Stop Fre
0.0						2.482500000 GH
0.0						CF Ste
						500.000 kH <u>Auto</u> Ma
0.0						FreqOffse
0.0						0 H
0.0						
	480000 GHz 1.5 MHz	#VB	N 5.0 MHz	Sweep 1	Span 5.000 MHz .066 ms (1000 pts)	
G				STATUS		



# 8. BANDWIDTH

## **8.1. MEASUREMENT PROCEDURE**

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW $\ge$ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
  4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

# 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

Test Data of Occupied Bandwidth and DTS Bandwidth							
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail		
	2402	1.051	0.674	≥0.5	Pass		
GFSK 1Mbps	2440	1.051	0.676	≥0.5	Pass		
	2480	1.052	0.674	≥0.5	Pass		
	2402	2.034	1.154	≥0.5	Pass		
GFSK 2Mbps	2440	2.036	1.156	≥0.5	Pass		
	2480	2.034	1.151	≥0.5	Pass		

## 8.3. LIMITS AND MEASUREMENT RESULTS





### Test Graphs of Occupied Bandwidth






Test\_Graph\_LE1M\_ANT1\_2480\_1Mbps\_OBW




Test Graphs of DTS Bandwidth










# Test Graphs of Occupied Bandwidth








Test\_Graph\_LE2M\_ANT1\_2480\_2Mbps\_OBW











# 9. CONDUCTED SPURIOUS EMISSION

#### 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

#### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

#### 9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

#### 9.4. LIMITS AND MEASUREMENT RESULT


LIMITS AND MEASUREMENT RESULT					
Angliaghta Limita	Measurement Result				
Applicable Limits	Test Data	Criteria			
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS			






## Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands

























#### Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands






## Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands





#### Report No.: AGC01741230307FE08 Page 33 of 61














#### Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands





Agilent Spectrum Analyzer - Swept SA LXI R RF 50 Ω AC	CORREC	SENSE:INT	ALIGNAUTO	07:33:07 PM Apr 18, 2023	Frequency	
Center Freq 2.487500000	PNO: Fast 🕶	Trig: Free Run	Avg Type: Log-Pwr Avg Hold: 100/100	TRACE 123456 TYPE MWWWWW DET P N N N N N	riequency	
	IFGain:Low	#Atten: 30 dB	Mkr2 2	.483 500 0 GHz	Auto Tune	
10 dB/div Ref 20.00 dBm				-61.097 dBm		
10.0					Center Freq	
0.00					2.487500000 GHz	
-10.0						
-20.0				-19,49 dBm	Start Freq	
-30.0	M				2.475000000 GHz	
-40.0						
-60.0	2 2 2	alander Harrison and Man Brieder	attende water from the state of the set second	ar a bha ann an ann an ann an an Airtean an Airte	Stop Freq	
-70.0					2.50000000 GHz	
Start 2.47500 GHz				Stop 2.50000 GHz	CF Step	
#Res BW 100 kHz	#VBW	/ 300 kHz	Sweep 4.0	000 ms (30000 pts)	2.500000 MHz Auto Man	
MKR MODE TRC SCL X	511 8 GHz	Y FU 0.514 dBm	INCTION FUNCTION WIDTH	FUNCTION VALUE		
	500 0 GHz	-61.097 dBm			Freq Offset	
4					0 Hz	
6						
8						
10						
•						
MSG			STATUS			
Test_Graph_LE	Test_Graph_LE2M_ANT1_2480_2Mbps_Higher Band Edge Emissions					



# **10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY**

## **10.1. MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

## **10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)**

Refer to Section 7.2.

## **10.3. MEASUREMENT EQUIPMENT USED**

Refer to Section 6.

## **10.4. LIMITS AND MEASUREMENT RESULT**

	Test Data of Conducted Output Power Spectral Density							
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail				
	2402	-15.157	≪8	Pass				
GFSK 1Mbps	2440	-15.312	≪8	Pass				
	2480	-14.461	≪8	Pass				
	2402	-18.507	≪8	Pass				
GFSK 2Mbps	2440	-18.594	≪8	Pass				
	2480	-17.946	≪8	Pass				






#### Test Graphs of Conducted Output Power Spectral Density






## Test Graphs of Conducted Output Power Spectral Density



#### Report No.: AGC01741230307FE08 Page 40 of 61








# **11. RADIATED EMISSION**

## **11.1. MEASUREMENT PROCEDURE**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



## 11.2. TEST SETUP





# **11.3. LIMITS AND MEASUREMENT RESULT**

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

# 11.4. TEST RESULT


# Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



EUT	Portable Power Station	Model Name	AC60			
Temperature	25° C	Relative Humidity	55.4%			
Pressure	960hPa	Test Voltage	Normal Voltage			
Test Mode	Mode 3	Antenna	Horizontal			

#### Radiated emission from 30MHz to 1000MHz




	INO. IVI	K. Fley.	Lever	Factor	ment	LIIIII	0101	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
	1	34.0365	17.22	10.12	27.34	50.00	-22.66	peak
	2 *	127.2176	23.31	17.01	40.32	53.50	-13.18	peak
-	3	191.7450	20.28	14.67	34.95	53.50	-18.55	peak
-	4	221.3921	16.76	15.61	32.37	56.00	-23.63	peak
	5	460.7271	7.43	27.23	34.66	56.00	-21.34	peak
	6	903.3094	7.01	31.34	38.35	56.00	-17.65	peak

# **RESULT: PASS**



EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		34.0365	17.22	10.12	27.34	50.00	-22.66	peak
2	*	127.2176	23.31	17.01	40.32	53.50	-13.18	peak
3		191.7450	20.28	14.67	34.95	53.50	-18.55	peak
4		221.3921	16.76	15.61	32.37	56.00	-23.63	peak
5		460.7271	7.43	27.23	34.66	56.00	-21.34	peak
6		903.3094	7.01	31.34	38.35	56.00	-17.65	peak

# RESULT: PASS Note:

Note:

1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been tested. The mode 3 is the worst case and recorded in the report.



#### Radiated emission above 1GHz

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
4804.000	52.33	0.08	52.41	74.00	-21.59	peak	
4804.000	43.15	0.08	43.23	54.00	-10.77	AVG	
7206.000	48.63	2.21	50.84	74.00	-23.16	peak	
7206.000	41.22	2.21	43.43	54.00	-10.57	AVG	
Remark:							
actor = Anter	nna Factor + Cable	Loss – Pre-	amplifier.				

 EUT
 Portable Power Station
 Model Name
 AC60

 Term and transmission
 05% O
 Delation Unwindity
 55.490

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type		
4804.000	52.33	0.08	52.41	74.00	-21.59	peak		
4804.000	42.04	0.08	42.12	54.00	-11.88	AVG		
7206.000	48.36	2.21	50.57	74.00	-23.43	peak		
7206.000	39.87	2.21	42.08	54.00	-11.92	AVG		
Remark:								
actor = Anter	nna Factor + Cabl	e Loss – Pre-a	amplifier.					



EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin				
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type			
4882.000	53.02	0.14	53.16	74.00	-20.84	peak			
4882.000	38.77	0.14	38.91	54.00	-15.09	AVG			
7323.000	51.28	2.36	53.64	74.00	-20.36	peak			
7323.000	35.78	2.36	38.14	54.00	-15.86	AVG			
Remark:									
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4882.000	48.32	0.14	48.46	74.00	-25.54	peak
4882.000	41.21	0.14	41.35	54.00	-12.65	AVG
7323.000	48.14	2.36	50.50	74.00	-23.50	peak
7323.000	40.25	2.36	42.61	54.00	-11.39	AVG
Remark:						
Factor = Anter	nna Factor + Cable	e Loss – Pre-a	amplifier.			



EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4960.000	41.33	0.22	41.55	74.00	-32.45	peak
4960.000	42.35	0.22	42.57	54.00	-11.43	AVG
7440.000	48.25	2.64	50.89	74.00	-23.11	peak
7440.000	39.47	2.64	42.11	54.00	-11.89	AVG
Remark:						
Factor = Anter	na Factor + Cabl	e Loss – Pre-a	amplifier.			

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4960.000	51.12	0.22	51.34	74.00	-22.66	peak
4960.000	42.35	0.22	42.57	54.00	-11.43	AVG
7440.000	48.00	2.64	50.64	74.00	-23.36	peak
7440.000	39.47	2.64	42.11	54.00	-11.89	AVG
Remark:						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			

#### **RESULT: PASS**

#### Note:


- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Amplifier gain, Over=Limit-Measure.
- 3. The "Factor" value can be calculated automatically by software of measurement system.
- 4. All modes have been tested, and the report only records mode 1-3 test results as the worst




# Test result for band edge emission at restricted bands

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




# **RESULT: PASS**




#### Report No.: AGC01741230307FE08 Page 50 of 61

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




**RESULT: PASS** 




#### Report No.: AGC01741230307FE08 Page 51 of 61

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




**RESULT: PASS** 



#### Report No.: AGC01741230307FE08 Page 52 of 61

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Test Graph for Peak Measurement




Test Graph for Average Measurement






EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




# **RESULT: PASS**




#### Report No.: AGC01741230307FE08 Page 54 of 61

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




**RESULT: PASS** 




#### Report No.: AGC01741230307FE08 Page 55 of 61

EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




**RESULT: PASS** 




EUT	Portable Power Station	Model Name	AC60
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 6	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



# **RESULT: PASS**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



# **12. LINE CONDUCTED EMISSION TEST**


## **12.1. LIMITS OF LINE CONDUCTED EMISSION TEST**

Frequency	Maximum RF Line Voltage				
Frequency	Q.P.( dBuV)	Average( dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





# 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


# 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 5. All modes have been tested, and the report only records (Mode 3) test results as the worst

# 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST








# MEASUREMENT RESULT: "agc fin"


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.154000 3.542000 3.558000 3.646000 4.990000 5.986000	49.60 42.30 40.00 41.40 43.00 44.00	6.2 6.4 6.4 6.4 6.4 6.5	66 56 56 56 60	16.2 13.7 16.0 14.6 13.0 16.0	QP QP QP QP QP QP	L1 L1 L1 L1 L1 L1

## MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
3.458000 3.498000 3.542000 3.586000 4.950000 5.986000	31.90 34.20 34.20 32.60 34.20 32.80	6.4 6.4 6.4 6.4 6.4 6.5	46 46 46 46 50	11.8	AV AV AV AV AV AV	L1 L1 L1 L1 L1 L1







# MEASUREMENT RESULT: "agc fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.154000 3.610000 4.990000 6.390000 6.430000 6.470000	50.20 42.80 43.20 43.70 44.50 44.30	6.2 6.4 6.5 6.5 6.6	66 56 50 60 60	15.6 13.2 12.8 16.3 15.5 15.7	QP QP QP QP QP QP	N N N N N

# MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
3.418000 3.498000 3.542000 3.650000 4.978000 5.986000	29.20 34.20 34.40 31.60 34.00 33.00	6.4 6.4 6.4 6.4 6.4 6.5	46 46 46 46 46 50	16.8 11.8 11.6 14.4 12.0 17.0	AV AV	N N N N N



# **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**

Refer to the Report No.: AGC01741230307AP02 **APPENDIX B: PHOTOGRAPHS OF EUT** Refer to the Report No.: AGC01741230307AP03

----END OF REPORT----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.