



FCC RF Test Report

APPLICANT : OnePlus Technology (Shenzhen) Co., Ltd.
EQUIPMENT : OnePlus AIRVOOC 50W Magnetic Charger
BRAND NAME : OnePlus
MODEL NAME : OAWV08
FCC ID : 2ABZ2-OAWV08
STANDARD : FCC Part 15 Subpart C §15.209
CLASSIFICATION : (DCD) Part 15 Low Power Transmitter Below 1705 kHz
TEST DATE(S) : Jul. 27, 2024 ~ Aug. 02, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Modification of EUT	5
1.5 Test Location	6
1.6 Test Software	6
1.7 Applied Standards	6
2 Test Configuration of Equipment Under Test	7
2.1 Test Mode	7
2.2 Connection Diagram of Test System	7
2.3 Support Unit used in test configuration and system	7
3 Test Result	8
3.1 20dB and 99% Occupied Bandwidth Measurement	8
3.2 Radiated Emission Measurement	10
3.3 AC Conducted Emission Measurement	18
3.4 Antenna Requirements.....	22
4 List of Measuring Equipment.....	23
5 Measurement Uncertainty	24
Appendix A. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR470802	01	Initial issue of report	Aug. 12, 2024

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	2.1049	20dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.209	Radiated Emission	Pass	Under limit 10.69 dB at 36.79 MHz
3.3	15.207	AC Conducted Emission	Pass	Under limit 14.53 dB at 0.64 MHz
3.4	15.203	Antenna Requirements	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04, and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen, Guangdong, P.R. China.

1.2 Manufacturer

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04, and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen, Guangdong, P.R. China.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	OnePlus AIRVOOC 50W Magnetic Charger
Brand Name	OnePlus
Model Name	OAWV08
FCC ID	2ABZ2-OAWV08
WPT Frequency Range	111 ~148.5 KHz
WPT Frequency Range	111 ~148.5 KHz
WPT Type of Modulation	ASK
WPT Antenna Type	Coil Antenna
HW Version	V.6
SW Version	V0.21
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Test Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH05-SZ	CN1256	421272

1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH05-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.209, §15.207
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.


2 Test Configuration of Equipment Under Test

2.1 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 1000 MHz).
- b. AC power line Conducted Emission was tested under maximum output power.

Test Items	Function Type
AC Conducted Emission	Mode 1 : WPT wireless charging with WPT Client + USB Cable + Adapter
Radiated Emission	Mode 1 : WPT wireless charging with WPT Client + USB Cable + Adapter

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WPT Client (Mobile phone)	OPPO	CPH2655	N/A	N/A	N/A
2.	USB Cable	OPPO	N/A	N/A	N/A	Shield, 1.0m
3.	AC Adapter (100W)	OPPO	N/A	N/A	N/A	N/A

3 Test Result

3.1 20dB and 99% Occupied Bandwidth Measurement

3.1.1 Limit of 20dB and 99% Occupied Bandwidth

Reporting only, 99% OBW shall not located within 15.205 restricted bands.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The 20dB bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while wirelessly charging a charging board.
2. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
3. Measure and record the results in the test report.

3.1.4 Test Setup




3.1.5 Test Result of 20dB and 99% Bandwidth

Test Engineer :	Faye	Temperature :	22~24℃
		Relative Humidity :	49~58%
Occupied Bandwidth (kHz)			
20dB Bandwidth(KHz)	2.557	99% Bandwidth(KHz)	2.188


Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW



20 dB Bandwidth Plot



99% Occupied Bandwidth Plot



3.2 Radiated Emission Measurement

3.2.1 Limit of Radiated Emission

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Receiver Parameter	Setting
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For radiated emissions from 9kHz to 1GHz test distance is 3m

For 9kHz ~ 30MHz

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
3. specific line (dBμV/m) = $20 \log$ Emission level (μV/m)
4. Limit line = specific limits (dBμV/m) + distance extrapolation factor.

3.2.2 Measuring Instruments


See list of measuring equipment of this test report.

3.2.3 Measuring Instrument Setting

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.2.4 Test Setup of Radiated Emission


For radiated emissions below 30MHz



Note:

1. There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.
2. Tested for radiated below 30 MHz using a loop antenna in accordance with C63.10, the antenna was positioned in three antenna orientations: horizontal, vertical, and ground-parallel three polarization's, the worst case is horizontal & vertical polarization, test data of two mode was reported.

For radiated emissions above 30MHz






3.2.5 Test Result of Fundamental Emission


Frequency (MHz)	Level (dBuV/m) @3m	Distance Factor (dB)	Corrected level @30m (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Remark	Pol/Phase
0.134	75.78	80	-4.22	-29.25	25.03	55.8	19.94	0.04	AVG	Perpendicular
0.134	70.79	80	-9.21	-34.24	25.03	50.81	19.94	0.04	AVG	Parallel

Note: The field strength is tested at 3m distance then convert to 30m by adding distance factor $40 \cdot \log(d1/d2)$





Test Engineer :	TaoZhang	Temperature :	22~25°C
Polarization :	Vertical	Relative Humidity :	48~52%
Test Distance	3m		



Site : 03CH05-SZ
Condition : FCC_WPC 3m LOOP ANTENNA-316424 VERTICAL


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	0.134	70.79	-34.24	105.03	50.81	19.94	0.04	---	---	Average

Note:

- Level @3m (dBuV/m) = Read Level @3m (dBuV) + Antenna Factor(dB/m) + Cable Loss(dB).
- Corrected Level @30m (dBuV/m) = Level @3m (dBuV/m) - Distance extrapolation factor (dB).
- Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
- Over Limit(dB) = Level(dBuV/m) – Limit Line(dBuV/m).




3.2.6 Test Result of Radiated Emission (9kHz ~ 30MHz)





Test Engineer :	ZhanSheng Liu	Temperature :	22~25°C
Polarization :	Vertical	Relative Humidity :	48~52%
Test Distance	3m		



Site : 03CH05-SZ
Condition : FCC WPC 3m LOOP ANTENNA-316424 VERTICAL

Plane : Y with Accessory


	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Aux	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	0.010	-31.06	-78.69	47.63	29.09	19.80	0.05	-80.00	---	---	Average
2	0.061	-36.61	-68.53	31.92	23.65	19.70	0.04	-80.00	---	---	Average
3	0.090	-41.34	-69.81	28.47	18.83	19.80	0.03	-80.00	---	---	QP
4	0.125	-46.82	-72.47	25.65	13.24	19.90	0.04	-80.00	---	---	Average
5	0.539	7.22	-25.76	32.98	26.92	20.20	0.10	-40.00	---	---	QP
6	2.288	-4.17	-33.71	29.54	15.49	20.14	0.20	-40.00	---	---	QP
7	12.224	-5.83	-35.37	29.54	12.95	20.34	0.88	-40.00	---	---	QP
8	17.827	-5.55	-35.09	29.54	13.19	20.26	1.00	-40.00	---	---	QP
9	28.585	-4.79	-34.33	29.54	13.54	20.48	1.19	-40.00	---	---	QP

Note:

- Level(dBuV/m) = Read Level @3m (dBuV) + Antenna Factor(dB/m) + Cable Loss(dB) – Aux Factor (distance extrapolation factor).
- Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
- Over Limit(dB) = Level(dBuV/m) – Limit Line(dBuV/m);




3.2.7 Test Result of Radiated Emission (30MHz ~ 1000MHz)





Test Engineer :	ZhanSheng Liu	Temperature :	22~25°C
Polarization :	Vertical	Relative Humidity :	48~52%



Site : 03CH05-SZ
Condition : FCC_WPC 3m VULB9168--01003 VERTICAL

Plane : Y with Accessory

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 *	36.79	29.31	-10.69	40.00	44.00	18.94	1.31	34.94	---	---	Peak
2	60.07	28.33	-11.67	40.00	42.93	18.75	1.75	35.10	---	---	Peak
3	86.26	26.92	-13.08	40.00	45.94	14.12	1.96	35.10	---	---	Peak
4	173.56	23.67	-19.83	43.50	38.55	17.61	2.46	34.95	---	---	Peak
5	210.42	24.88	-18.62	43.50	40.52	16.46	2.80	34.90	---	---	Peak
6	924.34	31.67	-14.33	46.00	31.70	29.52	4.46	34.01	---	---	Peak

3.3 AC Conducted Emission Measurement

3.3.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.3.4 Test Setup



3.3.5 Test Result of AC Conducted Emission

Test Engineer :	Yuki Tang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : C001-S2
Condition: FCC 15C_QP AC LISN 100063_L LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.18	34.53	-20.11	54.64	14.10	10.29	10.14	Average
2	0.18	46.03	-18.61	64.64	25.60	10.29	10.14	QP
3	0.22	30.28	-22.51	52.79	9.80	10.33	10.15	Average
4	0.22	42.08	-20.71	62.79	21.60	10.33	10.15	QP
5	0.40	32.40	-15.37	47.77	11.80	10.44	10.16	Average
6	0.40	36.40	-21.37	57.77	15.80	10.44	10.16	QP
7	0.64	30.87	-15.13	46.00	10.70	10.01	10.16	Average
8 *	0.64	41.47	-14.53	56.00	21.30	10.01	10.16	QP
9	1.01	24.00	-22.00	46.00	3.60	10.24	10.16	Average
10	1.01	34.50	-21.50	56.00	14.10	10.24	10.16	QP
11	23.51	24.59	-25.41	50.00	3.70	10.19	10.70	Average
12	23.51	28.19	-31.81	60.00	7.30	10.19	10.70	QP



Test Engineer :	Yuki Tang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
Condition: FCC 15C_QP AC LISN 100063_N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.17	30.94	-23.92	54.86	10.31	10.49	10.14	Average
2	0.17	42.14	-22.72	64.86	21.51	10.49	10.14	QP
3	0.22	28.16	-24.50	52.66	7.80	10.21	10.15	Average
4	0.22	37.96	-24.70	62.66	17.60	10.21	10.15	QP
5	0.40	31.98	-15.83	47.81	11.89	9.93	10.16	Average
6	0.40	32.88	-24.93	57.81	12.79	9.93	10.16	QP
7 *	0.65	31.03	-14.97	46.00	10.60	10.27	10.16	Average
8	0.65	40.63	-15.37	56.00	20.20	10.27	10.16	QP
9	0.98	23.21	-22.79	46.00	2.80	10.25	10.16	Average
10	0.98	34.21	-21.79	56.00	13.80	10.25	10.16	QP
11	22.90	23.61	-26.39	50.00	2.80	10.13	10.68	Average
12	22.90	26.21	-33.79	60.00	5.40	10.13	10.68	QP

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



3.4 Antenna Requirements

3.4.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.4.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Jul. 27, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	102261	9kHz~7GHz	Apr. 09, 2024	Aug. 02, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 27, 2024	Aug. 02, 2024	Jul. 26, 2025	Radiation (03CH05-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Aug. 20, 2023	Aug. 02, 2024	Aug. 19, 2025	Radiation (03CH05-SZ)
Amplifier	EM Electronics	EM330	060756	0.01Hz~3000MHz	Apr. 09, 2024	Aug. 02, 2024	Apr. 08, 2025	Radiation (03CH05-SZ)
AC Power Source	APC	AFV-S-600	F119050013	N/A	Oct. 18, 2023	Aug. 02, 2024	Oct. 17, 2024	Radiation (03CH05-SZ)
Turn Table	EMEC	T-200-S-1	060925-T	0~360 degree	NCR	Aug. 02, 2024	NCR	Radiation (03CH05-SZ)
Antenna Mast	EMEC	MBS-400-1	060927	1 m~4 m	NCR	Aug. 02, 2024	NCR	Radiation (03CH05-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Apr. 09, 2024	Aug. 02, 2024	Apr. 08, 2025	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Aug. 21, 2023	Aug. 02, 2024	Aug. 20, 2024	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 16, 2023	Aug. 02, 2024	Oct. 15, 2024	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Apr. 09, 2024	Aug. 02, 2024	Apr. 08, 2025	Conduction (CO01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Occupied Channel Bandwidth	± 0.012 MHz

Uncertainty of AC Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.5dB
--	-------

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.5dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.2dB
--	-------

----- THE END -----