



FCC ID:2AXCX-NT630

RF EXPOSURE EVALUATION

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the *published RF exposure KDB procedures*, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding *SAR Test Exclusion Threshold* condition(s), listed below, is (are) satisfied.

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison



Here,

For 2.4G WIFI								
Mode	Frequency (MHz)	Output power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Min. Distance (mm)	Calc. thresholds	limit
802.11b	2412	6.119	6±1	7	5.01	5	1.5562	3.0
802.11g	2462	6.236	6±1	7	5.01	5	1.5722	3.0
802.11n20	2412	5.603	5±1	6	3.98	5	1.2362	3.0
802.11n40	2437	5.712	5±1	6	3.98	5	1.2426	3.0

For 5.2G WIFI								
Mode	Frequency (MHz)	Output power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Min. Distance (mm)	Calc. thresholds	limit
802.11 a	5200	6.378	6±1	7	5.01	5	2.2849	3.0
802.11 n20	5180	5.971	5±1	6	3.98	5	1.8117	3.0
802.11 n40	5190	5.796	5±1	6	3.98	5	1.8134	3.0
802.11 ac20	5200	6.091	6±1	7	5.01	5	2.2849	3.0
802.11 ac40	5190	5.310	5±1	6	3.98	5	1.8134	3.0
802.11 ac80	5210	5.341	5±1	6	3.98	5	1.8169	3.0

For 5.8G WIFI								
Mode	Frequency (MHz)	Output power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Min. Distance (mm)	Calc. thresholds	limit
802.11 a	5825	6.737	6±1	7	5.01	5	2.4183	3.0
802.11 n20	5825	6.615	6±1	7	5.01	5	2.4183	3.0
802.11 n40	5755	5.690	5±1	6	3.98	5	1.9096	3.0
802.11 ac20	5745	5.957	5±1	6	3.98	5	1.9079	3.0
802.11 ac40	5755	5.690	5±1	6	3.98	5	1.9096	3.0
802.11 ac80	5775	5.302	5±1	6	3.98	5	1.9129	3.0

Note: The device can not transmit with 2.4G WIFI and 5.2G WIFI and 5.8G WIFI simultaneously.

Conclusion:

1. $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] < 3.0$.
2. SAR Test Exclusion Thresholds is 3.0 for separation distance 5mm. Therefore, SAR test is not required.