



## Appendix B

### RF Test Data for BT (BLE) (Conducted Measurement)

Product Name: GPS Bike Computer

Trade Mark: N/A

Test Model: M3

#### Environmental Conditions

|                    |             |
|--------------------|-------------|
| Temperature:       | 24.6° C     |
| Relative Humidity: | 52.4%       |
| ATM Pressure:      | 100.0 kPa   |
| Test Engineer:     | Emiya lin   |
| Supervised by:     | Simba Haung |



## Contents

|                                              | Page |
|----------------------------------------------|------|
| <b>COVER PAGE</b>                            |      |
| 1 Duty Cycle .....                           | 3    |
| 1.1 Test Result .....                        | 3    |
| 1.2 Test Graphs .....                        | 4    |
| 2 Maximum Conducted Output Power .....       | 6    |
| 2.1 Test Result .....                        | 6    |
| 2.2 Test Graphs .....                        | 7    |
| 3 -6dB Bandwidth .....                       | 9    |
| 3.1 Test Result .....                        | 9    |
| 3.2 Test Graphs .....                        | 10   |
| 4 Maximum Power Spectral Density Level ..... | 12   |
| 4.1 Test Result .....                        | 12   |
| 4.2 Test Graphs .....                        | 13   |
| 5 Band Edge .....                            | 15   |
| 5.1 Test Result .....                        | 15   |
| 5.2 Test Graphs .....                        | 16   |
| 6 Conducted RF Spurious Emission .....       | 18   |
| 6.1 Test Result .....                        | 18   |
| 6.2 Test Graphs .....                        | 19   |
| 7 Restrict Band .....                        | 22   |
| 7.1 Test Result .....                        | 22   |
| 7.2 Test Graphs .....                        | 23   |





# 1 Duty Cycle

## 1.1 Test Result

| Mode   | Frequency (MHz) | Duty Cycle (%) | Correction Factor | 1/T (kHz) |
|--------|-----------------|----------------|-------------------|-----------|
| BLE 1M | 2402            | 64.79          | 1.88              | 2.56      |
| BLE 1M | 2440            | 64.79          | 1.88              | 2.5       |
| BLE 1M | 2480            | 64.82          | 1.88              | 2.5       |

## 1.2 Test Graphs









## 2 Maximum Conducted Output Power

### 2.1 Test Result

| Mode   | Frequency (MHz) | Conducted Power<br>(dBm) | Limit (dBm) | Verdict |
|--------|-----------------|--------------------------|-------------|---------|
| BLE 1M | 2402            | 0.79                     | 30          | Pass    |
| BLE 1M | 2440            | 0.47                     | 30          | Pass    |
| BLE 1M | 2480            | 0.25                     | 30          | Pass    |

## 2.2 Test Graphs









### 3 -6dB Bandwidth

#### 3.1 Test Result

| Mode   | Frequency (MHz) | -6 dB Bandwidth (MHz) | Limit -6 dB Bandwidth (MHz) | Verdict |
|--------|-----------------|-----------------------|-----------------------------|---------|
| BLE 1M | 2402            | 0.675                 | 0.5                         | Pass    |
| BLE 1M | 2440            | 0.711                 | 0.5                         | Pass    |
| BLE 1M | 2480            | 0.704                 | 0.5                         | Pass    |

## 3.2 Test Graphs







## 4 Maximum Power Spectral Density Level

### 4.1 Test Result

| Mode   | Frequency (MHz) | Conducted PSD<br>(dBm/3-100kHz) | Limit<br>(dBm/3kHz) | Verdict |
|--------|-----------------|---------------------------------|---------------------|---------|
| BLE 1M | 2402            | -14.86                          | $\leq 8$            | Pass    |
| BLE 1M | 2440            | -15.18                          | $\leq 8$            | Pass    |
| BLE 1M | 2480            | -15.37                          | $\leq 8$            | Pass    |

## 4.2 Test Graphs









## 5 Band Edge

### 5.1 Test Result

| Mode   | Frequency (MHz) | Max Value (dBc) | Limit (dBc) | Verdict |
|--------|-----------------|-----------------|-------------|---------|
| BLE 1M | 2402            | -56.23          | -20         | Pass    |
| BLE 1M | 2480            | -53.3           | -20         | Pass    |

## 5.2 Test Graphs









## 6 Conducted RF Spurious Emission


### 6.1 Test Result

| Mode   | Frequency (MHz) | Max Value (dBc) | Limit (dBc) | Verdict |
|--------|-----------------|-----------------|-------------|---------|
| BLE 1M | 2402            | -43.37          | -20         | Pass    |
| BLE 1M | 2440            | -43.56          | -20         | Pass    |
| BLE 1M | 2480            | -42.99          | -20         | Pass    |

## 6.2 Test Graphs











## 7 Restrict Band

### 7.1 Test Result

| Mode   | Frequency<br>(MHz) | Spur Freq<br>(MHz) | Power<br>(dBm) | Gain<br>(dBi) | Duty<br>Factor | E<br>(dBuV/m) | Detector | Limit<br>(dBuV/m) | Verdict |
|--------|--------------------|--------------------|----------------|---------------|----------------|---------------|----------|-------------------|---------|
| BLE 1M | 2402               | 2310               | -48.69         | 2             | -              | 48.57         | Peak     | 74                | Pass    |
| BLE 1M | 2402               | 2310               | -57.48         | 2             | 1.88           | 41.66         | Average  | 54                | Pass    |
| BLE 1M | 2402               | 2380.08            | -46.04         | 2             | -              | 51.22         | Peak     | 74                | Pass    |
| BLE 1M | 2402               | 2339.376           | -54.83         | 2             | 1.88           | 44.31         | Average  | 54                | Pass    |
| BLE 1M | 2402               | 2390               | -51.17         | 2             | -              | 46.09         | Peak     | 74                | Pass    |
| BLE 1M | 2402               | 2390               | -56.82         | 2             | 1.88           | 42.32         | Average  | 54                | Pass    |
| BLE 1M | 2480               | 2483.5             | -48.98         | 2             | -              | 48.28         | Peak     | 74                | Pass    |
| BLE 1M | 2480               | 2483.5             | -56.52         | 2             | 1.88           | 42.62         | Average  | 54                | Pass    |
| BLE 1M | 2480               | 2487.352           | -47.63         | 2             | -              | 49.63         | Peak     | 74                | Pass    |
| BLE 1M | 2480               | 2498.512           | -55.74         | 2             | 1.88           | 43.4          | Average  | 54                | Pass    |
| BLE 1M | 2480               | 2500               | -49.49         | 2             | -              | 47.77         | Peak     | 74                | Pass    |
| BLE 1M | 2480               | 2500               | -56.28         | 2             | 1.88           | 42.86         | Average  | 54                | Pass    |

## 7.2 Test Graphs





---The End---