

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: YZP-BK1100

Equipment Under Test : Telematics Modem
 Model Name : LTD-BK1100
 Applicant : LG Innotek Co., Ltd.
 Manufacturer : LG Innotek Co., Ltd.
 Date of Receipt : 2017.09.07
 Date of Test(s) : 2017.09.15 ~ 2017.09.27
 Date of Issue : 2017.09.27

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Jaeha Chung

Date:

2017.09.27

Technical
Manager:



Harim Lee

Date:

2017.09.27

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

INDEX

<u>Table of Contents</u>	Page
1. General information -----	3
2. RF Exposure Evaluation -----	5

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

1. General information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of applicant

Applicant : LG Innotek Co., Ltd.

Address : 55, Hanyangdaehak-ro, Sangnok-gu, Anyang-si, Gyeonggido, 15588, Korea

Contact Person : Eum, Ki-Hun

Phone No. : +82 10 2701 4217

1.3. Details of manufacturer

Company : Same as applicant

Address : 26, Hanamsandan 5beon-ro, Gwangsan-gu, Gwangju, 62229, Korea

1.4. Description of EUT

Kind of Product	Telematics Modem
Model Name	LTD-BK1100
Power Supply	DC 4.0 V
Frequency Range	WCDMA 2: 1 850 MHz ~ 1 910 MHz, WCDMA 5: 824 MHz ~ 849 MHz, LTE Band 2: 1 850 MHz ~ 1 910 MHz, LTE Band 4: 1 710 MHz ~ 1 755 MHz, LTE Band 5: 824 MHz ~ 849 MHz, LTE Band 7: 2 500 MHz ~ 2 570 MHz, LTE Band 12: 699 MHz ~ 716 MHz, LTE Band 17: 704 MHz ~ 716 MHz
Antenna Type	Dipole Antenna
Antenna Gain	699 MHz ~ 716 MHz: 4.5 dB i, 824 MHz ~ 849 MHz: 4.5 dB i, 1 850 MHz ~ 1 910 MHz: 2.0 dB i, 1 710 MHz ~ 1 755 MHz: 2.0 dB i, 2 500 MHz ~ 2 570 MHz: 2.0 dB i

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL011857	2017.09.27	Initial

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30 – 300	61.4	0.163	1.0	6
300 – 1 500	-	-	f/300	6
1 500 – 100 000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
<u>300 – 1 500</u>	-	-	<u>f/1500</u>	<u>30</u>
<u>1 500 – 100 000</u>	-	-	<u>1.0</u>	<u>30</u>

2.1.1. Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Power Index table		
1. Maximum output Power (Target Power, Tolerance)		
	Target Power	Tolerance
LTE B2, B4, B5, B7, B12(17)	23	±2.7
WCDMA B2, B5	24	+1.7/-3.7

Copyright©, 2017, All Rights Reserved.

 LG Innotek

WCDMA Band 2

- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
9262	1 852.4	25.7	2.0	0.117 147	1

WCDMA Band 5

- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
4132	826.4	25.7	4.5	0.208 320	0.550 933

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

LTE Band 2
- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
18607	1 850.7	25.7	2.0	0.117 147	1

LTE Band 4
- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
19957	1 710.7	25.7	2.0	0.117 147	1

LTE Band 5
- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
20407	824.7	25.7	4.5	0.208 320	0.549 800

LTE Band 7
- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
20775	2 502.5	25.7	2.0	0.117 147	1

LTE Band 12
- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
23017	699.7	25.7	4.5	0.208 320	0.466 467

LTE Band 17
- Maximum tune up tolerance

Channel	Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
23755	706.5	25.7	4.5	0.208 320	0.471 000

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

Note :

- The power density Pd (5th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

- End of the Test Report -

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)