

# OTA TEST REPORT

Applicant      Shenzhen General Test System Co., Ltd  
Product          RayZone1800  
Issue Date      September 27, 2024

Shenzhen Fu Bang Wireless Technology Co., Ltd. tested the above equipment in accordance with the requirements in **ANTI/IEEE Std 149-2008**. The test results show that the equipment tested is capable of demonstrating compliance with the Requirements as documented in this report.

Prepared by:    Lunkang Yan

Approved by:    Hualong Zhang

**Shenzhen Fu Bang Wireless Technology Co., Ltd.**

*Room 302, lianjian Industry Part, Huarong road, Longhua District, Shenzhen, P.R. China*

# 1. Test Laboratory

## 1.1 Notes of the Test report

This report shall not be reproduced in full or partial. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of applicable standards stated above.

## 1.2 Test facility

*GTS1800* Microwave Anechoic Chamber : testing frequency ranges from 600MHz to 6GHz .

## 1.3 Testing Location

Company: Shenzhen Fu Bang Wireless Technology Co., Ltd

Address: Room 302, Lianjian Industry Part, Huarong road, Longhua District,  
Shenzhen, P.R. China

Contact: Iunkang Yan

Telephone: 13760182610

E-mail: 646363118@qq.com

## 1.4 Laboratory Environment

Temperature	Min.= 19℃, Max.=25℃	
Relative humidity	Min.=40%, Max.=72%	
Shield effect	0.6-7GHz	>100dB
Ground resistance	<0.5 Ω	

## 2. General Description of Equipment under Test

### 2.1 Applicant and Manufacturer information

<b>Applicant Name</b>	Shenzhen General Test System Co., Ltd
<b>Applicant address</b>	Building C-A7 Suite 805,2190 Liuxian Avenue, Nanshan District, Shenzhen, P.R. China
<b>Manufacturer Name</b>	Shenzhen General Test System Co., Ltd
<b>Manufacturer address</b>	Building C-A7 Suite 805,2190 Liuxian Avenue, Nanshan District, Shenzhen, P.R. China

### 2.2 General information

EUT Description	
Product Name	RayZone1800
Model	GTS-ANT D-H
HW Version	RayZone1800 V1.0
SW Version	MaxSign 100
Antenna Type	Antenna
Antenna Manufacturer	Shenzhen General Test System Co., Ltd
Test Frequency	600MHz-6GHz

### 2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test Method: **ANSI/IEEE Std 149-2008**

## 3. Test Conditions

### 3.1 Test Configuration

The method is used to measure the antenna 3D GAIN of EUT in OTA qualified anechoic chamber. Equipment Under Test (EUT) geometry centre vertical projection at the centre of platform, the distance from EUT to measurement antenna is 1m.

### 3.2 Test Measurement

**Spherical coordinate system**





Figure 1 Test coordinate system

Note: Theta is from 0-180degree. Phi is from EUT and record the Date, the step of rotation is 15 degree.

### Test Setup

#### RayZone1800 Test Setup



## 4. Test Results

### 4.1 Gain and Efficiency

Shenzhen Fu Bang Wireless Technology Co., Ltd.


This report shall not be reproduced except in full, without the written approval of Shenzhen Fu Bang Wireless Technology Co., Ltd.

Model	Test State	Frequency (MHz)	Efficiency (%)	Gain (dBi)	Test State	Frequency (MHz)	Efficiency (%)	Gain (dBi)
	ANT1	2400	22.5	0.8	ANT2	2400	20.5	0.5
		2410	23.8	0.9		2410	20.8	0.7
		2420	23.2	1.1		2420	21.2	0.8
		2430	24.2	1.2		2430	22.2	0.9
		2440	24.7	1.3		2440	23.0	1.0
		2450	25.6	1.4		2450	23.6	1.1
		2460	25.9	1.5		2460	23.9	1.1
		2470	26.7	1.5		2470	22.7	1.0
		2480	24.1	1.1		2480	22.1	0.9
		2490	23.9	0.9		2490	21.3	0.7
		2500	21.9	0.7		2500	20.3	0.6


## 5. Equipment List

Type of Equipment	Manufacture	Model Number
Network Analyzer	Key sight	E5071C
Switch control System	GTS	RayZone1800
Software	GTS	MaxSign 100 Patten Measurement software

## ANNEX A 3-D Patten Plots




2400MHz



2500MHz

## ANNEX B: The EUT Appearance and Test Configuration

### B.1 EUT Appearance



### B.2 Test Configuration

