

FCC Test Report

Report No.: AGC07434230105FE10

FCC ID	:	2ARXB-B21B
PRODUCT DESIGNATION	:	Label Printer
BRAND NAME	:	NIIMBOT
MODEL NAME	:	NIIMBOT B21S, NIIMBOT B21, B21, B21S
APPLICANT	:	Wuhan Jingchen Intelligent Identification Technology Co., Ltd.
DATE OF ISSUE	:	Mar. 06, 2023
STANDARD(S)	:	FCC Part 15 Subpart C §15.225
REPORT VERSION	:	V 1.0







REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar. 06, 2023	Valid	Initial Release



TABLE OF CONTENTS

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	6
2.3 RELATED SUBMITTAL(S) / GRANT (S)	7
2.4 TEST METHODOLOGY	7
2.5 SPECIAL ACCESSORIES	7
2.6 EQUIPMENT MODIFICATIONS	7
2.7 ANTENNA REQUIREMENT	7
3. TEST ENVIRONMENT	8
3.1 ADDRESS OF THE TEST LABORATORY	8
3.2 TEST FACILITY	8
3.3 ENVIRONMENTAL CONDITIONS	9
3.4 MEASUREMENT UNCERTAINTY	9
3.5 LIST OF EQUIPMENTS USED	10
4.SYSTEM TEST CONFIGURATION	11
4.1 EUT CONFIGURATION	
4.2 EUT EXERCISE	
4.3 CONFIGURATION OF TESTED SYSTEM	
4.4 EQUIPMENT USED IN TESTED SYSTEM	
4.5 SUMMARY OF TEST RESULTS	
5. DESCRIPTION OF TEST MODES	
6. FIELD STRENGTH OF FUNDAMENTAL	
6.1 PROVISIONS APPLICABLE	14
6.2 MEASUREMENT PROCEDURE	14
6.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	16
6.4 MEASUREMENT RESULTS	
7. RADIATED EMISSION	
7.1 LIMITS OF RADIATED EMISSION TEST	
7.2 MEASUREMENT PROCEDURE	
7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
7.4 MEASUREMENT RESULT	
8. 20 dB BANDWIDTH	
8.1 PROVISIONS APPLICABLE	24

^{8.2} MEASUREMENT PROCEDURE 24 Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection" Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



8.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	24
8.4 MEASUREMENT RESULTS	25
9. FREQUENCY STABILITY	27
9.1 PROVISIONS APPLICABLE	27
9.2 MEASUREMENT PROCEDURE	27
9.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
9.4 MEASUREMENT RESULTS	
10. AC POWER LINE CONDUCTED EMISSION TEST	29
10.1 LIMITS OF LINE CONDUCTED EMISSION TEST	29
10.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	29
10.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	30
10.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	30
10.5 MEASUREMENT RESULTS	
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	33
APPENDIX B: PHOTOGRAPHS OF TEST EUT	33



1. GENERAL INFORMATION

Applicant	Wuhan Jingchen Intelligent Identification Technology Co., Ltd.		
Address	Creative Workshop No. 5, Creative World, Yezhihu West Road, Hongshan District, Wuhan, China		
Manufacturer	Wuhan Jingchen Intelligent Identification Technology Co., Ltd.		
Address	Creative Workshop No. 5, Creative World, Yezhihu West Road, Hongshan District, Wuhan, China		
Factory	Huangpi branch of Wuhan Jingchen Intelligent Identification Technology Co., Ltd.		
Address	4th Floor, Block 6, Hui Qiang Technology Park, No. 1 Tianyang Road, Chuanlong Av, Hengdian street, Huangpi District, Wuhan, China		
Product Designation	Label Printer		
Brand Name	NIIMBOT		
Test Model	NIIMBOT B21S		
Series Model	NIIMBOT B21, B21, B21S		
Declaration Difference	All the same except for the model name		
Date of receipt of test item	Jan. 14, 2023		
Date of test	Jan. 14, 2023 to Mar. 03, 2023		
Deviation from Standard	No any deviation from the test method		
Test Result	Pass		
Test Report Form No	AGCTR-ER-FCC-NFCV1.0		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Part 15.225.

Prepared By

Bibo sho

Bibo Zhang (Project Engineer)

Mar. 06, 2023

Reviewed By

Calvin Liu (Reviewer)

Mar. 06, 2023

Approved By

Zhan

Max Zhang (Authorized Officer)

Mar. 06, 2023



2. PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	V40.01	
Software Version	V40.06	
Operation Frequency	13.56MHz	
Modulation Type	ASK/FSK	
Number of channels	1	
Field Strength of Fundamental	46.33dBuV/m	
Antenna Designation	Coil Antenna	
Antenna Gain	0dBi	
Power Supply	DC 7.4V by battery or DC 5V by adapter	
Note: The EUT has two batteries. One battery is JL-B201-1500mAh, and the other battery is PF106-11. All		

Note: The EUT has two batteries. One battery is JL-B201-1500mAh, and the other battery is PF106-11. All the parameters of the two batteries are the same except for the manufacturers. Two batteries have been evaluated, only the test data of battery (JL-B201-1500mAh) has been recorded in this report.

2.2 TEST FREQUENCY LIST

Frequency Band	Channel Number	Frequency
13.110~14.010 MHz	01	13.56 MHz



2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ARXB-B21B** filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title	
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations	
2	FCC 47 CFR Part 15	Radio Frequency Devices	
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices	

2.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7 ANTENNA REQUIREMENT

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antennathat uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a brokenantenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0dBi.



3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS		
Temperature range (°C)	15 - 35	-20 - 50 ℃		
Relative humidty range	20 % - 75 %	20 % - 75 %		
Pressure range (kPa)	86 - 106	86 - 106		
Power supply DC 3.7V LV:DC 3.33V HV:4.07V				
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.				

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 150kHz	$U_c = \pm 4.2 \text{ dB}$
Uncertainty of Radiated Emission below 30MHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_{c} = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
Artificial power network	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test Software	FARA	EZ-EMC	Ver.AGC-CON0 3A1	N/A	N/A
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Agilent	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn Antenna	SCHWARZBEC	BBHA9170	768	Oct. 31, 2021	Oct. 30, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Double-Ridged Waveguide Horn	ETS	3117	00154520	Sep. 06, 2021	Sep. 05, 2023
Preamplifier Assembly	ETS	3117PA	00225134	Sep. 01, 2022	Sep. 02, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	D69250	Apr. 28, 2021	Apr. 27, 2023
Test Software	FARA	EZ-EMC	Ver.RA-03A	N/A	N/A



4.SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:



Conducted Emission Configure:

EUT	AE

4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement: Test Accessories Come From The Laboratory

ltem	Equipment	Model No.	Identifier	Note
1	Adapter	HW-050200C01	DC 5V	AE

I Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	Label Printer	NIIMBOT B21S	2ARXB-B21B	EUT
2	Charger line	N/A	0.75m unshielded	Accessories



4.5 SUMMARY OF TEST RESULTS

Item	FCC Rules	Description Of Test	Result
1	§15.203	Antenna Equipment	Pass
2	15.225(a)(b)(c)	Field Strength of Fundamental	Pass
3	§15.209	Radiated Emission	Pass
4	§15.215(c)	20dB Bandwidth	Pass
5	§15.205(a)	Restricted Bands of Operation	Pass
6	§15.225(e)	Frequency Stability	Pass
7	§15.207	AC Power Line Conducted Emission	Pass



5. DESCRIPTION OF TEST MODES

	Summary table of Test Cases
Test Itom	Sepcification / Modulation
Test Item	NFC/ ASK/FSK
Radiated&Conducted Test Cases	Mode 1: NFC_ASK_Tx_13.56 MHz Mode 2: NFC_FSK_Tx_13.56 MHz
AC Conducted Emission	Mode 1: NFC Normal Operation + adapter power supply Tx_13.56 MHz
Note:	
1. Only the result of the wors	st case was recorded in the report, if no other cases.

The battery is full-charged during the test.

2. 3. 4. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

For Conducted Test method, a temporary antenna connector is provided by the manufacture.



6. FIELD STRENGTH OF FUNDAMENTAL

6.1 PROVISIONS APPLICABLE

Rules and specifications		FCC CFR 47 Part	15 section 15.225	
Description	Compliance v	vith the spectrum ma	sk is tested with RBV	V set to 9kHz.
Freq. of Emission (MHz)	Field Strength (µV/m) at 30m	Field Strength (dBµV/m) at 30m	Field Strength (dBµV/m) at 10m	Field Strength (dBµV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

6.2 MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the



pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
Start ~Stop Trequency	1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




6.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)

RADIATED EMISSION TEST SETUP 9KHz-30MHz




RADIATED EMISSION TEST SETUP 30MHz-1000MHz






6.4 MEASUREMENT RESULTS



RESULT: PASS





EUT		Label	Printer		Model Na	me	NIIMBO	OT B21S
Temperature	i.	22°C			Relative H	lumidity	52%	
Pressure		985hP	'a		Test Volta	ge	Normal	l Voltage
Test Mode		Mode	1		Antenna		Side	
132.0 d	BuV/m						Limit	
4/44	\$	ىمىرىنىڭ ^{مىر} ىيەتكەر ئىرىمى ئۇرىلۇ ^{ىلى}		martin runneliner	whether warm	m.m. mar	Alexandreensteensteensteensteensteensteensteens	6 Sharena an
12.0 12.560		að Staffarði þörði stærðar	n and the second s	. But a . Mar. and all and a set	whenthe	day and the second	after an and a star	6 0
12.560	Mk.	Freq.	Reading Level	(MHz) Correct Factor	Measure- ment	Limit	Over	6 14.560
12.560		Freq. MHz		(MHz)	Measure-	Limit	Over	6 14.560 Detector
12.560	Mk.		Level	(MH2) Correct Factor	Measure- ment	_		
12.560 No.	Mk.	MHz	Level dBuV	(MHz) Correct Factor dB	Measure- ment dBuV/m	dB/m	dB	Detector
12.560 No.	Mk. 1. 1	MHz 2.6820	Level dBuV -0.97	(MHz) Correct Factor dB 24.58	Measure- ment dBuV/m 23.61	dB/m 69.50	dB -45.89	Detector peak
12.560 No.	Mk. 1: 1: 1:	MHz 2.6820 3.1041	Level dBuV -0.97 0.00	(MHz) Correct Factor dB 24.58 24.61	Measure- ment dBuV/m 23.61 24.61	dB/m 69.50 69.50	dB -45.89 -44.89	Detector peak peak
12.560 No. 1 2 3	Mk. 1: 1: 1: 1:	MHz 2.6820 3.1041 3.3520	Level dBuV -0.97 0.00 0.27	(MHz) Correct Factor dB 24.58 24.61 24.62	Measure- ment dBuV/m 23.61 24.61 24.89	dB/m 69.50 69.50 80.50	dB -45.89 -44.89 -55.61	Detector peak peak peak

RESULT: PASS



7. RADIATED EMISSION

7.1 LIMITS OF RADIATED EMISSION TEST

According to 15.35, on any frequency or frequencies below or equal to 1000 MHz, the limits Shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test.

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed

the general radiated emissions limits.

15.209 LIMIT IN THE DEIOW L			
Frequency	Distance	Field Streng	jths Limit
(MHz)	Meters	μ V/m	dB(µV)/m
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV) 54.0 dB(μV)/n	. ,

15.209 Limit in the below table has to be followed:

Remark: (1) Emission level dB μ V = 20 log Emission level μ V/m.


(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

7.2 MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.





- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
Start ~Stop T lequency	1MHz/3MHz for Peak, 1MHz/3MHz for Average


The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)

RADIATED EMISSION TEST SETUP 9KHz-30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz





7.4 MEASUREMENT RESULT


RADIATED EMISSION BELOW 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

EUT				Labe	l Print	er		Model N	ame	NIIMB	OT B21S
Temper	rature)		22°C				Relative	Humidity	52%	
Pressu	re			985h	Pa			Test Volt	age	Norma	al Voltage
Test Mo	ode			Mode	э 1			Antenna		Horizo	ntal
7	'2.0 dB	3uV/m								Limit:	
:	32						1	2×1		Margi	
-8		ntred Alter	onternation	elination of	Nonan Indi		And have been marked	un vola balde and e			
-8		40	50		70 80	and be and the second second	(MHz)	30		500 600 71	00 1000.00
-8	30.000		50		70 80 Rea	ading				500 600 70 Over	00 1000.00
-8	30.000	40	50 Fr	60	70 80 Rea		(MHz) Correct	Measure	-		00 1000.00
-8 	30.000	40 Mk.	50 Fr	eq.	70 80 Rea Le	evel	(MHz) Correct Factor	Measurement	- Limit	Over	Detector
-8 	^{30.000} No.	40 Mk.	50 Fr	60 eq. Hz 329	70 80 Rea Le	evel BuV	(MH2) Correct Factor dB	Measure- ment dBuV/m	- Limit dB/m	Over dB	Detector peak
-8 	30.000 No.	40 Mk. 1	50 Fr MI 24.13	60 eq. Hz 329 904	70 80 Rea Le	evel BuV 6.30	(MHz) Correct Factor dB 20.93	Measurement dBuV/m 27.23	Limit dB/m 43.50	Over dB -16.27	Detector peak peak
-8 	30.000 No.	40 Mk. 1 2	50 Fr MI 24.13 27.69	60 eq. Hz 329 904 235	70 80 Rei d	evel BuV 6.30 2.74	(MHz) Correct Factor dB 20.93 15.78	Measurement dBuV/m 27.23 28.52	Limit dB/m 43.50 46.00	Over dB -16.27 -17.48	Detector peak peak peak
-8 	30.000 No. 1 2 3	40 Mk. 1 2 2 * 3	50 Fr 24.13 27.69 76.12	eq. Hz 329 904 235 045	70 80 Rei d d 12 15	evel BuV 6.30 2.74 5.65	(мнг) Correct Factor dB 20.93 15.78 15.88	Measurement dBuV/m 27.23 28.52 31.53	Limit dB/m 43.50 46.00 46.00	Over dB -16.27 -17.48 -14.47	Detector peak peak peak

RADIATED EMISSION FROM 30MHz ~1000MHz

RESULT: PASS





EUT	Label Printer	Model Na	me	NIIMBOT	B21S
Temperature	22°C	Relative H	lumidity	52%	
Pressure	985hPa	Test Volta	ge	Normal V	/oltage
Test Mode	Mode 1	Antenna		Vertical	
72.0 dBuV/m	2 2 3	× 5	S.	Limit: Margin:	
without the the second	Lawrence and the second and the second se	sthurten have been all the second states			
-8	60 Z0 80	server and a server and a server and a server a		0 500 700	1000 000
	60 70 80 Reading C	(MHz) 300 Correct Measure-	400 50		1000.000
-8	Reading C	(MHz) 300		0 600 700 Over	1000.000
-8 30.000 40 50 No. Mk. F	Reading C	(MHz) 300 Correct Measure-	400 50	Over	1000.000 Detector
-8 30.000 40 50 No. Mk. F	Reading C req. Level	(MHz) 300 Correct Measure- Factor ment	400 50 Limit	Over	
-8 30.000 40 50 No. Mk. F	Reading C Ireq. Level MHz dBuV 1779 17.07	(MHz) 300 Correct Measure- Factor ment dB dBuV/m	400 50 Limit dB/m	Over dB	Detector
-8 30.000 40 50 No. Mk. F	Reading C Ireq. Level C MHz dBuV C 1779 17.07 C 3431 17.54 C	(MHz) 300 Correct Measure- Factor ment dB dBuV/m 16.96 34.03	400 500 Limit dB/m 40.00 40.00	Over dB -5.97	Detector peak
-8 30.000 40 50 No. Mk. F 1 ! 46.1 2 ! 65.3	Reading C Ireq. Level I MHz dBuV I 1779 17.07 I 3431 17.54 I 9033 15.01 I	(MHz) 300 Correct Measure- Factor ment dB dBuV/m 16.96 34.03 16.78 34.32	400 500 Limit dB/m 40.00 40.00	Over dB -5.97 -5.68	Detector peak peak
-8 30.000 40 50 No. Mk. F M 1 ! 46.1 2 ! 65.3 3 104.9	Reading C Ireq. Level I MHz dBuV I 1779 17.07 I 3431 17.54 I 9033 15.01 I 5750 21.22 I	(MHz) 300 Correct Measure- Factor ment dB dBuV/m 16.96 34.03 16.78 34.32 14.81 29.82	400 500 Limit dB/m 40.00 40.00 43.50	Over dB -5.97 -5.68 -13.68	Detector peak peak peak

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.



8. 20 dB BANDWIDTH

8.1 PROVISIONS APPLICABLE


Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

8.2 MEASUREMENT PROCEDURE

Set the parameters of SPA as below:

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. Centre frequency = Operation Frequency
- 3. The resolution bandwidth of 10 kHz and the video bandwidth of 30 kHz were used.
- 4. Span: 100kHz, Sweep time: Auto
- 5. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 6. Measured the spectrum width with power higher than 20dB below carrier.
- 7. Measured the 99% OBW.
- 8. Record the plots and Reported.

8.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)




Spectrum Analyzer



8.4 MEASUREMENT RESULTS

	Tes	at Data of Occupied Bandwi	dth and -20dB Bandwid	lth	
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (kHz)	-20dB Bandwidth (kHz)	Limits (MHz)	Pass or Fail
NFC_ASK	13.56	26.812	27.38	N/A	Pass
NFC_FSK	13.56	25.918	27.24	N/A	Pass

Test Graphs of Occupied Bandwidth&-20dB Bandwidth_ASK







Test Graphs of Occupied Bandwidth&-20dB Bandwidth_FSK



9. FREQUENCY STABILITY


9.1 PROVISIONS APPLICABLE

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

9.2 MEASUREMENT PROCEDURE

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ±100ppm.
- 6. Extreme temperature rule is -20°C~50°C.

9.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





9.4 MEASUREMENT RESULTS

Operating frequency: 13.56MHz

Voltage vs. Frequency Stability (Test Temperature: 20°C)

Voltage(V)	Measurement Frequency (MHz)	Max. Deviation (ppm)	Limit(ppm)	Conclusion
7.4	13.56101			
6.66	13.56089	+74	±100	PASS
8.14	13.56075			

Temperature vs. Frequency Stability (Test Voltage: 7.4V)

Temperature	Measurement Frequency (MHz)	Max. Deviation (ppm)	Limit(ppm)	Conclusion
-20 ℃	13.56076			
-10 ℃	13.56060			
0 °C	13.56058			
10 ℃	13.56061	+68	±100	PASS
20 °C	13.56092	+00	±100	FA33
30 ℃	13.56073			
40 ℃	13.56039			
50 ℃	13.56052			

10. AC POWER LINE CONDUCTED EMISSION TEST


10.1 LIMITS OF LINE CONDUCTED EMISSION TEST

Framerau	Maximum RF	Line Voltage
Frequency	Q.P. (dBµV)	Average (dBµV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

10.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





10.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

10.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



10.5 MEASUREMENT RESULTS



MEASUREMENT RESULT: "agc_fin"


2023/1/17 14	:46						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
			-				
0.158000	44.40	6.8	66	21.2	QP	L1	GND
0.498000	35.60	5.4	56	20.4	QP	L1	GND
0.522000	36.10	5.4	56	19.9	0P	L1	GND
0.978000	28.40	5.4	56	27.6	ÕP	L1	GND
1.182000	30.10	5.7	56	25.9	ÕP	L1	GND
1.382000	29,90	5.9	56	26.1	0P	L1	GND
21002000					×-		GILD

MEASUREMENT RESULT: "agc fin2"

2023/1/17 14:	46						
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.506000	33.50	5.4	46	12.5	AV	L1	GND
0.594000	26.00	5.4	46	20.0	AV	L1	GND
1.190000	24.80	5.7	46	21.2	AV	L1	GND
1.214000	25.80	5.7	46	20.2	AV	L1	GND
1.234000	25.00	5.7	46	21.0	AV	L1	GND
1.258000	24.90	5.8	46	21.1	AV	L1	GND

RESULT: PASS





MEASUREMENT RESULT: "agc_fin"

2023/1/17 14: Frequency MHz	49 Level dBμV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.502000 1.002000 1.178000 1.210000 1.358000 1.406000	38.60 30.70 31.70 28.70 31.50 31.80	5.4 5.4 5.7 5.9 5.9	56 56 56 56 56	17.4 25.3 24.3 27.3 24.5 24.2	QP QP QP QP QP QP	N N N N N	GND GND GND GND GND GND

MEASUREMENT RESULT: "agc_fin2"

2023/1/17 14:	49						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
0.158000	32.00	6.8	56	23.6	AV	N	GND
0.506000	31.90	5.4	46	14.1	AV	N	GND
0.574000	23.10	5.4	46	22.9	AV	N	GND
0.598000	23.70	5.4	46	22.3	AV	N	GND
0.774000	22.00	5.4	46	24.0	AV	N	GND
1.214000	21.50	5.7	46	24.5	AV	N	GND

RESULT: PASS



Report No.: AGC07434230105FE10 Page 33 of 33

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC07434230105AP02

APPENDIX B: PHOTOGRAPHS OF TEST EUT

Refer to the Report No.: AGC07434230105AP03

-----END OF REPORT-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.