



FCC PART 15.247 TEST REPORT

For

Chengdu XGimi Technology Co., Ltd.

5F, Building A7, Tianfu Software Park, Tianfu Avenue, Hi-tech Zone, Chengdu, China

FCC ID: 2AFENXG08X

Report Type: Original Report	Product Name: LED Projector
Report Number: RSC170821002C	
Report Date: 2018-01-08	
Sula Huang	
Reviewed By:	Engineering Director
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No. 1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: +86-28-65525123 Fax: +86-28-65525125 www.baclcorp.com

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu).

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
MECHANICAL DESCRIPTION OF EUT	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
MEASUREMENT UNCERTAINTY	5
TEST METHODOLOGY	5
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE.....	8
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	12
EXTERNAL I/O CABLE	12
BLOCK DIAGRAM OF TEST SETUP	13
TEST EQUIPMENTS LIST.....	14
SUMMARY OF TEST RESULTS	15
FCC §15.247 & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	16
APPLICABLE STANDARD.....	16
FCC §15.203 - ANTENNA REQUIREMENT	18
APPLICABLE STANDARD.....	18
ANTENNA CONNECTOR CONSTRUCTION	18
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS.....	19
APPLICABLE STANDARD.....	19
EUT SETUP.....	19
EMI TEST RECEIVER SETUP	19
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST DATA	20
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	25
APPLICABLE STANDARD.....	25
EUT SETUP.....	25
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	26
TEST PROCEDURE	26
CORRECTED AMPLITUDE & MARGIN CALCULATION	26
TEST DATA	27
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	38
APPLICABLE STANDARD.....	38
TEST PROCEDURE	38
TEST DATA	39
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	54
APPLICABLE STANDARD.....	54
TEST PROCEDURE	54
TEST DATA	54
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	57
APPLICABLE STANDARD.....	57
TEST PROCEDURE	57
TEST DATA	57

FCC §15.247(e) - POWER SPECTRAL DENSITY	67
APPLICABLE STANDARD.....	67
TEST PROCEDURE	67
TEST DATA	67

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **Chengdu XGimi Technology Co., Ltd.**, model number: **XG08X (FCC ID: 2AFENXG08X)** or the "EUT" as referred to in this report was one **LED Projector**.

Mechanical Description of EUT

The EUT was measured approximately: 345 mm (L) x 338 mm (W) x 57 mm (H).
Rated input voltage: DC 19V from adapter.

AC Adapter information:

Manufacturer: SHENZHEN HUNTKEY ELECTRIC CO., LTD.

Model: HDZ1201-3C

Input: 100-240V AC, 50/60Hz

Current: 2.0A Max

Output: +19V DC, 6.32A

Note: The products, test model: XG08X, multiple models: XG07X, XG09X, XG10X, XG11X. Their differences were presented in Product Difference Statement provided by the applicant of this report. So we selected model XG08X to fully test.

**All measurement and test data in this report was gathered from final production sample, serial number: 170821002/01 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-08-14, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **Chengdu XGimi Technology Co., Ltd.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS submissions with FCC ID: 2AFENXG08X

FCC Part 15.407 NII submissions with FCC ID: 2AFENXG08X

FCC Part 15.249 DXX submissions with FCC ID: 2AFENB914C

Measurement Uncertainty

Item			Uncertainty
AC power line conducted emission			2.71 dB
Radiated Emission(Field Strength)	30MHz-200MHz	H	4.57 dB
		V	4.81 dB
	200MHz-1GHz	H	5.69 dB
		V	6.07 dB
	1GHz-6GHz		5.49 dB
	6GHz-18GHz		5.57 dB
	18GHz-40GHz		5.48 dB
Conducted RF Power			±0.61dB
Power Spectrum Density			±0.61dB
Occupied Bandwidth			±5%
Conducted Emission			±1.5dB
Humidity			±5%
Temperature			±1°C

Test Methodology

All measurements contained in this report were conducted with:

1. ANSI C63.10-2013 American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
2. KDB558074 D01 DTS Meas Guidance v04.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Chengdu) to collect test data is located No.5040, Huilongwan Plaza, No. 1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 910975, the FCC Designation No. : CN1186.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062C-1.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured in testing mode, which was provided by manufacturer.

For Wi-Fi mode, 802.11b, 802.11g, and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	-	-

For 802.11b, 802.11g, and 802.11n HT20 modes were tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	-	-

802.11n HT40 was tested with Channel 3, 6 and 9.

802.11b/g supports SISO, 802.11n supports SISO and MIMO mode. For Radiated Emission, according to pretest, the worst case for 802.11b/g is Antenna 1, the worst case for 802.11n is MIMO mode. So 802.11b/g Antenna 1 & 802.11n MIMO mode test data were recorded in the report.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software


The worst condition (maximum power with maximum duty cycle) was setting by the software as following table:

Test Mode	Test Software Version	DRTU		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	CCK 1M	CCK 1M	CCK 1M
	Power Level Setting Antenna 1	14	14	14
	Power Level Setting Antenna 2	14	14	14
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	OFDM 6M	OFDM 6M	OFDM 6M
	Power Level Setting Antenna 1	14	14	14
	Power Level Setting Antenna 2	14	14	14
802.11n-HT20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	HT0	HT0	HT0
	Power Level Setting Antenna 1	14	14	14
	Power Level Setting Antenna 2	14	14	14
802.11n-HT40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	HT0	HT0	HT0
	Power Level Setting Antenna 1	12	12	12
	Power Level Setting Antenna 2	12	12	12
BLE	Test Frequency	2402MHz	2440MHz	2480MHz
	Data Rate	Default	Default	Default
	Power Level Setting	Default	Default	Default


Duty Cycle information is below:

Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	100	100	100
802.11n-HT20	100	100	100
802.11n-HT40	100	100	100
BLE	100	100	100


802.11b




802.11g




802.11n-HT20



802.11n-HT40



Bluetooth LE mode



Local Support Equipment List and Details

Manufacturer	Description	Model Number	Serial Number
SONY	Laptop	SVF143A1QT	None
Logitech	Mouse	M-U0004	810-001808
TOSHIBA	Mobile HDD	V637020-A	1297FHOYSRE8
LAPOP	Keyboard	JT-505	JT5056UBD200312
HUAWEI	Earphone	P9	None
DL	Switch	DL-S1005PM	None

External I/O Cable

Cable Description	Length (m)	From / Port	To
Unshielded Power Cable	1.2	AC Adapter	EUT
Unshielded USB Cable	1.8	EUT/USB Port	Keyboard
Unshielded USB Cable	1.8	EUT/USB Port	Mouse
Unshielded USB Cable	0.3	EUT/USB Port	Mobile HDD
Shielded HDMI Cable	1.2	EUT / HDMI Port	Laptop
Unshielded RJ45 Cable	5.0	EUT / LAN Port	Switch
Unshielded Earphone Cable	1.0	EUT	Earphone

Test Equipments List

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	100018	2017-05-20	2018-05-19
Rohde & Schwarz	RF Limiter	ESH3Z2	DE14781	2017-11-10	2018-11-09
N/A	Conducted Cable	NO.5	N/A	2017-11-10	2018-11-09
Rohde & Schwarz	EMC32	N/A	V 8.52.0	N/A	N/A
Radiated Emissions Test					
Sonoma	Pre-Amplifier	310N	186684	2017-08-18	2018-08-17
Rohde & Schwarz	EMI Test Receiver	ESIB 40	100215	2017-09-12	2018-09-11
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2017-05-20	2018-05-19
Sunol Sciences	Broadband Antenna	JB3	A121808	2017-05-18	2020-05-17
ETS	Horn Antenna	3115	003-6076	2017-05-19	2020-05-18
A.H.Systems,inc	Horn Antenna	SAS-574	505	2017-12-02	2018-12-01
Mini-circuits	Pre-Amplifier	ZVA-183-S+	771001215	2017-05-20	2018-05-19
Quinstar	Pre-Amplifier	QLW-18405536-JO	15964004001	2017-05-20	2018-05-19
Sinoscite.,Co Ltd	Reject Band Filter	BSF 2402-2480MN	0898-005	2017-11-10	2018-11-09
INMET	Attenuator	N-6dB	/	2017-11-10	2018-11-09
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2017-11-10	2018-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2017-11-10	2018-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2017-11-10	2018-11-09
Rohde & Schwarz	EMC32	N/A	V 8.52.0	N/A	N/A
RF Conducted Test					
Agilent	USB Wideband Power Sensor	U2021XA	MY53320008	2017-11-10	2018-11-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2017-05-18	2018-05-17
WEINSCHL ENGINEERING	Attenuator	1A10dB	AA4135	2017-11-10	2018-11-09
N/A	RF Cable	NO.3	N/A	2017-11-09	2018-11-08
E-Microwave	DC Block	EMDCB-00036	OE01304225	Each Time	/
N/A	RF Cable	N/A	N/A	Each Time	/

* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Per 447498 D01 General RF Exposure Guidance v06, simultaneous transmission MPE test exclusion applies when the sum of the MPE for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0.

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where:

S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

MPE evaluation for single transmission:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
WLAN	2412-2462	5.60	3.63	16.00	39.81	20	0.029	1.0
	5150-5250	7.20	5.25	14.00	25.12	20	0.026	1.0
	5725-5850	7.20	5.25	15.00	31.62	20	0.033	1.0
BT3.0	2402-2480	5.60	3.63	4.00	2.51	20	0.002	1.0
BLE	2402-2480	5.60	3.63	1.00	1.26	20	0.001	1.0

Note: Wi-Fi (2.4G) & Wi-Fi (5G) or Wi-Fi & Bluetooth can not transmit simultaneously.

Result: MPE evaluation of single transmission meets the requirement of standard.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT used three built in FPC antennas (Antenna 1: Bluetooth, 2.4G&5GHz Wi-Fi; Antenna 2: 2.4G/5G Wi-Fi; antenna 3: 2.4G-RX), which connected to the main board with IPEX socket, fulfill the requirement of this section. Please refer to the EUT internal photos and the below table for detail.

Antenna Information

Antenna Model Number	Manufacturer	Band	Antenna Gain	Antenna type	Connector
AG-041533-1286 FPC(31.7mm x 23.4mm)	ZHONGSHAN B&T TECHONOLGY Co.,Ltd	Wi-Fi 2.4GHz/Bluetooth	5.6dBi	Omni-directional	IPEX
		Wi-Fi 5GHz	7.2dBi	Omni-directional	IPEX
AG-041533-1285 FPC(25.6mm x 24.5mm)	ZHONGSHAN B&T TECHONOLGY Co.,Ltd	Wi-Fi 2.4GHz	4.3dBi	Omni-directional	IPEX
		Wi-Fi 5GHz	6.7dBi	Omni-directional	IPEX
AG-041533-1287 FPC(26.9mm x 17.2mm)	ZHONGSHAN B&T TECHONOLGY Co.,Ltd	2.4G-RX	0.5 dBi	Omni-directional	IPEX


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to AC 120V/60Hz.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first L.I.S.N.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data


Environmental Conditions

Temperature:	19 °C
Relative Humidity:	64 %
ATM Pressure:	96.3 kPa

The testing was performed by Tom Tang on 2017-11-16.

Test Mode: Transmitting


Wi-Fi Mode



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Margin (dB)	Limit (dBμV)
0.331971	47.6	9.000	L1	19.7	11.8	59.4
0.394140	44.4	9.000	L1	19.8	13.6	58.0
0.529596	46.9	9.000	L1	19.8	9.1	56.0
0.594597	47.3	9.000	L1	19.8	8.7	56.0
0.922425	43.5	9.000	L1	19.8	12.5	56.0
0.991146	43.6	9.000	L1	19.8	12.4	56.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Margin (dB)	Limit (dBμV)
0.397299	39.9	9.000	L1	19.8	8.0	47.9
0.529596	38.8	9.000	L1	19.8	7.2	46.0
0.594597	39.1	9.000	L1	19.8	6.9	46.0
0.662266	37.7	9.000	L1	19.8	8.3	46.0
0.728856	38.4	9.000	L1	19.8	7.6	46.0
0.792592	36.7	9.000	L1	19.7	9.3	46.0

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Margin (dB)	Limit (dBμV)
0.400484	47.1	9.000	N	19.5	10.8	57.8
0.529596	45.9	9.000	N	19.5	10.1	56.0
0.599363	47.2	9.000	N	19.5	8.8	56.0
0.731772	44.1	9.000	N	19.5	11.9	56.0
0.798946	44.9	9.000	N	19.5	11.1	56.0
1.130707	43.2	9.000	N	19.5	12.8	56.0


Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Margin (dB)	Limit (dBμV)
0.398888	39.7	9.000	N	19.5	8.2	47.9
0.531715	38.0	9.000	N	19.5	8.0	46.0
0.599363	39.5	9.000	N	19.5	6.5	46.0
0.664915	38.0	9.000	N	19.5	8.0	46.0
0.728856	35.6	9.000	N	19.5	10.4	46.0
0.795763	36.7	9.000	N	19.5	9.3	46.0

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
The corrected factor has been input into the transducer of the test software.
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

BLE Mode


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Margin (dB)	Limit (dBμV)
0.330649	47.1	9.000	L1	19.7	12.3	59.4
0.405309	45.5	9.000	L1	19.8	12.2	57.7
0.535977	47.0	9.000	L1	19.8	9.0	56.0
0.604167	47.2	9.000	L1	19.8	8.8	56.0
0.865349	45.9	9.000	L1	19.8	10.1	56.0
1.130707	43.3	9.000	L1	19.7	12.7	56.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Margin (dB)	Limit (dBμV)
0.400484	39.8	9.000	L1	19.8	8.0	47.8
0.531715	38.5	9.000	L1	19.8	7.5	46.0
0.599363	39.9	9.000	L1	19.8	6.1	46.0
0.664915	37.8	9.000	L1	19.8	8.2	46.0
0.731772	37.6	9.000	L1	19.8	8.4	46.0
0.798946	37.4	9.000	L1	19.7	8.6	46.0

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Margin (dB)	Limit (dBμV)
0.402086	46.6	9.000	N	19.5	11.3	57.8
0.535977	45.9	9.000	N	19.5	10.1	56.0
0.664915	44.0	9.000	N	19.5	12.0	56.0
0.703134	45.4	9.000	N	19.5	10.6	56.0
0.798946	44.9	9.000	N	19.5	11.1	56.0
1.126203	42.7	9.000	N	19.5	13.3	56.0
0.402086	46.6	9.000	N	19.5	11.3	57.8

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Margin (dB)	Limit (dBμV)
0.398888	39.8	9.000	N	19.5	8.1	47.9
0.533841	37.4	9.000	N	19.5	8.6	46.0
0.599363	39.7	9.000	N	19.5	6.3	46.0
0.664915	37.8	9.000	N	19.5	8.2	46.0
0.731772	38.0	9.000	N	19.5	8.0	46.0
0.798946	37.2	9.000	N	19.5	8.8	46.0

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
The corrected factor has been input into the transducer of the test software.
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to AC 120V/60Hz.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP

Frequency Range	RBW	Video B/W	Duty Cycle	Detector
Above 1 GHz	1MHz	3 MHz	Any	PK
	1MHz	3 MHz	Any	AV

Note: T is Transmission Duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Environmental Conditions


Temperature:	29 °C
Relative Humidity:	55 %
ATM Pressure:	95.5 kPa

* The testing was performed by Tom Tang on 2017-11-21.

Test Mode: Transmitting

Wi-Fi Mode

30 MHz to 1 GHz



Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corrected Factor (dB/m)	Margin (dB)	Limit (dBμV/m)
288.141250	41.9	120.000	139.0	H	278.0	-11.0	*4.1	46.0
336.277500	41.7	120.000	118.0	H	61.0	-9.8	*4.3	46.0
360.406250	41.8	120.000	102.0	H	36.0	-9.6	*4.2	46.0
373.258750	41.3	120.000	132.0	H	78.0	-9.3	*4.7	46.0
384.292500	41.3	120.000	132.0	H	78.0	-9.0	*4.7	46.0
432.186250	42.9	120.000	199.0	H	65.0	-8.0	*3.1	46.0

*Within measurement uncertainty!

Above 1 GHz

802.11b Mode (SISO)-ANT 1

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
	Reading	Measurement	Polar	Factor					
MHz	dBμV	PK/AV	H/V	(dB/m)	dB	dB	dBμV/m	dBμV/m	dB
Frequency: 2412MHz									
2412	73.65	PK	H	28.74	3.00	0.00	105.39	N/A	N/A
2412	68.77	AV	H	28.74	3.00	0.00	100.51	N/A	N/A
2412	69.42	PK	V	28.74	3.00	0.00	101.16	N/A	N/A
2412	64.71	AV	V	28.74	3.00	0.00	96.45	N/A	N/A
2390	30.46	PK	H	28.67	3.00	0.00	62.13	74.00	11.87
2390	17.11	AV	H	28.67	3.00	0.00	48.78	54.00	5.22
4824	41.43	PK	H	33.91	5.11	26.87	53.58	74.00	20.42
4824	31.54	AV	H	33.91	5.11	26.87	43.69	54.00	10.31
7236	43.09	PK	H	36.43	6.18	26.36	59.34	74.00	14.66
7236	24.51	AV	H	36.43	6.18	26.36	40.76	54.00	13.24
Frequency: 2437MHz									
2437	73.04	PK	H	28.81	3.00	0.00	104.85	N/A	N/A
2437	68.70	AV	H	28.81	3.00	0.00	100.51	N/A	N/A
2437	69.97	PK	V	28.81	3.00	0.00	101.78	N/A	N/A
2437	65.63	AV	V	28.81	3.00	0.00	97.44	N/A	N/A
4874	41.12	PK	H	34.05	5.09	26.87	53.39	74.00	20.61
4874	31.02	AV	H	34.05	5.09	26.87	43.29	54.00	10.71
7311	42.59	PK	H	36.54	6.21	26.40	58.94	74.00	15.06
7311	24.22	AV	H	36.54	6.21	26.40	40.57	54.00	13.43
Frequency: 2462MHz									
2462	72.39	PK	H	28.89	2.99	0.00	104.27	N/A	N/A
2462	68.27	AV	H	28.89	2.99	0.00	100.15	N/A	N/A
2462	70.36	PK	V	28.89	2.99	0.00	102.24	N/A	N/A
2462	66.27	AV	V	28.89	2.99	0.00	98.15	N/A	N/A
2483.5	29.02	PK	H	28.95	2.99	0.00	60.96	74.00	13.04
2483.5	15.41	AV	H	28.95	2.99	0.00	47.35	54.00	6.65
4924	41.80	PK	H	34.19	5.07	26.88	54.18	74.00	19.82
4924	34.10	AV	H	34.19	5.07	26.88	46.48	54.00	7.52
7386	39.15	PK	H	36.64	6.25	26.43	55.61	74.00	18.39
7386	30.38	AV	H	36.64	6.25	26.43	46.84	54.00	7.16

**Within measurement uncertainty!*

802.11g Mode (SISO)-ANT 1

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
	Reading	Measurement	Polar	Factor					
MHz	dBμV	PK/AV	H/V	(dB/m)	dB	dB	dBμV/m	dBμV/m	dB
Frequency: 2412MHz									
2412	73.45	PK	H	28.74	3.00	0.00	105.19	N/A	N/A
2412	63.70	AV	H	28.74	3.00	0.00	95.44	N/A	N/A
2412	72.47	PK	V	28.74	3.00	0.00	104.21	N/A	N/A
2412	62.91	AV	V	28.74	3.00	0.00	94.65	N/A	N/A
2390	32.63	PK	H	28.67	3.00	0.00	64.30	74.00	9.70
2390	15.41	AV	H	28.67	3.00	0.00	47.08	54.00	6.92
4824	36.62	PK	H	33.91	5.11	26.87	48.77	74.00	25.23
4824	20.52	AV	H	33.91	5.11	26.87	32.67	54.00	21.33
7236	41.51	PK	H	36.43	6.18	26.36	57.76	74.00	16.24
7236	23.71	AV	H	36.43	6.18	26.36	39.96	54.00	14.04
Frequency: 2437MHz									
2437	73.01	PK	H	28.81	3.00	0.00	104.82	N/A	N/A
2437	63.54	AV	H	28.81	3.00	0.00	95.35	N/A	N/A
2437	71.12	PK	V	28.81	3.00	0.00	102.93	N/A	N/A
2437	61.50	AV	V	28.81	3.00	0.00	93.31	N/A	N/A
4874	36.49	PK	H	34.05	5.09	26.87	48.76	74.00	25.24
4874	20.55	AV	H	34.05	5.09	26.87	32.82	54.00	21.18
7311	42.67	PK	H	36.54	6.21	26.40	59.02	74.00	14.98
7311	24.12	AV	H	36.54	6.21	26.40	40.47	54.00	13.53
Frequency: 2462MHz									
2462	72.19	PK	H	28.89	2.99	0.00	104.07	N/A	N/A
2462	62.82	AV	H	28.89	2.99	0.00	94.70	N/A	N/A
2462	69.23	PK	V	28.89	2.99	0.00	101.11	N/A	N/A
2462	59.42	AV	V	28.89	2.99	0.00	91.30	N/A	N/A
2483.5	36.76	PK	H	28.95	2.99	0.00	68.70	74.00	5.30
2483.5	20.52	AV	H	28.95	2.99	0.00	52.46	54.00	1.54
4924	34.91	PK	H	34.19	5.07	26.88	47.29	74.00	26.71
4924	21.43	AV	H	34.19	5.07	26.88	33.81	54.00	20.19
7386	45.32	PK	H	36.64	6.25	26.43	61.78	74.00	12.22
7386	29.73	AV	H	36.64	6.25	26.43	46.19	54.00	7.81

**Within measurement uncertainty!*

802.11n-HT20 Mode (MIMO)

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
	Reading	Measurement	Polar	Factor					
MHz	dBμV	PK/AV	H/V	(dB/m)	dB	dB	dBμV/m	dBμV/m	dB
Frequency: 2412MHz									
2412	74.39	PK	H	28.74	3.00	0.00	106.13	N/A	N/A
2412	64.90	AV	H	28.74	3.00	0.00	96.64	N/A	N/A
2412	68.88	PK	V	28.74	3.00	0.00	100.62	N/A	N/A
2412	57.74	AV	V	28.74	3.00	0.00	89.48	N/A	N/A
2390	35.18	PK	H	28.67	3.00	0.00	66.85	74.00	7.15
2390	17.09	AV	H	28.67	3.00	0.00	48.76	54.00	5.24
4824	42.06	PK	H	33.91	5.11	26.87	54.21	74.00	19.79
4824	24.96	AV	H	33.91	5.11	26.87	37.11	54.00	16.89
7236	41.01	PK	H	36.43	6.18	26.36	57.26	74.00	16.74
7236	21.43	AV	H	36.43	6.18	26.36	37.68	54.00	16.32
Frequency: 2437MHz									
2437	73.79	PK	H	28.81	3.00	0.00	105.60	N/A	N/A
2437	63.47	AV	H	28.81	3.00	0.00	95.28	N/A	N/A
2437	68.49	PK	V	28.81	3.00	0.00	100.30	N/A	N/A
2437	57.67	AV	V	28.81	3.00	0.00	89.48	N/A	N/A
4874	41.05	PK	H	34.05	5.09	26.87	53.32	74.00	20.68
4874	25.13	AV	H	34.05	5.09	26.87	37.40	54.00	16.60
7311	40.55	PK	H	36.54	6.21	26.40	56.90	74.00	17.10
7311	21.21	AV	H	36.54	6.21	26.40	37.56	54.00	16.44
Frequency: 2462MHz									
2462	73.44	PK	H	28.89	2.99	0.00	105.32	N/A	N/A
2462	62.13	AV	H	28.89	2.99	0.00	94.01	N/A	N/A
2462	68.15	PK	V	28.89	2.99	0.00	100.03	N/A	N/A
2462	57.71	AV	V	28.89	2.99	0.00	89.59	N/A	N/A
2483.5	38.47	PK	H	28.95	2.99	0.00	70.41	74.00	3.59
2483.5	19.51	AV	H	28.95	2.99	0.00	51.45	54.00	2.55
4924	37.25	PK	H	34.19	5.07	26.88	49.63	74.00	24.37
4924	21.43	AV	H	34.19	5.07	26.88	33.81	54.00	20.19
7386	34.84	PK	H	36.64	6.25	26.43	51.30	74.00	22.70
7386	21.51	AV	H	36.64	6.25	26.43	37.97	54.00	16.03

**Within measurement uncertainty!*


802.11n-HT40 Mode (MIMO)

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
	Reading	Measurement	Polar	Factor					
MHz	dBμV	PK/AV	H/V	(dB/m)	dB	dB	dBμV/m	dBμV/m	dB
Frequency: 2422MHz									
2422	70.17	PK	H	28.77	3.00	0.00	101.94	N/A	N/A
2422	59.81	AV	H	28.77	3.00	0.00	91.58	N/A	N/A
2422	62.03	PK	V	28.77	3.00	0.00	93.80	N/A	N/A
2422	51.65	AV	V	28.77	3.00	0.00	83.42	N/A	N/A
2390	33.93	PK	H	28.67	3.00	0.00	65.60	74.00	8.40
2390	18.34	AV	H	28.67	3.00	0.00	50.01	54.00	3.99
4844	35.29	PK	H	33.96	5.10	26.87	47.48	74.00	26.52
4844	20.49	AV	H	33.96	5.10	26.87	32.68	54.00	21.32
7266	36.94	PK	H	36.47	6.19	26.38	53.22	74.00	20.78
7266	24.96	AV	H	36.47	6.19	26.38	41.24	54.00	12.76
Frequency: 2437MHz									
2437	69.65	PK	H	28.81	3.00	0.00	101.46	N/A	N/A
2437	59.42	AV	H	28.81	3.00	0.00	91.23	N/A	N/A
2437	64.07	PK	V	28.81	3.00	0.00	95.88	N/A	N/A
2437	54.15	AV	V	28.81	3.00	0.00	85.96	N/A	N/A
4874	35.18	PK	H	34.05	5.09	26.87	47.45	74.00	26.55
4874	21.03	AV	H	34.05	5.09	26.87	33.30	54.00	20.70
7311	36.23	PK	H	36.54	6.21	26.40	52.58	74.00	21.42
7311	24.31	AV	H	36.54	6.21	26.40	40.66	54.00	13.34
Frequency: 2452MHz									
2452	69.72	PK	H	28.86	3.00	0.00	101.58	N/A	N/A
2452	59.31	AV	H	28.86	3.00	0.00	91.17	N/A	N/A
2452	66.54	PK	V	28.86	3.00	0.00	98.40	N/A	N/A
2452	57.17	AV	V	28.86	3.00	0.00	89.03	N/A	N/A
2483.5	34.68	PK	H	28.95	2.99	0.00	66.62	74.00	7.38
2483.5	19.50	AV	H	28.95	2.99	0.00	51.44	54.00	2.56
4904	34.89	PK	H	34.13	5.08	26.87	47.23	74.00	26.77
4904	20.52	AV	H	34.13	5.08	26.87	32.86	54.00	21.14
7356	33.89	PK	H	36.60	6.23	26.42	50.30	74.00	23.70
7356	20.52	AV	H	36.60	6.23	26.42	36.93	54.00	17.07


*Within measurement uncertainty!

Please refer to the below pre-scan plot of worst case:


802.11g Mode: Low Channel_Horizontal_1GHz-18GHz




802.11g Mode: Low Channel_Horizontal_18GHz-25GHz



802.11g Mode: Low Channel_Vertical_1GHz-18GHz




802.11g Mode: Low Channel_Vertical_18GHz-25GHz



BLE Mode

30 MHz to 1 GHz-High channel-worst case



Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corrected Factor (dB/m)	Margin (dB)	Limit (dBµV/m)
288.262500	39.9	120.000	101.0	H	24.0	-11.0	6.1	46.0
336.156250	39.8	120.000	158.0	H	52.0	-9.8	6.2	46.0
360.163750	43.0	120.000	131.0	H	52.0	-9.6	*3.0	46.0
373.380000	42.2	120.000	121.0	H	85.0	-9.3	*3.8	46.0
384.171250	42.2	120.000	122.0	H	69.0	-9.0	*3.8	46.0
432.307500	43.6	120.000	199.0	H	38.0	-8.0	*2.4	46.0

**Within measurement uncertainty!*

Above 1 GHz

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Limit	Margin
	Reading	Measurement	Polar	Factor					
MHz	dBμV	PK/AV	H/V	(dB/m)	dB	dB	dBμV/m	dBμV/m	dB
frequency: 2402MHz									
2402	61.64	PK	H	28.71	3.00	0.00	93.35	N/A	N/A
2402	57.07	AV	H	28.71	3.00	0.00	88.78	N/A	N/A
2402	66.91	PK	V	28.71	3.00	0.00	98.62	N/A	N/A
2402	62.26	AV	V	28.71	3.00	0.00	93.97	N/A	N/A
2390	29.61	PK	V	28.67	3.00	0.00	61.28	74.00	12.72
2390	15.41	AV	V	28.67	3.00	0.00	47.08	54.00	6.92
4804	35.31	PK	V	33.85	5.12	26.87	47.41	74.00	26.59
4804	19.43	AV	V	33.85	5.12	26.87	31.53	54.00	22.47
7206	33.24	PK	V	36.39	6.16	26.35	49.44	74.00	24.56
7206	18.49	AV	V	36.39	6.16	26.35	34.69	54.00	19.31
frequency: 2440MHz									
2440	61.44	PK	H	28.82	3.00	0.00	93.26	N/A	N/A
2440	56.94	AV	H	28.82	3.00	0.00	88.76	N/A	N/A
2440	66.63	PK	V	28.82	3.00	0.00	98.45	N/A	N/A
2440	62.13	AV	V	28.82	3.00	0.00	93.95	N/A	N/A
4880	34.90	PK	V	34.06	5.09	26.87	47.18	74.00	26.82
4880	19.68	AV	V	34.06	5.09	26.87	31.96	54.00	22.04
7320	33.15	PK	V	36.55	6.22	26.40	49.52	74.00	24.48
7320	18.46	AV	V	36.55	6.22	26.40	34.83	54.00	19.17
frequency: 2480MHz									
2480	61.36	PK	H	28.94	2.99	0.00	93.29	N/A	N/A
2480	56.81	AV	H	28.94	2.99	0.00	88.74	N/A	N/A
2480	66.59	PK	V	28.94	2.99	0.00	98.52	N/A	N/A
2480	62.05	AV	V	28.94	2.99	0.00	93.98	N/A	N/A
2483.5	30.35	PK	V	28.95	2.99	0.00	62.29	74.00	11.71
2483.5	18.52	AV	V	28.95	2.99	0.00	50.46	54.00	*3.54
4960	34.70	PK	V	34.29	5.05	26.88	47.16	74.00	26.84
4960	19.50	AV	V	34.29	5.05	26.88	31.96	54.00	22.04
7440	34.42	PK	V	36.72	6.27	26.45	50.96	74.00	23.04
7440	18.34	AV	V	36.72	6.27	26.45	34.88	54.00	19.12

**Within measurement uncertainty!*

Note:

Corrected Amplitude = Corrected Factor + Reading


Corrected Factor=Antenna factor (RX) + Cable Loss – Amplifier Factor

Margin = Limit- Corr. Amplitude


Spurious emissions more than 20 dB below the limit were not reported.

Please refer to the below pre-scan plot of worst case:


High Channel_Horizontal_1GHz-18GHz




High Channel_Horizontal_18GHz-25GHz



High Channel_Vertical_1GHz-18GHz



High Channel_Vertical_18GHz-25GHz



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	19 ~ 20 °C
Relative Humidity:	54 ~ 66 %
ATM Pressure:	95.6 ~ 96.6 kPa

* The testing was performed by Tom Tang on 2017-11-17 & 2017-11-20.

Test Mode: Transmitting



Test Result: Compliance. Please refer to the following table and plots.

Wi-Fi mode


Mode	Channel	Frequency (MHz)	6dB Emission Bandwidth (MHz)		Limit (MHz)
			Antenna 1	Antenna 2	
802.11b	Low	2412	10.10	8.90	≥0.50
	Middle	2437	10.02	8.90	≥0.50
	High	2462	9.94	9.46	≥0.50
802.11g	Low	2412	15.63	15.07	≥0.50
	Middle	2437	15.63	16.11	≥0.50
	High	2462	15.95	15.55	≥0.50
802.11n-HT20	Low	2412	16.99	15.79	≥0.50
	Middle	2437	16.91	16.03	≥0.50
	High	2462	16.83	16.35	≥0.50
802.11n-HT40	Low	2422	35.27	35.59	≥0.50
	Middle	2437	34.95	35.75	≥0.50
	High	2452	35.43	35.75	≥0.50

BLE mode


Mode	Channel	Frequency (MHz)	6dB Emission Bandwidth (MHz)	Limit (MHz)
BLE	Low	2402	0.70	≥0.50
	Middle	2440	0.71	≥0.50
	High	2480	0.71	≥0.50




Wi-Fi mode, 802.11b High Channel (Antenna 1)




Wi-Fi mode, 802.11g Low Channel (Antenna 1)




Wi-Fi mode, 802.11g Middle Channel (Antenna 1)




Wi-Fi mode, 802.11g High Channel (Antenna 1)




Wi-Fi mode, 802.11n-HT20 Low Channel (Antenna 1)



Wi-Fi mode, 802.11n-HT20 Middle Channel (Antenna 1)




Wi-Fi mode, 802.11n-HT20 High Channel (Antenna 1)





Date: 20.NOV.2017 11:52:24


Wi-Fi mode, 802.11n-HT40 Low Channel (Antenna 1)




Date: 20.NOV.2017 11:42:04




Wi-Fi mode, 802.11b Low Channel (Antenna 2)




Wi-Fi mode, 802.11b Middle Channel (Antenna 2)




Wi-Fi mode, 802.11b High Channel (Antenna 2)




Wi-Fi mode, 802.11g Low Channel (Antenna 2)




Wi-Fi mode, 802.11g Middle Channel (Antenna 2)




Wi-Fi mode, 802.11g High Channel (Antenna 2)




Wi-Fi mode, 802.11n-HT20 Low Channel (Antenna 2)




Wi-Fi mode, 802.11n-HT20 Middle Channel (Antenna 2)




Wi-Fi mode, 802.11n-HT20 High Channel (Antenna 2)




Wi-Fi mode, 802.11n-HT40 Low Channel (Antenna 2)




Wi-Fi mode, 802.11n-HT40 Middle Channel (Antenna 2)




Wi-Fi mode, 802.11n-HT40 High Channel (Antenna 2)




BLE mode, Low Channel



BLE mode, Middle Channel





FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	66 %
ATM Pressure:	95.6 kPa

* The testing was performed by Tom Tang on 2017-11-17.

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Wi-Fi mode

Mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)		Total (dBm)	Limit (dBm)
			Antenna 1	Antenna 2		
802.11b	Low	2412	15.80	16.35	/	30
	Middle	2437	16.55	17.30	/	30
	High	2462	16.18	16.31	/	30
802.11g	Low	2412	20.53	20.35	/	30
	Middle	2437	21.21	20.90	/	30
	High	2462	20.74	20.85	/	30
802.11n-HT20	Low	2412	20.61	19.90	23.28	30
	Middle	2437	21.11	20.90	24.02	30
	High	2462	20.81	20.91	23.87	30
802.11n-HT40	Low	2422	19.94	18.32	22.22	30
	Middle	2437	19.74	18.87	22.34	30
	High	2452	19.80	18.57	22.24	30

Mode	Channel	Frequency (MHz)	Max Conducted Average Output Power (dBm)		Total (dBm)	Limit (dBm)
			Antenna 1	Antenna 2		
802.11b	Low	2412	13.21	12.31	/	30
	Middle	2437	13.23	12.86	/	30
	High	2462	12.81	11.92	/	30
802.11g	Low	2412	12.54	11.47	/	30
	Middle	2437	13.30	11.83	/	30
	High	2462	12.90	12.62	/	30
802.11n-HT20	Low	2412	12.34	11.67	15.03	30
	Middle	2437	13.09	11.91	15.55	30
	High	2462	12.67	12.50	15.60	30
802.11n-HT40	Low	2422	10.98	9.80	13.44	30
	Middle	2437	10.69	10.19	13.46	30
	High	2452	11.31	10.16	13.78	30

Note: The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4;

So:

Directional gain = GANT + Array Gain = 5.6 dBi < 6.0dBi.

No power limit was reduced in MIMO mode.

BLE mode

Mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Limit (dBm)
BLE	Low	2402	0.62	30
	Middle	2440	0.49	30
	High	2480	-0.03	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


Temperature:	19 ~ 20 °C
Relative Humidity:	54 ~ 66 %
ATM Pressure:	95.6 ~ 96.6 kPa

** The testing was performed by Tom Tang on 2017-11-17 & 2017-11-20.*

Test mode: Transmitting


Test Result: Compliance. Please refer to following plots.

802.11g: Band Edge, Left Side (Antenna 1)




Date: 20.NOV.2017 14:08:03

802.11g: Band Edge, Right Side (Antenna 1)




Date: 20.NOV.2017 14:10:42


802.11n-HT20 Band Edge, Left Side (Antenna 1)



802.11n-HT20 Band Edge, Right Side (Antenna 1)




802.11n-HT40 Band Edge, Left Side (Antenna 1)




Date: 20.NOV.2017 14:05:54

802.11n-HT40 Band Edge, Right Side (Antenna 1)




Date: 20.NOV.2017 14:03:37

802.11b: Band Edge, Left Side (Antenna 2)




Date: 17.NOV.2017 18:08:48

802.11b: Band Edge, Right Side (Antenna 2)




Date: 17.NOV.2017 18:07:39


802.11n-HT20 Band Edge, Left Side (Antenna 2)




802.11n-HT20 Band Edge, Right Side (Antenna 2)



802.11n-HT20 Band Edge, Left Side (Antenna 2)




802.11n-HT20 Band Edge, Right Side (Antenna 2)




BLE mode

Band Edge, Left Side



Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	19 ~ 20 °C
Relative Humidity:	54 ~ 66 %
ATM Pressure:	95.6 ~ 96.6 kPa

** The testing was performed by Tom Tang on 2017-11-17 & 2017-11-20.*

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots

Wi-Fi mode

Mode	Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)		Total (dBm/3kHz)	Limit (dBm/3kHz)
			Antenna 1	Antenna 2		
802.11b	Low	2412	-10.52	-11.83	/	8
	Middle	2437	-10.98	-11.02	/	8
	High	2462	-11.22	-11.43	/	8
802.11g	Low	2412	-11.46	-13.39	/	8
	Middle	2437	-11.47	-12.09	/	8
	High	2462	-10.84	-11.13	/	8
802.11n-HT20	Low	2412	-11.93	-11.65	-8.78	5.4
	Middle	2437	-11.35	-11.41	-8.37	5.4
	High	2462	-12.28	-11.37	-8.79	5.4
802.11n-HT40	Low	2422	-15.01	-16.38	-12.63	5.4
	Middle	2437	-14.78	-16.00	-12.34	5.4
	High	2452	-14.73	-15.62	-12.14	5.4

Note: The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:
 Array Gain = $10 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB.

So:


Directional gain = $G_{\text{ANT}} + \text{Array Gain} = 5.6 + 10 \log(2) = 8.6 \text{ dBi} > 6 \text{ dBi}$
 Power density Limit was reduced 2.6dB in MIMO mode.

BLE mode


Mode	Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BLE	Low	2402	-15.75	8
	Middle	2440	-15.27	8
	High	2480	-16.12	8

Wi-Fi mode


Power Spectral Density, 802.11b Low Channel (Antenna 1)




Power Spectral Density, 802.11b Middle Channel (Antenna 1)




Power Spectral Density, 802.11b High Channel (Antenna 1)



Power Spectral Density, 802.11g Low Channel (Antenna 1)




Power Spectral Density, 802.11g Middle Channel (Antenna 1)




Date: 20.NOV.2017 14:28:03

Power Spectral Density, 802.11g High Channel (Antenna 1)




Date: 20.NOV.2017 14:26:29


Power Spectral Density, 802.11n-HT20 Low Channel (Antenna 1)




Power Spectral Density, 802.11n-HT20 Middle Channel (Antenna 1)




Power Spectral Density, 802.11n-HT20 High Channel (Antenna 1)




Power Spectral Density, 802.11n-HT40 Low Channel (Antenna 1)




Power Spectral Density, 802.11n-HT40 Middle Channel (Antenna 1)




Power Spectral Density, 802.11n-HT40 High Channel (Antenna 1)




Power Spectral Density, 802.11b Low Channel (Antenna 2)




Power Spectral Density, 802.11b Middle Channel (Antenna 2)




Power Spectral Density, 802.11b High Channel (Antenna 2)




Power Spectral Density, 802.11g Low Channel (Antenna 2)




Power Spectral Density, 802.11g Middle Channel (Antenna 2)




Power Spectral Density, 802.11g High Channel (Antenna 2)




Power Spectral Density, 802.11n-HT20 Low Channel (Antenna 2)




Power Spectral Density, 802.11n-HT20 Middle Channel (Antenna 2)




Power Spectral Density, 802.11n-HT20 High Channel (Antenna 2)




Power Spectral Density, 802.11n-HT40 Low Channel (Antenna 2)



Power Spectral Density, 802.11n-HT40 Middle Channel (Antenna 2)




Power Spectral Density, 802.11n-HT40 High Channel (Antenna 2)




BLE mode


Power Spectral Density, Low Channel



Power Spectral Density, Middle Channel



Power Spectral Density, High Channel



***** END OF REPORT *****