



# TEST REPORT

Applicant Name : Shenzhen Hollyland Technology Co.,Ltd  
Address : 8F,Building 5D,Skyworth Innovation Valley, Tangtou Road.  
Shiyan Street, Baoan District, Shenzhen, China 518055  
Report Number : SZNS220321-09684E-RF-00B  
FCC ID: 2ADZC-5802R

## Test Standard (s)

FCC PART 15.407

## Sample Description

Product Type: FULL-DUPLEX WIRELESS INTERCOM SYSTEM  
Model No.: SOLIDCOM C1  
Multiple Model(s) No.: SOLIDCOM C2, SOLIDCOM C3, SOLIDCOM C4, SOLIDCOM S1, SOLIDCOM S2, SOLIDCOM S3, SOLIDCOM M2, SOLIDCOM M3 (Please refer to DOS for Model difference)  
Trade Mark: HOLLYLAND, HOLLYVIEW  
Date Received: 2022/03/21  
Report Date: 2022/05/06

Test Result:	Pass*
--------------	-------

\* In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:

## Approved By:

Black Ding  
EMC Engineer

Robert Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
<b>SYSTEM TEST CONFIGURATION</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE	7
BLOCK DIAGRAM OF TEST SETUP	7
<b>SUMMARY OF TEST RESULTS</b>	<b>9</b>
<b>TEST EQUIPMENT LIST</b>	<b>10</b>
<b>FCC PART §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)</b>	<b>12</b>
APPLICABLE STANDARD	12
RESULT	12
<b>FCC §15.203 – ANTENNA REQUIREMENT</b>	<b>14</b>
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
<b>FCC §15.407 (B) (6) §15.207 (A) – CONDUCTED EMISSIONS</b>	<b>15</b>
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP	15
TEST PROCEDURE	15
CORRECTED FACTOR & MARGIN CALCULATION	16
TEST DATA	16
<b>§15.205 &amp; §15.209 &amp; §15.407(B)– UNDESIRABLE EMISSION</b>	<b>19</b>
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED FACTOR & MARGIN CALCULATION	21
TEST DATA	21
<b>FCC §15.407(A),(E) – 26 DB &amp; 6DB EMISSION BANDWIDTH</b>	<b>27</b>
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27
<b>FCC §15.407(A) – CONDUCTED TRANSMITTER OUTPUT POWER</b>	<b>28</b>
APPLICABLE STANDARD	28
TEST PROCEDURE	28

TEST DATA .....	28
<b>FCC §15.407(A) - POWER SPECTRAL DENSITY .....</b>	<b>29</b>
TEST PROCEDURE .....	29
TEST DATA .....	29
<b>APPENDIX .....</b>	<b>30</b>
APPENDIX A1: EMISSION BANDWIDTH .....	30
APPENDIX A2: OCCUPIED CHANNEL BANDWIDTH .....	31
APPENDIX B: MAXIMUM CONDUCTED OUTPUT POWER .....	32
APPENDIX C: MAXIMUM POWER SPECTRAL DENSITY .....	33
APPENDIX E: DUTY CYCLE .....	34

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Frequency Range	5G Wi-Fi: 5190MHz
Mode	802.11 n40
Maximum Conducted Average Output Power	9.10dBm
Modulation Technique	OFDM
Antenna Specification*	2.5dBi (It is provided by the applicant)
Voltage Range	DC 7.4V or 14.8V from battery or DC 12.0V from adapter
Sample number	SZNS220321-09684E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter information	Model: GQ24-120200-AX Input: AC 100-240V, 50/60Hz, 1.0A Max Output: DC 12.0V, 2.0A, 24.0W

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		$0.082 \times 10^{-7}$
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1 °C
Humidity		6%
Supply voltages		0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $K$  with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

### EUT Exercise Software

“XCOM.exe”\* exercise software was used. The software and power level was provided by the applicant.

The worst case was performed under:

Mode	Data Rate	Power Level*
		5190MHz
802.11 n40	MCS0	0B

### Duty cycle

Test Result: Pass. Please refer to the Appendix.

### Equipment Modifications

No modification was made to the EUT tested.

### Local Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	Laptop	ThinkPad	1
Unknown	Battery*3	Unknown	Unknown
Unknown	Load*3	Unknown	Unknown
Lenovo	Earphone	Unknown	Unknown
Hollyland	Wireless Earphone	Solidcom C1	Unknown
Hikvision	Router*2	DS-3WR03-E	Unknown

**External I/O Cable**


Cable Description	Length (m)	From Port	To
Un-Shielding Detachable RJ45 Cable	8.0	EUT	Router 1
Un-Shielding Detachable RJ45 Cable	8.0	EUT	Router 2
Un-Shielding Un-detachable DC Cable	1.0	Adapter	EUT
Shielding Detachable USB Cable	1.0	EUT	Laptop

**Block Diagram of Test Setup**

For conducted emission



For radiated emission



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§ 2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.407(b)(9)& §15.207(a)	Conducted Emissions	Compliant
§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliant
§15.407(a) (e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliant
§15.407(a)	Conducted Transmitter Output Power	Compliant
§15.407 (a)	Power Spectral Density	Compliant
§15.407 (h)	Transmit Power Control (TPC)	Not Applicable
§15.407 (h)	Dynamic Frequency Selection (DFS)	Not Applicable

Not Applicable: the EUT only supports the 5190MHz.

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emission test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ESH3-Z5	100305	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated emission test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
CD	Band Reject Filter	BRM-5.15/5.35g-45	075	2021/12/14	2022/12/13

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF conducted test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2021/12/13	2022/12/12
Tonscend	RF Control Unit	JS0806-2	19G8060182	2021/07/06	2022/07/05
WEINSCHEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Unknown	RF Cable	Unknown	Unknown	Each time	

\* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC Part §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

#### Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### Result

#### Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Mode	Frequency (MHz)	Antenna Gain		Max Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
DECT	1921.536-1928.448	3.0	2.0	20.8	120.23	20	0.048	1
5G Wi-Fi	5190	2.5	1.8	10.0	10.0	20	0.004	1

Note: 1. the tune up conducted power was declared by the applicant  
 2. the DECT and 5G Wi-Fi can transmit at the same time.

Simultaneous transmitting consideration:

The ratio= $MPE_{DECT}/limit + MPE_{5GWi-Fi}/limit = 0.048/1 + 0.004/1 = 0.052 < 1.0$

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Pass**

---

## **FCC §15.203 – ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has one internal anantenna arrangement for 5G Wi-Fi which were permanently attached and the antenna gain is 2.5dBi. Please refer to the EUT photos.


**Result:** Compliant.

## FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207, §15.407(b) (6)

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and Average detection mode.

## Corrected Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Over Limit} = \text{level} - \text{Limit}$$

$$\text{Level} = \text{reading level} + \text{Transd Factor}$$


## Test Data

### Environmental Conditions


Temperature:	23 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

*The testing was performed by Caro Hu on 2022-05-05.*

*EUT operation mode: Transmitting*

**AC 120V/60 Hz, Line:**

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.178	9.80	19.58	29.38	54.56	-25.18	Average
2	0.178	9.80	34.93	44.73	64.56	-19.83	QP
3	0.201	9.80	19.99	29.79	53.55	-23.76	Average
4	0.201	9.80	32.34	42.14	63.55	-21.41	QP
5	0.453	9.80	28.45	38.25	46.82	-8.57	Average
6	0.453	9.80	29.26	39.06	56.82	-17.76	QP
7	0.501	9.80	23.28	33.08	46.00	-12.92	Average
8	0.501	9.80	24.97	34.77	56.00	-21.23	QP
9	2.073	9.82	6.81	16.63	46.00	-29.37	Average
10	2.073	9.82	11.72	21.54	56.00	-34.46	QP
11	7.956	9.88	13.53	23.41	50.00	-26.59	Average
12	7.956	9.88	19.98	29.86	60.00	-30.14	QP

**AC 120V/60 Hz, Neutral:**

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.154	9.80	19.62	29.42	55.80	-26.38	Average
2	0.154	9.80	37.77	47.57	65.80	-18.23	QP
3	0.200	9.80	16.36	26.16	53.61	-27.45	Average
4	0.200	9.80	31.59	41.39	63.61	-22.22	QP
5	0.473	9.80	26.87	36.67	46.46	-9.79	Average
6	0.473	9.80	26.94	36.74	56.46	-19.72	QP
7	0.501	9.80	18.38	28.18	46.00	-17.82	Average
8	0.501	9.80	20.33	30.13	56.00	-25.87	QP
9	2.250	9.82	12.60	22.42	46.00	-23.58	Average
10	2.250	9.82	19.19	29.01	56.00	-26.99	QP
11	9.229	9.99	13.46	23.45	50.00	-26.55	Average
12	9.229	9.99	20.51	30.50	60.00	-29.50	QP

## §15.205 & §15.209 & §15.407(B)– UNDESIRABLE EMISSION

### Applicable Standard

FCC §15.407 (b); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

### EUT Setup

Below 1 GHz:



**Above 1 GHz:**

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1MHz	10 Hz <sup>Note 1</sup>	/	Average
	1MHz	> 1/T <sup>Note 2</sup>	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

**Test Procedure****Radiated Spurious Emission**

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to ANSI C63.10-2013,9.4: For field strength measurements made at other than the distance at which the applicable limit is specified, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left( \frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dBμV/m
$E_{\text{Meas}}$	is the field strength of the emission at the measurement distance, in dBμV/m
$d_{\text{Meas}}$	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is  $20 \cdot \log(1/3) = -9.5$  dB, for 18-40GHz range, the limit of 1m distance was added by 9.5dB from limit of 3m to compared with the result measurement at 1m distance.

### Corrected Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25.5~28 °C
<b>Relative Humidity:</b>	50~54 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Nick Fang on 2022-05-05 for below 1GHz, Nick Fang and Level Li on 2022-04-29 and 2022-05-05 for above 1GHz.*

*EUT operation mode: Transmitting(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded)*

**30 MHz – 1 GHz:**


*Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.*

Horizontal



	Freq Factor		Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	140.897	-15.48	52.76	37.28	43.50	-6.22	QP
2	225.012	-11.26	52.35	41.09	46.00	-4.91	QP
3	350.016	-7.31	48.70	41.39	46.00	-4.61	QP
4	374.951	-7.27	48.09	40.82	46.00	-5.18	QP
5	425.028	-5.86	46.01	40.15	46.00	-5.85	QP
6	525.014	-4.37	45.60	41.23	46.00	-4.77	QP

Vertical



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	225.012	-11.26	44.41	33.15	46.00	-12.85	Peak
2	374.951	-7.27	45.16	37.89	46.00	-8.11	Peak
3	425.028	-5.86	45.83	39.97	46.00	-6.03	QP
4	475.083	-5.42	43.63	38.21	46.00	-7.79	Peak
5	497.677	-4.35	46.23	41.88	46.00	-4.12	QP
6	525.014	-4.37	46.50	42.13	46.00	-3.87	QP

**1 GHz-40 GHz:**

Frequency (MHz)	Receiver		Turn- Table Angle Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407	
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5190 MHz									
4500	64.24	PK	185	1.6	H	-4.72	59.52	74	-14.48
4500	50.77	PK	185	1.6	H	-4.72	46.05	54	-7.95
4500	63.49	AV	172	1	V	-4.72	58.77	74	-15.23
4500	50.34	AV	172	1	V	-4.72	45.62	54	-8.38
5150	68.54	PK	100	2.3	H	-2.73	65.81	74	-8.19
5150	50.87	PK	100	2.3	H	-2.73	48.14	54	-5.86
5150	63.57	AV	349	2	V	-2.73	60.84	74	-13.16
5150	50.78	AV	349	2	V	-2.73	48.05	54	-5.95
5350	62.37	PK	318	2.2	H	-2.33	60.04	74	-13.96
5350	49.08	PK	318	2.2	H	-2.33	46.75	54	-7.25
5350	62.09	AV	311	2.3	V	-2.33	59.76	74	-14.24
5350	48.97	AV	311	2.3	V	-2.33	46.64	54	-7.36
5460	62.43	PK	140	2.1	H	-2.3	60.13	74	-13.87
5460	49.23	PK	140	2.1	H	-2.3	46.93	54	-7.07
5460	62.38	AV	15	1.3	V	-2.3	60.08	74	-13.92
5460	49.19	AV	15	1.3	V	-2.3	46.89	54	-7.11
10380	40.85	PK	197	2.4	H	8.2	49.05	68.2	-19.15
10380	40.71	PK	197	2.4	V	8.2	48.91	68.2	-19.29

**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected Amplitude – Limit


The other spurious emission which is in the noise floor level was not recorded.

1 GHz - 18 GHz: (Pre-Scan plots)

Horizontal




Vertical




18-40GHz: (Pre-Scan plots)

Horizontal



Vertical




**FCC §15.407(a),(e) – 26 dB & 6dB EMISSION BANDWIDTH****Applicable Standard**

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.15-5.25 GHz, bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

**Test Procedure****1. Emission Bandwidth (EBW)**

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Ting Lü on 2022-04-30.*

*EUT operation mode: Transmitting*

**Test Result: Pass**

*Please refer to the Appendix.*

## FCC §15.407(a) – CONDUCTED TRANSMITTER OUTPUT POWER


### Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Test Procedure

- c. Place the EUT on a bench and set it in transmitting mode.
- d. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- e. Add a correction factor to the display.



Note: The RF control Unit built-in a power sensor.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Ting Lü on 2022-04-30.*

*EUT operation mode: Transmitting*

**Test Result: Pass**

*Please refer to the Appendix.*

## FCC §15.407(a) - POWER SPECTRAL DENSITY


For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Test Procedure

For devices operating in the bands 5.15-5.25 GHz the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). a) Set  $RBW \geq 1/T$ , where T is defined in section II.B.1.a).

b) Set  $VBW \geq 3 RBW$ .

c) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.



### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Ting Lü on 2022-04-30.*

*EUT operation mode: Transmitting*

**Test Result: Pass**


*Please refer to the Appendix.*

## APPENDIX

### Appendix A1: Emission Bandwidth Test Result

Test Mode	Antenna	Channel	26db EBW [MHz]	Limit[MHz]	Verdict
11N40SISO	Ant1	5190	62.16	---	---

### Test Graphs




## Appendix A2: Occupied channel bandwidth Test Result

Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11N40SISO	Ant1	5190	38.202	---	---

Note: OBWfor U-NII-1 band will not within frequency range for U-NII-2A and U-NII-2C bands.

## Test Graphs



**Appendix B: Maximum conducted output power  
Test Result**


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11N40SISO	Ant1	5190	9.10	≤23.98	PASS

## Appendix C: Maximum power spectral density

### Test Result

Test Mode	Antenna	Channel	Result [dBm/MHz]	Limit[dBm/MHz]	Verdict
11N40SISO	Ant1	5190	-1.5	≤11.00	PASS


### Test Graphs



## Appendix E: Duty Cycle Test Result

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11N40SISO	Ant1	5190	0.95	0.98	95.94

## Test Graphs



\*\*\*\*\* END OF REPORT \*\*\*\*\*