















Page 500 of 507

11.6. APPENDIX F: FREQUENCY STABILITY

11.6.1. Test Result

Frequency Error vs. Voltage									
				802	11a:5200MHz	4			
	Volt.	0 Minute		2 Minute		5 Minute		10 Minute	
Temp.		Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)
TN	VL	5199.9893	-2.07	5199.9902	-1.89	5199.9847	-2.94	5199.9894	-2.04
TN	VN	5200.0012	0.23	5199.9946	-1.04	5200.0016	0.30	5200.0079	1.52
TN	VH	5199.9763	-4.56	5199.9834	-3.20	5199.9970	-0.58	5199.9763	-4.55
	Frequency Error vs. Temperature								
	802.11a:5200MHz								
_		0 Minute		2 Minute		5 Minute		10 Minute	
Temp.	Volt.	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)	Freq.Error (MHz)	Tolerance (ppm)
70	VN	5199.9792	-3.99	5200.0051	0.99	5200.0103	1.98	5199.9817	-3.52
60	VN	5199.9898	-1.96	5199.9827	-3.33	5200.0224	4.31	5200.0149	2.86
50	VN	5199.9927	-1.41	5199.9771	-4.39	5199.9958	-0.81	5200.0191	3.68
40	VN	5200.0041	0.79	5200.0057	1.09	5199.9957	-0.83	5199.9988	-0.23
30	VN	5199.9881	-2.29	5199.9845	-2.98	5199.9777	-4.28	5200.0035	0.67
20	VN	5200.0190	3.66	5199.9796	-3.93	5199.9763	-4.57	5200.0231	4.44
10	VN	5200.0218	4.18	5200.0103	1.97	5199.9999	-0.01	5200.0135	2.59
0	VN	5199.9928	-1.39	5200.0086	1.65	5200.0085	1.64	5200.0032	0.61

Note:

2. For the detail Test Conditions, please refer to section 7.5 TEST ENVIRONMENT.

^{1.} All antennas, test modes and test channels have been tested, only the worst data record in the report.



Page 501 of 507

11.7. APPENDIX G: DUTY CYCLE 11.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
11A	1.36	1.86	0.7312	73.12	1.36	0.74	1
11N20MIMO	1.14	1.64	0.6951	69.51	1.58	0.88	1
11N40MIMO	0.57	1.07	0.5327	53.27	2.74	1.75	2
11AC80MIMO	0.29	0.79	0.3671	36.71	4.35	3.45	4
11AX20MIMO	0.99	1.49	0.6644	66.44	1.78	1.01	2
11AX80MIMO	0.28	0.78	0.3590	35.90	4.45	3.57	4

Note:

Duty Cycle Correction Factor=10log (1/x).


Where: x is Duty Cycle (Linear)

Where: T is On Time


If that calculated VBW is not available on the analyzer then the next higher value should be used.




11.7.2. Test Graphs
















Page 505 of 507

11.8. APPENDIX H: CALIBRATION

Mode	Frequency (MHz)	Туре	Result	Verdict
ax80	5530	DFS_FCC_T0	See test Graph	Pass






Page 506 of 507

11.9. APPENDIX I: SHUTDOWN TIME

Mo	ode	Frequency (MHz)	Channel Move Time (s)	Limit Channel Move Time (s)	Close Transmission Time (s)	Limit Close Transmission Time (s)	Close Transmission Time after 200ms(s)	Limit Close Transmission Time after 200ms (s)	Verdict
ax	(80	5530	0.496	10	0.007	0.26	0.004	0.06	Pass

Note: refer to KDB 905462 D02 table 2, this report only records the widest BW mode test data.






Page 507 of 507

11.10. APPENDIX J: NON-OCCUPANCY

Mode	Frequency (MHz)	Result	Verdict	
ax80	5530	See test Graph	Pass	

Note: refer to KDB 905462 D02 table 2, this report only records the widest BW mode test data.



END OF REPORT