FCC Test Report

Report No.: AGC10516220206FE02

FCC ID	:	2AWM4KEYBOARD
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	KLIM Wireless Keyboards
BRAND NAME	:	KLIM
MODEL NAME	:	KLIM Light V2, KLIM Tandem
APPLICANT	:	Marcus Excelsior Limited
DATE OF ISSUE	:	Mar. 11, 2022
STANDARD(S)	:	FCC Part 15.247
REPORT VERSION	:	V1.0

*A*ttestation of *G*lobal *C*ompliance (Shenzhen) Co., Ltd

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar. 11, 2022	Valid	Initial Release

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE 5

2. GENERAL INFORMATION 6

2.1. PRODUCT DESCRIPTION 6
2.2. TABLE OF CARRIER FREQUENCYS 7
2.3. RELATED SUBMITTAL(S)/GRANT(S) 8
2.4. TEST METHODOLOGY 8
2.5. SPECIAL ACCESSORIES 8
2.6. EQUIPMENT MODIFICATIONS 8
2.7. ANTENNA REQUIREMENT 8

3. MEASUREMENT UNCERTAINTY 9

4. DESCRIPTION OF TEST MODES 10

5. SYSTEM TEST CONFIGURATION 11

5.1. CONFIGURATION OF TESTED SYSTEM 11
5.2. EQUIPMENT USED IN TESTED SYSTEM 11
5.3. SUMMARY OF TEST RESULTS 11

6. TEST FACILITY 12

7. PEAK OUTPUT POWER 13

7.1. MEASUREMENT PROCEDURE 13
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 13
7.3. LIMITS AND MEASUREMENT RESULT 14

8. BANDWIDTH 16

8.1. MEASUREMENT PROCEDURE 16
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16
8.3. LIMITS AND MEASUREMENT RESULTS 16

9. CONDUCTED SPURIOUS EMISSION 20

9.1. MEASUREMENT PROCEDURE 20
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 20
9.3. MEASUREMENT EQUIPMENT USED 20
9.4. LIMITS AND MEASUREMENT RESULT 20

10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY 27

10.1. MEASUREMENT PROCEDURE 27
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 27
10.3. MEASUREMENT EQUIPMENT USED 27
10.4. LIMITS AND MEASUREMENT RESULT 27

11. RADIATED EMISSION 29

11.1. MEASUREMENT PROCEDURE 29
11.2. TEST SETUP 30
11.3. LIMITS AND MEASUREMENT RESULT 31
11.4. TEST RESULT 31

12. LINE CONDUCTED EMISSION TEST 41

12.1. LIMITS OF LINE CONDUCTED EMISSION TEST 41
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 41

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 42
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 42
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 43
APPENDIX A: PHOTOGRAPHS OF TEST SETUP 45
APPENDIX B: PHOTOGRAPHS OF EUT 45

1. VERIFICATION OF COMPLIANCE

Applicant	Marcus Excelsior Limited
Address	2512, Langham Place Office Tower, 8 Argyle Street, Mongkok, Kowloon, HONG KONG
Manufacturer	Shenzhen WINOMOKO KLIM technology Co., ltd
Address	B207, Jianan Road, luther Industry zone, Tangwei community, Fuhai street, Bao'an District, Shenzhen, Guangdong province, China 518101
Factory	Shenzhen WINOMOKO KLIM technology Co., ltd
Address	B207, Jianan Road, luther Industry zone, Tangwei community, Fuhai street, Bao'an District, Shenzhen, Guangdong province, China 518101
Product Designation	KLIM Wireless Keyboards
Brand Name	KLIM
Test Model	KLIM Light V2
Series Model	KLIM Tandem
Declaration of Difference	All the series models are the same as the test model except for the model names.
Date of test	Feb. 28, 2022 to Mar. 11, 2022
Deviation	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-US-BLE/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By	Bibo Zhang (Project Engineer)	Mar. 11, 2022
Reviewed By	Calvin Liu (Reviewer)	Mar. 11, 2022
Approved By	Max Zhang (Authorized Officer)	Mar. 11, 2022

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as a “KLIM Wireless Keyboards”. It is designed by way of utilizing the GFSK technology to achieve the system operation
A major technical description of EUT is described as following

Operation Frequency	2.403 GHz to 2.479GHz
RF Output Power	-2.680dBm (Max)
Modulation	GFSK
Number of channels	77 Channels
Antenna Designation	PCB Antenna (Comply with requirements of the FCC part 15.203)
Antenna Gain	2.34dBi
Hardware Version	V1.0
Software Version	V1.0
Power Supply	DC 3.7V by battery or DC 5V by adapter

2.2. TABLE OF CARRIER FREQUENCYS

Channel Number	Frequency	Channel Number	Frequency	Channel Number	Frequency
0	2403 MHz	26	2429 MHz	52	2455 MHz
1	2404 MHz	27	2430 MHz	53	2456 MHz
2	2405 MHz	28	2431 MHz	54	2457 MHz
3	2406 MHz	29	2432 MHz	55	2458 MHz
4	2407 MHz	30	2433 MHz	56	2459 MHz
5	2408 MHz	31	2434 MHz	57	2460 MHz
6	2409 MHz	32	2435 MHz	58	2461 MHz
7	2410 MHz	33	2436 MHz	59	2462 MHz
8	2411 MHz	34	2437 MHz	60	2463 MHz
9	2412 MHz	35	2438 MHz	61	2464 MHz
10	2413 MHz	36	2439 MHz	62	2465 MHz
11	2414 MHz	37	2440 MHz	63	2466 MHz
12	2415 MHz	38	2441 MHz	64	2467 MHz
13	2416 MHz	39	2442 MHz	65	2468 MHz
14	2417 MHz	40	2443 MHz	66	2469 MHz
15	2418 MHz	41	2444 MHz	67	2470 MHz
16	2419 MHz	42	2445 MHz	68	2471 MHz
17	2420 MHz	43	2446 MHz	69	2472 MHz
18	2421 MHz	44	2447 MHz	70	2473 MHz
19	2422 MHz	45	2448 MHz	71	2474 MHz
20	2423 MHz	46	2449 MHz	72	2475 MHz
21	2424 MHz	47	2450 MHz	73	2476 MHz
22	2425 MHz	48	2451 MHz	74	2477 MHz
23	2426 MHz	49	2452 MHz	75	2478 MHz
24	2427 MHz	50	2453 MHz	76	2479 MHz
25	2428 MHz	51	2454 MHz		

2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2AWM4KEYBOARD** filing to comply with the FCC Part 15.247 requirements.

2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device.
For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	U_c = ±3.1 dB
Uncertainty of Radiated Emission below 1GHz	U_c = ±4.0 dB
Uncertainty of Radiated Emission above 1GHz	U_c = ±4.8 dB
Uncertainty of total RF power, conducted	U_c = ±0.8 dB
Uncertainty of RF power density, conducted	U_c = ±2.6 dB
Uncertainty of spurious emissions, conducted	U_c = ±2 %
Uncertainty of Occupied Channel Bandwidth	U_c = ±2 %

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
4. The EUT adjusts the frequency through the button.

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:

Conducted Emission Configure:



5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	KLIM Wireless Keyboards	KLIM Light V2	2AWM4KEYBOARD	EUT
2	Adapter	HW-200325cpo	N/A	AE

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	May 11, 2021	May 10, 2022
LISN	R&S	ESH2-Z5	100086	Jun. 09, 2021	Jun. 08, 2022
Test software	R&S	ES-K1(Ver.V1.71)	N/A	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	May 15,2021	May 14,2022
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	Mar. 23, 2020	Mar. 22, 2022
Attenuator	ZHINAN	E-002	N/A	Sep. 03, 2020	Sep. 02, 2022
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	May 22, 2020	May 21, 2022
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 03, 2020	Sep. 02, 2022
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A

7. PEAK OUTPUT POWER

7.1. MEASUREMENT PROCEDURE

For peak power test:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. RBW≥DTS bandwidth
3. VBW≥3*RBW.
4. SPAN≥VBW.
5. Sweep: Auto.
6. Detector function: Peak.
7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

PEAK POWER TEST SETUP



7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power				
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
GFSK	2403	-3.178	≤30	Pass
	2441	-2.814	≤30	Pass
	2479	-2.680	≤30	Pass

Test Graphs of Conducted Output Power



Test_Graph_LE1M_ANT1_2403_1Mbps_Peak Power

Test_Graph_LE1M_ANT1_2441_1Mbps_Peak Power

Test_Graph_LE1M_ANT1_2479_1Mbps_Peak Power

8. BANDWIDTH

8.1. MEASUREMENT PROCEDURE

6dB bandwidth:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW≥3×RBW.
4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
   The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail
GFSK	2403	2.578	1.364	≥0.5	Pass
	2441	2.206	1.400	≥0.5	Pass
	2479	2.100	1.430	≥0.5	Pass

Test Graphs of Occupied Bandwidth

Test_Graph_LE1M_ANT1_2403_1Mbps_OBW



Test_Graph_LE1M_ANT1_2441_1Mbps_OBW



Test_Graph_LE1M_ANT1_2479_1Mbps_OBW

Test Graphs of DTS Bandwidth

Test_Graph_LE1M_ANT1_2403_1Mbps_DTSBW



Test_Graph_LE1M_ANT1_2441_1Mbps_DTSBW



Test_Graph_LE1M_ANT1_2479_1Mbps_DTSBW

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	**Measurement Result**	
	Test Data	**Criteria**
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS

Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands

Test_Graph_LE1M_ANT1_2403_1Mbps_Reference Level



Test_Graph_LE1M_ANT1_2403_1Mbps_Lower Band Emissions



Test_Graph_LE1M_ANT1_2403_1Mbps_Higher Band Emissions

Test_Graph_LE1M_ANT1_2441_1Mbps_Reference Level



Test_Graph_LE1M_ANT1_2441_1Mbps_Lower Band Emissions

Test_Graph_LE1M_ANT1_2441_1Mbps_Higher Band Emissions

Test_Graph_LE1M_ANT1_2479_1Mbps_Reference Level



Test_Graph_LE1M_ANT1_2479_1Mbps_Lower Band Emissions



Test_Graph_LE1M_ANT1_2479_1Mbps_Higher Band Emissions

Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands

Test_Graph_LE1M_ANT1_2403_1Mbps_Lower Band Edge Emissions



Test_Graph_LE1M_ANT1_2479_1Mbps_Higher Band Edge Emissions

10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1. MEASUREMENT PROCEDURE

(1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator

(2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.

(3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer to Section 7.2.

10.3. MEASUREMENT EQUIPMENT USED

Refer to Section 6.

10.4. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power Spectral Density				
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail
GFSK	2403	-22.187	≤8	Pass
	2441	-20.568	≤8	Pass
	2479	-21.101	≤8	Pass

Test Graphs of Conducted Output Power Spectral Density



Test_Graph_LE1M_ANT1_2403_1Mbps_PSD

Test_Graph_LE1M_ANT1_2441_1Mbps_PSD

Test_Graph_LE1M_ANT1_2479_1Mbps_PSD

11. RADIATED EMISSION

11.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

11.2. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



11.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT

Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

Radiated emission from 30MHz to 1000MHz

EUT	KLIM Wireless Keyboards	**Model Name**	KLIM Light V2
Temperature	21.8° C	**Relative Humidity**	58%
Pressure	960hPa	**Test Voltage**	Normal Voltage
Test Mode	Mode 3	**Antenna**	Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		68.8000	13.98	12.03	26.01	40.00	-13.99	peak
2		135.0833	15.33	12.72	28.05	43.50	-15.45	peak
3		301.6000	14.84	16.48	31.32	46.00	-14.68	peak
4		375.9667	15.40	18.14	33.54	46.00	-12.46	peak
5	*	738.1000	16.57	18.63	35.20	46.00	-10.80	peak
6		995.1500	15.35	22.96	38.31	54.00	-15.69	peak

RESULT: PASS

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		30.0000	20.52	7.17	27.69	40.00	-12.31	peak
2		68.8000	14.07	12.08	26.15	40.00	-13.85	peak
3		141.5500	14.29	13.07	27.36	43.50	-16.14	peak
4		287.0500	14.97	14.77	29.74	46.00	-16.26	peak
5		599.0667	15.03	19.92	34.95	46.00	-11.05	peak
6	*	877.1333	15.49	22.59	38.08	46.00	-7.92	peak

RESULT: PASS
Note:
1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.
2. All test modes had been tested. The mode 3 is the worst case and recorded in the report.

Radiated emission above 1GHz

EUT	KLIM Wireless Keyboards	**Model Name**	KLIM Light V2
Temperature	21.8° C	**Relative Humidity**	58%
Pressure	960hPa	**Test Voltage**	Normal Voltage
Test Mode	Mode 1	**Antenna**	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4806.000	43.98	0.08	44.06	74	-29.94	peak
4806.000	35.73	0.08	35.81	54	-18.19	AVG
7209.000	38.66	2.21	40.87	74	-33.13	peak
7209.000	31.47	2.21	33.68	54	-20.32	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT	KLIM Wireless Keyboards	**Model Name**	KLIM Light V2
Temperature	21.8° C	**Relative Humidity**	58%
Pressure	960hPa	**Test Voltage**	Normal Voltage
Test Mode	Mode 1	**Antenna**	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4806.000	44.88	0.08	44.96	74	-29.04	peak
4806.000	34.56	0.08	34.64	54	-19.36	AVG
7209.000	38.45	2.21	40.66	74	-33.34	peak
7209.000	30.73	2.21	32.94	54	-21.06	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4882.000	44.37	0.14	44.51	74	-29.49	peak
4882.000	35.34	0.14	35.48	54	-18.52	AVG
7323.000	39.28	2.36	41.64	74	-32.36	peak
7323.000	31.53	2.36	33.89	54	-20.11	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4882.000	45.45	0.14	45.59	74	-28.41	peak
4882.000	38.54	0.14	38.68	54	-15.32	AVG
7323.000	40.67	2.36	43.03	74	-30.97	peak
7323.000	32.42	2.36	34.78	54	-19.22	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4958.000	44.75	0.22	44.97	74	-29.03	peak
4958.000	35.67	0.22	35.89	54	-18.11	AVG
7437.000	38.74	2.64	41.38	74	-32.62	peak
7437.000	29.52	2.64	32.16	54	-21.84	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4958.000	42.36	0.22	42.58	74	-31.42	peak
4958.000	34.27	0.22	34.49	54	-19.51	AVG
7437.000	38.59	2.64	41.23	74	-32.77	peak
7437.000	29.18	2.64	31.82	54	-22.18	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Level-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

Test result for band edge emission at restricted bands

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Test Graph for Peak Measurement

Test Graph for Average Measurement

RESULT: PASS

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Test Graph for Peak Measurement

Test Graph for Average Measurement

RESULT: PASS

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement

RESULT: PASS

EUT	KLIM Wireless Keyboards	Model Name	KLIM Light V2
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement

RESULT: PASS

Note: The factor had been edited in the “Input Correction” of the Spectrum Analyzer.

12. LINE CONDUCTED EMISSION TEST

12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipment received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT: "agc_fin"

2022/3/2 17:36

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.562000	43.30	5.4	56	12.7	QP	L1
0.642000	47.40	5.4	56	8.6	QP	L1
0.662000	47.20	5.4	56	8.8	QP	L1
0.974000	33.50	5.4	56	22.5	QP	L1
1.282000	33.90	5.8	56	22.1	QP	L1
2.022000	34.80	6.5	56	21.2	QP	L1

MEASUREMENT RESULT: "agc_fin2"

2022/3/2 17:36

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.542000	27.70	5.4	46	18.3	AV	L1
0.562000	29.40	5.4	46	16.6	AV	L1
0.582000	28.20	5.4	46	17.8	AV	L1
0.622000	27.80	5.4	46	18.2	AV	L1
0.642000	34.00	5.4	46	12.0	AV	L1
0.662000	33.10	5.4	46	12.9	AV	L1

Line Conducted Emission Test Line 2-N



MEASUREMENT RESULT: "agc_fin"

2022/3/2 17:33

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.562000	43.20	5.4	56	12.8	QP	N
0.642000	49.40	5.4	56	6.6	QP	N
1.154000	36.20	5.6	56	19.8	QP	N
1.242000	42.50	5.8	56	13.5	QP	N
1.258000	40.10	5.8	56	15.9	QP	N
1.618000	36.40	6.2	56	19.6	QP	N

MEASUREMENT RESULT: "agc_fin2"

2022/3/2 17:33

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.526000	29.30	5.4	46	16.7	AV	N
0.542000	33.20	5.4	46	12.8	AV	N
0.566000	30.40	5.4	46	15.6	AV	N
0.622000	35.70	5.4	46	10.3	AV	N
0.642000	41.10	5.4	46	4.9	AV	N
0.658000	38.70	5.4	46	7.3	AV	N

RESULT: PASS

Note: All the test modes had been tested, the mode 3 was the worst case. Only the data of the worst case would be record in this test report.

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC10516220206AP01

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC10516220206AP02

----END OF REPORT----

Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3.The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.