



BELKIN INTERNATIONAL

**12045 East Waterfront Drive
Playa Vista, CA 90094-2536 USA
P 310 751 5100**

Applicant: Belkin International, Inc.	
FCC ID: K7SWIA004	
RF Exposure Requirements (FCC KDB 680106 D01 V03)	
Requirements	Statements
(a) Power transfer frequency is less than 1 MHz	The resonator system shall operate at 360.0kHz
(b) Output power from each primary coil is less than 15 watts	Dimension for iPhone charging coil: 16.62cm ² (Diameter=46.01mm) Max output Power for Phone charging coil: 15W
(c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils	Device has one coils for 360.0kHz (iPhone). Coupling is only between individual pairs of coils.
(d) Client device is inserted in or placed directly in contact with the transmitter	Client device is placed directly in contact with the transmitter
(e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	It's portable device, and provided RF exposure report to evaluate
(f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Please refer to RF Exposure Report.

Name: Rossi Wu

Title: Senior Regulatory Compliance Engineer

Phone: +1 310 633 9309*2960

E-mail: Rossi.Wu@belkin.com