In order to better use this product, please read the instructions carefully before installation!

Touch Button instruction manual

product overview

The transmitter and receiver are used together, no wiring, no installation is simple and flexible, this product is mainly suitable for orchard farm alarm, family residence, company, hospital, hotel, factory doors and Windows. **product feature**

.Touch signals automatically

.The remote control distance can reach 300 meters in an open barrier-free environment: the remote control signal is stable and does not interfere with each other.

Product icon

emitter



Operating Instructions

1. Start by putting the receiver into code matching mode.

2. Touch the front to complete matching with the receiver

3. Attach the transmitter to the doors and Windows, and the receiver will ring automatically every time the magnetic strip is opened.

replace battery

1. Snap off the bottom shell

2. Open 1 screw with a screwdriver

3. Remove the battery from the transmitter PCB board and dispose of it properly; Install a new CR2450 battery into the battery slot, noting that the positive and negative terminals cannot be inverted.

technical reference

operating temperature	-30℃ [~] +70℃
operating frequency	433.92MH/±280KHz
Transmitter battery	CR2450 600mAH
Standby time	3 years

FCC Warning:

This device complies with part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance

could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception,

which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-- Reorient or relocate the receiving antenna.

 $-\!-$ Increase the separation between the equipment and receiver.

-- Connect the equipment into an outlet on a circuit different

from that to which the receiver is connected.

-- Consult the dealer or an experienced radio/TV technician for help.

To maintain compliance with FCC' s RF Exposure guidelines, This equipment should be installed and operated with minimum distance between 20cm the radiator your body:

Use only the supplied antenna.