



CTC Laboratories, Inc. (FCC Designation Number: CN1208)

Room 101 Building B, No. 7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-27521059 Fax: +86-755-27521011 <http://www.sz-ctc.org.cn>

Maximum Permissible Exposure Evaluation

FCC ID: 2APN5SGC

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

EUT Specification

Applicant	Shenzhen Sonoff Technologies Co.,Ltd.
Address	3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China
Product Name:	Smart Garage Door Controller
Trade Mark:	Sonoff
Model/Type Reference:	SGC300
Listed Model(s):	SGC200, SGC100
Model Differences:	All these models are identical in the same PCB, layout, electrical circuit. The difference is controlling the number of channels. The SGC300 controls three channels. The SGC200 controls two channels. SGC100 controls one channel.
Frequency Band (Operating)	BT: 2402~2480MHz WiFi: 2412-2462MHz
Device Category	☐ Portable (<5mm separation) ☐ Mobile (>20cm separation) ☒ Fixed (>20cm separation) ☐ Others ____
Exposure Classification	☐ Occupational/Controlled exposure ($S=5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna Diversity	☒ Single antenna ☐ Multiple antennas ☐ TX diversity ☐ RX diversity ☐ TX/RX diversity
Antenna Gain (Max)	2.82dBi
Evaluation Applied	☒ MPE Evaluation ☐ SAR Evaluation

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhua Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 [Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

**Limits for Maximum Permissible Exposure (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
300-1500	--	--	F/300	<6
1500-100000	--	--	5	<6
(B) Limits for General Population/Uncontrolled Exposure				
300-1500	--	--	F/1500	<30
1500-100000	--	--	1	<30

Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where:

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d limit of MPE is 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune Up Tolerance (dB)	Max. Tune Up Power (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Result
BT	2480	2.82	1.81	±1	3.00	0.0008	1	Pass
802.11n(HT20)	2462	2.82	21.17	±1	22.00	0.0604	1	Pass

The BT and WiFi can transmit simultaneously.

Mode	Frequency (MHz)	Antenna Gain (dBi)	Power Density at 20cm (mW/cm ²)	Total Power density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Result
BT	2480	2.82	0.0008	0.0612	1	Pass
802.11n(HT20)	2462	2.82	0.0604			

Note:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

*****THE END*****